

MAXIMUM PERMISSIBLE EXPOSURE EVALUATION REPORT

Applicant: Beijing Orion Star Technology Co., Ltd.

Address: Room A-2570, 2nd Floor No. 30 Shixing Street, Shijingshan District, Beijing China.

Product Name: Dispatch Center

FCC ID: 2A3BD-OSADF02R

Standard(s): 47 CFR §1.1310, 47 CFR §2.1091,
47 CFR §15.247(i), 47 CFR §15.407(f)

Report Number: 2402W68103E-RF-00E

Report Date: 2024/10/12

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Gavin Xu

Reviewed By: Gavin Xu
Title: RF Engineer

Ivan Cao

Approved By: Ivan Cao
Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	3
1. GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST.....	4
2. RF EXPOSURE EVALUATION (MPE).....	5
2.1 RF EXPOSURE EVALUATION	5
2.1.1 Applicable Standard.....	5
2.1.2 Calculation formula:	5
2.1.3 Calculated Data:	6
EXHIBIT A - EUT PHOTOGRAPHS.....	7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402W68103E-RF-00E	Original Report	2024/10/12

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	Dispatch Center
EUT Model:	OS-A-DF02R
Rated Input Voltage:	DC 12V from Adapter
EUT Received Date:	2024/8/30
EUT Received Status:	Good

2. RF EXPOSURE EVALUATION (MPE)

2.1 RF Exposure Evaluation

2.1.1 Applicable Standard

According to subpart 15.247(i), 15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

2.1.2 Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

2.1.3 Calculated Data:

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G SRD	2419	3.48	2.23	4	2.51	20.00	0.001	1.0
2.4G Wifi	2412-2462	3.48	2.23	19	79.43	20.00	0.035	1.0
5.2G Wifi	5150-5250	4.16	2.61	12	15.85	20.00	0.008	1.0
5.3G Wifi	5250-5350	4.16	2.61	12	15.85	20.00	0.008	1.0
5.6G Wifi	5470-5725	4.32	2.70	12.5	17.78	20.00	0.010	1.0
5.8G Wifi	5725-5850	4.23	2.65	13	19.95	20.00	0.011	1.0

Note:

The Conducted output power including Tune-up Tolerance provided by manufacturer.

Simultaneous transmission:

2.4G Wifi and 5G Wifi can't transmit simultaneously, but 2.4G Wifi or 5G Wifi can transmit simultaneously with 2.4G SRD:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$S_{SRD}/S_{limit-SRD} + S_{2.4G\ Wifi}/S_{limit-2.4G\ Wifi}$$

$$= 0.001/1.0 + 0.035/1.0$$

$$= 0.036$$

$$< 1.0$$

Result: Compliant. The device compliant Simultaneous transmission at 20cm distances.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2402W68103E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402W68103E-RF-INP EUT INTERNAL PHOTOGRAPHS.

******* END OF REPORT *******