

FCC AND ISCED CERTIFICATION TEST REPORT

FOR

Applicant	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China
Equipment under Test	:	AI Delivery Robot
Model No.	:	OS-R-DR01
Trade Mark	:	ORIONSTAR
FCC ID	:	2A3BD-OSRDR01
IC	:	27780-OSRDR01
Manufacturer	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

Test report declares.....	4
1. Summary of test results	6
2. General test information.....	7
2.1. Description of EUT	7
2.2. Accessories of EUT	8
2.3. Assistant equipment used for test.....	8
2.4. Block diagram of EUT configuration for test.....	8
2.5. Deviations of test standard	10
2.6. Test environment conditions	10
2.7. Test laboratory	10
2.8. Measurement uncertainty	11
3. Equipment used during test.....	12
4. 26dB Bandwidth, 6dB Bandwidth and 99% Bandwidth.....	14
4.1. Block diagram of test setup	14
4.2. Limits	14
4.3. Test Procedure.....	14
4.4. Test Result	15
4.5. Original test data	20
5. Maximum Output Power	110
5.1. Block diagram of test setup	110
5.2. Limits	110
5.3. Test Procedure.....	110
5.4. Test Result	111
6. Power Spectral Density.....	116
6.1. Block diagram of test setup	116
6.2. Limits	116
6.3. Test Procedure.....	116
6.4. Test Result	117
6.5. Original test data	122
7. Frequency Stability Measurement	162
7.1. Limit of Frequency Stability.....	162
7.2. Measuring Instruments	162
7.3. Test Procedures.....	162
7.4. Test Setup	162
7.5. Test Result	162
8. Emissions in restricted frequency bands.....	170

8.1.	Block diagram of test setup	170
8.2.	Limit.....	171
8.3.	Test Procedure.....	173
8.4.	Test result.....	174
9.	Band Edge Compliance	185
9.1.	Block diagram of test setup	185
9.2.	Limit.....	185
9.3.	Test Procedure.....	185
9.4.	Test result.....	185
10.	Power Line Conducted Emission.....	251
10.1.	Block diagram of test setup	251
10.2.	Power Line Conducted Emission Limits (Class B)	251
10.3.	Test Procedure.....	251
10.4.	Test Result	252
11.	Antenna Requirements	255
11.1.	Limit.....	255
11.2.	Result	255
12.	Dynamic Frequency Selection	256
12.1.	Applicability of DFS requirements	256
12.2.	Limit.....	257
12.3.	Parameters of radar test waveforms.....	257
12.4.	Calibration of radar waveform.....	258
12.5.	Channel closing transmission time, channel move time and non-occupancy period.....	262
12.6.	Test setup.....	263
12.7.	Test result.....	263

Test Report Declare

Applicant	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China
Equipment under Test	:	AI Delivery Robot
Model No.	:	OS-R-DR01
Trade Mark	:	ORIONSTAR
Manufacturer	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China

Test Standard Used: FCC Rules and Regulations Part 15 Subpart E, RSS-247 Issue 2 February 2017.

Test procedure used: ANSI C63.10:2013, 789033 D02 General U-NII Test Procedures New Rules v02r01, RSS-Gen Issue 5, Apr. 2018, 662911 D01 Multiple Transmitter Output v02r01

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&ISED standards.

Report No:	DDT-R21091301-1E02		
Date of Receipt:	Sep. 13, 2021	Date of Test:	Sep. 13, 2021 ~ Oct. 19, 2021

Prepared By:

Ben Jin

Ben Jin/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Oct. 20, 2021	

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.

Description of Test Item	Standard	Results
6/26db Bandwidth and 99% Bandwidth	FCC 15.407 (e) RSS-247 Clause 6.2	PASS
Maximum Conducted Output Power	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
Power Spectral Density	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
Frequency Stability Measurement	FCC 15.407 (g)	PASS
Emissions in restricted frequency bands	FCC 15.407 (a) FCC 15.209 FCC 15.205 RSS-247 Clause 6.2 RSS-GEN Clause 8.9	PASS
Band Edge Compliance	FCC 15.407 (a) FCC 15.209 FCC 15.205 RSS-247 Clause 6.2 RSS-GEN Clause 8.9	PASS
Power Line Conducted Emission	FCC 15.207 RSS-GEN Clause 8.8	PASS
Antenna requirement	FCC 15.203 RSS-GEN Clause 8.3	PASS
Dynamic Frequency Selection	FCC 15.407 (h) RSS-247 Clause 6.3	PASS

2. General test information

2.1. Description of EUT

EUT* Name	: AI Delivery Robot
Model Number	: OS-R-DR01
EUT function description	: Please reference user manual of this device
Power supply	: DC 32V 3.93A from external AC/DC Adapter DC 29.4V from Li-ion battery
Radio Technology	: IEEE 802.11a/n/ac
FCC Operation frequency	: IEEE 802.11a: 5180MHz-5240MHz, 5260MHz-5320MHz, 5500MHz-5700MHz, 5745MHz-5825MHz IEEE 802.11n HT20: 5180MHz-5240MHz, 5260MHz-5320MHz, 5500MHz-5700MHz, 5745MHz-5825MHz IEEE 802.11n HT40: 5190MHz-5230MHz, 5270MHz-5310MHz, 5510MHz-5670MHz, 5755MHz-5755MHz IEEE 802.11ac HT20: 5180MHz-5240MHz, 5260MHz-5320MHz, 5500MHz-5700MHz, 5745MHz-5825MHz IEEE 802.11ac HT40: 5190MHz-5230MHz, 5270MHz-5310MHz, 5510MHz-5670MHz, 5755MHz-5755MHz IEEE 802.11ac HT80: 5210MHz, 5290MHz, 5530MHz, 5610MHz, 5775MHz
Modulation	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: 14.4, 28.9, 43.3, 57.8, 86.7, 115.6, 130.0, 144.4 Mbps IEEE 802.11n HT40: 30, 60, 90, 120, 180, 240, 270, 300 Mbps IEEE 802.11ac HT20: 14.4, 28.8, 43.4, 57.8, 86.6, 115.6, 130, 144.4, 173.4 Mbps IEEE 802.11ac HT40: 30, 60, 90, 120, 180, 240, 270, 300, 360, 400 Mbps IEEE 802.11ac HT80: 65, 130, 195, 260, 390, 520, 585, 650, 780, 866.6 Mbps
Antenna Gain	: Antenna 1: maximum PK gain: 2.88 dBi Antenna 2: maximum PK gain: 1.55 dBi
Sample Type	: Series production
Serial number	: N/A

Note: EUT is the ab. of equipment under test.


Antenna information			
	Ant1 gain	Ant2 gain	MIMO
IEEE 802.11a	2.88	1.55	/
IEEE 802.11n HT20	2.88	1.55	5.25
IEEE 802.11n HT40	2.88	1.55	5.25
IEEE 802.11ac VHT20	2.88	1.55	5.25
IEEE 802.11ac VHT40	2.88	1.55	5.25
IEEE 802.11ac VHT80	2.88	1.55	5.25

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
AC/DC Adapter	GUAN YU DA	GM130-3200 393-1F	N/A	Input: AC 100-240V, 50/60Hz, 2.5A; Output: DC 32V 3.93A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test

Test software: QRCT.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11a	14	6	Low: CH36	5180
	14	6	Middle: CH40	5200
	14	6	High: CH48	5240
	14	6	Low: CH52	5260
	14	6	Middle: CH56	5280
	14	6	High: CH64	5320
	14	6	Low: CH100	5500
	14	6	Middle: CH116	5580
	14	6	High: CH140	5700
	14	6	Low: CH149	5745
	14	6	Middle: CH157	5785
	14	6	High: CH165	5825
IEEE 802.11n HT20	13	MCS 8	Low: CH36	5180
	13	MCS 8	Middle: CH40	5200
	13	MCS 8	High: CH48	5240
	13	MCS 8	Low: CH52	5260
	13	MCS 8	Middle: CH56	5280
	13	MCS 8	High: CH64	5320
	13	MCS 8	Low: CH100	5500
	13	MCS 8	Middle: CH116	5580
	13	MCS 8	High: CH140	5700
	13	MCS 8	Low: CH149	5745
	13	MCS 8	Middle: CH157	5785
	13	MCS 8	High: CH165	5825
IEEE 802.11n HT40	8	MCS 8	Low: CH38	5190
	8	MCS 8	Middle: CH46	5230
	8	MCS 8	High: CH54	5270
	8	MCS 8	Low: CH62	5310
	8	MCS 8	Middle: CH102	5510
	8	MCS 8	High: CH110	5550
	8	MCS 8	Low: CH134	5670
	8	MCS 8	Middle: CH151	5755
	8	MCS 8	High: CH159	5795
IEEE 802.11ac HT20	11	MCS 8	Low: CH36	5180
	11	MCS 8	Middle: CH40	5200
	11	MCS 8	High: CH48	5240
	11	MCS 8	Low: CH52	5260
	11	MCS 8	Middle: CH56	5280
	11	MCS 8	High: CH64	5320
	11	MCS 8	Low: CH100	5500
	11	MCS 8	Middle: CH116	5580
	11	MCS 8	High: CH140	5700
	11	MCS 8	Low: CH149	5745
	11	MCS 8	Middle: CH157	5785
	11	MCS 8	High: CH165	5825

IEEE 802.11ac HT40	8	MCS 8	Low: CH38	5190
	8	MCS 8	Middle: CH46	5230
	8	MCS 8	High: CH54	5270
	8	MCS 8	Low: CH62	5310
	8	MCS 8	Middle: CH102	5510
	8	MCS 8	High: CH110	5550
	8	MCS 8	Low: CH134	5670
	8	MCS 8	Middle: CH151	5755
	8	MCS 8	High: CH159	5795
IEEE 802.11ac HT80	8	MCS 8	CH42	5210
	8	MCS 8	CH58	5290
	8	MCS 8	CH106	5530
	8	MCS 8	CH122	5610
	8	MCS 8	CH155	5775

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106 kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
	1.66 dB ($8 \text{ GHz} \leq f < 22 \text{ GHz}$)
Uncertainty for radio frequency (RBW<20kHz)	3×10^{-8}
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10 dB (1-6 GHz)
	4.40 dB (6 GHz-18 GHz)
	3.54 dB (18 GHz-26 GHz)
	4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☐ RF Connected Test (Tonscend RF Measurement System 1#)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 02, 2021	1 Year
Wideband Radio Communication tester	R&S	CMW500	120259	Sep. 02, 2021	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 18, 2021	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 01, 2021	1 Year
RF Control Unit	Tonsend	JS0806-2	158060010	Jun. 01, 2021	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Jun. 01, 2021	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.6.77.0518	N/A	N/A
☒ RF Connected Test (Tonscend RF Measurement System 2#)					
Signal analyzer	R&S	FSQ26	101272	Jun. 01, 2021	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 01, 2021	1 Year
Vector Signal Generator	Agilent	N5182A	MY19060405	Jun. 01, 2021	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180912	Jun. 01, 2021	1 Year
RF Control Unit	Tonsend	JS0806-2	DDT-ZC01449	Jun. 01, 2021	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Jun. 01, 2021	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.6.77.0518	N/A	N/A
☒ Radiation 3#chamber					
EMI Test Receiver	R&S	ESU	100472	Jun. 01, 2021	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 01, 2021	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Nov. 18, 2020	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Aug. 07, 2021	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120	02108	Jul. 17, 2021	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 08, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Sep. 02, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Mar. 15, 2021	1 Year
Test software	Audix	E3	V 6.1.1.1	N/A	N/A
☐ Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Sep. 02, 2021	1 Year
LISN 1	R&S	ENV216	101109	Sep. 02, 2021	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 02, 2021	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 02, 2021	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 02, 2021	1 Year
LISN 3	SCHWARZBECK	NSLK 8163	00017	Sep. 02, 2021	1 Year

Test software	Audix	E3	V 6.11111b	N/A	N/A
☑Power Line Conducted Emissions Test 2#					
Test Receiver	R&S	ESCI	101028	Sep. 02, 2021	1 Year
LISN 1	R&S	ENV216	101170	Sep. 02, 2021	1 Year
Pulse Limiter	R&S	KH43101	431011801568-1 2#	Jun. 01, 2021	1 Year
CE Cable 2	HUBSER	RG214-5	N/A	Jun. 01, 2021	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A