



Date: 16/1/2024

FCC ID:2A3C7-RFID

IC: 27924-RFID

Type of Module: Limited Single Modular Approval			
No.	Requirements	Device Conditions	Comply (Y/N)
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	the radio elements of the RFID Board TMOD are not shielded	N
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	All possible modulations/data input settings are managed/buffered within the RFID Board TMOD board itself	Y
3	The modular transmitter must have its own power supply regulation.	The device is powered in DC	Y
4	<p>The modular transmitter must comply with the antenna and transmission system requirements of §15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler.</p> <p>The module shall comply with the provisions for external power amplifiers and antennas detailed in the applicable RSS. A detailed description of the configuration of highest antenna gain for each type of transmitting antenna for licence-exempt modules and/or the maximum transmitting antenna gain for licence modules, a detailed description of the configuration of lowest antenna gain for each type of receiving antenna for Dynamic Frequency Selection (DFS) modules with removable antenna(s).</p>	Click here to enter text.	Y
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during	Click here to enter text.	Y




	testing for compliance with part 15 requirements and ISSED's requirements.		
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number and IC certification number.	Click here to enter text.	Y
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	<p>RFID Board TMOD is to be used exclusively in EVBox products (not for sale to third party). Full compliance of the end product is verified by testing the end/host product with the RFID Board TMOD installed.</p> <p>The integration of RFID Board TMOD in the end product is part of an internal confidential manufacturing process and an explicative description is given in the Operational Description document.</p>	Y
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Click here to enter text.	Y

If you have any questions regarding this, please don't hesitate to contact us.

Sincerely,

DocuSigned by:



Click here to enter text.
Jim Stephenson President

EVBox North America Inc.