

Maximum Permissible Exposure Report

Product Information

EUT : Granary Automatic Pet Feeder-WiFi Control
 Model Number : PLAF103
 Model Declaration : N/A
 Test Model : PLAF103
 Power Supply : 1,DC 5V by Adapter
 : 2,DC 4.5V by 3 * alkaline D batteries(not included)
 Hardware version : PLAF103_MB_V1.0
 Software version : 1.0.7
 Sample ID : TZ230204015-2#&TZ230204015-4#

Bluetooth

Bluetooth Version : V5.0
 Operation Frequency : 2402- 2480 MHz
 Channel Number : 40 Channels for BLE (DTS)
 Modulation Technology : GFSK for BLE (DTS)
 Data Rates : BLE (DTS): 1Mbps
 Antenna Type And Gain : Internal Antenna:
 : 2.27dBi

WiFi

WLAN : Supported IEEE 802.11a/b/g/n
 IEEE 802.11b:2412-2462MHz
 IEEE 802.11g:2412-2462MHz
 WLAN FCC Operation : IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz
 Frequency : IEEE 802.11n HT40: 2422-2452MHz / 5190-5230MHz / 5755-5795MHz
 IEEE 802.11a: 5180-5240MHz / 5745-5825MHz
 WLAN Channel Number : 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20)
 7 Channels for 2422-2452MHz(IEEE 802.11n HT40)
 4 Channels for 5180-5240MHz (IEEE 802.11a/ n HT20)
 2 Channels for 5190-5230MHz (IEEE 802.11 n HT40)
 5 Channels for 5745-5825MHz(IEEE 802.11a/n HT20)
 2 Channels for 5755-5795MHz(IEEE 802.11n HT40)
 WLAN Modulation : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
 Technology : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
 Antenna Type And Gain : Internal Antenna:
 : 2.27dBi (Max.), for TX/RX (WLAN 2.4G Band)
 : 2.25dBi (Max.), for TX/RX (WLAN 5.2G Band)
 : 2.24dBi (Max.), for TX/RX (WLAN 5.8G Band)

Note 1: Antenna position refer to EUT Photos.

Note 2: the above information was supplied by the applicant.

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer evaluation method

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.
FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.
FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
 Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

This Product can only use antennas certificated as follows provided by manufacturer;

Antenna Gain and type refer to Product information

6. Conducted Power

2.4G Band:

Bluetooth(BLE)

TestMode	Antenna	Channel	Result[dBm]
BLE_1M	Ant1	2402	-4.72
		2440	-1.98
		2480	-1.76

WiFi 2.4GHz Band

TestMode	Antenna	Channel	Result[dBm]
11B	Ant1	2412	11.83
		2437	13.35
		2462	12.62
11G	Ant1	2412	13.09
		2437	13.75
		2462	12.82
11N20SISO	Ant1	2412	12.76
		2437	13.63
		2462	12.78
11N40SISO	Ant1	2422	10.94
		2437	11.09
		2452	10.58

5G Band

UNII-1 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5180	-1.54
		5200	-0.22
		5240	0.98
11N20SISO	Ant1	5180	-1.78
		5200	-0.59
		5240	0.96
11N40SISO	Ant1	5190	0.39
		5230	1.54

UNII-3 Band

TestMode	Antenna	Channel	Result[dBm]
11A	Ant1	5745	2.27
		5785	0.52
		5825	-0.23
11N20SISO	Ant1	5745	1.96
		5785	0.22
		5825	-0.36
11N40SISO	Ant1	5755	1.78
		5795	0.17

7. Manufacturing Tolerance

Bluetooth(BLE)

GFSK(1Mbps) (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-5.0	-2.5	-2.5
Tolerance \pm (dB)	1.0	1.0	1.0

WiFi 2.4GHz Band – Antenna 1

IEEE 802.11b(Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.5	13.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11g (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.5	13.5	12.5
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.5	13.0	12.5
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	10.5	10.5	10.0
Tolerance \pm (dB)	1.0	1.0	1.0

UNII-1 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	-2.0	-0.5	0.5
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.5	5.5	7.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	5.0	5.5	7.5
Tolerance \pm (dB)	1.0	1.0	1.0

UNII-3 Band – Antenna 1

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	2.0	0.0	-0.5
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	1.5	-0.5	-1.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	--
Target (dBm)	1.5	-0.5	--
Tolerance \pm (dB)	1.0	1.0	--

8. Measurement Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Bluetooth(BLE)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK(1Mbps)	-1.5	0.7079	2.27	1.6866	100%	0.0002	1.0000

WiFi 2.4GHz Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	14.0	25.1189	2.27	1.6866	100%	0.0084	1.0000
IEEE 802.11g	14.5	28.1838	2.27	1.6866	100%	0.0095	1.0000
IEEE 802.11n HT20	14.0	25.1189	2.27	1.6866	100%	0.0084	1.0000
IEEE 802.11n HT40	11.5	14.1254	2.27	1.6866	100%	0.0047	1.0000

UNII-1 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	1.5	1.4125	2.25	1.6788	100%	0.0005	1.0000
IEEE 802.11n HT20	1.5	1.4125	2.25	1.6788	100%	0.0005	1.0000
IEEE 802.11n HT40	2.0	1.5849	2.25	1.6788	100%	0.0005	1.0000

UNII-3 Band – Ant 1

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11a	3.0	1.9953	2.24	1.6749	100%	0.0007	1.0000
IEEE 802.11n HT20	2.5	1.7783	2.24	1.6749	100%	0.0006	1.0000
IEEE 802.11n HT40	2.5	1.7783	2.24	1.6749	100%	0.0006	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----