

Page 157 of 183

Test Laboratory: AGC Lab Date: Sep. 08, 2024

LTE Band 41 Mid-Touch-Left (1RB#0)

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: LTE; Communication System Band: LTE Band 41; Duty Cycle:1:1.58; Conv.F=2.06 Frequency: 2593MHz; Medium parameters used: f = 2600 MHz;  $\sigma = 1.91 \text{ mho/m}$ ;  $\epsilon = 39.66$ ;  $\rho = 1000 \text{ kg/m}^3$ ;

Phantom section: Left Section

Ambient temperature ( $^{\circ}$ ): 21.6, Liquid temperature ( $^{\circ}$ ): 21.1

## **SATIMO Configuration:**

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32


Configuration/ LTE BAND 41 Mid-Touch-Left/Area Scan: Measurement grid: dx=8mm, y=8mm Configuration/ LTE BAND 41 Mid-Touch-Left/Zoom Scan: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Area Scan	dx=8mm dy=8mm, h= 5.00 mm			
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm			
Phantom	Left head			
Device Position	Cheek			
Band	LTE BAND 41			
Channels	Middle			
Signal	OFDM (Crest factor: 1.58)			





Maximum location: X=-47.00, Y=-62.00 SAR Peak: 0.08 W/kg

<b>SAR 10g (W/Kg)</b>	0.037111		
SAR 1g (W/Kg)	0.053794		











Page 159 of 183

Test Laboratory: AGC Lab Date: Sep. 08, 2024

LTE Band 41 Mid-Body-Back(1RB#0)

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: LTE; Communication System Band: LTE Band 41; Duty Cycle:1:1.58; Conv.F=2.06 Frequency: 2593MHz; Medium parameters used: f =2600 MHz;  $\sigma$ =1.91 mho/m;  $\epsilon$ r =39.66;  $\rho$ = 1000 kg/m³;

Phantom section: Flat Section

Ambient temperature (°C): 21.6, Liquid temperature (°C): 21.1

### SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

Measurement SW: OpenSAR V4\_02\_32

Configuration/ LTE BAND 41 Mid-Body-Back /Area Scan: Measurement grid: dx=8mm, y=8mm Configuration/ LTE BAND 41 Mid-Body-Back /Zoom Scan: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Area Scan	surf_sam_plan.txt, h= 5.00 mm				
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm				
Phantom	Validation plane				
Device Position	Body Back				
Band	LTE BAND 41				
Channels	Middle				
Signal	OFDM (Crest factor: 1.58)				




Maximum location: X=-8.00, Y=-40.00 SAR Peak: 0.48 W/kg


<b>SAR 10g (W/Kg)</b>	0.121979		
SAR 1g (W/Kg)	0.258493		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Page 161 of 183

**WIFI MODE** 

Test Laboratory: AGC Lab Date: Sep. 07, 2024

802.11b Mid-Touch-Left

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=2.16; Frequency: 2437 MHz; Medium parameters used: f = 2450 MHz;  $\sigma = \delta Pmho/m$ ;  $\epsilon r = 39.77$   $\rho = 1000$  kg/m³;

Phantom section: Left Section

Ambient temperature ( $^{\circ}$ C):21.9, Liquid temperature ( $^{\circ}$ C): 21.4

#### SATIMO Configuration:

· Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4 02 32

Configuration/802.11b Mid- Touch-Left/Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/802.11b Mid- Touch-Left/Zoom Scan: Measurement grid: dx=5mm,dy=5mm, dz=5mm


Area Scan	dx=8mm dy=8mm, h= 5.00 mm			
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm			
Phantom	Left head			
Device Position	Cheek			
Band	2450MHz			
Channels	Middle			
Signal	Crest factor: 1.0			




Maximum location: X=-15.00, Y=18.00 SAR Peak: 0.92 W/kg


SAR 10g (W/Kg)	0.237248
SAR 1g (W/Kg)	0.493502

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Page 163 of 183

Test Laboratory: AGC Lab Date: Sep. 07, 2024

802.11b Mid-Body-Worn- Front

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11b; Duty Cycle: 1:1; Conv.F=2.16; Frequency: 2437 MHz; Medium parameters used: f = 2450 MHz;  $\sigma = \delta Pmho/m$ ;  $\epsilon = 39.77$ ;  $\rho = 1000$  kg/m³;

Phantom section: Flat Section

Ambient temperature (°C):21.9, Liquid temperature (°C): 21.4

#### **SATIMO Configuration:**

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32

Configuration/802.11b Mid- Body- Front /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/802.11b Mid- Body- Front /Zoom Scan: Measurement grid: dx=5mm, dy=5mm, dz=5mm;


Area Scan	surf_sam_plan.txt, h= 5.00 mm			
ZoomScan	7x7x7,dx=5mm dy=5mm dz=5mm			
Phantom	Validation plane			
Device Position	Body Front			
Band	2450MHz			
Channels	Middle			
Signal	Crest factor: 1.0			




Maximum location: X=23.00, Y=40.00 SAR Peak: 0.62 W/kg


	<u> </u>
SAR 10g (W/Kg)	0.178259
SAR 1g (W/Kg)	0.348671

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Page 165 of 183

5.2GHz 802.11ac VHT80

Test Laboratory: AGC Lab

Date: Sep. 11, 2024
802.11a CH40-Tilt -Left

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=1.53; Frequency: 5200MHz; Medium parameters used: f = 5200~MHz;  $\sigma = 4.57mho/m$ ;  $\epsilon r = 35.34$ ;  $\rho = 1000~kg/m^3$ ;

Phantom section: Left Section

Ambient temperature ( $^{\circ}$ C): 20.9, Liquid temperature ( $^{\circ}$ C): 20.6

### SATIMO Configuration:

· Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32

Configuration/802.11a CH40- Tilt -Left /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/802.11a CH40- Tilt -Left /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm


Area Scan	dx=8mm dy=8mm, h= 5.00 mm			
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm			
Phantom	Left head			
Device Position	Tilt			
Band	5200MHz			
Channels	CH40			
Signal	Crest factor: 1.0			



Maximum location: X=0.00, Y=26.00 SAR Peak: 2.50 W/kg


	0
SAR 10g (W/Kg)	0.318684
SAR 1g (W/Kg)	0.604804

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.





Z (0.00 (m m) SA 2.53 R 01 (W/ Kg)		0.55 82	8.00 0.30 46	10.0 0 0.18 02	12.0 0 0.13 22	14.0 0 0.08 93	16.0 0 0.06 87	18.0 0 0.06 81	20.0 0 0.07 20	22.0 0 0.07 67	24.0 0 0.07 09
	2.5- 2.0- (%) 1.5- 1.0- 0.5- 0.1-		4 6	8 1	0 12 Z (mi	14 16 m)	18 20	22 2	4 26		





Page 167 of 183

Test Laboratory: AGC Lab Date: Sep. 11, 2024

802.11a CH40-Edge1

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=2.35; Frequency: 5200MHz; Medium parameters used: f = 5200 MHz;  $\sigma = 4.57 \text{mho/m}$ ;  $\epsilon = 35.34$ ;  $\rho = 1000 \text{ kg/m}^3$ ;

Phantom section: Flat Section

Ambient temperature (°C): 20.9, Liquid temperature (°C): 20.6

#### SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414

· Sensor-Surface: 4mm (Mechanical Surface Detection)


· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32

Configuration/802.11a CH40- Edge1 /Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/802.11a CH40- Edge1 /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm


Area Scan	sam_direct_droit2_surf8mm.txt			
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm			
Phantom	Validation plane			
Device Position	Edge1			
Band	5200MHz			
Channels	CH40			
Signal	Crest factor: 1.0			




Maximum location: X=6.00, Y=8.00 SAR Peak: 1.18 W/kg


	8
<b>SAR 10g (W/Kg)</b>	0.203563
SAR 1g (W/Kg)	0.473581

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Page 169 of 183

5.8GHz 802.11n HT20
Test Laboratory: AGC Lab
Date: Sep. 12, 2024
802.11a CH157- Tilt-Left

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11n HT20; Duty Cycle: 1:1; Conv.F=1.37; Frequency: 5785MHz; Medium parameters used: f = 5800 MHz;  $\sigma = 5.23mho/m$ ;  $\epsilon = 37.42$ ;  $\rho = 1000$  kg/m³;

Phantom section: Left Section

Ambient temperature (°C): 21.2, Liquid temperature (°C): 20.8

#### SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


· Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32


Configuration/802.11a CH157- Tilt-Left /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/802.11a CH157- Tilt-Left /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm

Area Scan	dx=8mm dy=8mm, h= 5.00 mm	
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm	
Phantom	Left head	
Device Position	Tilt	
Band	5800MHz	
Channels	Middle	
Signal	Crest factor: 1.0	




Maximum location: X=8.00, Y=19.00 SAR Peak: 1.24 W/kg

SAR 10g (W/Kg)	0.191559
SAR 1g (W/Kg)	0.452130





Z (m m) SA R (W/ Kg)	0.00 1.24 57	4.00 0.46 67	6.00 0.24 18	8.00 0.16 37	10.0 0 0.09 67	12.0 0 0.07 57	14.0 0 0.07 87	16.0 0 0.07 54	18.0 0 0.07 09	20.0 0 0.06 89	22.0 0 0.06 62	24.0 0 0.05 88
		1.2 1.0 (\$0.8 0.6 0.4 0.2 0.1		4 6	8 1	0 12 Z (m	14 16 m)	18 20	) 22 2	24 26		





Page 171 of 183

Test Laboratory: AGC Lab Date: Sep. 12, 2024

802.11a CH157-Edge1

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: Wi-Fi; Communication System Band: 802.11a; Duty Cycle: 1:1; Conv.F=1.37; Frequency: 5785MHz; Medium parameters used: f = 5800 MHz;  $\sigma = 5.23 \text{mho/m}$ ;  $\epsilon = 37.42$ ;  $\rho = 1000 \text{ kg/m}^3$ ;

Phantom section: Flat Section

Ambient temperature ( $^{\circ}$ C): 21.2, Liquid temperature ( $^{\circ}$ C): 20.8

#### **SATIMO Configuration:**

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414

· Sensor-Surface: 4mm (Mechanical Surface Detection)


· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32

Configuration/ 802.11a CH157- Edge1 /Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/ 802.11a CH157- Edge1 /Zoom Scan: Measurement grid: dx=4mm,dy=4mm, dz=2mm


Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	7x7x12 dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Edge1
Band	5800MHz
Channels	Middle
Signal	Crest factor: 1.0




Maximum location: X=8.00, Y=6.00 SAR Peak: 1.49 W/kg


	<u> </u>
SAR 10g (W/Kg)	0.251738
SAR 1g (W/Kg)	0.501901

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.











Page 173 of 183

Repeated SAR

Test Laboratory: AGC Lab Date: Sep. 06, 2024

LTE Band 2 Low-Tilt - Right (1 RB#0)

DUT: 4G Smart Phone; Type: AGM\_H\_MAX

Communication System: LTE; Communication System Band: LTE Band 2; Duty Cycle:1:1; Conv.F=2.08; Frequency:1860MHz; Medium parameters used: f = 1900 MHz;  $\sigma = 1.33 \text{mho/m}$ ;  $\epsilon = 41.65$ ;  $\rho = 1000 \text{ kg/m}^3$ ;

Phantom section: Right Section

Ambient temperature ( $^{\circ}$ ): 21.2, Liquid temperature ( $^{\circ}$ ): 20.9

#### SATIMO Configuration:

Probe: SSE2; Calibrated: Apr. 30, 2024; Serial No.: 2023-EPGO-414


Sensor-Surface: 4mm (Mechanical Surface Detection)

· Phantom: SAM twin phantom

· Measurement SW: OpenSAR V4\_02\_32

Configuration/ LTE Band 2 Low - Tilt - Right /Area Scan: Measurement grid: dx=8mm, dy=8mm Configuration/ LTE Band 2 Low - Tilt - Right /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;


Area Scan	dx=8mm dy=8mm, h= 5.00 mm		
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm		
Phantom	Right head		
Device Position	Tilt		
Band	LTE Band 2		
Channels	Low		
Signal	OFDM (Crest factor: 1.0)		




Maximum location: X=9.00, Y=18.00 SAR Peak: 1.76 W/kg


SAR 10g (W/Kg)	0.473200
SAR 1g (W/Kg)	0.986359

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.













## APPENDIX C. TEST SETUP PHOTOGRAPHS

LEFT-CHEEK TOUCH



LEFT-TILT 15°




































Edge 1(Top) 10mm-Hotspot Mode












Edge 3(Bottom) 10mm-Hotspot Mode














## DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN


Note: The position used in the measurement were according to IEEE 1528-2013


















Page 183 of 183

## APPENDIX D. CALIBRATION DATA

Refer to Attached files.

----END OF REPORT----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.