

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: [2A3FK-DC02](#)

EUT Specification

| | |
|-----------------------------------|--|
| EUT | Dash Camera |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others: BLE: 2402-2480MHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm2) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm2) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | 16.04 dBm (0.0402W) |
| Antenna gain (Max) | 2 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

| Operating Mode | Channel Frequency (MHz) | Maximum output power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 20cm (mW/ cm2) | Power density Limits (mW/cm2) |
|----------------|-------------------------|----------------------------|-------------------------|--------------------------|--------------------|----------------------------------|--------------------------------|
| 802.11b | 2412 | 14.12 | 14.12 ± 1 | 15.12 | 2 | 0.0103 | 1 |
| | 2437 | 13.89 | 13.89 ± 1 | 14.89 | 2 | 0.0097 | 1 |
| | 2462 | 12.79 | 12.79 ± 1 | 13.79 | 2 | 0.0076 | 1 |
| 802.11g | 2412 | 14.24 | 14.24 ± 1 | 15.24 | 2 | 0.0105 | 1 |
| | 2437 | 16.04 | 16.04 ± 1 | 17.04 | 2 | 0.0160 | 1 |
| | 2462 | 14.98 | 14.98 ± 1 | 15.98 | 2 | 0.0125 | 1 |
| 802.11n (HT20) | 2412 | 14.30 | 14.30 ± 1 | 15.30 | 2 | 0.0107 | 1 |
| | 2437 | 16.01 | 16.01 ± 1 | 17.01 | 2 | 0.0158 | 1 |
| | 2462 | 15.03 | 15.03 ± 1 | 16.03 | 2 | 0.0126 | 1 |
| 802.11n (HT40) | 2422 | 14.00 | 14.00 ± 1 | 15.00 | 2 | 0.0100 | 1 |
| | 2437 | 13.29 | 13.29 ± 1 | 14.29 | 2 | 0.0085 | 1 |
| | 2452 | 12.64 | 12.64 ± 1 | 13.64 | 2 | 0.0073 | 1 |