

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	ACTTO RETRO WIRELESS KEYBOARD
Model Name	W503(IVORY)
Series Model	W503(MINT), W503(NAVY), W503(PINK), W503(WHITE), W505(IVORY), W505(MINT), W505(NAVY), W505(PINK), W505(WHITE)
FCC ID	2A3GJ-W503

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$$P_t = -3.312 \text{ dBm} = 0.47 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47

§15.247.

The result for RF exposure evaluation $\text{SAR} = (0.47 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.475(\text{GHz})}] = 0.15 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.