

## RF Exposure Evaluation Report

**Report Reference No.**.....: **MTEB22120172-H**  
**FCC ID**.....: **2A3IW-R2-4KPRO**  
 Compiled by  
 ( position+printed name+signature)..: File administrators Alisa Luo  
 Supervised by  
 ( position+printed name+signature)..: Test Engineer Sunny Deng  
 Approved by  
 ( position+printed name+signature)..: Manager Yvette Zhou  
 Date of issue.....: January 09,2023

*Alisa*  
*Sunny*  
*Yvette*

**Representative Laboratory Name.:** **Shenzhen Most Technology Service Co., Ltd.**  
 Address .....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**.....: **Aarna Sales Corporation**  
 Address .....: 1940 N Municipal Way, UNIT 2020, Round Lake, IL 60073

**Test specification/ Standard** .....: **47 CFR Part 1.1307**  
**47 CFR Part 1.1310**  
**KDB447498D01 General RF Exposure Guidance v06**  
 TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**  
 This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description** .....: Car Dash Camera  
 Trade Mark .....: ROVE  
 Manufacturer .....: Shenzhen Samoon Technology Co.,Ltd  
 Model/Type reference.....: R2-4K PRO  
 Listed Models .....: N/A  
 Modulation Type.....: CCK/DSSS/ OFDM  
 Operation Frequency.....: From 2412 - 2462MHz for wifi 2.4G  
 From 5180-5240MHz for wifi 5.2G  
 Hardware Version.....: CHF43-MAN-A1 2020-08-011  
 Software Version .....: V1  
 Rating .....: DC 5.5V(by Super Capacitor)  
 DC 5V (by Car charger)  
 Result.....: **PASS**

# TEST REPORT

Equipment under Test : Car Dash Camera

Model /Type : R2-4K PRO

Listed Models : N/A

Remark : N/A

**Applicant** : **Aarna Sales Corporation**

Address : 1940 N Municipal Way, UNIT 2020, Round Lake, IL 60073

**Manufacturer** : **Shenzhen Samoon Technology Co.,Ltd**

Address : Floor 6, Building 7, Zhongyuntai Science and Technology Industrial  
Factory, Songbai Road, Shiyan Street, Baoan District, Shenzhen  
China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## 1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2023.01.09	Initial Issue	Alisa Luo

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to §1.1307(e)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

#### 2.1.2 Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.1.3 EUT RF Exposure

WIFI 2.4G

Antenna Gain: 3.1dBi

IEEE for 802.11b mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	11.523	$11.523 \pm 1$	12.523
Middle(2437MHz)	11.856	$11.856 \pm 1$	12.856
Highest(2462MHz)	10.523	$10.523 \pm 1$	11.523

IEEE for 802.11g mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	8.892	$8.892 \pm 1$	9.892
Middle(2437MHz)	9.255	$9.255 \pm 1$	10.255
Highest(2462MHz)	8.220	$8.220 \pm 1$	9.220

IEEE for 802.11n(HT20) mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	8.824	$8.824 \pm 1$	9.824
Middle(2437MHz)	8.562	$8.562 \pm 1$	9.562
Highest(2462MHz)	8.998	$8.998 \pm 1$	9.998

IEEE for 802.11n(HT40) mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	5.882	$5.882 \pm 1$	6.882
Middle(2437MHz)	5.843	$5.843 \pm 1$	6.843
Highest(2462MHz)	4.162	$4.162 \pm 1$	5.162

WIFI 5G

Antenna Gain: 3.8dBi

IEEE for 802.11a			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
36	12.55	$12.55 \pm 1$	13.55
40	12.22	$12.22 \pm 1$	13.22
48	13.31	$13.31 \pm 1$	14.31

IEEE for 802.11n(HT20)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
36	11.21	$11.21 \pm 1$	12.21
40	11.20	$11.20 \pm 1$	12.20
48	11.52	$11.52 \pm 1$	12.52

IEEE for 802.11n(HT40)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
38	10.94	$10.94 \pm 1$	11.94
46	10.85	$10.85 \pm 1$	11.85

IEEE for 802.11ac(HT20)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
36	10.51	$10.51 \pm 1$	11.51
40	10.13	$10.13 \pm 1$	11.13
48	9.85	$9.85 \pm 1$	10.85

IEEE for 802.11ac(HT40)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
38	9.87	$9.87 \pm 1$	10.87
46	9.64	$9.64 \pm 1$	10.64

IEEE for 802.11ac(HT80)			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
42	9.52	9.52 ± 1	10.52

Worst case: IEEE for 802.11b mode						
Channel	Maximum Peak Conducted Output Power	Maximum Peak Conducted Output Power	Antenna Gain	Power Density at R = 20 cm	Limit	Result
	(dBm)	(MW)	(dBi)	(mW/cm <sup>2</sup> )		
Lowest (2437MHz)	12.856	19.3	3.1	0.0078	1.0	Pass

Note: 1) Refer to report MTEB22120172-R1 for EUT test Max Conducted average Output Power value.  
 Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (19.3 * 2.04) / (4 * 3.1416 * 20^2) = 0.0078$

Worst case: IEEE for 802.11a						
Channel	Maximum Peak Conducted Output Power	Maximum Peak Conducted Output Power	Antenna Gain	Power Density at R = 20 cm	Limit	Result
	(dBm)	(MW)	(dBi)	(mW/cm <sup>2</sup> )		
Lowest (5180MHz)	12.52	17.87	3.8	0.0084	1.0	Pass

Note: 1) Refer to report MTEB22120172-R1 for EUT test Max Conducted average Output Power value.  
 Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (17.87 * 2.39) / (4 * 3.1416 * 20^2) = 0.0084$

.....**THE END OF REPORT**.....