

# RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	WIRELESS FM TRANSMITTER
Model Name	CZ649
Series Model	BH649, BH649A, BH649B, BH649C, CZ649A, CZ649B, CZ649C
FCC ID	2A3JH-CZ649

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

## 3. CALCULATION

P<sub>+</sub>= -0.365dBm=0.92mW

The value of the Maximum output power P<sub>t</sub> is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(0.92mW / 5mm) .[ $\sqrt{2.402\text{GHz}}$ )]=0.29<3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.