

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | *900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3. Result

| Mode | Frequency (MHz) | Prediction distance (cm) | RF output power | MAX tune-uppower | | MPE (mW/cm ²) | Limit (mW/cm ²) | SAR Test Exclusion |
|------------------|-----------------|--------------------------|-----------------|------------------|-----------|---------------------------|-----------------------------|--------------------|
| | | | dBm | dBm | mW | | | |
| BT | 2441 | 80 | 7.138 | 7.5 | 5.6234 | 0.0001 | 1 | Yes |
| 2.4G WiFi | 2437 | 80 | 21.510 | 22 | 158.4893 | 0.0028 | 1 | Yes |
| UHF | 440 | 80 | 37.115 | 38 | 6309.5734 | 0.1971 | 0.304 | Yes |
| GSM850 | 824.2 | 80 | 25.81 | 26 | 398.1072 | 0.0124 | 0.5495 | Yes |
| GSM1900 | 1850.2 | 80 | 22.81 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| WCDMA B2 | 1852.4 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| WCDMA B4 | 1712.4 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| WCDMA B5 | 826.4 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.5509 | Yes |
| LTE B2 | 1850.7 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| LTE B4 | 1710.7 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| LTE B5 | 824.70 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.5498 | Yes |
| LTE B7 | 2502.50 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| LTE B12 | 699.70 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.4665 | Yes |
| LTE B13 | 779.50 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.5197 | Yes |
| LTE B25 | 1850.7 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| LTE B26(814-824) | 814.7 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.5431 | Yes |
| LTE B26(824-849) | 824.7 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 0.5498 | Yes |
| LTE B38 | 2572.5 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |
| LTE B41 | 2498.5 | 80 | 25.00 | 26 | 398.1072 | 0.0124 | 1.0000 | Yes |

Maximum Simultaneous transmission MPE Ratios for BT+WIFI +UHF+WWAN:

| Max MPE ratio _{BT} /Limit | Max MPE ratio _{WIFI} /Limit | Max MPE ratio _{UHF} /Limit | Max MPE ratio _{2/3/4G} /Limit | ΣMPE ratios | Limit | Result |
|------------------------------------|--------------------------------------|-------------------------------------|--|-------------|-------|--------|
| 0.0001 | 0.0028 | 0.1971 | 0.0124 | 0.2124 | 1 | PASS |

BT&WIFI Antenna Gain: 1.51dBi, 1.42(numeric)

UHF Antenna Gain: 4dBi, 2.51(numeric)

2/3/4G Antenna Gain: 4dBi, 2.51(numeric), (2/3/4GContains FCC ID: XMR201903EG25G).

In summary, SAR evaluation is not required.