

TEST REPORT

Product Name	:	Wireless Carplay Activator
Brand Mark	:	N/A
Model No.	:	ZCWS-C06
Extension model	:	ZCWS-C01~C18
FCC ID	:	2A3NH-ZCWS-C06
Report Number	:	BLA-EMC-202111-A6703
Date of Sample Receipt	:	2021/11/11
Date of Test	:	2021/12/8 to 2021/12/22
Date of Issue	:	2021/12/22
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Guangzhou Loyal Defender Electronics Co., Ltd.
1-4F, NO.3 Jiahe Street, PengShang ZhiFu Road, Baiyun District,
Guangzhou, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Jozu
Blue.Zhong

Approved by:

Review by:

Date:

Sweety

2021/12/22



REPORT REVISE RECORD

Version No.	Date	Description
00	2021/12/22	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	5
2	GENERAL INFORMATION.....	6
3	GENERAL DESCRIPTION OF E.U.T.....	6
4	TEST ENVIRONMENT.....	7
5	TEST MODE.....	7
6	MEASUREMENT UNCERTAINTY.....	7
7	DESCRIPTION OF SUPPORT UNIT.....	8
8	LABORATORY LOCATION.....	8
9	TEST INSTRUMENTS LIST.....	9
10	CONDUCTED PEAK OUTPUT POWER.....	12
10.1	LIMITS.....	12
10.2	BLOCK DIAGRAM OF TEST SETUP.....	12
10.3	TEST DATA.....	13
11	MINIMUM 6DB BANDWIDTH.....	14
11.1	LIMITS.....	14
11.2	BLOCK DIAGRAM OF TEST SETUP.....	14
11.3	TEST DATA.....	14
12	ANTENNA REQUIREMENT.....	15
12.1	CONCLUSION.....	15
13	CONDUCTED BAND EDGES MEASUREMENT.....	16
13.1	LIMITS.....	16
13.2	BLOCK DIAGRAM OF TEST SETUP.....	16
13.3	TEST DATA.....	17
14	RADIATED SPURIOUS EMISSIONS.....	18
14.1	LIMITS.....	18
14.2	BLOCK DIAGRAM OF TEST SETUP.....	19
14.3	PROCEDURE.....	19
14.4	TEST DATA.....	21
15	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	29

15.1	LIMITS.....	29
15.2	BLOCK DIAGRAM OF TEST SETUP.....	30
15.3	PROCEDURE.....	30
15.4	TEST DATA.....	32
16	CONDUCTED SPURIOUS EMISSIONS.....	36
16.1	LIMITS.....	36
16.2	BLOCK DIAGRAM OF TEST SETUP.....	36
16.3	TEST DATA.....	37
17	POWER SPECTRUM DENSITY.....	38
17.1	LIMITS.....	38
17.2	BLOCK DIAGRAM OF TEST SETUP.....	38
17.3	TEST DATA.....	38
18	APPENDIX.....	39
APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....		54
APPENDIX B: PHOTOGRAPHS OF EUT.....		56

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass

2 GENERAL INFORMATION

Applicant	Guangzhou Loyal Defender Electronics Co., Ltd.
Address	1-4F, NO.3 Jiahe Street, PengShang ZhiFu Road, Baiyun District, Guangzhou, China
Manufacturer	Guangzhou Loyal Defender Electronics Co., Ltd.
Address	1-4F, NO.3 Jiahe Street, PengShang ZhiFu Road, Baiyun District, Guangzhou, China
Factory	Guangzhou Loyal Defender Electronics Co., Ltd.
Address	1-4F, NO.3 Jiahe Street, PengShang ZhiFu Road, Baiyun District, Guangzhou, China
Product Name	Wireless Carplay Activator
Test Model No.	ZCWS-C06
Extension model	ZCWS-C01~C18
Remark	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	USBdongle_TF V:05 20210701
Software Version	tina_v459-carplay-aic8800-1011-noid
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	4dBi(Provided by the applicant)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC5V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation.

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30MHz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	Hasee	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Power Spectrum Density					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022


10 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

10.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


11 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

11.1 LIMITS

Limit: ≥ 500 kHz

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

12 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


12.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 4dBi.




13 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

13.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

13.2 BLOCK DIAGRAM OF TEST SETUP



13.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

14 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

14.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

14.4 TEST DATA

[TestMode: TX below 1G]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202112-A67
EUT: Wireless Carplay Activator	Test Engineer: York
M/N: ZCWS-C06	Temperature:
S/N:	Humidity:
Test Mode: BLE mode	Test Voltage:
Note:	Test Data: 2021-12-17 09:42:42




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	60.798MHz	40.0	24.2	-15.8	0.9	23.3	QP	Ver	100.0	299.0
2*	135.609MHz	43.5	24.3	-19.2	0.8	23.5	QP	Ver	100.0	238.0
3*	243.764MHz	46.0	23.9	-22.1	1.1	22.8	QP	Ver	100.0	25.0
4*	399.934MHz	46.0	37.1	-8.9	9.8	27.3	QP	Ver	100.0	0.0
5*	535.128MHz	46.0	33.8	-12.2	4.4	29.4	QP	Ver	100.0	312.0
6*	800.059MHz	46.0	40.2	-5.8	6.0	34.2	QP	Ver	100.0	220.0

Test Result: Pass

[TestMode: TX below 1G]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202112-A67
EUT: Wireless Carplay Activator	Test Engineer: York
M/N: ZCWS-C06	Temperature:
S/N:	Humidity:
Test Mode: BLE mode	Test Voltage:
Note:	Test Data: 2021-12-17 09:51:08



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	55.099MHz	40.0	24.9	-15.1	1.3	23.6	QP	Hor	200.0	334.0
2*	132.578MHz	43.5	24.1	-19.4	0.8	23.3	QP	Hor	100.0	0.0
3*	203.388MHz	43.5	31.9	-11.6	11.1	20.8	QP	Hor	100.0	0.0
4*	399.934MHz	46.0	39.7	-6.3	12.4	27.3	QP	Hor	100.0	0.0
5*	587.750MHz	46.0	33.0	-13.0	2.1	30.9	QP	Hor	200.0	91.0
6*	799.938MHz	46.0	38.9	-7.1	4.7	34.2	QP	Hor	100.0	307.0

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data :#13

2021/12/21

15:56:43



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-L

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3843.500	43.03	7.12	50.15	74.00	-23.85	peak
2		4804.000	47.02	3.71	50.73	74.00	-23.27	peak
3		7206.000	40.21	5.96	46.17	74.00	-27.83	peak
4		8308.500	41.67	8.25	49.92	74.00	-24.08	peak
5		9608.000	39.62	9.29	48.91	74.00	-25.09	peak
6	*	11293.000	39.22	11.91	51.13	74.00	-22.87	peak

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data :#14

2021/12/21

15:59:02



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: 0%RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-L

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3608.500	42.58	7.80	50.38	74.00	-23.62	peak	
2		4807.000	50.88	3.71	54.59	74.00	-19.41	peak	
3	*	4807.000	47.98	3.71	51.69	54.00	-2.31	AVG	
4		7206.000	40.18	5.96	46.14	74.00	-27.86	peak	
5		8026.500	41.06	7.98	49.04	74.00	-24.96	peak	
6		9608.000	39.10	9.29	48.39	74.00	-25.61	peak	
7		11128.500	39.64	12.02	51.66	74.00	-22.34	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data :#15

2021/12/21

16:14:25



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-M

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3655.500	42.26	7.76	50.02	74.00	-23.98	peak
2		4877.500	46.63	3.37	50.00	74.00	-24.00	peak
3		7326.000	39.61	6.44	46.05	74.00	-27.95	peak
4		8026.500	41.18	7.98	49.16	74.00	-24.84	peak
5		9768.000	38.24	9.63	47.87	74.00	-26.13	peak
6	*	11340.000	40.00	11.85	51.85	74.00	-22.15	peak

*:Maximum data x:Over limit !:over margin

Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data :#16

2021/12/21

16:19:14



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-M

Note:-


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3655.500	44.16	7.76	51.92	74.00	-22.08	peak
2	*	4877.500	49.12	3.37	52.49	74.00	-21.51	peak
3		7323.000	39.48	6.43	45.91	74.00	-28.09	peak
4		8261.500	40.65	8.23	48.88	74.00	-25.12	peak
5		9768.000	38.21	9.63	47.84	74.00	-26.16	peak
6		11692.500	39.79	11.82	51.61	74.00	-22.39	peak

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMethod: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement


Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-H

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3632.000	42.37	7.77	50.14	74.00	-23.86	peak
2	*	4948.000	48.41	3.65	52.06	74.00	-21.94	peak
3		7440.000	39.70	6.86	46.56	74.00	-27.44	peak
4		7815.000	41.54	7.72	49.26	74.00	-24.74	peak
5		9920.000	37.16	10.16	47.32	74.00	-26.68	peak
6		11481.000	39.50	11.88	51.38	74.00	-22.62	peak

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data :#20

2021/12/21

16:36:59



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-H

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3843.500	43.58	7.12	50.70	74.00	-23.30	peak
2		4948.000	46.68	3.65	50.33	74.00	-23.67	peak
3		7440.000	39.99	6.86	46.85	74.00	-27.15	peak
4		8073.500	41.47	8.04	49.51	74.00	-24.49	peak
5		9920.000	38.55	10.16	48.71	74.00	-25.29	peak
6	*	11457.500	39.93	11.84	51.77	74.00	-22.23	peak

*:Maximum data x:Over limit !:over margin

Reference Only

Test Result: Pass

15 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

15.4 TEST DATA

[TestMode: TX low channel]; [Polarity: Vertical]



*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]


Radiated Emission Measurement

Project No.: RE

Data :#12

2021/12/21

15:53:52



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-L

Note:-


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		2310.000	45.66	-3.93	41.73	74.00	-32.27	peak	
2	*	2390.000	49.30	-3.58	45.72	74.00	-28.28	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only

Test Result: Pass

[TestMethod: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement


Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-H

Note:

No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	53.27	-3.14	50.13	74.00	-23.87	peak
2		2500.000	46.83	-3.08	43.75	74.00	-30.25	peak

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]


Radiated Emission Measurement

Project No.: RE

Data :#18

2021/12/21

16:27:08



Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Wireless Carplay Activator

M/N: ZCWS-C06

Mode: BLE-TX-H

Note:-

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		D	Detector
			MHz	dBuV	dB/m	dBuV/m		
1		2483.500	57.88	-3.14	54.74	74.00	-19.26	peak
2	*	2483.500	49.77	-3.14	46.63	54.00	-7.37	AVG
3		2500.000	48.71	-3.08	45.63	74.00	-28.37	peak

*:Maximum data x:Over limit !:over margin

(Reference Only

Test Result: Pass


16 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

16.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


17 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25 °C
Humidity	60%

17.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


18 APPENDIX

Appendix1


Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	0.08	30	Pass
NVNT	BLE	2442	Ant1	0.263	30	Pass
NVNT	BLE	2480	Ant1	0.769	30	Pass


Power NVNT BLE 2402MHz Ant1



Power NVNT BLE 2442MHz Ant1





Power NVNT BLE 2480MHz Ant1




-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant1	0.568	0.5	Pass
NVNT	BLE	2442	Ant1	0.551	0.5	Pass
NVNT	BLE	2480	Ant1	0.562	0.5	Pass

-6dB Bandwidth NVNT BLE 2402MHz Ant1

-6dB Bandwidth NVNT BLE 2442MHz Ant1



-6dB Bandwidth NVNT BLE 2480MHz Ant1




Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE	2402	Ant1	1.057025643
NVNT	BLE	2442	Ant1	1.054903132
NVNT	BLE	2480	Ant1	1.057527805

OBW NVNT BLE 2402MHz Ant1



OBW NVNT BLE 2442MHz Ant1



OBW NVNT BLE 2480MHz Ant1



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-11.371	8	Pass
NVNT	BLE	2442	Ant1	-11.114	8	Pass
NVNT	BLE	2480	Ant1	-10.704	8	Pass

PSD NVNT BLE 2402MHz Ant1

PSD NVNT BLE 2442MHz Ant1



PSD NVNT BLE 2480MHz Ant1




Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-55.48	-30	Pass
NVNT	BLE	2480	Ant1	-50.51	-30	Pass

Band Edge NVNT BLE 2402MHz Ant1 Ref


Band Edge NVNT BLE 2402MHz Ant1 Emission



Band Edge NVNT BLE 2480MHz Ant1 Ref



Band Edge NVNT BLE 2480MHz Ant1 Emission




Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-44.26	-30	Pass
NVNT	BLE	2442	Ant1	-44.55	-30	Pass
NVNT	BLE	2480	Ant1	-40.11	-30	Pass

Tx. Spurious NVNT BLE 2402MHz Ant1 Ref


Tx. Spurious NVNT BLE 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 2442MHz Ant1 Ref




Tx. Spurious NVNT BLE 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 2480MHz Ant1 Emission



APPENDIX A: PHOTOGRAPHS OF TEST SETUP



Radiated Emissions which fall in the restricted bands



BlueX

APPENDIX B: PHOTOGRAPHS OF EUT

Reference to the test report No. BLA-EMC-202111-A6701

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.