

# **FCC Test Report**

Report No.: AGC13372240201FR01

**FCC ID** : 2A300-P2

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Two Way Radio

**BRAND NAME** : RETEVIS

**MODEL NAME** : P2, EZTalk2

**APPLICANT**: Shenzhen Ysair Technology Co., LTD

**DATE OF ISSUE** : Mar. 13, 2024

**STANDARD(S)** : FCC Part 95 Subpart E

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 53


# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 13, 2024	Valid	Initial Release



# **Table of Contents**

1. General Information	5
2. Product Information	e
2.1 Product Technical Description	6
2.2 Test Frequency List	7
2.3 Related Submittal(S) / Grant (S)	8
2.4 Test Methodology	8
2.5 Calculation of Emission Indicators	8
2.6 Special Accessories	8
2.7 Equipment Modifications	8
2.8 Antenna Requirement	9
3. Test Environment	10
3.1 Address of The Test Laboratory	10
3.2 Test Facility	10
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	11
3.5 List of Equipment Used	12
4. System Test Configuration	12
4.1 EUT Configuration	14
4.2 EUT Exercise	14
4.3 Configuration of Tested System	14
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	14
5. Description of Test Modes	16
6. Frequency Stability	17
6.1 Provisions Applicable	17
6.2 Measurement Procedure	17
6.3 Measurement Setup	17
6.4 Measurement Result	
7. 26dB Emission Bandwidth and 99% Occupied Bandwidth	19
7.1 Provisions Applicable	19
7.2 Measurement Procedure	19
7.3 Measurement Setup	19
7.4 Measurement Result	20
8. Spurious Radiated Emission	22
8.1 Provisions Applicable	22
8.2 Measurement Procedure	22
8.3 Measurement Setup	23
8.4 Measurement Result	
8.5 Emission Mask Measurement Part	
9. Modulation Characteristics  Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspect Stamp" is deemed to be invalid. Conving or experting portion of or altering the content of the report is not permitted without the written authorization of AGC. The test	36





	9.1 Provisions Applicable	. 36
	9.2 Measurement Procedure	. 36
	9.3 Measurement Setup	. 36
	9.4 Measurement Result	. 37
10	. Maximum Transmitter Power	. 41
	10.1 Provisions Applicable	. 41
	10.2 Measurement Procedure	. 41
	10.3 Measurement Setup	. 42
	10.4 Measurement Result	. 44
11.	. Spurious Emission on Antenna Port	46
	11.1 Provisions Applicable	. 46
	11.2 Measurement Procedure	46
	11.3 Measurement Setup	. 46
	11.4 Measurement Result	. 47
12	. Audio Low Pass Filter Response	. 50
	12.1 Provisions Applicable	. 50
	12.2 Measurement Procedure	. 50
	12.3 Measurement Setup	. 50
	12.4 Measurement Result	. 51
Αp	pendix I: Photographs of Test Setup	. 53
Αp	pendix II: Photographs of Test EUT	. 53



Report No.: AGC13372240201FR01 Page 5 of 53

# 1. General Information

	, , , , , , , , , , , , , , , , , , , ,		
Applicant	Shenzhen Ysair Technology Co., LTD		
Address	Room 403, 4th Floor, Building 4, Yunli intelligent Park, No. 3 Changfa Middle		
/ ludi 033	Road, Yangmei Community, Bantian Street, Longgang District, Shenzhen, China		
Manufacturer	Shenzhen Ysair Technology Co., LTD		
Address	Room 403, 4th Floor, Building 4, Yunli intelligent Park, No. 3 Changfa Middle		
, tadi 600	Road, Yangmei Community, Bantian Street, Longgang District, Shenzhen, China		
Factory	N/A		
Address	N/A		
Product Designation	Two Way Radio		
Brand Name	RETEVIS		
Test Model	P2		
Series Model	EZTalk2		
Difference Description	Only the model name is different.		
Date of receipt of test item	Feb. 03, 2024		
Date of Test	Feb. 03, 2024~Mar. 13, 2024		
Deviation from Standard	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Test Report Form No	AGCER-FCC-GMRS-V1		
Test Report Form No	AGCER-FCC-GMRS-V1		

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhang	
	Bibo Zhang (Project Engineer)	Mar. 13, 2024
Reviewed By	Calvin Lin	
	Calvin Liu (Reviewer)	Mar. 13, 2024
Approved By	Max Zhang	
	Max Zhang Authorized Officer	Mar. 13, 2024



Page 6 of 53

## 2. Product Information

# 2.1 Product Technical Description

Communication Type	Voice / Tone only				
	462.5500MHz-462.7250MHz (GMRS 462 MHz main channels)				
0 " 5 5	462.5625MHz-462.7125MHz (GMRS 462 MHz interstitial channels)				
Operation Frequency Range	467.5500MHz-467.7250MHz (GMRS 467 MHz main channels)				
	467.5625MHz-467.7125MHz (GMRS 467 MHz interstitial channels)				
Hardware Version	Ver 1.2				
Software Version	V1.01				
Modulation Type	FM				
Channel Separation	12.5 KHz/25 KHz				
Emission Bandwidth	10.52 kHz(5W-12.5KHz), 15.71kHz(5W-25KHz) 10.52 kHz(0.5W-12.5KHz)				
Emission Designator	11K0F3E/16K0F3E.				
Number of Channels:	30 Channels				
Rated Output Power	5W/0.5W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)				
Maximum Transmitter Power	GMRS: 36.29dBm (5W-12.5KHz) GMRS: 26.89dBm (0.5W-12.5KHz)				
Maximum Hansmiller Fower	GMRS: 36.35dBm (5W-25KHz)				
Antenna Designation	Detachable Antenna				
Antenna Gain	2.15dBi				
Frequency Tolerance	1.097ppm				
Power Supply	DC 7.4V 2500mAh				



Page 7 of 53

# 2.2 Test Frequency List

According to ANSI C63.26 section 5.1.2.1:

Measurements of transmitters shall be performed and, if required, reported for each frequency band in which the EUT can be operated with the device transmitting at the number of frequencies in each band specified in Table 2.

Frequency range Over which EUT operates	Number of Frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

Channel. No	CH. Freq	Rated Power	CH. No	CH. Freq	Rated Power
1	462.5625		15	462.5500	
2	462.5875		16	462.5750	
3	462.6125		17	462.6000	
4	462.6375	5W	18	462.6250	5W
5	462.6625		19	462.6500	SVV
6	462.6875		20	462.6750	
7	462.7125		21	462.7000	
8	467.5625		22	462.7250	
9	467.5875		23	467.5500	
10	467.6125		24	467.5750	
11	467.6375	0.5W	25	467.6000	
12	467.6625		26	467.6250	E\A/
13	467.6875		27	467.6500	5W
14	467.7125		28	467.6750	
			29	467.7000	
	<del></del>			467.7250	



Page 8 of 53

# 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2A300-P2**, filing to comply with Part 2, Part 95 of the Federal Communication Commission rules.

## 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Identity Document Title			
1	FCC 47 CFR Part 95	Personal Radio Services			
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations			
3	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services			
4	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards			
5	KDB 888861 D01	888861 D01 Part 95 GMRS FRS v01			

#### 2.5 Calculation of Emission Indicators

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

## For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

BW = 2(M+D) = 2\*(3.0 kHz + 2.5 kHz) = 11 kHz = 11KO

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

# For FM Mode (Channel Spacing: 25kHz)

Emission Designator 16K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 5.0 kHz deviation.

BW = 2(M+D) = 2\*(3.0 kHz + 5.0 kHz) = 16 kHz = 16K0

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.

# 2.6 Special Accessories

Not available for this EUT intended for grant.

#### 2.7 Equipment Modifications

Not available for this EUT intended for grant.



Page 9 of 53

#### 2.8 Antenna Requirement

## Excerpt from §95.1787 of the FCC Rules/Regulations:

The antenna of each GMRS transmitter type must meet the following requirements.

- This GMRS device has a fixed antenna port
- This GMRS equipment is a mobile station or a fixed station, which can be connected to an external antenna

Conclusion: The unit complies with the requirement of §95.1787.



Page 10 of 53

#### 3. Test Environment

#### 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

# A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

# FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

## IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Report No.: AGC13372240201FR01 Page 11 of 53

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions	
Temperature range (°C)	15 - 35	-30 - 50	
Relative humidty range	20 % - 75 %	20 % - 75 %	
Pressure range (kPa)	86 - 106	86 - 106	
Power supply	DC 7.4V	LV DC 6.29V/ HV DC 8.51V	

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

## 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty		
Frequency stability	±0.5%		
Transmitter power conducted	±0.8dB		
Transmitter power Radiated	±1.3dB		
Conducted spurious emission 9kHz-40 GHz	±2.7dB		
Conducted Emission	±3.2 dB		
Radiated Emission below 1GHz	±3.9 dB		
Radiated Emission above 1GHz	±4.8 dB		
Occupied Channel Bandwidth	±2 %		
FM deviation	±2 %		
Audio level	±0.98dB		
Low Pass Filter Response	±0.65dB		
Modulation Limiting	0.42 %		
Transient Frequency Behavior	6.8 %		



Report No.: AGC13372240201FR01 Page 12 of 53

# 3.5 List of Equipment Used

RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-ER-E086	Spectrum Analyzer	KEYSIGHT	N9020A	MY53300860	2023-06-01	2024-05-31
	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2023-06-02	2024-06-01
$\boxtimes$	AGC-ER-E059	Signal Generator	Agilent	N5182B	MY53050647	2024-02-01	2025-01-31
	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2023-06-01	2024-05-31
$\boxtimes$	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2022-08-03	2024-08-02
$\boxtimes$	AGC-EM-A007	30dB Attenuator	Weinachel	58-30-33	ML030	2023-06-01	2024-05-31
$\boxtimes$	AGC-EM-E040	Directional coupler	Werlatone	C5571-10	99463	2024-02-01	2025-01-31
$\boxtimes$	1	RF Connection Cable	N/A	1#	N/A	Each time	N/A
		RF Connection Cable	N/A	2#	N/A	Each time	N/A

• F	Radiated Spurious Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
$\boxtimes$	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
$\boxtimes$	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMW500	120909	2023-07-05	2024-07-04
	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2022-03-07	2024-03-06
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
$\boxtimes$	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023-01-05	2025-01-04
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22
	AGC-EM-E102	Broadband Ridged Horn Antenna	ETS	3117	00154520	2023-06-03	2024-06-02
	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-11-13	2024-11-12
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
	AGC-EM-E021	Pre-amplifier	MITEQ	AM-4A-000115	1465421	2022-06-08	2024-06-07
$\boxtimes$	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2023-06-01	2024-05-31
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08
$\boxtimes$	AGC-EM-A088	UHF Filter	Microwave	N26460M1	498705	2023-06-01	2024-05-31
	AGC-EM-A089	VHF Filter	Microwave	N25155M2	498703	2023-06-01	2024-05-31



Page 13 of 53

Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
$\boxtimes$	AGC-EM-S004	RE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS32-RE)	4.0.0.0



Page 14 of 53

# 4. System Test Configuration

# 4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

# 4.3 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

# 4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

□ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Adapter	HW-200440C00	Huawei	Input(AC):100V-240V 50/60Hz 2.4A Output(DC): 5V/3A	N/A

## □ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	BL89	RETEVIS	DC 7.4V 2500mAh	N/A
2	Charger	N/A	RETEVIS	Input: DC 5V 1000mA Output: DC 9.3V 800-850mA	N/A
3	USB Cable	N/A	N/A	N/A	1.0m unshielded
4	Antenna	N/A	N/A	N/A	N/A
5	Back Clip	N/A	N/A	N/A	N/A
6	Lanyard	N/A	N/A	N/A	0.8m unshielded



Page 15 of 53

# 4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	FCC 47 CFR PART 95	Antenna Equipment	Pass
2	§ 95.1767& 2.1046(a)	Maximum Transmitter Power	Pass
3	§95.1775& 2.1047(a) (b)	Modulation Limit	Pass
4	§95.1775& 2.1047(a)	Audio Frequency Response	Pass
4	§95.1775(e)	Audio Low Pass Filter Response	Pass
5	§95.1773& 2.1049	26dB Emission Bandwidth and 99% Occupied Bandwidth	Pass
6	§95.1779& 2.1049	Emission Mask	Pass
7	§95.1765& 2.1055(a) (1)	Frequency Stability	Pass
9	§95.1779& 2.1051	Spurious Emission on Antenna Port	Pass
10	§95.1779& 2.1053	Spurious Radiated Emission	Pass



Page 16 of 53

# 5. Description of Test Modes

The EUT (**Two Way Radio**) has been tested under normal operating condition. (GMRS TX) are chosen for testing at each channel separation.

No.	Test Mode Description Channel Separation			
1	GMRS TX Channel 4	12.5 kHz/25 kHz		
2	GMRS TX Channel 11	12.5 kHz		
3	GMRS TX Channel 19	12.5 kHz/25 kHz		
4	GMRS TX Channel 27	12.5 kHz/25 kHz		

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details



Page 17 of 53

# 6. Frequency Stability

#### 6.1 Provisions Applicable

Standard Applicable [Part 95.1765] The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

GMRS: The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth of 12.5 kHz or less must remain within 2.5 ppm

The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth greater than 12.5 kHz must remain within 5 ppm

#### **6.2 Measurement Procedure**


## 6.2.1 Frequency stability versus environmental temperature

- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- 2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz.Record this frequency as reference frequency.
- 3. Set the temperature of chamber to 50°C. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- 4. Repeat step 2 with a 10℃ decreased per stage until the lowest temperature -30℃ is measured, record all measured frequencies on each temperature step.

## 6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15℃ to 25℃.
   Otherwise, an environment chamber set for a temperature of 20℃ shall be used. The EUT shall be powered by DC 7.4V.
- 2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- 3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

#### 6.3 Measurement Setup





Report No.: AGC13372240201FR01 Page 18 of 53

**6.4 Measurement Result** 

12.5 kHz Channel Separation, FM modulation, Assigned Frequency For GMRS							
Test conditions			Frequency	error (ppm)			
Voltage	Temp		Test Frequ	ency (MHz)		Limit (ppm)	Result
(V)	(℃)	462.6375	462.6500	467.6500	467.6375	(PPIII)	
	-30	0.711	0.653	0.581	0.895		
	-20	0.504	0.530	1.061	0.516		
	-10	0.876	0.813	1.083	0.480		
	0	1.007	0.829	0.651	0.439		
7.40	10	0.558	0.595	1.031	0.793		
	20	1.033	0.984	0.777	0.692	2.5	Pass
	30	0.637	0.593	0.918	0.305		
	40	0.855	0.971	1.047	0.783		
	50	1.005	1.097	0.562	0.959		
8.51	20	0.701	0.950	0.687	0.475		
6.29	20	0.964	0.714	0.811	0.563	]	

	25 kHz Channel Separation, FM modulation, Assigned Frequency For GMRS						
Test conditions		F	requency error (ppm)		Limit		
Voltage	Temp	-	Test Frequency (MHz)				
(V)	(℃)	462.6375	462.6500	467.6500	(ppm)		
	-30	0.301	0.653	0.924			
	-20	1.022	0.832	0.843			
	-10	0.599	0.687	0.678			
	0	1.054	0.884	0.809			
7.40	10	0.971	1.099	1.028			
	20	0.923	0.991	0.888	5	Pass	
	30	0.858	0.776	0.661			
	40	1.063	0.746	0.985			
	50	1.064	0.997	0.639			
8.51	20	0.895	0.778	0.794	]		
6.29	20	0.979	0.904	0.639	]		



Report No.: AGC13372240201FR01 Page 19 of 53

# 7. 26dB Emission Bandwidth and 99% Occupied Bandwidth

## 7.1 Provisions Applicable

FCC Part 95.1773: GMRS: Main channels. The authorized bandwidth is 20 kHz for GMRS transmitters operating on any of the 462 MHz main channels, or any of the 467 MHz main channels.


Interstitial channels. The authorized bandwidth is 20 kHz for GMRS transmitters operating on any of the 462 MHz interstitial channels, and is 12.5 kHz for GMRS transmitters operating on any of the 467 MHz interstitial channels.


Occupied Bandwidth: The EUT was connected to the audio signal generator and the spectrum analyzer via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyzer.

#### 7.2 Measurement Procedure

- The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.
- 2. Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).
- 3. Spectrum set as follow:
- 4. Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=300Hz, VBW=1KHz, Sweep = auto,
- 5. Detector function = peak, Trace = max hold
- 6. Set 99% Occupied Bandwidth and 26dB Emission Bandwidth.
- 7. Measure and record the results in the test report.

#### 7.3 Measurement Setup









#### 7.4 Measurement Result

Emission Bandwidth Measurement Result-GMRS				
Operating Frequency		12.5 kHz Channel Sepa	ration	
Operating Frequency	Occupied Bandwidth	Emission Bandwidth	Limits	Result
462.6375 MHz	9.949 kHz	10.48 kHz	20.0 kHz	Pass
462.6500 MHz	9.951 kHz	10.52 kHz	20.0 kHz	Pass
467.6500 MHz	9.951 kHz	10.51 kHz	20.0 kHz	Pass
467.6375 MHz	9.965 kHz	10.52 kHz	12.5 kHz	Pass

#### Test plot as follows:








Emission Bandwidth Measurement Result-GMRS					
Operating Frequency	25 kHz Channel Separation				
Operating Frequency	Occupied Bandwidth	Emission Bandwidth	Limits	Result	
462.6375 MHz	15.049 kHz	15.71 kHz	20 kHz	Pass	
462.6500 MHz	15.026 kHz	15.60 kHz	20 kHz	Pass	
467.6500 MHz	15.034 kHz	15.70 kHz	20 kHz	Pass	

# Test plot as follows:





Report No.: AGC13372240201FR01 Page 22 of 53

# 8. Spurious Radiated Emission

# 8.1 Provisions Applicable

Standard Applicable [FCC Part 95.1779] According to FCC section 95.1779, the unwanted emission should be attenuated below TP by at least 43+10 log (Transmit Power) dB

#### **8.2 Measurement Procedure**

Each GMRS transmitter type must be designed to comply with the applicable unwanted emissions limits in this section.

a) Emission masks. Emission masks applicable to transmitting equipment in the GMRS are defined by the requirements in the following table. The numbers in the attenuation requirements column refer to rule paragraph numbers under paragraph (b) of this section.

Emission types filter	Attenuation requirements
A1D, A3E, F1D, G1D, F2D, F3E, G3E with audio filter	(1), (2), (7)
A1D, A3E, F1D, G1D, F3E, G3E without audio filter	(3), (4), (7)
H1D, J1D, R1D, H3E, J3E, R2E	(5), (6), (7)

- 1) Filtering noted for GMRS transmitters refers to the requirement in §95.1775(e).
- 2) Unwanted emission power may be measured as either mean power or peak envelope power, provided that the transmitter output power is measured the same way.
- b) Attenuation requirements. The power of unwanted emissions must be attenuated below the transmitter output power in Watts (P) by at least:
- 25 dB (decibels) on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.
- 2) 35 dB on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 250% of the authorized bandwidth.
- 3) 83 log (fd ÷ 5) dB on any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5 kHz up to and including 10 kHz.
- 4) 116 log (fd ÷ 6.1) dB or 50 + 10 log (P) dB, whichever is the lesser attenuation, on any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz), of more than 10 kHz up to and including 250% of the authorized bandwidth.
- 5) 25 dB on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 150% of the authorized bandwidth.
- 6) 35 dB on any frequency removed from the center of the authorized bandwidth by more than 150% up to and including 250% of the authorized bandwidth.
- 7) 43 + 10 log (P) dB on any frequency removed from the center of the authorized bandwidth by more than 250%.




Report No.: AGC13372240201FR01 Page 23 of 53

#### Detailed Overview of the Test Method is as Follows:


- 1) EUT was placed on a 0.8 or 1.5meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- 2) A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3) The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- 4) The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5) A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (PcI) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test
- 6) The measurement results are obtained as described below: Power(EIRP)=PMea- PAg Pcl Ga The measurement results are amend as described below:Power(EIRP)=PMea- Pcl Ga
- 7) This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 8) ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.
- 9) Test the EUT in the lowest channel, the middle channel the Highest channel


#### 8.3 Measurement Setup







# Radiated Emissions 30MHz to 1GHz Test setup





Radiated Emissions Above 1GHz Test setup








Page 25 of 53


#### 8.4 Measurement Result

Preliminary calculation	Final Result
At least 43+10 log (P) =43+10log (5) =49.99 (dB)	Limit=P- Preliminary calculation=36.99-49.99=-13 dBm
At least 43+10 log (P) =43+10log (0.5) =39.99 (dB)	Limit=P- Preliminary calculation=26.99-39.99=-13 dBm


- 1. Factor=Antenna Factor + Cable loss. (Below 1GHz)
- 2. Factor=Antenna Factor+ Cable loss -Pre-amplifier. (Above 1 GHz)
- 3. Margin=Limit- Level









NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-59.14	-21.09	-13.00	8.09	38.05	265	Horizontal
2	1387.7888	-18.61	-22.72	-13.00	9.72	-4.11	1	Horizontal
3	2313.7814	-30.18	-27.84	-13.00	14.84	2.34	321	Horizontal
4	2775.6026	-35.28	-33.31	-13.00	20.31	1.97	77	Horizontal
5	3238.5989	-28.55	-26.66	-13.00	13.66	1.89	348	Horizontal
6	4626.4126	-38.04	-33.47	-13.00	20.47	4.57	311	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-56.33	-18.28	-13.00	5.28	38.05	2	Vertical
2	1387.7888	-18.49	-22.60	-13.00	9.60	-4.11	0	Vertical
3	2313.7814	-30.45	-28.11	-13.00	15.11	2.34	303	Vertical
4	2775.6026	-35.54	-33.57	-13.00	20.57	1.97	66	Vertical
5	3238.5989	-28.54	-26.65	-13.00	13.65	1.89	331	Vertical
6	4626.4126	-37.81	-33.24	-13.00	20.24	4.57	293	Vertical









NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	935.98	-60.23	-21.99	-13.00	8.99	38.24	265	Horizontal
2	1403.0653	-29.65	-33.76	-13.00	20.76	-4.11	350	Horizontal
3	1870.7621	-29.97	-29.54	-13.00	16.54	0.43	57	Horizontal
4	2338.4588	-30.74	-28.37	-13.00	15.37	2.37	321	Horizontal
5	3273.8524	-30.07	-28.13	-13.00	15.13	1.94	341	Horizontal
6	3741.5492	-39.04	-36.65	-13.00	23.65	2.39	181	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	935.98	-54.98	-16.74	-13.00	3.74	38.24	4	Vertical
2	1403.0653	-29.47	-33.58	-13.00	20.58	-4.11	334	Vertical
3	1870.7621	-30.01	-29.58	-13.00	16.58	0.43	40	Vertical
4	2338.4588	-30.68	-28.31	-13.00	15.31	2.37	316	Vertical
5	3273.8524	-30.02	-28.08	-13.00	15.08	1.94	334	Vertical
6	3741.5492	-39.04	-36.65	-13.00	23.65	2.39	164	Vertical









NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-58.41	-20.36	-13.00	7.36	38.05	258	Horizontal
2	1387.7888	-18.77	-22.88	-13.00	9.88	-4.11	1	Horizontal
3	1850.7851	-35.39	-35.21	-13.00	22.21	0.18	45	Horizontal
4	2313.7814	-31.15	-28.81	-13.00	15.81	2.34	324	Horizontal
5	3238.5989	-28.37	-26.48	-13.00	13.48	1.89	334	Horizontal
6	5089.4089	-39.45	-34.33	-13.00	21.33	5.12	314	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-54.87	-16.82	-13.00	3.82	38.05	5	Vertical
2	1387.7888	-18.65	-22.76	-13.00	9.76	-4.11	342	Vertical
3	2313.7814	-31.19	-28.85	-13.00	15.85	2.34	305	Vertical
4	3238.5989	-28.36	-26.47	-13.00	13.47	1.89	333	Vertical
5	4626.4126	-38.85	-34.28	-13.00	21.28	4.57	305	Vertical
6	6940.219	-42.37	-34.14	-13.00	21.14	8.23	13	Vertical









	<u></u>							<u> </u>
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	935.98	-56.80	-18.56	-13.00	5.56	38.24	265	Horizontal
2	1403.0653	-19.47	-23.58	-13.00	10.58	-4.11	341	Horizontal
3	2338.4588	-30.55	-28.18	-13.00	15.18	2.37	311	Horizontal
4	3273.8524	-28.27	-26.33	-13.00	13.33	1.94	331	Horizontal
5	4676.9427	-38.20	-33.58	-13.00	20.58	4.62	293	Horizontal
6	5144.6395	-37.43	-32.22	-13.00	19.22	5.21	321	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	647.89	-79.80	-45.07	-13.00	32.07	34.73	351	Vertical
2	935.98	-55.02	-16.78	-13.00	3.78	38.24	7	Vertical
3	1403.0653	-19.35	-23.46	-13.00	10.46	-4.11	341	Vertical
4	2338.4588	-30.49	-28.12	-13.00	15.12	2.37	312	Vertical
5	3273.8524	-28.17	-26.23	-13.00	13.23	1.94	331	Vertical
6	5144.6395	-37.50	-32.29	-13.00	19.29	5.21	296	Vertical









NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-59.33	-21.28	-13.00	8.28	38.05	249	Horizontal
2	1387.7888	-27.47	-31.58	-13.00	18.58	-4.11	351	Horizontal
3	1850.7851	-29.55	-29.37	-13.00	16.37	0.18	137	Horizontal
4	3701.5952	-31.62	-29.25	-13.00	16.25	2.37	211	Horizontal
5	4626.4126	-35.32	-30.75	-13.00	17.75	4.57	249	Horizontal
6	5089.4089	-35.92	-30.80	-13.00	17.80	5.12	267	Horizontal




	<u></u>							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-54.78	-16.73	-13.00	3.73	38.05	9	Vertical
2	1387.7888	-17.70	-21.81	-13.00	8.81	-4.11	353	Vertical
3	1850.7851	-31.48	-31.30	-13.00	18.30	0.18	327	Vertical
4	2313.7814	-33.68	-31.34	-13.00	18.34	2.34	299	Vertical
5	4626.4126	-36.47	-31.90	-13.00	18.90	4.57	37	Vertical
6	5089.4089	-33.08	-27.96	-13.00	14.96	5.12	317	Vertical









NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-59.28	-21.23	-13.00	8.23	38.05	242	Horizontal
2	1387.7888	-27.33	-31.44	-13.00	18.44	-4.11	306	Horizontal
3	1850.7851	-30.22	-30.04	-13.00	17.04	0.18	139	Horizontal
4	3701.5952	-31.98	-29.61	-13.00	16.61	2.37	222	Horizontal
5	4626.4126	-34.69	-30.12	-13.00	17.12	4.57	242	Horizontal
6	5089.4089	-36.47	-31.35	-13.00	18.35	5.12	270	Horizontal




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	926.28	-55.03	-16.98	-13.00	3.98	38.05	9	Vertical
2	1387.7888	-17.93	-22.04	-13.00	9.04	-4.11	348	Vertical
3	1850.7851	-31.86	-31.68	-13.00	18.68	0.18	321	Vertical
4	2313.7814	-32.62	-30.28	-13.00	17.28	2.34	293	Vertical
5	4626.4126	-36.45	-31.88	-13.00	18.88	4.57	29	Vertical
6	5089.4089	-33.20	-28.08	-13.00	15.08	5.12	311	Vertical







NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	935.98	-58.99	-20.75	-13.00	7.75	38.24	249	Horizontal
2	1403.0653	-24.92	-29.03	-13.00	16.03	-4.11	118	Horizontal
3	2338.4588	-33.00	-30.63	-13.00	17.63	2.37	342	Horizontal
4	3273.8524	-28.54	-26.60	-13.00	13.60	1.94	316	Horizontal
5	4676.9427	-34.00	-29.38	-13.00	16.38	4.62	257	Horizontal
6	5144.6395	-37.62	-32.41	-13.00	19.41	5.21	41	Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	935.98	-55.07	-16.83	-13.00	3.83	38.24	18	Vertical
2	1403.0653	-18.87	-22.98	-13.00	9.98	-4.11	346	Vertical
3	1870.7621	-33.80	-33.37	-13.00	20.37	0.43	318	Vertical
4	2338.4588	-31.59	-29.22	-13.00	16.22	2.37	326	Vertical
5	3273.8524	-33.33	-31.39	-13.00	18.39	1.94	326	Vertical
6	3741.5492	-35.52	-33.13	-13.00	20.13	2.39	158	Vertical





Report No.: AGC13372240201FR01 Page 33 of 53

#### 8.5 Emission Mask Measurement Part

The detailed procedure employed for Emission Mask measurements are specified as following:


- -Connect the equipment as illustrated.
- -Spectrum set as follow:
- Centre frequency = fundamental frequency, Span=150kHz for 12.5kHz and 25kHz channel spacing, RBW=300Hz, VBW=1000Hz for 12.5kHz, RBW=300Hz, VBW=1000Hz for 25kHz, Sweep = auto, Detector function = peak, Trace = max hold
- 2. Key the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0dB reference for the measurement.
- 3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).
  The input level shall be established at the frequency of maximum response of the audio modulating circuit.
- 4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
- 5. Measure and record the results in the test report.









## Test plot as follows:











Page 36 of 53

#### 9. Modulation Characteristics

### 9.1 Provisions Applicable

According to FCC§2.1047 and §95.1775, for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

Each GMRS transmitter type must be designed to satisfy the modulation requirements in this section. Operation of GMRS stations must also be in compliance with these requirements.

- (a) Main channels. The peak frequency deviation for emissions to be transmitted on the main channels must not exceed  $\pm$  5 kHz.
- (b) 462 MHz interstitial channels. The peak frequency deviation for emissions to be transmitted on the 462 MHz interstitial channels must not exceed  $\pm$  5 kHz.
- (c) 467 MHz interstitial channels. The peak frequency deviation for emissions to be transmitted on the 467 MHz interstitial channels must not exceed  $\pm$  2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

#### 9.2 Measurement Procedure


#### Modulation Limit


- 1. Test layout and build equipment as shown below.
- 2. adjust the audio input for 60% of rated system deviation at 1kHz using this level as a reference (0dB).
- 3. Vary the input level from -20 to +20dB.
- 4. Record the frequency deviation obtained as a function of the input level.
- 5. Repeat step 2 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

#### Audio Frequency Response

- 1. Test layout and build equipment as shown below.
- Adjust the audio input for 20% of rated system deviation at 1 kHz using this level as a reference (0 dB).
- 3. Vary the Audio frequency from 100 Hz to 10 kHz and record the frequency deviation.
- 4. Audio Frequency Response = 20log10 (Deviation of test frequency/Deviation of 1 kHz reference).

# 9.3 Measurement Setup









### 9.4 Measurement Result

#### A. Modulation Limit:

	12.5kHz, FM modulation, Assigned Frequency:462.6500MHz-5W					
Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (kHz)	Peak Freq. Deviation At 1000 Hz (kHz)	Peak Freq. Deviation At 1500 Hz (kHz)	Peak Freq. Deviation At 3000 Hz (kHz)		
-20	0.19	0.51	0.78	1.03		
-15	0.35	0.62	1.06	1.25		
-10	0.36	0.74	1.15	1.46		
-5	0.52	0.82	1.26	1.52		
0	0.66	0.89	1.34	1.64		
+5	0.74	1.12	1.45	1.79		
+10	1.03	1.36	1.63	1.88		
+15	1.05	1.47	1.74	1.96		
+20	1.04	1.45	1.69	1.95		




Note: All the modes had been tested, but only the worst data recorded in the report






#### **B.** Modulation Limit:

	25kHz, FM modulation, Assigned Frequency:462.6500MHz-5W					
Modulation Level (dB)	Peak Freq. Deviation At 300 Hz (kHz)	Peak Freq. Deviation At 1000 Hz (kHz)	Peak Freq. Deviation At 1500 Hz (kHz)	Peak Freq. Deviation At 3000 Hz (kHz)		
-20	0.66	0.85	1.33	1.85		
-15	0.74	1.12	1.52	2.05		
-10	0.82	1.26	1.63	2.12		
-5	0.99	1.33	1.89	2.23		
0	1.05	1.55	2.06	2.63		
+5	1.14	1.64	2.15	2.74		
+10	1.26	1.76	2.22	3.05		
+15	1.33	1.88	2.74	3.12		
+20	1.29	1.75	2.69	3.11		




Note: All the modes had been tested, but only the worst data recorded in the report






# C. Audio Frequency Response:

12.5kHz, Analog modulation, Assigned Frequency:462.6500MHz				
Frequency (Hz)	Deviation (kHz)	Audio Frequency Response(dB)		
100				
200				
300	0.16	-13.30		
400	0.25	-9.43		
500	0.31	-7.56		
600	0.42	-4.92		
700	0.45	-4.32		
800	0.53	-2.90		
900	0.66	-0.99		
1000	0.74	0.00		
1200	0.82	0.89		
1400	0.99	2.53		
1600	1.11	3.52		
1800	1.24	4.48		
2000	1.29	4.83		
2400	1.44	5.78		
2500	1.69	7.17		
2800	1.74	7.43		
3000 1.82		7.82		




Note: All the modes had been tested, but only the worst data recorded in the report.





# D. Audio Frequency Response:

25kH	25kHz, Analog modulation, Assigned Frequency:462.6500MHz				
Frequency (Hz)	Deviation (kHz)	Audio Frequency Response(dB)			
100					
200					
300	0.22	-12.24			
400	0.31	-9.26			
500	0.44	-6.22			
600	0.52	-4.76			
700	0.63	-3.10			
800	0.66	-2.69			
900	0.74	-1.70			
1000	0.9	0.00			
1200	0.99	0.83			
1400	1.12	1.90			
1600	1.32	3.33			
1800	1.45	4.14			
2000	1.66	5.32			
2400	1.78	5.92			
2500	1.92	6.58			
2800	2.15	7.56			
3000	2.22	7.84			



Note: All the modes had been tested, but only the worst data recorded in the report.



Report No.: AGC13372240201FR01 Page 41 of 53

#### 10. Maximum Transmitter Power

#### 10.1 Provisions Applicable

FCC Part 95.1767 For GMRS, the maximum permissible transmitter output power effective radiated power (E.R.P.) as follows.

This section contains transmitting power limits for GMRS stations. The maximum transmitting power depends on which channels are being used and the type of station.

462/467 MHz main channels. The limits in this paragraph apply to stations transmitting on any of the 462 MHz main channels or any of the 467 MHz main channels. Each GMRS transmitter type must be capable of operating within the allowable power range. GMRS licensees are responsible for ensuring that their GMRS stations operate in compliance with these limits.

The transmitter output power of mobile, repeater and base stations must not exceed 50 Watts.

The transmitter output power of fixed stations must not exceed 15 Watts.


462 MHz interstitial channels. The effective radiated power (ERP) of mobile, hand-held portable and base stations transmitting on the 462 MHz interstitial channels must not exceed 5 Watts.

(467 MHz interstitial channels. The effective radiated power (ERP) of hand-held portable units transmitting on the 467 MHz interstitial channels must not exceed 0.5 Watt. Each GMRS transmitter type capable of transmitting on these channels must be designed such that the ERP does not exceed 0.5 Watt.

#### **10.2 Measurement Procedure**

- 1. EUT was placed on a 0.8 or 1.5meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- 2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- 4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the

Any repseubstitution antennational adjust of the nevel and the notional is generatory output the without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.







- reach the previously recorded (P<sub>r</sub>). The power of signal source (P<sub>Mea</sub>) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Aq}$ ) should be recorded after test
- 6. The measurement results are obtained as described below: Power(EIRP)=P<sub>Mea</sub>- P<sub>Ag</sub> P<sub>cl</sub> G<sub>a</sub> The measurement results are amend as described below:Power(EIRP)=P<sub>Mea</sub>- P<sub>cl</sub> G<sub>a</sub>
- 7. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 8. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.
- 9. Test the EUT in the lowest channel, the middle channel the Highest channel

# 10.3 Measurement Setup

# ⊠Conducted Output Power:





⊠Effective Radiated Power:







## **Radiated Below 1GHz**





# **Radiated Above 1 GHz**







Report No.: AGC13372240201FR01

Page 44 of 53

#### 10.4 Measurement Result

#### ERP Result:

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.G ain	ERP Level	ERP Level	Limit	Margin
(MHz)	(dBµV/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(W)	(W)	(W)
			ChannelS	eparation	1:12.5kHz	2			
462.6375	104.90	V	29.70	0.38	6.6	35.92	3.91	5	1.09
462.6375	104.83	Н	29.63	0.38	6.6	35.85	3.85	5	1.15
462.6500	104.93	V	29.73	0.38	6.6	35.95	3.94	50	46.06
462.6500	104.72	Н	29.52	0.38	6.6	35.74	3.75	50	46.25
467.6500	104.87	V	29.67	0.38	6.6	35.89	3.88	50	46.12
467.6500	104.75	Н	29.55	0.38	6.6	35.77	3.78	50	46.22
467.6375	95.51	V	20.31	0.38	6.6	26.53	0.45	0.5	0.05
467.6375	95.46	Н	20.26	0.38	6.6	26.48	0.44	0.5	0.06
	ChannelSeparation:25kHz								
462.6375	105.00	V	29.80	0.38	6.6	36.02	4.00	5	1.00
462.6375	104.87	Н	29.67	0.38	6.6	35.89	3.88	5	1.12
462.6500	105.03	V	29.83	0.38	6.6	36.05	4.03	50	45.97
462.6500	104.88	Н	29.68	0.38	6.6	35.90	3.89	50	46.11
467.6500	105.02	V	29.82	0.38	6.6	36.04	4.02	50	45.98
467.6500	104.85	Н	29.65	0.38	6.6	35.87	3.86	50	46.14

#### Note:

- 1. Calculation Formula: Emission Level(dBm) = S.G. (dBm)- Cable Loss(dB)+ Ant.Gain(dBi)
- 2. The Ant. Gain including the correct factor 2.15
- 3. Margin (dB) = Limit(dBm)- Emission Level(dBm)



Report No.: AGC13372240201FR01

Page 45 of 53

#### Conducted Power Result:

The maximum Power (CP) for GMRS is

Analog: 5W/0.5W for 12.5 kHz/25 kHz Channel Separation

Calculation Formula: CP = R + A + L

\* Note:

CP: The final Conducted Power

R: The reading value from spectrum analyzer A: The attenuation value of the used attenuator

L: The loss of all connection cables

Conducted Power Measurement Results					
Mode	Channel Separation Test Channel Measurem		Measurement Result (dBm)		
	12.5 kHz	462.6375 MHz	36.28		
GMRS TX		462.6500 MHz	36.29		
		467.6500 MHz	36.28		
		467.6375 MHz	26.89		
	25 kHz	462.6375 MHz	36.35		
		462.6500 MHz	36.35		
		467.6500 MHz	36.34		



Report No.: AGC13372240201FR01

Page 46 of 53

# 11. Spurious Emission on Antenna Port

### 11.1 Provisions Applicable

Please refer to FCC 47 CFR 2.1051, 2.1057, 22.359 & 90.210 for specification details. Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Attenuation Limit (dBc)	
§ 95.1779	At least 43 + 10 log (P) dB	

43 + 10 log (P<sub>watts</sub>)

Calculation: Limit (dBm) =EL-43-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,


In this application, the EL is P(dBm).

Limit (dBm) = P( dBm)-43-10 log ( $P_{watts}$ ) = -13 dBm

#### 11.2 Measurement Procedure


- 1. The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation.
- 2. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to
- 3. Show any out of band emission up to 10th. Harmonic for the lower and the highest frequency range.
- Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set 4.
- 5. RBW=1MHz.VBW=3MHz from the 1GHz to 10th Harmonic.
- 6. The audio input was set the unmodulated carrier, the resulting picture is print out for each channel separation.


## 11.3 Measurement Setup







#### 11.4 Measurement Result









# 12.5kHz, FM modulation, Assigned Frequency:467.6500MHz, 5W

