

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2A3PA-ROCK4C

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m) Power Density (S) (mW/ cm ²)		Averaging Time E ² , H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

. -... / Controlled E

Note: *f* is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Limits for General Population / Uncontrolled Exposure

Note: f = frequency in MHz

* = Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01 $S=PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
вт	2±1	3	2.0	1.58(2dBi)	0.000629	1	Pass
BLE	4±1	5	3.16	1.58(2dBi)	0.000994	1	Pass
2.4G WIFI	11±1	12	15.85	1.58(2dBi)	0.004984	1	Pass
5G WIFI	12±1	13	19.95	1.58(2dBi)	0.006273	1	Pass

For the max result : $0.006273 \le 1.0$, compliance with FCC's RF Exposure