


Appendix A: Test Results of FCC Part 15C


APPENDIX A: TEST RESULTS OF FCC PART 15C.....	1
APPENDIX A.1: TEST RESULTS OF 20dB BANDWIDTH	2
APPENDIX A.2: TEST RESULTS OF 99% BANDWIDTH	3
APPENDIX A.3: TEST RESULTS OF RADIATED SPURIOUS EMISSION	4
9kHz - 90KHz	4
9KHz – 30MHz	7
110KHz - 490KHz	10
30MHz - 1GHz.....	13
APPENDIX A.4: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS	15

Appendix A.1: Test Results of 20dB Bandwidth



Date: 15.SEP.2023 13:18:12

Appendix A.2: Test Results of 99% Bandwidth



Date: 15.SEP.2023 13:05:05


Appendix A.3: Test Results of Radiated Spurious Emission

Note: The highest waveform in the figure is Fundamental.

9kHz - 90KHz

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019183	62.87	---	141.93	79.06	100.0	X	65.0	20.0
0.019183	---	57.36	121.93	64.57	100.0	X	65.0	20.0
0.036540	---	31.84	116.34	84.49	100.0	X	165.0	20.0
0.037003	40.36	---	136.23	95.86	100.0	X	158.0	20.0
0.076924	47.18	---	129.87	82.70	100.0	X	81.0	20.0
0.076924	---	46.01	109.87	63.86	100.0	X	81.0	20.0

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019125	60.81	---	141.96	81.14	100.0	Y	213.0	20.0
0.019183	---	55.60	121.93	66.33	100.0	Y	107.0	20.0
0.035904	39.86	---	136.49	96.63	100.0	Y	228.0	20.0
0.036482	---	31.07	116.35	85.28	100.0	Y	175.0	20.0
0.076635	42.63	---	129.91	87.28	100.0	Y	38.0	20.0
0.076635	---	40.97	109.91	68.94	100.0	Y	38.0	20.0

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019183	60.46	---	141.93	81.47	100.0	Z	152.0	20.0
0.019183	---	54.99	121.93	66.94	100.0	Z	152.0	20.0
0.062634	37.67	---	131.66	93.99	100.0	Z	33.0	20.0
0.062634	---	32.60	111.66	79.06	100.0	Z	33.0	20.0
0.078197	41.13	---	129.73	88.60	100.0	Z	76.0	20.0
0.078197	---	39.56	109.73	70.17	100.0	Z	76.0	20.0

9KHz – 30MHz

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019172	61.22	121.94	60.72	100.0	X	0.0	20.1
0.076781	47.39	109.89	62.50	100.0	X	93.0	20.1
0.150000	67.87	104.08	36.21	100.0	X	236.0	20.1
0.303640	44.68	97.95	53.28	100.0	X	77.0	20.1
0.448500	41.42	94.57	53.15	100.0	X	84.0	20.1
6.321927	28.12	69.50	41.38	100.0	X	162.0	20.3
22.146816	27.71	69.50	41.79	100.0	X	117.0	20.6

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019071	60.53	121.98	61.45	100.0	Y	210.0	20.1
0.076680	42.10	109.90	67.80	100.0	Y	38.0	20.1
0.149899	62.15	104.08	41.93	100.0	Y	152.0	20.1
0.448500	38.19	94.57	56.38	100.0	Y	19.0	20.1
2.406309	28.91	69.50	40.59	100.0	Y	345.0	20.2
19.829052	27.74	69.50	41.76	100.0	Y	333.0	20.6

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019071	58.93	121.98	63.05	100.0	Z	62.0	20.1
0.079601	40.36	109.58	69.22	100.0	Z	88.0	20.1
0.150000	65.98	104.08	38.10	100.0	Z	231.0	20.1
0.448500	40.19	94.57	54.38	100.0	Z	212.0	20.1
1.905882	28.73	69.50	40.77	100.0	Z	58.0	20.2
12.669441	27.86	69.50	41.64	100.0	Z	252.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

110KHz - 490KHz**EUT Information**


EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin

**Critical Freqs**

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.150000	68.06	---	124.08	56.01	100.0	X	243.0	20.0
0.150000	---	67.77	104.08	36.30	100.0	X	243.0	20.0
0.231150	---	42.19	100.32	58.13	100.0	X	79.0	20.0
0.232850	45.03	---	120.26	75.22	100.0	X	79.0	20.0
0.307000	43.52	---	117.86	74.34	100.0	X	79.0	20.0
0.310350	---	39.46	97.77	58.30	100.0	X	73.0	20.0
0.381400	38.72	---	115.98	77.26	100.0	X	79.0	20.0
0.384250	---	34.53	95.91	61.38	100.0	X	79.0	20.0
0.450500	41.37	---	114.53	73.16	100.0	X	236.0	20.0
0.450800	---	40.26	94.52	54.26	100.0	X	236.0	20.0

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.150000	62.50	---	124.08	61.57	100.0	Y	146.0	20.0
0.150050	---	61.99	104.07	42.08	100.0	Y	146.0	20.0
0.232200	41.39	---	120.28	78.89	100.0	Y	34.0	20.0
0.232200	---	37.53	100.28	62.75	100.0	Y	34.0	20.0
0.301550	40.76	---	118.01	77.26	100.0	Y	40.0	20.0
0.301550	---	35.03	98.01	62.98	100.0	Y	40.0	20.0
0.450100	---	33.97	94.54	60.57	100.0	Y	153.0	20.0
0.451450	37.41	---	114.51	77.10	100.0	Y	153.0	20.0

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.150000	66.28	---	124.08	57.79	100.0	Z	237.0	20.0
0.150000	---	66.12	104.08	37.95	100.0	Z	237.0	20.0
0.232450	---	35.40	100.27	64.87	100.0	Z	83.0	20.0
0.233050	40.05	---	120.25	80.20	100.0	Z	83.0	20.0
0.301150	---	34.09	98.03	63.94	100.0	Z	285.0	20.0
0.301450	39.22	---	118.02	78.79	100.0	Z	285.0	20.0
0.450500	---	37.93	94.53	56.60	100.0	Z	243.0	20.0
0.450800	39.27	---	114.52	75.26	100.0	Z	243.0	20.0

30MHz - 1GHz

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.639231	20.30	40.00	19.70	100.0	H	344.0	-18.9
106.928462	19.56	43.50	23.94	100.0	H	108.0	-19.2
211.128846	28.09	43.50	15.41	100.0	H	167.0	-19.1
497.838462	20.10	46.00	25.90	100.0	H	5.0	-12.3
915.236923	25.38	46.00	20.62	100.0	H	0.0	-5.3

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage:	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.461539	30.01	40.00	9.99	100.0	V	168.0	-21.3
58.838846	28.72	40.00	11.28	100.0	V	58.0	-19.2
115.621154	17.90	43.50	25.60	100.0	V	168.0	-20.2
203.704615	21.70	43.50	21.80	100.0	V	334.0	-19.3
722.542692	22.90	46.00	23.10	100.0	V	168.0	-8.0
985.673846	26.99	54.00	27.01	100.0	V	247.0	-4.3


Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Appendix A.4: Test Results of Conducted Emission on AC Mains

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage::	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.386000	---	17.11	48.15	31.04	L1	9.9
0.386000	27.42	---	58.15	30.73	L1	9.9
3.050000	---	13.06	46.00	32.94	L1	10.2
3.058000	26.61	---	56.00	29.39	L1	10.2
4.666000	---	14.74	46.00	31.26	L1	10.2
4.738000	27.23	---	56.00	28.77	L1	10.2
8.534000	33.55	---	60.00	26.45	L1	10.3
8.610000	---	23.75	50.00	26.25	L1	10.3
10.318000	---	23.41	50.00	26.59	L1	10.3
10.442000	33.47	---	60.00	26.53	L1	10.3
11.154000	---	23.62	50.00	26.38	L1	10.3
11.194000	33.43	---	60.00	26.57	L1	10.3

Final Result

[illegible]

EUT Information

EUT Name:	Travel Case with Wireless Charging
Model:	C0220
Test Mode:	Charging
Order No/Sample No:	168443782/A003562080-008
Test Voltage::	120V/60Hz
Remark:	Temp 24 Humi:50%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.314000	27.98	---	59.86	31.89	N	9.8
0.334000	---	15.39	49.35	33.96	N	9.8
2.126000	---	10.98	46.00	35.02	N	9.9
2.126000	25.67	---	56.00	30.33	N	9.9
4.830000	27.70	---	56.00	28.30	N	9.9
4.906000	---	13.89	46.00	32.11	N	9.9
10.318000	32.21	---	60.00	27.79	N	10.0
10.342000	---	21.52	50.00	28.48	N	10.0
11.090000	32.14	---	60.00	27.86	N	10.0
11.098000	---	21.79	50.00	28.21	N	10.0
11.998000	31.32	---	60.00	28.68	N	10.1
12.014000	---	21.82	50.00	28.18	N	10.1

Final_Result

[illegible]