


2DH5_Ant1_2480_0~Reference






3DH5_Ant1_2402_0~Reference

Date: 17.AUG.2022 17:43:12






3DH5_Ant1_2441_0~Reference




Date: 17.AUG.2022 17:44:40





3DH5_Ant1_2480_0~Reference





Date: 17.AUG.2022 17:47:21



3.5. Bandwidth

Limit

N/A

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. OCB and 20dB Spectrum Setting:
 - (1) Set RBW = $1\% \sim 5\%$ occupied bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Note: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.


Test Mode

Please refer to the clause 2.4.


Test Results


Modulation type	Channel	99% Bandwidth (MHz)	20dB Bandwidth (MHz)	20dB Bandwidth *2/3 (MHz)
	00	0.857	1.104	0.736
GFSK	39	0.857	1.104	0.736
	78	0.860	1.104	0.736
	00	1.172	1.371	0.914
π/4-DQPSK	39	1.172	1.371	0.914
	78	1.169	1.374	0.916
	00	1.181	1.371	0.914
8-DPSK	39	1.178	1.374	0.916
	78	1.181	1.371	0.914

Occupied Bandwidth:




















3DH5_Ant1_2402






3.6. Channel Separation

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b:

Test Item	Limit	Frequency Range(MHz)
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Test Mode

Please refer to the clause 2.4.

Test Results

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
GFSK	39	1.003	>0.736	Pass
π/4-DQPSK	39	1.000	>0.914	Pass
8-DPSK	39	1.003	>0.916	Pass



Test plot as follows:








3.7. Number of Hopping Channel

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)/ RSS-247 5.1 d:

Section Test Item		Limit
15.247 (a)(iii)/ RSS-247 5.1 d:	Number of Hopping Channel	>15

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
 - (1) Peak Detector: RBW=100 kHz, VBW≥RBW, Sweep time= Auto.

Test Mode


Please refer to the clause 2.4.

Test Result

Modulation type	Channel number	Limit	Result
GFSK	79		
π/4-DQPSK	79	≥15.00 Pas	Pass
8DPSK	79		



Test plot as follows:










3.8. Dwell Time

Limit

Section	Test Item	Limit	
15.247(a)(iii)/ RSS-247 5.1 d	Average Time of Occupancy	0.4 sec	

Test Configuration



Test Procedure

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. Spectrum Setting:
 - (1) Spectrum Setting: RBW=1MHz, VBW≥RBW.
 - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
 - (3) Sweep Time is more than once pulse time.
- (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
 - (5) Measure the maximum time duration of one single pulse.
 - (6) Set the EUT for packet transmitting.

Test Mode

Please refer to the clause 2.4.






Test Result


Modulation type	Channel	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (ms)	Limit (Second)	Result
	DH1	2441	0.37	118.40	31.60		
GFSK	DH3	2441	1.62	259.20	31.60	≤ 0.40	Pass
	DH5	2441	2.86	305.07	31.60		
	2DH1	2441	0.38	121.60	31.60		
π/4-DQPSK	2DH3	2441	1.63	260.80	31.60	≤ 0.40	Pass
	2DH5	2441	2.87	306.13	31.60		
8-DPSK	3DH1	2441	0.38	121.60	31.60		
	3DH3	2441	1.63	260.80	31.60	≤ 0.40	Pass
	3DH5	2441	2.87	306.13	31.60		

Note: 1DH1/2DH1/3DH1 Total of Dwell = Pulse Time*(1600/2)*31.6/79 1DH3/2DH3/3DH3 Total of Dwell = Pulse Time*(1600/4)*31.6/79 1DH5/2DH5/3DH5 Total of Dwell = Pulse Time*(1600/6)*31.6/79






Test plot as follows:








3DH1_Ant1_Hop





Date: 17.AUG.2022 18:24:38

Page 72 of 77

Report No.: CTC20221545E01




3.9. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1) / RSS-247 5.4 b:

Test Item	Limit	Frequency Range(MHz)	
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125mW(21dBm)	2400~2483.5	

Test Configuration



Test Procedure

- 1. The maximum conducted output power may be measured using a broadband Peak RF power meter.
- 2. Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor.
- 3. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
- 4. Record the measurement data.

Test Mode

Please refer to the clause 2.4.

Test Result

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
	00	-3.51		
GFSK	39	-2.42	≤ 21.00	Pass
	78	-1.69		
	00	-2.82		
π/4-DQPSK	39	-1.76	≤ 21.00	Pass
	78	-0.88		
	00	-2.27		
8-DPSK	39	-1.49	≤ 21.00	Pass
	78	-0.81		




3.10. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
- 3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.

Set the span to 0Hz Set the RBW to 10MHz Set the VBW to 10MHz

Detector: Peak Sweep time: Auto

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.


Test Mode

Please refer to the clause 2.4.

Test Result

Test Mode	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
	2402	2.88	3.75	76.80	0.35	1
GFSK	2441	2.89	3.76	76.86	0.35	1
	2480	2.88	3.75	76.80	0.35	1
	2402	2.88	3.75	76.80	0.35	1
π/4-DQPSK	2441	2.88	3.75	76.80	0.35	1
	2480	2.89	3.75	77.07	0.35	1
8-DPSK	2402	2.87	3.73	76.94	0.35	1
	2441	2.87	3.73	76.94	0.35	1
	2480	2.87	3.73	76.94	0.35	1
















Page 77 of 77

Report No.: CTC20221545E01



3.11. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional gain of the antenna less than 6dBi, please refer to the EUT internal photographs antenna photo.



