



# TEST REPORT

page : (1) / Total (13)

성적서 번호 Report No.		ICRT-TR-E232413-0A			
신청자 Client	기관명 Name	HANMI MICRONICS INC.			
	주 소 Address	72, Samdo-ro 48beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea.			
시험대상품목 Product name		Wireless Keyboard			
모델명 Model name		CaluX			
정격 Ratings		DC 3.7 V			
시험장소 Place of test		<input checked="" type="checkbox"/> 고정시험(Inside test) <input type="checkbox"/> 현장시험(Field test) 주소지(Address): 112, 113 Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea			
시험기간 Date of test		11. Sep. 2023 ~ 20. Sep. 2023			
시험방법/항목 Test Method/Item		FCC Part 15 Subpart C			
시험결과 Test Results		Refer to 3. Test Summary			
확인 Affirmation	작성자 Tested by 성명 Name Si-Yeon, Hwang (서명) (Signature)		기술책임자 Technical Manager 성명 Name Tae-Yang, Yoon (서명) (Signature)		
	<input type="checkbox"/> 위 성적서는 고객이 제공한 시료에 대한 시험결과입니다. <input type="checkbox"/> The above test report is certified that the above mentioned products have been tested for the sample. <input type="checkbox"/> 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다. <input type="checkbox"/> The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme <input type="checkbox"/> 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다. <input type="checkbox"/> The test report is prohibited for some reproduction without the approval of the ICR.				
<p style="text-align: center;"><b>2023. 09. 26</b></p> <p style="text-align: center;"><b>주식회사 아이씨알 대표이사</b></p> <p style="text-align: center;">The head of INTERNATIONAL CERTIFICATION REGISTRAR</p>					

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6

112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea / Tel: 02-6351-9001 ~ 6

# TEST REPORT

page : (2) / Total (13)

## Contents

<b>1. Applicant &amp; Manufacturer &amp; Test Laboratory Information</b>	<u>4</u>
<b>2. Equipment under Test(EUT) Information</b>	<u>5</u>
<b>3. Test Summary</b>	<u>6</u>
<b>4. Test Result</b>	<u>8</u>
<b>5. Used equipment</b>	<u>13</u>



# TEST REPORT

page : (3) / Total (13)

## Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E232413-0A	2023. 09. 26	Initial Issue	All



# TEST REPORT

page : (4) / Total (13)

## 1. Applicant & Manufacturer & Test Laboratory Information

### 1.1 Applicant information

Applicant	HANMI MICRONICS INC.
Address	72, Samdo-ro 48beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea.

### 1.2 Manufacturer Information

Applicant	HANMI MICRONICS INC.
Address	72, Samdo-ro 48beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea.

### 1.3 Test Laboratory Information

Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
KOLAS No.	KT652
KC & FCC	KR0165

### 1.4 Measurement Uncertainty

Parameter	Uncertainty	Limit
Occupied Channel Bandwidth	2.75%	±5 %
RF output power, conducted	1.39 dB	±1.5 dB
Power Spectral Density, conducted	1.65 dB	±3 dB
Unwanted Emissions, conducted	1.82 dB	±3 dB
Supply voltages	0.06%	±3 %
Time	1.17%	±5 %
All emissions, radiated (Under the 1 GHz)	3.22 dB	±6 dB
All emissions, radiated (Above the 1 GHz)	3.67 dB	±6 dB



# TEST REPORT

page : (5) / Total (13)

## 2. Equipment under Test(EUT) Information

### 2.1 General Information

Product Name	Wireless Keyboard
Model Name	CaluX
Additional Model Name	-
FCC ID	2A3QW-CALUX
Power Supply	DC 3.7 V

### 2.2 Additional Information

Equipment Class	DTS-Digital Transmission System	
Device Type	Stand-alone	
Operating Frequency	Bluetooth LE	2 402 MHz ~ 2 480 MHz
RF Output Power	Bluetooth LE	-4.18 dBm
Number of Channel	Bluetooth LE	40
Modulation Type	GFSK	
Antenna Type	PCB Antenna	
Antenna Gain	1.58 dBi	



# TEST REPORT

page : (6) / Total (13)

## 3. Test Summary

### 3.1 Test standards and results

FCC Part 15 Subpart C			
Clause	Test items	Applied	Results
§15.247 (a) (2)	6 dB Bandwidth	■	N/A (See note 1)
§15.247 (b) (3)	Maximum Conducted Output Power	■	N/A (See note 1)
§15.247 (e)	Power Spectral Density	■	N/A (See note 1)
§15.247 (d)	Conducted Spurious Emission & band Edge	■	N/A (See note 1)
§15.247 (d) & §15.209 & §15.205	Radiated Spurious Emission	■	PASS
§15.207	Power Line Conducted Emission	■	N/A (See note 1)

Note 1 : Refer to original report (ICRT-TR-E231115-0A)

### 3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in section 3.1 and the provision of Article 3.2 of Directive 2014/53/EU

### 3.3 Test Methodology

- Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

### 3.4 Configuration of Test System

- Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

#### 3.4.1 Radiated emission test

- Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.



# TEST REPORT

page : (7) / Total (13)

## 3.5 Antenna requirement

- According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Result: Pass

The transmitter has a **PCB Antenna**. The directional gain of the antenna is **1.58dBi**.



# TEST REPORT

page : (8) / Total (13)

## 4. Test Result

---

### 4.1 Radiated Spurious Emission

#### 4.1.1 Test procedure

ANSI C63.10-2013 Clause 11.11, 11.12

#### 4.1.2 Limit

§15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

§15.209 Radiated emission limits; general requirements.(a)

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.



# TEST REPORT

page : (9) / Total (13)

## §15.205 Restricted bands of operation.(a),(b)

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
<sup>1</sup> 0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	<sup>(2)</sup>
13.36–13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz.

<sup>2</sup> Above 38.6

Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements.



# TEST REPORT

page : (10) / Total (13)

## 4.1.3 Test data

Result : Pass

- Below 30 MHz\_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
It was not found any emissions peaks found from the EUT.								

- Below 30 MHz\_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
It was not found any emissions peaks found from the EUT.								

- Below 30 MHz\_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
It was not found any emissions peaks found from the EUT.								



# TEST REPORT

page : (11) / Total (13)

- 30 MHz ~ 1 GHz\_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
72.00	57.06	QP	H	-28.1	28.96	40.00	11.04	
131.27	52.61	QP	V	-27.9	24.71	43.50	18.79	
143.98	54.38	QP	H	-28.4	25.98	43.50	17.52	
182.48	52.82	QP	H	-26.5	26.32	43.50	17.18	

- 30 MHz ~ 1 GHz\_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
72.00	58.11	QP	H	-28.1	30.01	40.00	9.99	
131.27	52.51	QP	V	-27.9	24.61	43.50	18.89	
143.98	54.69	QP	H	-28.4	26.29	43.50	17.21	
168.03	53.32	QP	H	-27.5	25.82	43.50	17.68	

- 30 MHz ~ 1 GHz\_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
72.00	58.14	QP	H	-28.1	30.04	40.00	9.96	
143.98	54.65	QP	H	-28.4	26.25	43.50	17.25	
182.68	49.90	QP	H	-26.4	23.50	43.50	20.00	
264.35	47.27	QP	H	-22.6	24.67	46.00	21.33	



# TEST REPORT

page : (12) / Total (13)

## - 1 GHz Above\_Low ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
2 316.00	46.30	PK	V	-10.9	35.40	74	38.60	Restricted band
	32.53	AVG	V		21.63	54	32.37	
4 805.00	42.62	PK	V	-1.7	40.92	74	33.08	2nd Harmonic
	29.14	AVG	V		27.44	54	26.56	
7 206.00	40.47	PK	H	3	43.47	74	30.53	3rd Harmonic
	26.90	AVG	H		29.90	54	24.10	
9 608.40	39.70	PK	V	5.5	45.20	74	28.80	4nd Harmonic
	26.37	AVG	V		31.87	54	22.13	

## - 1 GHz Above\_Mid ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
4 879.00	43.85	PK	V	-1.6	42.25	74	31.75	2nd Harmonic
	30.38	AVG	V		28.78	54	25.22	
7 320.00	41.01	PK	V	2.7	43.71	74	30.29	3rd Harmonic
	26.86	AVG	V		29.56	54	24.44	
9 760.80	39.31	PK	V	6.4	45.71	74	28.29	4nd Harmonic
	25.57	AVG	V		31.97	54	22.03	

## - 1 GHz Above\_High ch

Frequency (MHz)	Reading (dBuV/m)	Detector	Pol.	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dBuV/m)	Note
2 486.50	51.12	PK	V	-10.2	40.92	74	33.08	Restricted band
	33.46	AVG	V		23.26	54	30.74	
4 960.00	44.87	PK	V	-1.5	43.37	74	30.63	2nd Harmonic
	33.55	AVG	V		32.05	54	21.95	
7 440.00	40.34	PK	H	2.5	42.84	74	31.16	3rd Harmonic
	26.85	AVG	H		29.35	54	24.65	
9 920.40	38.06	PK	V	5.8	43.86	74	30.14	4nd Harmonic
	24.92	AVG	V		30.72	54	23.28	



# TEST REPORT

page : (13) / Total (13)

## 5. Used equipment

	Description	Model Name	Manufacturer	Serial Number	Next Cal
■	DC POWER SUPPLY	E3632A	AGILANT	MY51300069	2024-03-03
■	LOOP ANTENNA	HFH2-Z2	R&S	100271	2025-03-08
■	BI-Log ANTENNA	VULB 9162	SCHWARZBECK	120	2024-12-26
■	SIGNAL CONDITIONING UNIT	SCU 08	R&S	100746	2024-04-03
■	EMI TEST RECEIVER	ESR26	R&S	101462	2024-04-04
■	DOUBLE RIDGED HORN ANTENNA	HF907	R&S	102556	2024-08-04
■	SIGNAL CONDITIONING UNIT	SCU18	R&S	102342	2024-04-03
■	EMI TEST RECEIVER	ESR26	R&S	101461	2024-04-04
■	HORN ANTENNA	LB-42-10-C-KF	A-INFOMW	J202024625	2024-03-07
■	PREAMPLIFIER	AMF-4F-18265-35-8P-1	MITEQ	-	2024-03-07

- END OF REPORT.