



FCC Part 15, Subpart B, Class B

Zhenjiang Electronics (Shenzhen) Co., LTD.

Cord Extension set(with Power Adapter)

Test Model: ZJP7K021

Additional Model No.: QY07

Prepared for : Zhenjiang Electronics (Shenzhen) Co., LTD.  
Address : 401, Building 2, No. 39, Hengling North Road, Nianfeng Community, Pingdi Street, Longgang District, Shenzhen China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 23, 2022  
Number of tested samples : 2  
Sample No. : A111522136-1; A111522136-2  
Serial number : Prototype  
Date of Test : November 23, 2022~ November 28, 2022  
Date of Report : November 28, 2022





FCC Part 15, Subpart B, Class B
FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Report Reference No. : LCSA111522136E

Date Of Issue : November 28, 2022

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure : Full application of Harmonised standards
Partial application of Harmonised standards
Other standard testing method

Applicant's Name : Zhenjiang Electronics (Shenzhen) Co., LTD.

Address : 401, Building 2, No. 39, Hengling North Road, Nianfeng Community, Pingdi Street, Longgang District, Shenzhen China

Test Specification

Standard : FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : Cord Extension set(with Power Adapter)

Trade Mark : ZHENJIANG Qiyuan Soodatek

Test Model : ZJP7K021

Ratings : Input: AC 100-125V, 60Hz, 15A, 1875W Max.
USB Output: DC 5V, 2.4A, 12W Max.

Result : Positive

Compiled by:

Diamond Lu

Diamond Lu/ Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





### FCC SDOC-- TEST REPORT

<b>Test Report No. :</b> LCSA111522136E	<u>November 28, 2022</u> Date of issue
---	---

Test Model .....	: ZJP7K021
EUT.....	: Cord Extension set(with Power Adapter)
<b>Applicant.....</b>	<b>: Zhenjiang Electronics (Shenzhen) Co., LTD.</b>
Address.....	: 401, Building 2, No. 39, Hengling North Road, Nianfeng Community, Pingdi Street, Longgang District, Shenzhen China
Telephone.....	: /
Fax.....	: /
<b>Manufacturer.....</b>	<b>: Zhenjiang Electronics (Shenzhen) Co., LTD.</b>
Address.....	: 401, Building 2, No. 39, Hengling North Road, Nianfeng Community, Pingdi Street, Longgang District, Shenzhen China
Telephone.....	: /
Fax.....	: /
<b>Factory.....</b>	<b>: Zhenjiang Electronics (Shenzhen) Co., LTD.</b>
Address.....	: 401, Building 2, No. 39, Hengling North Road, Nianfeng Community, Pingdi Street, Longgang District, Shenzhen China
Telephone.....	: /
Fax.....	: /

**Test Result** according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	November 28, 2022	Initial Issue	--





## TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Support Equipment List .....	8
2.3 External I/O Cable .....	8
2.4. Description of Test Facility .....	8
2.4. Statement of the Measurement Uncertainty .....	9
2.5. Measurement Uncertainty .....	9
<b>3. TEST RESULTS .....</b>	<b>10</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	10
3.2. Radiated emission Measurement .....	14
<b>4. TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>19</b>
<b>5. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>19</b>
<b>6. INTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>19</b>





# 1. SUMMARY OF STANDARDS AND RESULTS

## 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
N/A is an abbreviation for Not Applicable.			

Test mode:		
Mode 1	Full Load	Record





## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT : Cord Extension set(with Power Adapter)

Trade Mark :   Soodatek

Test Model : ZJP7K021

Additional Model No. : QY07

Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested

Power Supply : Input: AC 100-125V, 60Hz, 15A, 1875W Max.  
USB Output: DC 5V, 2.4A, 12W Max.

Highest internal frequency (Fx) :  $F_x \leq 108 \text{ MHz}$

Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz
$F_x > 1 \text{ GHz}$	5th harmonic of the highest frequency or 40 GHz, whichever is lower.







## 2.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

## 2.3 External I/O Cable

I/O Port Description	Quantity	Cable
USB Port	2	N/A
Type-C Port	1	N/A

## 2.4. Description of Test Facility

### Site Description

EMC Lab.

: NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
CAB identifier is CN0071.  
CNAS Registration Number is L4595.  
Test Firm Registration Number: 254912.







### 2.4. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 2.5. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Radiated Emission	Level accuracy (9kHz to 30MHz)	± 3.68 dB	N/A
Radiated Emission	Level accuracy (30MHz to 1000MHz)	± 3.48 dB	± 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	± 3.90 dB	± 5.2 dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.



### 3. TEST RESULTS


#### 3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	Farad	EZ	/	N/A	N/A
2	EMI Test Receiver	R&S	ESR3	102312	2022-02-16	2023-02-15
3	Artificial Mains	R&S	ENV216	101288	2022-06-16	2023-06-15
4	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2022-08-19	2023-08-18
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2022-10-29	2023-10-28

##### 3.1.2. Block Diagram of Test Setup



##### 3.1.3. Test Standard

###### Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

##### 3.1.4. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.





### 3.1.5. Operating Condition of EUT

3.1.5.1. Setup the EUT as shown on Section 3.1.2

3.1.5.2. Turn on the power of all equipments.

3.1.5.3. Let the EUT work in measuring Mode 1 and measure it.

### 3.1.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is investigated

### 3.1.7. Test Results


**PASS.**

The test result please refer to the next page.





<b>Test Model</b>	ZJP7K021	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.5°C, 53.2% RH	<b>Test Engineer</b>	Nick Peng
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1996	28.78	19.63	48.41	63.63	-15.22	QP	
2		0.1996	15.32	19.63	34.95	53.63	-18.68	AVG	
3		0.3031	23.10	19.63	42.73	60.16	-17.43	QP	
4		0.3031	11.15	19.63	30.78	50.16	-19.38	AVG	
5		0.6180	15.59	19.66	35.25	56.00	-20.75	QP	
6		0.6180	2.61	19.66	22.27	46.00	-23.73	AVG	
7		3.0886	12.64	19.70	32.34	56.00	-23.66	QP	
8		3.0886	-0.46	19.70	19.24	46.00	-26.76	AVG	
9		7.9351	20.71	19.77	40.48	60.00	-19.52	QP	
10		7.9351	3.34	19.77	23.11	50.00	-26.89	AVG	
11	*	15.0901	31.49	19.88	51.37	60.00	-8.63	QP	
12		15.0901	14.00	19.88	33.88	50.00	-16.12	AVG	





<b>Test Model</b>	ZJP7K021	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.5°C, 53.2% RH	<b>Test Engineer</b>	Nick Peng
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2041	23.21	19.63	42.84	63.44	-20.60	QP	
2		0.2041	9.40	19.63	29.03	53.44	-24.41	AVG	
3		0.6226	14.98	19.66	34.64	56.00	-21.36	QP	
4		0.6226	6.28	19.66	25.94	46.00	-20.06	AVG	
5		1.1626	14.31	19.65	33.96	56.00	-22.04	QP	
6		1.1626	1.35	19.65	21.00	46.00	-25.00	AVG	
7		3.2010	14.65	19.76	34.41	56.00	-21.59	QP	
8		3.2010	-0.31	19.76	19.45	46.00	-26.55	AVG	
9		7.8091	22.16	19.84	42.00	60.00	-18.00	QP	
10		7.8091	7.05	19.84	26.89	50.00	-23.11	AVG	
11	*	15.5446	32.64	19.90	52.54	60.00	-7.46	QP	
12		15.5446	16.17	19.90	36.07	50.00	-13.93	AVG	

Note: Pre-Scan all mode, Thus record worse case mode result in this report.

Margin= Reading level + Correct factor – Limit

Correct Factor= Lisen Factor+Cable Factor






### 3.2. Radiated emission Measurement

#### 3.2.1. Test Equipment

The following test equipments are used during the radiated emission measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2022-06-16	2023-06-15
3	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
4	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
5	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
6	EMI Test Receiver	R&S	ESPI	101940	2022-08-18	2023-08-17
7	Broadband Preamplifier	/	BP-01M18G	P190501	2022-06-16	2023-06-15
8	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2022-10-29	2023-10-28
9	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2022-10-29	2023-10-28

#### 3.2.2. Block Diagram of Test Setup





### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54
Remark: (1) Emission level $(\text{dB})\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$ (2) The smaller limit shall apply at the cross point between two frequency bands. (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.			
Limits for Radiated Emission Above 1GHz			
Frequency (MHz)	Distance (Meters)	Peak Limit ( $\text{dB}\mu\text{V}/\text{m}$ )	Average Limit ( $\text{dB}\mu\text{V}/\text{m}$ )
Above 1000	3	74	54
***Note: The lower limit applies at the transition frequency.			

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Mode 1 and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

### 3.2.7. Radiated Emission Noise Measurement Result

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity





Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

The frequency range from 30MHz to 1000MHz is checked.

### 3.2.8. Radiated Emission Noise Measurement Result


**PASS.**

The scanning waveforms please refer to the next page.





<b>Test Model</b>	ZJP7K021	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.8°C, 52.3% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Nick Peng	<b>Test Voltage</b>	AC 120V/60Hz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.4238	41.70	-18.40	23.30	40.00	-16.70	QP
2	75.7114	44.64	-19.71	24.93	40.00	-15.07	QP
3	164.3301	51.85	-19.62	32.23	43.50	-11.27	QP
4	266.6089	36.82	-15.45	21.37	46.00	-24.63	QP
5	535.7073	29.07	-12.32	16.75	46.00	-29.25	QP
6	801.7863	29.46	-9.89	19.57	46.00	-26.43	QP





<b>Test Model</b>	ZJP7K021	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.8°C, 52.3% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Nick Peng	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.5306	41.02	-18.39	22.63	40.00	-17.37	QP
2	75.4463	43.15	-19.69	23.46	40.00	-16.54	QP
3	140.3420	53.43	-20.86	32.57	43.50	-10.93	QP
4	210.7860	46.94	-17.12	29.82	43.50	-13.68	QP
5	271.3245	38.80	-15.40	23.40	46.00	-22.60	QP
6	742.2587	29.98	-10.26	19.72	46.00	-26.28	QP

Note: Pre-Scan all mode, Thus record worse case mode result in this report.

Margin= Reading level + Correct factor – Limit

Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor





#### 4. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

#### 5. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

#### 6. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----

