



FCC TEST REPORT

Test report
On Behalf of
Keefe Group
For
SCORE Tablets

Model No.: SCORE 810

FCC ID: 2A3XN-SCORE810

Prepared For : Keefe Group
10880 Linpage Pl, St. Louis, MO 63132, United States

Prepared By : Shenzhen HUAKE Testing Technology Co., Ltd.
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Date of Test: Aug. 14, 2023 ~ Aug. 31, 2023

Date of Report: Aug. 31, 2023

Report Number: HK2308144037-1E

**TEST RESULT CERTIFICATION****Applicant's name** : Keefe Group

Address : 10880 Linpage Pl, St. Louis, MO 63132, United States

Manufacture's Name : Central Tech International Limited

Address : Room 608, Zhuguang Innovation Park, Taoyuan Road, Nanshan District, Shenzhen, China

Product description

Trade Mark: SCORE

Product name : SCORE Tablets

Model and/or type reference : SCORE 810

Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :Date (s) of performance of tests : **Aug. 14, 2023 ~ Aug. 31, 2023**Date of Issue : **Aug. 31, 2023**Test Result : **Pass**

Testing Engineer : _____

(Gary Qian)

Technical Manager : _____

(Eden Hu)

Authorized Signatory : _____

(Jason Zhou)



TABLE OF CONTENTS

| | |
|--|-----------|
| 1. TEST RESULT SUMMARY | 5 |
| 1.1. TEST PROCEDURES AND RESULTS | 5 |
| 1.2. INFORMATION OF THE TEST LABORATORY | 5 |
| 1.3. MEASUREMENT UNCERTAINTY | 6 |
| 2. EUT DESCRIPTION | 7 |
| 2.1. GENERAL DESCRIPTION OF EUT | 7 |
| 2.2. CARRIER FREQUENCY OF CHANNELS | 8 |
| 2.3. OPERATION OF EUT DURING TESTING..... | 8 |
| 2.4. DESCRIPTION OF TEST SETUP | 9 |
| 2.5. DESCRIPTION OF SUPPORT UNITS | 10 |
| 3. ENERA INFORMATION | 11 |
| 3.1. TEST ENVIRONMENT AND MODE | 11 |
| 4. TEST RESULTS AND MEASUREMENT DATA | 13 |
| 4.1. CONDUCTED EMISSION | 13 |
| 4.2. TEST RESULT | 15 |
| 4.3. MAXIMUM CONDUCTED OUTPUT POWER..... | 17 |
| 4.4. EMISSION BANDWIDTH..... | 19 |
| 4.5. POWER SPECTRAL DENSITY | 25 |
| 4.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT | 32 |
| 4.7. RADIATED SPURIOUS EMISSION MEASUREMENT | 42 |
| 4.8. ANTENNA REQUIREMENT | 68 |
| 5. PHOTOGRAPH OF TEST | 69 |
| 6. PHOTOS OF THE EUT | 71 |



**** Modified History ****

| Revision | Description | Issued Data | Remark |
|--------------|-----------------------------|---------------|------------|
| Revision 1.0 | Initial Test Report Release | Aug. 31, 2023 | Jason Zhou |
| | | | |
| | | | |



1. TEST RESULT SUMMARY

1.1. TEST PROCEDURES AND RESULTS

| Requirement | CFR 47 Section | Result |
|----------------------------------|-----------------------|--------|
| Antenna requirement | §15.203/§15.247(b)(4) | PASS |
| AC Power Line Conducted Emission | §15.207 | PASS |
| Conducted Peak Output Power | §15.247(b)(3) | PASS |
| 6dB Emission Bandwidth | §15.247(a)(2) | PASS |
| Power Spectral Density | §15.247(e) | PASS |
| Band Edge | §15.247(d) | PASS |
| Spurious Emission | §15.205/§15.209 | PASS |

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2. INFORMATION OF THE TEST LABORATORY

Shenzhen HUAKE Testing Technology Co., Ltd.

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Testing Laboratory Authorization :

A2LA Accreditation Code is 4781.01.

FCC Designation Number is CN1229.

Canada IC CAB identifier is CN0045.

CNAS Registration Number is L9589.



1.3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | MU |
|-----|-------------------------------|---------------------------|
| 1 | Conducted Emission | $\pm 2.71\text{dB}$ |
| 2 | RF power, conducted | $\pm 0.37\text{dB}$ |
| 3 | Spurious emissions, conducted | $\pm 0.11\text{dB}$ |
| 4 | All emissions, radiated(<1G) | $\pm 3.90\text{dB}$ |
| 5 | All emissions, radiated(>1G) | $\pm 4.28\text{dB}$ |
| 6 | Temperature | $\pm 0.1^{\circ}\text{C}$ |
| 7 | Humidity | $\pm 1.0\%$ |



2. EUT DESCRIPTION

2.1. GENERAL DESCRIPTION OF EUT

| | |
|----------------------|--|
| Equipment: | SCORE Tablets |
| Model Name: | SCORE 810 |
| Series Model: | N/A |
| Model Difference: | N/A |
| FCC ID: | 2A3XN-SCORE810 |
| Antenna Type: | PIFA Antenna |
| Antenna Gain: | 2.16dBi |
| Operation frequency: | 802.11b/g/n 20:2412~2462 MHz 802.11n 40: 2422~2452MHz |
| Number of Channels: | 802.11b/g/n20: 11CH 802.11n 40: 7CH |
| Modulation Type: | CCK/OFDM/DBPSK/DAPSK |
| Power Source: | DC 5V from Type-C or DC 3.7V from battery |
| Power Rating: | DC 5V from Type-C or DC 3.7V from battery |
| Hardware Version | V1 |
| Software Version | V1 |



2.2. Carrier Frequency of Channels

| Channel List For 802.11b/802.11g/802.11n (HT20) | | | | | | | |
|---|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01 | 2412 | 04 | 2427 | 07 | 2442 | 10 | 2457 |
| 02 | 2417 | 05 | 2432 | 08 | 2447 | 11 | 2462 |
| 03 | 2422 | 06 | 2437 | 09 | 2452 | -- | -- |

| Channel List For 802.11n (HT40) | | | | | | | |
|---------------------------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| -- | -- | 04 | 2427 | 07 | 2442 | -- | -- |
| -- | -- | 05 | 2432 | 08 | 2447 | -- | -- |
| 03 | 2422 | 06 | 2437 | 09 | 2452 | -- | -- |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2.3. OPERATION OF EUT DURING TESTING

Operating Mode

The mode is used: **Transmitting mode for 802.11b/802.11g/802.11n (HT20)**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

The mode is used: **Transmitting mode for 802.11n (HT40)**

Low Channel: 2422MHz


Middle Channel: 2437MHz

High Channel: 2452MHz



2.4. DESCRIPTION OF TEST SETUP

Operation of EUT during conducted and under 1GHz radiation testing:



Operation of EUT Above 1GHz Radiation testing:



The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.



2.5. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Specification | Note |
|------|----------------|-----------|----------------|---|-----------|
| 1 | SCORE Tablets | N/A | Tab S9 | N/A | EUT |
| 2 | AC Adapter | HUAWEI | HW-100225O00 | Input: 100-240V~50/60Hz 0.75A Output: USB-A: 5.0V 2.0A or 9.0V 2.0A or 10.0V 2.25A | Accessory |
| 3 | USB Cable | N/A | N/A | 1m | Accessory |
| 4 | Wired earphone | N/A | N/A | 1.5m | Accessory |
| | | | | | |

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



3. ENERA INFORMATION

3.1. TEST ENVIRONMENT AND MODE

Operating Environment:

| | |
|-----------------------|-----------|
| Temperature: | 25.0 °C |
| Humidity: | 56 % RH |
| Atmospheric Pressure: | 1010 mbar |

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

| Mode | Data rate |
|--------------|-----------|
| 802.11b | 1Mbps |
| 802.11g | 6Mbps |
| 802.11n(H20) | 6.5Mbps |
| 802.11n(H40) | 13.5Mbps |


Final Test Mode:

| | |
|-----------------|---|
| Operation mode: | Keep the EUT in continuous transmitting with modulation |
|-----------------|---|

1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.
2. According to ANSI C63.10 standards, the test results are both the "worst case" and "worst setup" 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 13.5Mbps for 802.11(H40).
3. Mode Test Duty Cycle

| Mode | Duty Cycle | Duty Cycle Factor (dB) |
|--------------|------------|------------------------|
| 802.11b | 0.9953 | -0.02 |
| 802.11g | 0.9722 | -0.12 |
| 802.11n(H20) | 0.9701 | -0.13 |
| 802.11n(H40) | 0.9420 | -0.26 |

Test plots as follows:





4. TEST RESULTS AND MEASUREMENT DATA

4.1. CONDUCTED EMISSION

Test Specification

| Test Requirement: | FCC Part15 C Section 15.207 | | | | | | | | | | | | | | |
|--------------------------|---|--------------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method: | ANSI C63.10:2013 | | | | | | | | | | | | | | |
| Frequency Range: | 150 kHz to 30 MHz | | | | | | | | | | | | | | |
| Receiver setup: | RBW=9 kHz, VBW=30 kHz, Sweep time=auto | | | | | | | | | | | | | | |
| Limits: | <table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> | Frequency range (MHz) | Limit (dBuV) | | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV) | | | | | | | | | | | | | | |
| | Quasi-peak | Average | | | | | | | | | | | | | |
| 0.15-0.5 | 66 to 56* | 56 to 46* | | | | | | | | | | | | | |
| 0.5-5 | 56 | 46 | | | | | | | | | | | | | |
| 5-30 | 60 | 50 | | | | | | | | | | | | | |
| Test Setup: | <div><div><div>Reference Plane</div><div>40cm</div><div><div><div>E.U.T</div><div>AC power</div></div><div>Test table/Insulation plane</div></div><div>80cm</div><div><div>LISN</div><div>Filter</div><div>AC power</div></div><div>EMI Receiver</div></div><div><div>Remark</div><div>E.U.T: Equipment Under Test</div><div>LISN: Line Impedance Stabilization Network</div><div>Test table height=0.8m</div></div></div> | | | | | | | | | | | | | | |
| Test Mode: | Charging + transmitting with modulation | | | | | | | | | | | | | | |
| Test Procedure: | <div><div>1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</div></div> | | | | | | | | | | | | | | |
| Test Result: | PASS | | | | | | | | | | | | | | |



Test Instruments


| Conducted Emission Shielding Room Test Site (843) | | | | | |
|---|--------------|-----------------|---------------|------------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Date | Calibration Due |
| Receiver | R&S | ESR-7 | HKE-010 | Feb. 17, 2023 | Feb. 16, 2024 |
| LISN | R&S | ENV216 | HKE-002 | Feb. 17, 2023 | Feb. 16, 2024 |
| Coax cable (9KHz-30MHz) | Times | 381806-002 | N/A | Feb. 17, 2023 | Feb. 16, 2024 |
| Conducted test software | Tonscend | TS+ Rev 2.5.0.0 | HKE-081 | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



4.2. TEST RESULT

Remark: All the test modes completed for test. only the worst result of 802.11b was reported as below:
Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Suspected List

| NO. | Freq. [MHz] | Level [dBμV] | Factor [dB] | Limit [dBμV] | Margin [dB] | Reading [dBμV] | Detector | Type |
|-----|-------------|--------------|-------------|--------------|-------------|----------------|----------|------|
| 1 | 0.5775 | 46.24 | 20.05 | 56.00 | 9.76 | 26.19 | PK | L |
| 2 | 1.4010 | 44.47 | 20.11 | 56.00 | 11.53 | 24.36 | PK | L |
| 3 | 1.9770 | 44.77 | 20.14 | 56.00 | 11.23 | 24.63 | PK | L |
| 4 | 2.4585 | 45.06 | 20.19 | 56.00 | 10.94 | 24.87 | PK | L |
| 5 | 2.9175 | 43.19 | 20.21 | 56.00 | 12.81 | 22.98 | PK | L |
| 6 | 4.1730 | 48.27 | 20.25 | 56.00 | 7.73 | 28.02 | PK | L |

Final Data List

| NO. | Freq. [MHz] | Correction factor[dB] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | QP Reading [dBμV] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] | AV Reading [dBμV] | Type |
|-----|-------------|-----------------------|-----------------|-----------------|----------------|-------------------|-----------------|-----------------|----------------|-------------------|------|
| 1 | 0.5833 | 20.05 | 43.44 | 56.00 | 12.56 | 23.39 | 32.15 | 46.00 | 13.85 | 12.10 | L |
| 2 | 4.2033 | 20.25 | 42.57 | 56.00 | 13.43 | 22.32 | 30.44 | 46.00 | 15.56 | 10.19 | L |

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction facto


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.



Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)

FCC PART 15 C CLASS B (N)



Suspected List

| NO. | Freq. [MHz] | Level [dBμV] | Factor [dB] | Limit [dBμV] | Margin [dB] | Reading [dBμV] | Detector | Type |
|-----|----------------|-----------------|----------------|-----------------|----------------|-------------------|----------|------|
| 1 | 0.5820 | 45.49 | 20.05 | 56.00 | 10.51 | 25.44 | PK | N |
| 2 | 0.8925 | 41.86 | 20.06 | 56.00 | 14.14 | 21.80 | PK | N |
| 3 | 1.4280 | 43.20 | 20.11 | 56.00 | 12.80 | 23.09 | PK | N |
| 4 | 1.9770 | 43.69 | 20.14 | 56.00 | 12.31 | 23.55 | PK | N |
| 5 | 2.4855 | 43.05 | 20.19 | 56.00 | 12.95 | 22.86 | PK | N |
| 6 | 4.2315 | 46.68 | 20.25 | 56.00 | 9.32 | 26.43 | PK | N |

Final Data List

| NO. | Freq. [MHz] | Correction factor[dB] | QP Value [dBμV] | QP Limit [dBμV] | QP Margin [dB] | QP Reading [dBμV] | AV Value [dBμV] | AV Limit [dBμV] | AV Margin [dB] | AV Reading [dBμV] | Type |
|-----|----------------|--------------------------|-----------------------|-----------------------|----------------------|-------------------------|-----------------------|-----------------------|----------------------|-------------------------|------|
| 1 | 4.2361 | 20.25 | 42.35 | 56.00 | 13.65 | 22.10 | 35.44 | 46.00 | 10.56 | 15.19 | N |

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.



4.3. MAXIMUM CONDUCTED OUTPUT POWER

Test Specification

| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | KDB 558074 |
| Limit: | 30dBm |
| Test Setup: |  Power meter EUT |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none">1. The testing follows the Measurement Procedure of FCC KDB 558074 D01 15.247 Meas Guidance v05r02.2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.3. Set to the maximum power setting and enable the EUT transmit continuously.4. Measure the Peak output power and record the results in the test report. |
| Test Result: | PASS |

Test Instruments

| RF Test Room | | | | | |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer | Agilent | N9020A | HKE-048 | Feb. 17, 2023 | Feb. 16, 2024 |
| Power meter | Agilent | E4419B | HKE-085 | Feb. 17, 2023 | Feb. 16, 2024 |
| Power Sensor | Agilent | E9300A | HKE-086 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF cable | Times | 1-40G | HKE-034 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Feb. 17, 2023 | Feb. 16, 2024 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



Test Data

| Test Channel | Frequency | Maximum Peak Conducted Output Power | LIMIT |
|-------------------|-----------|---|-------|
| | (MHz) | (dBm) | dBm |
| TX 802.11b Mode | | | |
| CH01 | 2412 | 13.02 | 30 |
| CH06 | 2437 | 14.10 | 30 |
| CH11 | 2462 | 14.03 | 30 |
| TX 802.11g Mode | | | |
| CH01 | 2412 | 12.47 | 30 |
| CH06 | 2437 | 12.04 | 30 |
| CH11 | 2462 | 12.45 | 30 |
| TX 802.11n20 Mode | | | |
| CH01 | 2412 | 11.28 | 30 |
| CH06 | 2437 | 13.00 | 30 |
| CH11 | 2462 | 12.81 | 30 |
| TX 802.11n40 Mode | | | |
| CH03 | 2422 | 12.03 | 30 |
| CH06 | 2437 | 11.92 | 30 |
| CH09 | 2452 | 12.90 | 30 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



4.4. EMISSION BANDWIDTH

Test Specification

| | |
|-------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) |
| Test Method: | KDB 558074 |
| Limit: | >500kHz |
| Test Setup: |  Spectrum Analyzer EUT |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none">1. The testing follows FCC KDB Publication 558074 D01 15.247 Meas Guidance v05r02.2. Set to the maximum power setting and enable the EUT transmit continuously.3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.4. Measure and record the results in the test report. |
| Test Result: | PASS |

Test Instruments

| RF Test Room | | | | | |
|---------------------------|--------------|----------|---------------|------------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer | Agilent | N9020A | HKE-048 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF cable | Times | 1-40G | HKE-034 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Feb. 17, 2023 | Feb. 16, 2024 |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



Test data

| Test channel | 6dB Emission Bandwidth (MHz) | | | |
|--------------|------------------------------|---------|--------------|--------------|
| | 802.11b | 802.11g | 802.11n(H20) | 802.11n(H40) |
| Lowest | 7.080 | 13.200 | 13.800 | 34.960 |
| Middle | 8.040 | 15.880 | 16.320 | 35.200 |
| Highest | 7.560 | 15.680 | 16.280 | 31.200 |
| Limit: | >500k | | | |
| Test Result: | PASS | | | |

Test plots as follows:



802.11b Modulation

Lowest channel



Middle channel



Highest channel





802.11g Modulation

Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n (HT20) Modulation

Lowest channel



Middle channel



Highest channel





802.11n (HT40) Modulation

Lowest channel



Middle channel




Highest channel





4.5. POWER SPECTRAL DENSITY

Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (e) |
| Test Method: | KDB 558074 |
| Limit: | The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission. |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer EUT</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none">1. The testing follows Measurement procedure 10.2 method PKPSD of FCC KDB Publication 558074 D01 15.247 Meas Guidance v05r02.2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.3. Set to the maximum power setting and enable the EUT transmit continuously.4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW.5. Detector = RMS, Sweep time = auto couple.6. Employ trace averaging (Peak) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.7. Measure and record the results in the test report. |
| Test Result: | PASS |



Test Instruments

| RF Test Room | | | | | |
|---------------------------|--------------|----------------------|---------------|------------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer | Agilent | N9020A | HKE-048 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF Cable (9KHz-26.5GHz) | Tonscend | 170660 | N/A | Feb. 17, 2023 | Feb. 16, 2024 |
| RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF test software | Tonscend | JS1120-B Version 2.6 | HKE-083 | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



Test data

| EUT Set Mode | Channel | Result (dBm/10kHz) | 10log (3/10) | Result (dBm/3kHz) |
|---|---------|--------------------|--------------|-------------------|
| 802.11b | Lowest | -12.58 | -5.23 | -17.81 |
| | Middle | -12.17 | -5.23 | -17.4 |
| | Highest | -11.87 | -5.23 | -17.1 |
| 802.11g | Lowest | -15.5 | -5.23 | -20.73 |
| | Middle | -16.12 | -5.23 | -21.35 |
| | Highest | -15.52 | -5.23 | -20.75 |
| 802.11n(H20) | Lowest | -15.52 | -5.23 | -20.75 |
| | Middle | -15.14 | -5.23 | -20.37 |
| | Highest | -12.43 | -5.23 | -17.66 |
| 802.11n(H40) | Lowest | -17.59 | -5.23 | -22.82 |
| | Middle | -19.13 | -5.23 | -24.36 |
| | Highest | -16.46 | -5.23 | -21.69 |
| PSD Test Result (dBm/10kHz)= Result +Offset Offset= Instrument attenuation +cable loss PSD test result (dBm/3kHz)= PSD test result (dBm/10kHz)-5.23 | | | | |
| Limit: 8dBm/3kHz | | | | |
| Test Result: | PASS | | | |

Test plots as follows:



802.11b Modulation

Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11g Modulation

Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11n (HT20) Modulation

Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




802.11n (HT40) Modulation


Lowest channel



Middle channel



Highest channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



4.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT

Test Specification

| | |
|--------------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | KDB558074 |
| Limit: | In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). |
| Test Setup: |  <p>The diagram shows a green Spectrum Analyzer connected to a yellow EUT (Equipment Under Test) via a white RF cable and a small white attenuator block. Labels 'Spectrum Analyzer' and 'EUT' are placed below their respective components.</p> |
| Test Mode: | Transmitting mode with modulation |
| Test Procedure: | <ol style="list-style-type: none">1. The testing follows FCC KDB Publication 558074 D01 15.247 Meas Guidance v05r02.2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.3. Set to the maximum power setting and enable the EUT transmit continuously.4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).5. Measure and record the results in the test report.6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. |
| Test Result: | PASS |



Test Instruments


| RF Test Room | | | | | |
|---------------------------|--------------|----------------------|---------------|------------------|-----------------|
| Equipment | Manufacturer | Model | Serial Number | Calibration Date | Calibration Due |
| Spectrum analyzer | Agilent | N9020A | HKE-048 | Feb. 17, 2023 | Feb. 16, 2024 |
| High pass filter unit | Tonscend | JS0806-F | HKE-055 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF Cable (9KHz-26.5GHz) | Tonscend | 170660 | N/A | Feb. 17, 2023 | Feb. 16, 2024 |
| RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Feb. 17, 2023 | Feb. 16, 2024 |
| RF test software | Tonscend | JS1120-B Version 2.6 | HKE-083 | N/A | N/A |

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



Test Data


802.11b Modulation



The results shown in this test report refer only to the sample(s) tested and otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.


TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China






802.11g Modulation




The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China




Spurious emission(2437MHz)





802.11n (HT20) Modulation



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



802.11n (HT40) Modulation



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by HUAKE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.cer-mark.com>.

TEL : +86-755 2302 9901 FAX : +86-755 2302 9901 E-mail : service@cer-mark.com

Add: 1-2F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China