

acknowledgement

SPECIFICATION FOR

Customer
CUSTOMER: Forever diffuse

Customer
 Material
Number: CUS
T P / N:

Material No. :
P / N : φ 14.0*20.5-0.08*24P-14TS-8-25C

Product
 Model
Number: 2023/12/05
DESC:

date
DATE : A . 0

edition:
Version :


Fitting the P R E P A R E D B Y	Review the C H E C K E D B Y	Approval of the A P P R O V E D B Y	The customer acknowledged that the C U S T O M E R A P P R O V E
	chen lihua		

SHENZHEN YONGMAN DIGITAL CO.,LTD

S PECIFICATION


Product model number: D E SC	φ 14.0*20.5-0.08*24P-14TS-8- 25CC	Rev : A.0	Customer CUST:
			Customer material number CUST P / N:

1. Dimension DIMENSION: (mm)



A	8.0±0.5
B	25.0±0.5
C	14.0±1
D	20.5±1
E	13.0 mm
F	3.00±0.5
G	2.6±0.5

2. A Schematic diagram of the SCHEMATIC DIAGRA M



3. Winding parameter Winding Specification:

- pour :
1. Cross coil outlet
 2. The coil is attached with circular soft magnetic sheet with size φ 8*25*1.0mm;
 3. The lead outlet position is shown above (when the outlet is up, the deep gap is below)
 4. The overall thickness of the coil is not more than 3mm;
 - 5

order number NO .	Termina l, TERMINA L	Line diameter WI RE	number of turns T urns	Winding direction is Winding Direc tion
1	S F	0.08*24	13Ts	anticlockwise

4. Electrical characteristics E LECTRICAL CHARACTERISTICS:

Temperature TEMPERATURE: 25 ± 10°C, humidity RELATIVE HUMIDITY: 65 ± 20%

orde r num ber NO.	The Proje ct ITE M	Terminal, TERMINA L	standard SPECIFICATIO N	test condition TEST FREQU ENCY	measuring and test instruments TEST EQUIP MENTS
1	IND .	S -F	4.8 uH ± 10%, individual coil	100KHz/1.0V	LCZ METER 1062B
2	IND .	S -F	7.8 uH ± 10% tape magnetic tape	100KHz/1.0V	LCZ METER 1062B
3	DC R	S -F	600m Ω Max		LCZ METER 502B

File / date PREPARED BY / DATE	Review / Date CHECKED BY / DATE
chen lihua 2023 / 12 / 05	