

## FCC 47 CFR MPE REPORT

Hong Kong Etech Groups Ltd.

Smart Outdoor Plug

Model Number: EST-C-045

Additional Model: XWS7-2002-BLK, XWS7-2002

FCC ID: 2A3ZO-ETS-C-045

Applicant:	Hong Kong Etech Groups Ltd.
Address:	16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang, Baoan, Shenzhen, China
Prepared By:	EST Technology Co., Ltd. Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2207068
Date of Test:	Jun. 23~Jul. 14, 2022
Date of Report:	Jul. 15, 2022

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
BLE	2402	0.76	1.1912
	2440	-0.02	0.9954
	2480	-1.43	0.7194
IEEE 802.11b	2412	15.81	38.1066
	2437	16.28	42.4620
	2462	16.92	49.2040
IEEE 802.11g	2412	18.59	72.2770
	2437	17.64	58.0764
	2462	18.21	66.2217
IEEE 802.11n HT20	2412	17.03	50.4661
	2437	16.73	47.0977
	2462	17.35	54.3250
IEEE 802.11n HT40	2422	16.20	41.6869
	2437	15.36	34.3558
	2452	15.01	31.6957

## 3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBi)	(Linear)			
2.4G Band								
BLE	0.76	0±1	1	-0.68	0.855	0.0003	1	Complies
IEEE 802.11b	16.92	16±1	17	-0.68	0.855	0.0100	1	Complies
IEEE 802.11g	18.59	18±1	19	-0.68	0.855	0.0158	1	Complies
IEEE 802.11n HT20	17.35	17±1	18	-0.68	0.855	0.0126	1	Complies
IEEE 802.11n HT40	16.2	16±1	17	-0.68	0.855	0.0100	1	Complies

**End of Test Report**