SHENZHEN CHENYANSHI TECHNOLOGY CO.,LTD.

2022/03/04

To: Federal Communications Commission 7435 Oakland Mills Road Columbia, MD

FCC ID: 2A45H303-0079

To Whom It May Concern:

This letter is to ascertain that, Product: **Wireless Charging Stand M/N: 303-0079** has been the units used for conducting FCC compliance testing, and it meets 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) all 6 conditions.

1	Power transfer frequency is less that 1 MHz
Reply:	Yes, Power transfer frequency is less that 1 MHz; Ans: EUT operating frequency range is 0.11~0.205MHz.
2	Output power from each primary coil is less than or equal to 15 watts.
Reply:	Yes, Output power from each primary coil is equal to 15 watts. The max output power is 15W.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
Reply:	Yes, The EUT has only one primary coil.
4	Client device is placed directly in contact with the transmitter.
Reply:	Yes, The client device needs to be in contact with the transmitter base, and the contact distance is less than 10mm.
5	Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
Reply:	Yes, EUT Meets Mobile exposure conditions.
6	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Reply:	No. The measurement is based on KDB inquiry which 0mm distance is set for all positions testing.

If you have any question or concerns, pls. contact us.

Sincerely,

RongHe Zhong

Manager

SHENZHEN CHENYANSHI TECHNOLOGY CO.,LTD.

ROOM 401,NO.41 QINGSHUI ROAD LONGXI COMMUNITY LONGGANG DISTRICT,SHENZHEN CITY,GUANGDONG PROVINCE,CHINA