

## FCC RF EXPOSURE REPORT

For

**P40 Agricultural Drone** 

**MODEL NUMBER: 3WWDZ-20BH** 

FCC ID: 2A46G-3WWDZ-20BH

REPORT NUMBER: 4790254511-7

ISSUE DATE: March 31, 2022

Prepared for

**Guangzhou Xaircraft Technology CO.,LTD** 

Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang-dong,

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China


> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4790254511-7 Page 2 of 8

# **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	03/31/2022	Initial Issue	





# **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4.	REQUIREMENT	F



REPORT NO.: 4790254511-7

Page 4 of 8

### 1. ATTESTATION OF TEST RESULTS

**Applicant Information** 

Company Name: Guangzhou Xaircraft Technology CO.,LTD

Address: Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang-dong,

China

**Manufacturer Information** 

Company Name: Guangzhou Xaircraft Technology CO.,LTD

Address: Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang-dong,

China

**EUT Information** 

EUT Name: P40 Agricultural Drone

Model: 3WWDZ-20BH Sample Received Date: February 14, 2022

Sample Status: Normal Sample ID: 4675027-2

Date of Tested: February 14, 2022 ~ March 30, 2022

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC 47CFR§2.1091	PASS			
KDB-447498 D01 V06	PASS			

Prepared By:	Checked By:		
kebo. zhang.	Shemmer		
Kebo Zhang Project Engineer	Shawn Wen Laboratory Leader		

Approved By:

Stephen Guo Laboratory Manager



### 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB 447498 D01 General RF Exposure Guidance v06.

#### 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	,
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification
	rules
	ISED (Company No.: 21320)
Accreditation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Certificate	has been registered and fully described in a report filed with ISED.
Cortinicato	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011
	Children in the foot registration 140. Is 0-20012 and 1-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



REPORT NO.: 4790254511-7 Page 6 of 8

### 4. REQUIREMENT

#### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

#### RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

### **CALCULATION METHOD**

 $S=PG/4\pi R^2 c$ 

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

REPORT NO.: 4790254511-7 Page 7 of 8

# **CALCULATED RESULTS**

Radio Frequency Radiation Exposure Evaluation

(Worst case)					
Operating	Max. Tune up Power	Max. Antenna Gain	Power density	Limit	
Mode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )	Liiiii	
GSM850	34	2	0.79201	1	

(Worst case)					
Operating	Max. Tune up Power	Max. Antenna Gain	Power density	Limit	
Mode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )		
WCDMA B4	23	2.8	0.07564	1	

(Worst case)				
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density	Limit
Wode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )	
LTE B25	24	2.8	0.09522	1

(Worst case)					
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density	Limit	
Wode	(dBm)	(dBi) (mW/ cm <sup>2</sup> )			
LTE B12	24	-3	0.02505	0.47	

	(Worst case)					
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density	Limit		
Mode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )			
LTE B38	23	2.5	0.07059	1		

WiFi (Worst case)					
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density	Limit	
Mode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )		
WIFI 2.4G	20	2	0.03153	1	



REPORT NO.: 4790254511-7 Page 8 of 8

#### Note:

- 1. The calculated distance is 20 cm.
- 2. 2.4 GHz WiFi & GSM can transmit simultaneously.
  - 2.4 GHz WiFi & WCDMA can transmit simultaneously.
  - 2.4 GHz WiFi & LTEcan transmit simultaneously.
- 3. 2.4 GHz WiFi + GSM850= 0.03153 + 0.79201= 0.82354 (mW/cm<sup>2</sup>)

Therefor the maximum calculations (worst case) of above situations are less than the "1" limit.

4. WIFI power comes form report 4790254511-4. (FCC ID: 2A46G-WM101)

END OF REPORT