

广州极飞科技股份有限公司

样品承认书

产品料号: 01-003-00450

产品版本: A0

产品名称: 2. 4G内置PCB天线

产品规格: 2.4G PCB 天线 1.13mm 黑色线 L=140mm
+IPEX

原料牌号:

表面处理: 丝印

供 应 商: 东莞市海恒电子科技有限公司

极飞签核		
结构设计	可靠性质量	中试审批
说明:		

供应商签核		
制作	审核	核准
邓文兵	胡超	陈鹏
说明:		

Product Number: AN2400-PCB87BX
Product Name: Antenna

Index:

- 1. Specification (规格)
- 2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
- 3. Antenna - S Parameter Test Data (样品测试数据)
- 4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
- 5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2024.1.17	初版	

Product Number: AN2400-PCB87BX

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500 MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	3.82dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	OD1.13mm , Black
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number: AN2400-PCB87BX

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: $260 \pm 5^{\circ}\text{C}$; Duration: 5 seconds 温度 $260 \pm 5^{\circ}\text{C}$; 持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol. $\leq 5\%$ 符合待测物规范; 频率偏移 $\leq 5\%$	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process. 检查尺寸, 颜色, 材料, 包装, 表面处理	Directive DUT specification 符合待测物规范	PASS
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C ; RH: $\geq 95\%$; NaCl solution: $\geq 5\%$; Time: 24H 温度 35°C ; 湿度 $\geq 95\%$; 盐水浓度 $\geq 5\%$; 测试 24H	1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2400-PCB87BX

Product Name: Antenna

3. Antenna - S Parameter Test Data



Product Number: AN2400-PCB87BX
Product Name: Antenna

4. Antenna - Radiation Pattern Test Data


Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	3.02	3.08	3.16	3.47	3.71	3.82	3.68	3.67	3.47	3.40	3.39
Efficiency (%)	60.33	60.48	60.99	62.90	64.76	64.86	63.13	63.79	62.22	62.36	62.57

XZ


YX

XY


2400MHz




2450MHz



2500MHz



5. Mechanical Drawing See attached files



HF	☐
RoHS 2.0	☒
REACH	☐
CONFIDENTIAL	

SIGN	DATE	DESCRIPTION	APPROVER
☒			
☒			
☒			

印白色字体

RF CONDUCTIVE PASTE

- Note:
- 1.Mark * is important dimension;"Cpk "Identify for process control(CpK≥ 1.33).
 - 2.Tolerance:Unmarked tolerance refer to the standard tolerance please.
 - 3.Pay attention to the direction of the connector.

东莞市海恒电子科技有限公司

3	CR-113-ZP-A	I-PEX	Cu	Au Plated	1
2	CB-113BS	Coaxial Cable		Ø1.13mm,Black	1
1	AN2400-PCB106013	PCB	FR4	Black T=0.8mm	1
No.	Part Number	Name	Material	Finish	Q'ty

TITLE: Antenna					
PART NO.: AN2400-PCB87BX				CUSTOMER P/N: /	
APP BY	CHK BY	RF BY	DES BY		Tolerance
YCX	HC	WJ	SY	UNITS: mm	X.X ±0.5
2024.01.17	2024.01.17	2024.01.17	2024.01.17	SCALE: 1/1	X.XX ±0.2
				REVISION: A	X° ±1

产品包装规范


PACKING CRITERION

Date: 2024.01.17

Page: 1 of 1


Part Number : AN2400-PCB87BX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。




8000pcs/Carton



3. SEALING。



SIDE



FRONT



APPROVED BY : YCX CHECKED BY : HC DESIGNED BY : SY Y