

广州极飞科技股份有限公司

样品承认书

产品料号: _____

产品版本: **A0**

产品名称: **WIFI内置FPC天线**

产品规格: **2.4G FPC 天线,1.13mm 黑色线 L=50mm + I-PEX**

原料牌号: _____

表面处理: **丝印**

供 应 商: **东莞市海恒电子科技有限公司**

极飞签核		
结构设计	可靠性质量	中试审批
说明:		

供应商签核		
制作	审核	核准
邓文兵	胡超	陈鹏
说明:		

Product Number: AN2400-FPC27BX
Product Name: Antenna

Index:

- 1. Specification (规格)
- 2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
- 3. Antenna - S Parameter Test Data (样品测试数据)
- 4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
- 5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2023.9.5	初版	

Product Number: AN2400-FPC27BX

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500 MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	2.14dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	OD1.13mm ,Black
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 30°C ~ +80 °C
Operation Temperature 工作温度	- 30°C ~ +80 °C

Product Number: AN2400-FPC27BX

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C;Duration: 5 seconds 温度 260±5° C;持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面处理	Directive DUT specification 符合待测物规范	PASS
6	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 72H 温度 35°C; 湿度≥95%;盐水浓度≥5%; 测试 72H	1. No Visual Damage 2. Frequency Tol.≤5% 无明显外观不良;频率偏移≤5%	PASS
7	Temperature and Humidity Chamber 恒温恒湿	GB / T 2423.3-2006 Temp: 80°C / 12 H; -30°C / 12H RH: ≥ 90%; Time: 24H 温度 80°C 测试 12H 转-40°C 测试 12H; 湿度≥ 90%; 时间 48H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢复 2H 后, 无明显外观不良;频率偏移≤5%	PASS
8	Thermal Shock 冷热冲击	GB / T 2423.22 - 2008 - 30° C (30 minutes) to + 80° C (30 minutes); Cycles: 24 - 30° C 测试 30 分转 80° C 测试 30 分为一个周期; 共 24 周期	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢复 2H 后, 无明显外观不良;频率偏移≤5%	PASS
9	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2400-FPC27BX

Product Name: Antenna

3. Antenna - S Parameter Test Data







4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	1.66	1.71	1.72	1.68	1.85	1.90	2.08	2.14	2.04	1.94	1.82
Efficiency (%)	52.30	53.00	55.04	54.47	58.39	60.81	52.45	56.04	53.56	54.98	53.74





Product Number: AN2400-FPC27BX

Product Name: Antenna





2400MHz




2450MHz



2500MHz



5. Mechanical Drawing See attached files



Note:

- 1.Mark * is important dimension;"Cpk "Identify for process control(CpK≧1.33).
- 2.Tolerance:Unmarked tolerance refer to the standard tolerance please.
- 3.Pay attention to the direction of the connector.

3	CR-113-ZP-A	I-PEX	Cu	Au Plated	1
2	CB-113BS	Coaxial Cable	OD1.13mm	Black	1
1	AN2400-FPC402154	FPC		Black	1
No.	Part Number	Name	Material	Finish	Q'ty

东莞市海恒电子科技有限公司					
TITLE: Antenna					
PART NO.: AN2400-FPC27BX				CUSTOMER P/N: /	
APP BY	CHK BY	RF BY	DES BY		Tolerance
WJ	YCX	HC	SY		X.X ±0.5
2023.08.25	2023.08.25	2023.08.25	2023.08.25		X.XX ±0.2
				UNITS: mm	X° ±1
				SCALE: 1/1	
				REVISION: A	

HF	☐
RoHS2.0	☒
REACH	☐
CONFIDENTIAL	

SIGN	DATE	DESCRIPTION	APPROVER

产品包装规范


PACKING CRITERION

Date: 2023.08.25

Page: 1 of 1


Part Number : AN2400-FPC27BX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。



8000pcs/Carton

3. SEALING。




SIDE

ITEM NO:
QTY: PCS
N W: KGS
G W: KGS
MEAS

FRONT

C/NO
MADE IN CHINA



APPROVED BY: YCX

CHECKED BY: HC

DESIGNED BY: SY Y