

FCC RF EXPOSURE REPORT

For

XAG WCP1 Wireless Control Panel

MODEL NUMBER: M6CPAPC4B

REPORT NUMBER: 4791318657-5-RF-2

ISSUE DATE: March 19, 2024

FCC ID: 2A46G-M6CPAPC4B

Prepared for

Guangzhou Xaircraft Technology CO.,LTD Block C, No.115, Gaopu Road, Tianhe District, GuangzhouCity, Guangdong, P.R. 510663 China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev. Issue Date		Revisions	Revised By	
V0	March 19, 2024	Initial Issue	\	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4.	REQUIREMENT	6



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Address:	Guangzhou Xaircraft Technology CO., LTD Block C, No.115, Gaopu Road, Tianhe District, GuangzhouCity, Guangdong, P.R. 510663 China		
Manufacturer Information1			
Company Name:	Guangzhou Xaircraft Technology CO., LTD		
Address:	Block C, No.115, Gaopu Road, Tianhe District, Guangzhou Guangdong, P.R. 510663 China		
EUT Information			
EUT Name:	XAG WCP1 Wireless Control Panel		
Model:	M6CPAPC4B		
Sample Received Date:	February 28, 2024		
Sample Status:	Normal		
Sample ID:	7208081		

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC 47CFR§2.1091	PASS			
KDB 447498 D01	PASS			

Prepared By:

Date of Tested:

Checked By: Sucur Denny

James Qin **Project Engineer**

Denny Huang Senior Project Engineer

Approved By:

Stephen Guo Operations Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB447498 D01 v06.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No : 4102 01)
Accreditation Certificate	 A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name:
	Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

|--|

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

S=PG/4mR² Where: S=power density P=power input to antenna G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



CALCULATED RESULTS

For Single RF Source

Operation Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducted Average Output Power (dBm)	Power Density at R = 20 cm (W/m ²)	FCC Limit (W/m ²)	FCC Conclusion
BLE	2402	2.13	2.0	0.0051	10.0000	Pass

Note:

- 1. The calculated distance is 20 cm.
- 2. The power comes from operation description.

END OF REPORT