

# FCC RF EXPOSURE REPORT

## **CERTIFICATION TEST REPORT**

For

## WLAN Model

## MODEL NUMBER: WM101

## FCC ID: 2A46G-WM101

### **REPORT NUMBER: 4790254511-4**

### ISSUE DATE: March 17, 2022

**Prepared for** 

Guangzhou Xaircraft Technology CO.,LTD Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang-dong,China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



## **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	3/17/2022	Initial Issue	



# TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4.	REQUIREMENT	6



# **1. ATTESTATION OF TEST RESULTS**

#### Applicant Information

Company Name:	Guangzhou Xaircraft Technology CO.,LTD
Address:	Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang-
	dong,China

#### Manufacturer Information

Company Name:	Guangzhou Xaircraft Technology CO.,LTD
Address:	Block C, 115 Gaopu Rd, Tianhe Dist, Guangzhou, Guang- dong, China

#### **EUT Information**

EUT Name:	WLAN Model
Model:	WM101
Sample Received Date:	Feb 16, 2022
Sample Status:	Normal
Sample ID:	4675027
Date of Tested:	Feb 16,2022 ~ Mar 15, 2022

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC 47CFR§2.1091	PASS			

Prepared By:

Kebo. zhong.

Shenny les

Shawn Wen Laboratory Leader

Checked By:

Kebo Zhang Project Engineer

Approved By:

ephentus

Stephen Guo Laboratory Manager



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

# 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
Accreditation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Certificate	has been registered and fully described in a report filed with ISED.
Certificate	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



## 4. REQUIREMENT

### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

|--|

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

## **CALCULATION METHOD**

 $\begin{array}{l} S=PG/4\pi R^2 \\ Where: \\ S=power density \\ P=power input to antenna \\ G=power gain of the antenna in the direction of interest relative to an isotropic radiator \\ R=distance to the center of radiation of the antenna \end{array}$ 



## CALCULATED RESULTS

Worst Case					
Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm2	mW/cm2	
WIFI 2.4G	20	2	0.03153	1.0	Complies

Note:

- 1. The Power comes from report operation description.
- 2. The EUT cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 3. Calculate by WORST-CASE mode.

## **END OF REPORT**