

600W储能效果a








600W储能效果b



600W储能效果c




600W储能效果d



单位: MM




1、晒纹区域
工艺:转印亮UV
(参考600W储能效果b)



2、晒纹区域
工艺:晒纹
(参考600W储能效果b)



3、字符01
工艺:移印
PANTONE 1505C
PANTONE COOL 445C
(参考600W储能效果a)



4、字符02
工艺:丝印
PANTONE 1505C
(参考600W储能效果d)



5、字符03
工艺:丝印
PANTONE 1505C
PANTONE 445C
(参考600W储能效果a)



6、字符04
工艺:移印
PANTONE 418C
(参考600W储能效果c)



7、产品信息
工艺:镭雕

Name: Digital Power Bank 420W

Model No.: BPE42B Capacity: 9000mAh/288Wh

Solar DC Input: 12-25V=8A 100W Max.

Type-C1 Input: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A 140W Max.

AC Output: 100V~120V~, 3.82A, 60Hz, 420W (Pure Sine Wave; Peak power: 840W)

USB1/USB2 Output: 5V=3A, 9V=3A, 10V=2A, 12V=2.5A

Type-C1 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A 140W Max.

Type-C2 Output: 5V=3A, 9V=3A, 12V=2.5A Type-C1+Type-C2 Output: 100W+30W

USB1+USB2 Output: 5V=5A USB 1+TYPE C1 Output: 30W+100W

USB 2+TYPE C2 Output: 5V=5A

Type-C1+(Type-C2+USB1+USB2) Output: 100W+25W

DC+Car Charger Output: 13.5V=7.4A 100W Max.

Total output: 420W

Manufacturer: Shenzhen Baseus Technology Co., Ltd.

Execution Standard: Q/BASEUS047

FCC ID: 2A482-BPE42B

Made in China SN: JK221201

Service Hotline: 400-071-2711



株式会社波洋



WARNING

1.If you need to dispose of this product, please refer to local laws and regulations.
2.Never strongly bash this product. Do not drop or use the product in high temperature environments. Keep the product out of the reach of children. Please follow the safety instructions.
3.Only applicable to altitudes below 2000m and non-tropical areas.

修改点:

SN码追溯批次更新要求说明:

SN码后4位序列码为日期码:日期码为年/月码,如2020年5月则为2005,
请根据每批次订单实际交货日期月份而更新此后4位序列日期码。

制图:

杜仲航

设计审核:

黄宜成

内容审核: