

版本号Version Number: SPEC-HEK
生效日期Effective Date: 20240202001

东莞市合康电子有限公司
Dongguan Hekang Electronic co., LTD
Chip Antenna

承认书

客户名称: 惠州今科电子有限公司 Customer name: Huizhou JoneTech Electronic Co.,LTD	制造商: 东莞市合康电子有限公司 Manufacturer: Dongguan Hekang Electronics Co., Ltd.
客户料号 Customer part number: D00FPE321600	产品型号 Product number: 2.4GHz 3216 Chip Antenna
部品名: 陶瓷天线 Product Name: Chip Antenna	产品料号 Product part number: ANT3216R2400A1L0 版本 Version: A01

客户接受

This Specifications is received

签章 SIGN:

接受日 DATE:

拟制 Drawn by	审核 Checked by	批准 Approved by
梁梅 Liang Mei	任振康 Ren Zhenkang	彭军 Peng Jun

TEL:0769-87888306

FAX:0769-87888656

Business Mailbox : fae@hekc corp.com

地址: 广东省东莞市常平镇卢屋三联路 159 号时代智睿科技 7 栋 301 室
Room 301, Building 7, Time Intelligence Technology, No. 159, Luwu Sanlian Road,
Changping Town, Dongguan City, Guangdong Province


2.4GHz 3216 Chip Antenna: ANT3216R2400A1L0

Application:

WLAN, 802.11b/g, Bluetooth, etc...

Features

SMD, high reliability, ultra compact, Omni-directional...



Part number

ANT 3216 R 2400 A1 L0
 (1) (2) (3) (4) (5) (6)


(1) Product Code	Chip Antenna
(2) Size Code	3.2x1.6mm
(3) Packing	Tape and reel
(4) Frequency	2.4GHz
(5) Series	A1
(6) Type	L0

Electrical Specification

Working Frequency Range	2400 ~2484 MHz
Peak Gain	1.08dBi (Typ.)
Impedance	50 Ohm
VSWR	2.5(Max)
Polarization	Linear
Azimuth Beamwidth	Omni-directional
Operation Temperature(°C)	-40~85°C


The specification is defined on HEK EVB.

Dimension and Terminal Configuration




Dimension (mm)	
L	3.20±0.15
W	1.60±0.15
T	0.60±0.10
D1	0.50±0.15
D2	1.30±0.15

No.	Terminal Name
1	Feeding
2	Ground




Evaluation Board Reference

PCB Dimension





Antenna Layout Reference





Unit : mm

Electrical Characteristics


VSWR




Radiation Pattern




2441.000MHz H



2441.000MHz E1




2441.000MHz E2



Taping Specifications


Reel and Taping Specification

Reel Specification



TYPE	SIZE		A	ψB	ψC	ψD	W	ψM
3216	7"	3K/Reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0	11.5±2.0	178±2.0


Taping Specification



Packaging	Type	A	B	W	E	F	G	H	T	ψD	P
Paper Type	3216	1.90±0.20	3.50±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10	1.50±0.10	4.0±0.1

Recommended Reflow Profile

Pb free solder



Soaking		Working		Soldering		Peak	
Temp.	Time	Temp.	Time	Temp.	Time	Temp.	
T1	T2	t1	T3	t2	T4	t3	T5
150°C	180°C	60 to 120sec	230°C	more than 30sec	247 to 253°C	within 10sec	260°C Max.

APR. 2023 Ver.01