Product Specifications sheet



Specification No.	2022012023001				
Effective date	2022/12/23				

Customer Name:	安聚
Product Model	
DZ Part No.	TX-DZ5005.3008-K6.3-L10开双槽
Customer item No	0130063301

【 New issue, □ version revision】

【 This specification includes contents and 7 pages in total 】 【 RoHS Compliant Parts 】

organize	Check	Approval
钟建立	1	马湘平

Dongguan Top Wiser Electronic Technology Co., Ltd

Factory address: 7th floor, east of building, xinbosheng Industrial Park,

No. 5, Xinyuan South Road, Tangxia Town, Dongguan City

Tel: 13147097490

[Within 30 days after the customer receives this acknowledgement, please return it with your signature and seal. If it is overdue, it will be deemed that the production will be carried out according to the standards of this acknowledgement].

recognition status:	$\begin{tabular}{lll} \textbf{Date:}\\ \hline \square full recognition \square conditional recognition \square refusal \\ \hline \end{tabular}$						
Approval	Review	Recheck	Check				
remark:							

Product Specifications sheet

Customer Name:	安聚	Customer item No	Y103000206			
DZ Part No.	TX-DZ5005.3008-K6.3-L10开双槽	Specification No.	2022012023001			

Issue/Revision History

Version	/ersion Effective date Change content / reason						
Version 01	Effective date 2022/12/23	Change content / reason New specification release		Approval 马湘平			
	organize	check	approval				
	钟建立	1	马湘平				

Product Specifications sheet

	1 1 \	Juucu	БРС	70111	cations	Biic				
Customer Name:	安聚anju				Customer item No			Y103000206		
DZ Part No	TX-DZ5005.3008-K6.3-L10开双槽 Specification No. 20220120					2300 ⁻	00 Version 01			
♦、Overall dimensions								(unit: mm)		
							Α	\	50.0	±1.5
		-		Α	-		В		42.0	±1.5
	. G	-		В			С	;	20.5	±1.5
	I		-	C			D)	5.3Ref	±0.5
							E		11.0	Ref
							F	:	3.0	±1.0
							G	;	2.7	±0.2
							Н	ı	10.0	±1.0
			//// 🗼	\downarrow	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\				0.8	±0.2(磁片厚度)
			T					e diar	meter: 0.08	* 105p silk-covered
							wire (2)Nur	mber (of windings:	10TS
							(3)Wh	ether		and ending lines
	+	_			/		cross: (4)Coi tape		8mm wide	high temperature
l	i		<u> </u>				(5)The		and magne	tic sheet shall be
							white	glue	tic sheet b ain:0dBi	ack 49 round
♦、Electrical cl	haracteristics	::								
parameter	•	ification			conditions		Test instrument			
L0		±10%	μH ·		00KHz/1V	■TH1816				
Q DCR	>40 <95		min mΩ		00KHz/1V @ 25℃	■TH1816				
◆、Temperatur			11122		<u>ug 20 c</u>	12011 002				
Operating temperature	1									
peak Gain: 0dbi										
♦ list of mater	rials:									
Item	Product Name	Material	specif	fication	Supplier	Remark				
1	Magnetic sheet		3 * 0.8T ∃		- *	1	PC40 mengzinc			
2	Copper wire	0. 08*105P				silk-covered w			ire	
3	High temperature adhesive tape		8MM			Rosh tape		Э		
4	White glue	D=49roun	d of whi	ite glue		Rosh tape				
5	tin		107H			ROSH tin				
6	glue	黄胶	yellow ;	glue		ROSH	glue	9		
organize					check				appro	oval
钟建立					1				马湘	平