FCC ID: 22A48M-X9

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)		SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.565	1.14	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	-0.687	0.85	-0±1	1.00	1.26	<5	0.39330	3.00	YES
	2.480	-1.537	0.70	-1±1	0.00	1.00	<5	0.31496	3.00	YES

Conclusion:

For the max result : 0.49127 ≤ FCC Limit 3.0 for 1g SAR.

EDR:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.57	1.14	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.44	-0.728	0.85	-0±1	1.00	1.26	<5	0.39330	3.00	YES
	2.480	-1.525	0.70	-1±1	0.00	1.00	<5	0.31496	3.00	YES

Conclusion:

For the max result : 0.49127 ≤ FCC Limit 3.0 for 1g SAR.

Note that "the device cannot support BT BLE, non-standard 2.4g and BT EDR transmissions at the same time;