

RF Mode	TX 802.11a 6G	Channel	CH 105 : 6475 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	117.3 PK			2.00 H	106	113.9	3.4
2	*6475.00	109.8 AV			2.00 H	106	106.4	3.4
3	#12950.00	54.9 PK	88.2	-33.3	2.10 H	106	44.2	10.7
4	#12950.00	45.0 AV	68.2	-23.2	2.10 H	106	34.3	10.7
5	19425.00	54.9 PK	74.0	-19.1	1.58 H	99	61.1	-6.2
6	19425.00	44.3 AV	54.0	-9.7	1.58 H	99	50.5	-6.2
7	#25900.00	46.0 PK	88.2	-42.2	2.17 H	171	47.2	-1.2
8	#25900.00	36.1 AV	68.2	-32.1	2.17 H	171	37.3	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	118.2 PK			2.36 V	86	114.8	3.4
2	*6475.00	110.7 AV			2.36 V	86	107.3	3.4
3	#12950.00	56.3 PK	88.2	-31.9	1.23 V	247	45.6	10.7
4	#12950.00	45.4 AV	68.2	-22.8	1.23 V	247	34.7	10.7
5	19425.00	58.5 PK	74.0	-15.5	2.44 V	267	64.7	-6.2
6	19425.00	47.1 AV	54.0	-6.9	2.44 V	267	53.3	-6.2
7	#25900.00	46.4 PK	88.2	-41.8	2.19 V	227	47.6	-1.2
8	#25900.00	36.5 AV	68.2	-31.7	2.19 V	227	37.7	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	117.8 PK			2.07 H	97	114.1	3.7
2	*6515.00	110.0 AV			2.07 H	97	106.3	3.7
3	#13030.00	55.3 PK	88.2	-32.9	2.20 H	118	44.3	11.0
4	#13030.00	45.3 AV	68.2	-22.9	2.20 H	118	34.3	11.0
5	19545.00	54.2 PK	74.0	-19.8	1.59 H	100	60.4	-6.2
6	19545.00	44.1 AV	54.0	-9.9	1.59 H	100	50.3	-6.2
7	#26060.00	45.8 PK	88.2	-42.4	2.05 H	155	46.8	-1.0
8	#26060.00	35.7 AV	68.2	-32.5	2.05 H	155	36.7	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	118.5 PK			2.40 V	79	114.8	3.7
2	*6515.00	111.1 AV			2.40 V	79	107.4	3.7
3	#13030.00	57.2 PK	88.2	-31.0	1.33 V	244	46.2	11.0
4	#13030.00	45.9 AV	68.2	-22.3	1.33 V	244	34.9	11.0
5	19545.00	58.9 PK	74.0	-15.1	2.39 V	287	65.1	-6.2
6	19545.00	47.1 AV	54.0	-6.9	2.39 V	287	53.3	-6.2
7	#26060.00	47.0 PK	88.2	-41.2	2.15 V	210	48.0	-1.0
8	#26060.00	36.7 AV	68.2	-31.5	2.15 V	210	37.7	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	116.9 PK			2.08 H	108	113.0	3.9
2	*6535.00	109.7 AV			2.08 H	108	105.8	3.9
3	#13070.00	55.2 PK	88.2	-33.0	2.15 H	119	44.1	11.1
4	#13070.00	45.2 AV	68.2	-23.0	2.15 H	119	34.1	11.1
5	19605.00	54.3 PK	74.0	-19.7	1.62 H	100	60.5	-6.2
6	19605.00	44.0 AV	54.0	-10.0	1.62 H	100	50.2	-6.2
7	#26140.00	45.8 PK	88.2	-42.4	2.11 H	164	46.8	-1.0
8	#26140.00	35.7 AV	68.2	-32.5	2.11 H	164	36.7	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	117.9 PK			2.30 V	94	114.0	3.9
2	*6535.00	110.6 AV			2.30 V	94	106.7	3.9
3	#13070.00	56.9 PK	88.2	-31.3	1.27 V	244	45.8	11.1
4	#13070.00	45.7 AV	68.2	-22.5	1.27 V	244	34.6	11.1
5	19605.00	58.9 PK	74.0	-15.1	2.40 V	281	65.1	-6.2
6	19605.00	47.2 AV	54.0	-6.8	2.40 V	281	53.4	-6.2
7	#26140.00	46.9 PK	88.2	-41.3	2.20 V	217	47.9	-1.0
8	#26140.00	36.8 AV	68.2	-31.4	2.20 V	217	37.8	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	117.1 PK			2.03 H	109	113.0	4.1
2	*6715.00	109.9 AV			2.03 H	109	105.8	4.1
3	#13430.00	55.4 PK	88.2	-32.8	2.16 H	121	42.9	12.5
4	#13430.00	45.2 AV	68.2	-23.0	2.16 H	121	32.7	12.5
5	20145.00	54.5 PK	74.0	-19.5	1.65 H	109	60.0	-5.5
6	20145.00	44.0 AV	54.0	-10.0	1.65 H	109	49.5	-5.5
7	#26860.00	45.8 PK	88.2	-42.4	2.16 H	164	46.7	-0.9
8	#26860.00	35.4 AV	68.2	-32.8	2.16 H	164	36.3	-0.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	117.9 PK			2.33 V	79	113.8	4.1
2	*6715.00	110.6 AV			2.33 V	79	106.5	4.1
3	#13430.00	56.6 PK	88.2	-31.6	1.26 V	232	44.1	12.5
4	#13430.00	45.4 AV	68.2	-22.8	1.26 V	232	32.9	12.5
5	20145.00	59.1 PK	74.0	-14.9	2.45 V	295	64.6	-5.5
6	20145.00	47.4 AV	54.0	-6.6	2.45 V	295	52.9	-5.5
7	#26860.00	47.3 PK	88.2	-40.9	2.17 V	233	48.2	-0.9
8	#26860.00	37.3 AV	68.2	-30.9	2.17 V	233	38.2	-0.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	117.4 PK			2.08 H	109	112.9	4.5
2	*6855.00	109.8 AV			2.08 H	109	105.3	4.5
3	#13710.00	54.8 PK	88.2	-33.4	2.15 H	106	41.7	13.1
4	#13710.00	44.9 AV	68.2	-23.3	2.15 H	106	31.8	13.1
5	20565.00	54.3 PK	74.0	-19.7	1.56 H	87	59.4	-5.1
6	20565.00	43.7 AV	54.0	-10.3	1.56 H	87	48.8	-5.1
7	#27420.00	45.8 PK	88.2	-42.4	2.11 H	177	47.3	-1.5
8	#27420.00	35.7 AV	68.2	-32.5	2.11 H	177	37.2	-1.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	118.5 PK			2.37 V	97	114.0	4.5
2	*6855.00	110.8 AV			2.37 V	97	106.3	4.5
3	#13710.00	57.3 PK	88.2	-30.9	1.28 V	247	44.2	13.1
4	#13710.00	45.9 AV	68.2	-22.3	1.28 V	247	32.8	13.1
5	20565.00	58.7 PK	74.0	-15.3	2.43 V	292	63.8	-5.1
6	20565.00	47.0 AV	54.0	-7.0	2.43 V	292	52.1	-5.1
7	#27420.00	47.1 PK	88.2	-41.1	2.25 V	218	48.6	-1.5
8	#27420.00	36.9 AV	68.2	-31.3	2.25 V	218	38.4	-1.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	117.7 PK			2.05 H	99	113.0	4.7
2	*6875.00	109.9 AV			2.05 H	99	105.2	4.7
3	#13750.00	55.0 PK	88.2	-33.2	2.16 H	119	41.7	13.3
4	#13750.00	45.2 AV	68.2	-23.0	2.16 H	119	31.9	13.3
5	20625.00	54.1 PK	74.0	-19.9	1.62 H	86	59.0	-4.9
6	20625.00	44.0 AV	54.0	-10.0	1.62 H	86	48.9	-4.9
7	#27500.00	46.0 PK	88.2	-42.2	2.09 H	158	47.4	-1.4
8	#27500.00	35.6 AV	68.2	-32.6	2.09 H	158	37.0	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	117.9 PK			2.34 V	99	113.2	4.7
2	*6875.00	110.6 AV			2.34 V	99	105.9	4.7
3	#13750.00	56.3 PK	88.2	-31.9	1.22 V	234	43.0	13.3
4	#13750.00	45.3 AV	68.2	-22.9	1.22 V	234	32.0	13.3
5	20625.00	58.9 PK	74.0	-15.1	2.35 V	274	63.8	-4.9
6	20625.00	47.2 AV	54.0	-6.8	2.35 V	274	52.1	-4.9
7	#27500.00	46.5 PK	88.2	-41.7	2.15 V	226	47.9	-1.4
8	#27500.00	36.5 AV	68.2	-31.7	2.15 V	226	37.9	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	117.3 PK			2.02 H	107	111.6	5.7
2	*7015.00	109.9 AV			2.02 H	107	104.2	5.7
3	#14030.00	55.0 PK	88.2	-33.2	2.18 H	112	41.5	13.5
4	#14030.00	45.1 AV	68.2	-23.1	2.18 H	112	31.6	13.5
5	21045.00	54.7 PK	74.0	-19.3	1.66 H	87	59.2	-4.5
6	21045.00	44.4 AV	54.0	-9.6	1.66 H	87	48.9	-4.5
7	#28060.00	45.5 PK	88.2	-42.7	2.12 H	155	47.3	-1.8
8	#28060.00	35.6 AV	68.2	-32.6	2.12 H	155	37.4	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	117.7 PK			2.35 V	77	112.0	5.7
2	*7015.00	110.2 AV			2.35 V	77	104.5	5.7
3	#14030.00	57.0 PK	88.2	-31.2	1.30 V	239	43.5	13.5
4	#14030.00	45.8 AV	68.2	-22.4	1.30 V	239	32.3	13.5
5	21045.00	59.2 PK	74.0	-14.8	2.41 V	285	63.7	-4.5
6	21045.00	47.6 AV	54.0	-6.4	2.41 V	285	52.1	-4.5
7	#28060.00	47.0 PK	88.2	-41.2	2.18 V	222	48.8	-1.8
8	#28060.00	37.1 AV	68.2	-31.1	2.18 V	222	38.9	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	103.2 PK			1.94 H	118	97.0	6.2
2	*7115.00	95.7 AV			1.94 H	118	89.5	6.2
3	#7125.00	81.4 PK	88.2	-6.8	1.94 H	118	75.1	6.3
4	#7125.00	64.0 AV	68.2	-4.2	1.94 H	118	57.7	6.3
5	#14230.00	50.1 PK	88.2	-38.1	2.13 H	124	35.7	14.4
6	#14230.00	40.2 AV	68.2	-28.0	2.13 H	124	25.8	14.4
7	21345.00	51.8 PK	74.0	-22.2	1.71 H	102	56.0	-4.2
8	21345.00	41.1 AV	54.0	-12.9	1.71 H	102	45.3	-4.2
9	#28460.00	45.3 PK	88.2	-42.9	2.17 H	148	47.2	-1.9
10	#28460.00	35.3 AV	68.2	-32.9	2.17 H	148	37.2	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	106.6 PK			2.30 V	95	100.4	6.2
2	*7115.00	99.4 AV			2.30 V	95	93.2	6.2
3	#7125.00	83.9 PK	88.2	-4.3	2.30 V	95	77.6	6.3
4	#7125.00	67.8 AV	68.2	-0.4	2.30 V	95	61.5	6.3
5	#14230.00	51.3 PK	88.2	-36.9	1.34 V	240	36.9	14.4
6	#14230.00	41.2 AV	68.2	-27.0	1.34 V	240	26.8	14.4
7	21345.00	52.7 PK	74.0	-21.3	2.45 V	278	56.9	-4.2
8	21345.00	42.6 AV	54.0	-11.4	2.45 V	278	46.8	-4.2
9	#28460.00	47.2 PK	88.2	-41.0	2.13 V	209	49.1	-1.9
10	#28460.00	37.3 AV	68.2	-30.9	2.13 V	209	39.2	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 1 : 5955 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	63.1 PK	88.2	-25.1	1.92 H	104	61.3	1.8
2	#5925.00	52.7 AV	68.2	-15.5	1.92 H	104	50.9	1.8
3	*5955.00	116.2 PK			1.92 H	104	114.4	1.8
4	*5955.00	107.0 AV			1.92 H	104	105.2	1.8
5	11910.00	54.5 PK	74.0	-19.5	2.23 H	98	43.0	11.5
6	11910.00	44.7 AV	54.0	-9.3	2.23 H	98	33.2	11.5
7	17865.00	54.9 PK	74.0	-19.1	1.66 H	92	33.3	21.6
8	17865.00	44.3 AV	54.0	-9.7	1.66 H	92	22.7	21.6
9	23820.00	45.5 PK	74.0	-28.5	2.17 H	169	48.8	-3.3
10	23820.00	35.5 AV	54.0	-18.5	2.17 H	169	38.8	-3.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	65.8 PK	88.2	-22.4	2.32 V	90	64.0	1.8
2	#5925.00	54.0 AV	68.2	-14.2	2.32 V	90	52.2	1.8
3	*5955.00	117.7 PK			2.32 V	90	115.9	1.8
4	*5955.00	109.1 AV			2.32 V	90	107.3	1.8
5	11910.00	56.7 PK	74.0	-17.3	1.23 V	236	45.2	11.5
6	11910.00	44.9 AV	54.0	-9.1	1.23 V	236	33.4	11.5
7	17865.00	59.1 PK	74.0	-14.9	2.43 V	264	37.5	21.6
8	17865.00	47.3 AV	54.0	-6.7	2.43 V	264	25.7	21.6
9	23820.00	47.0 PK	74.0	-27.0	2.21 V	215	50.3	-3.3
10	23820.00	37.1 AV	54.0	-16.9	2.21 V	215	40.4	-3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 45 : 6175 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6175.00	116.2 PK			1.89 H	92	113.8	2.4
2	*6175.00	107.2 AV			1.89 H	92	104.8	2.4
3	12350.00	55.0 PK	74.0	-19.0	2.22 H	102	44.4	10.6
4	12350.00	45.2 AV	54.0	-8.8	2.22 H	102	34.6	10.6
5	18525.00	54.1 PK	74.0	-19.9	1.71 H	96	60.7	-6.6
6	18525.00	44.0 AV	54.0	-10.0	1.71 H	96	50.6	-6.6
7	#24700.00	45.7 PK	88.2	-42.5	2.10 H	139	47.8	-2.1
8	#24700.00	35.7 AV	68.2	-32.5	2.10 H	139	37.8	-2.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6175.00	117.0 PK			2.30 V	94	114.6	2.4
2	*6175.00	108.7 AV			2.30 V	94	106.3	2.4
3	12350.00	57.3 PK	74.0	-16.7	1.21 V	250	46.7	10.6
4	12350.00	45.9 AV	54.0	-8.1	1.21 V	250	35.3	10.6
5	18525.00	59.3 PK	74.0	-14.7	2.39 V	280	65.9	-6.6
6	18525.00	47.2 AV	54.0	-6.8	2.39 V	280	53.8	-6.6
7	#24700.00	46.6 PK	88.2	-41.6	2.25 V	223	48.7	-2.1
8	#24700.00	37.0 AV	68.2	-31.2	2.25 V	223	39.1	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 93 : 6415 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	116.6 PK			1.90 H	114	113.4	3.2
2	*6415.00	107.3 AV			1.90 H	114	104.1	3.2
3	#12830.00	55.4 PK	88.2	-32.8	2.15 H	103	44.6	10.8
4	#12830.00	45.6 AV	68.2	-22.6	2.15 H	103	34.8	10.8
5	19245.00	54.6 PK	74.0	-19.4	1.65 H	80	61.2	-6.6
6	19245.00	44.4 AV	54.0	-9.6	1.65 H	80	51.0	-6.6
7	#25660.00	46.0 PK	88.2	-42.2	2.08 H	160	47.3	-1.3
8	#25660.00	35.9 AV	68.2	-32.3	2.08 H	160	37.2	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	118.3 PK			2.28 V	98	115.1	3.2
2	*6415.00	109.5 AV			2.28 V	98	106.3	3.2
3	#12830.00	56.3 PK	88.2	-31.9	1.25 V	248	45.5	10.8
4	#12830.00	44.9 AV	68.2	-23.3	1.25 V	248	34.1	10.8
5	19245.00	59.4 PK	74.0	-14.6	2.46 V	289	66.0	-6.6
6	19245.00	47.4 AV	54.0	-6.6	2.46 V	289	54.0	-6.6
7	#25660.00	47.1 PK	88.2	-41.1	2.22 V	225	48.4	-1.3
8	#25660.00	37.2 AV	68.2	-31.0	2.22 V	225	38.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 97 : 6435 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	115.9 PK			1.91 H	105	112.6	3.3
2	*6435.00	107.0 AV			1.91 H	105	103.7	3.3
3	#12870.00	55.2 PK	88.2	-33.0	2.22 H	108	44.5	10.7
4	#12870.00	45.2 AV	68.2	-23.0	2.22 H	108	34.5	10.7
5	19305.00	54.4 PK	74.0	-19.6	1.60 H	88	60.9	-6.5
6	19305.00	44.3 AV	54.0	-9.7	1.60 H	88	50.8	-6.5
7	#25740.00	45.7 PK	88.2	-42.5	2.14 H	155	47.0	-1.3
8	#25740.00	35.6 AV	68.2	-32.6	2.14 H	155	36.9	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	117.5 PK			2.34 V	82	114.2	3.3
2	*6435.00	109.1 AV			2.34 V	82	105.8	3.3
3	#12870.00	57.1 PK	88.2	-31.1	1.22 V	242	46.4	10.7
4	#12870.00	45.7 AV	68.2	-22.5	1.22 V	242	35.0	10.7
5	19305.00	59.1 PK	74.0	-14.9	2.43 V	271	65.6	-6.5
6	19305.00	47.3 AV	54.0	-6.7	2.43 V	271	53.8	-6.5
7	#25740.00	47.5 PK	88.2	-40.7	2.20 V	236	48.8	-1.3
8	#25740.00	37.7 AV	68.2	-30.5	2.20 V	236	39.0	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 105 : 6475 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	115.9 PK			1.93 H	100	112.5	3.4
2	*6475.00	106.7 AV			1.93 H	100	103.3	3.4
3	#12950.00	55.0 PK	88.2	-33.2	2.19 H	115	44.3	10.7
4	#12950.00	45.0 AV	68.2	-23.2	2.19 H	115	34.3	10.7
5	19425.00	54.8 PK	74.0	-19.2	1.68 H	71	61.0	-6.2
6	19425.00	44.4 AV	54.0	-9.6	1.68 H	71	50.6	-6.2
7	#25900.00	45.4 PK	88.2	-42.8	2.10 H	156	46.6	-1.2
8	#25900.00	35.5 AV	68.2	-32.7	2.10 H	156	36.7	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	117.6 PK			2.33 V	82	114.2	3.4
2	*6475.00	109.1 AV			2.33 V	82	105.7	3.4
3	#12950.00	56.5 PK	88.2	-31.7	1.31 V	252	45.8	10.7
4	#12950.00	45.2 AV	68.2	-23.0	1.31 V	252	34.5	10.7
5	19425.00	59.3 PK	74.0	-14.7	2.43 V	272	65.5	-6.2
6	19425.00	47.5 AV	54.0	-6.5	2.43 V	272	53.7	-6.2
7	#25900.00	46.4 PK	88.2	-41.8	2.21 V	234	47.6	-1.2
8	#25900.00	36.8 AV	68.2	-31.4	2.21 V	234	38.0	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	116.2 PK			1.88 H	108	112.5	3.7
2	*6515.00	106.8 AV			1.88 H	108	103.1	3.7
3	#13030.00	55.1 PK	88.2	-33.1	2.16 H	110	44.1	11.0
4	#13030.00	45.5 AV	68.2	-22.7	2.16 H	110	34.5	11.0
5	19545.00	54.2 PK	74.0	-19.8	1.72 H	72	60.4	-6.2
6	19545.00	44.0 AV	54.0	-10.0	1.72 H	72	50.2	-6.2
7	#26060.00	46.2 PK	88.2	-42.0	2.07 H	163	47.2	-1.0
8	#26060.00	36.1 AV	68.2	-32.1	2.07 H	163	37.1	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	117.9 PK			2.34 V	94	114.2	3.7
2	*6515.00	109.4 AV			2.34 V	94	105.7	3.7
3	#13030.00	56.6 PK	88.2	-31.6	1.27 V	254	45.6	11.0
4	#13030.00	45.2 AV	68.2	-23.0	1.27 V	254	34.2	11.0
5	19545.00	59.7 PK	74.0	-14.3	2.37 V	272	65.9	-6.2
6	19545.00	47.6 AV	54.0	-6.4	2.37 V	272	53.8	-6.2
7	#26060.00	47.6 PK	88.2	-40.6	2.16 V	237	48.6	-1.0
8	#26060.00	37.5 AV	68.2	-30.7	2.16 V	237	38.5	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	116.8 PK			1.94 H	109	112.9	3.9
2	*6535.00	107.4 AV			1.94 H	109	103.5	3.9
3	#13070.00	55.3 PK	88.2	-32.9	2.17 H	123	44.2	11.1
4	#13070.00	45.5 AV	68.2	-22.7	2.17 H	123	34.4	11.1
5	19605.00	54.8 PK	74.0	-19.2	1.60 H	82	61.0	-6.2
6	19605.00	44.5 AV	54.0	-9.5	1.60 H	82	50.7	-6.2
7	#26140.00	45.1 PK	88.2	-43.1	2.08 H	164	46.1	-1.0
8	#26140.00	35.4 AV	68.2	-32.8	2.08 H	164	36.4	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	117.6 PK			2.27 V	89	113.7	3.9
2	*6535.00	109.0 AV			2.27 V	89	105.1	3.9
3	#13070.00	57.0 PK	88.2	-31.2	1.23 V	235	45.9	11.1
4	#13070.00	45.3 AV	68.2	-22.9	1.23 V	235	34.2	11.1
5	19605.00	59.2 PK	74.0	-14.8	2.41 V	280	65.4	-6.2
6	19605.00	47.5 AV	54.0	-6.5	2.41 V	280	53.7	-6.2
7	#26140.00	47.2 PK	88.2	-41.0	2.20 V	219	48.2	-1.0
8	#26140.00	37.3 AV	68.2	-30.9	2.20 V	219	38.3	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	115.7 PK			1.88 H	97	111.6	4.1
2	*6715.00	106.5 AV			1.88 H	97	102.4	4.1
3	#13430.00	55.0 PK	88.2	-33.2	2.24 H	120	42.5	12.5
4	#13430.00	45.0 AV	68.2	-23.2	2.24 H	120	32.5	12.5
5	20145.00	54.6 PK	74.0	-19.4	1.66 H	81	60.1	-5.5
6	20145.00	44.6 AV	54.0	-9.4	1.66 H	81	50.1	-5.5
7	#26860.00	45.2 PK	88.2	-43.0	2.09 H	140	46.1	-0.9
8	#26860.00	35.2 AV	68.2	-33.0	2.09 H	140	36.1	-0.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	117.8 PK			2.36 V	78	113.7	4.1
2	*6715.00	109.4 AV			2.36 V	78	105.3	4.1
3	#13430.00	57.4 PK	88.2	-30.8	1.31 V	231	44.9	12.5
4	#13430.00	45.6 AV	68.2	-22.6	1.31 V	231	33.1	12.5
5	20145.00	58.9 PK	74.0	-15.1	2.38 V	261	64.4	-5.5
6	20145.00	47.1 AV	54.0	-6.9	2.38 V	261	52.6	-5.5
7	#26860.00	46.7 PK	88.2	-41.5	2.25 V	239	47.6	-0.9
8	#26860.00	37.2 AV	68.2	-31.0	2.25 V	239	38.1	-0.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	116.1 PK			1.88 H	115	111.6	4.5
2	*6855.00	107.1 AV			1.88 H	115	102.6	4.5
3	#13710.00	54.9 PK	88.2	-33.3	2.13 H	111	41.8	13.1
4	#13710.00	45.1 AV	68.2	-23.1	2.13 H	111	32.0	13.1
5	20565.00	55.4 PK	74.0	-18.6	1.70 H	90	60.5	-5.1
6	20565.00	44.8 AV	54.0	-9.2	1.70 H	90	49.9	-5.1
7	#27420.00	45.4 PK	88.2	-42.8	2.09 H	156	46.9	-1.5
8	#27420.00	35.3 AV	68.2	-32.9	2.09 H	156	36.8	-1.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	117.5 PK			2.33 V	89	113.0	4.5
2	*6855.00	109.0 AV			2.33 V	89	104.5	4.5
3	#13710.00	56.2 PK	88.2	-32.0	1.32 V	238	43.1	13.1
4	#13710.00	45.0 AV	68.2	-23.2	1.32 V	238	31.9	13.1
5	20565.00	59.2 PK	74.0	-14.8	2.37 V	264	64.3	-5.1
6	20565.00	47.6 AV	54.0	-6.4	2.37 V	264	52.7	-5.1
7	#27420.00	46.8 PK	88.2	-41.4	2.18 V	215	48.3	-1.5
8	#27420.00	36.9 AV	68.2	-31.3	2.18 V	215	38.4	-1.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	116.3 PK			1.93 H	117	111.6	4.7
2	*6875.00	107.0 AV			1.93 H	117	102.3	4.7
3	#13750.00	55.4 PK	88.2	-32.8	2.13 H	101	42.1	13.3
4	#13750.00	45.4 AV	68.2	-22.8	2.13 H	101	32.1	13.3
5	20625.00	54.2 PK	74.0	-19.8	1.66 H	99	59.1	-4.9
6	20625.00	44.0 AV	54.0	-10.0	1.66 H	99	48.9	-4.9
7	#27500.00	45.7 PK	88.2	-42.5	2.18 H	155	47.1	-1.4
8	#27500.00	35.8 AV	68.2	-32.4	2.18 H	155	37.2	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	118.3 PK			2.28 V	102	113.6	4.7
2	*6875.00	109.4 AV			2.28 V	102	104.7	4.7
3	#13750.00	56.6 PK	88.2	-31.6	1.26 V	243	43.3	13.3
4	#13750.00	45.2 AV	68.2	-23.0	1.26 V	243	31.9	13.3
5	20625.00	59.6 PK	74.0	-14.4	2.46 V	288	64.5	-4.9
6	20625.00	47.9 AV	54.0	-6.1	2.46 V	288	52.8	-4.9
7	#27500.00	47.1 PK	88.2	-41.1	2.17 V	228	48.5	-1.4
8	#27500.00	37.2 AV	68.2	-31.0	2.17 V	228	38.6	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	116.4 PK			1.89 H	102	110.7	5.7
2	*7015.00	107.4 AV			1.89 H	102	101.7	5.7
3	#14030.00	54.5 PK	88.2	-33.7	2.23 H	109	41.0	13.5
4	#14030.00	44.8 AV	68.2	-23.4	2.23 H	109	31.3	13.5
5	21045.00	55.1 PK	74.0	-18.9	1.64 H	81	59.6	-4.5
6	21045.00	44.8 AV	54.0	-9.2	1.64 H	81	49.3	-4.5
7	#28060.00	46.1 PK	88.2	-42.1	2.15 H	166	47.9	-1.8
8	#28060.00	36.1 AV	68.2	-32.1	2.15 H	166	37.9	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	117.9 PK			2.38 V	97	112.2	5.7
2	*7015.00	109.0 AV			2.38 V	97	103.3	5.7
3	#14030.00	57.3 PK	88.2	-30.9	1.21 V	240	43.8	13.5
4	#14030.00	45.8 AV	68.2	-22.4	1.21 V	240	32.3	13.5
5	21045.00	59.8 PK	74.0	-14.2	2.44 V	284	64.3	-4.5
6	21045.00	48.0 AV	54.0	-6.0	2.44 V	284	52.5	-4.5
7	#28060.00	47.3 PK	88.2	-40.9	2.25 V	228	49.1	-1.8
8	#28060.00	37.6 AV	68.2	-30.6	2.25 V	228	39.4	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	96.3 PK			1.94 H	120	90.1	6.2
2	*7115.00	87.2 AV			1.94 H	120	81.0	6.2
3	#7125.00	71.2 PK	88.2	-17.0	1.94 H	120	64.9	6.3
4	#7125.00	60.0 AV	68.2	-8.2	1.94 H	120	53.7	6.3
5	#14230.00	50.8 PK	88.2	-37.4	2.20 H	102	36.4	14.4
6	#14230.00	40.1 AV	68.2	-28.1	2.20 H	102	25.7	14.4
7	21345.00	51.1 PK	74.0	-22.9	1.65 H	96	55.3	-4.2
8	21345.00	41.9 AV	54.0	-12.1	1.65 H	96	46.1	-4.2
9	#28460.00	46.0 PK	88.2	-42.2	2.14 H	171	47.9	-1.9
10	#28460.00	35.9 AV	68.2	-32.3	2.14 H	171	37.8	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	99.9 PK			2.20 V	108	93.7	6.2
2	*7115.00	90.7 AV			2.20 V	108	84.5	6.2
3	#7125.00	74.3 PK	88.2	-13.9	2.20 V	108	68.0	6.3
4	#7125.00	67.9 AV	68.2	-0.3	2.20 V	108	61.6	6.3
5	#14230.00	51.6 PK	88.2	-36.6	1.36 V	234	37.2	14.4
6	#14230.00	41.3 AV	68.2	-26.9	1.36 V	234	26.9	14.4
7	21345.00	52.0 PK	74.0	-22.0	2.43 V	264	56.2	-4.2
8	21345.00	42.2 AV	54.0	-11.8	2.43 V	264	46.4	-4.2
9	#28460.00	47.4 PK	88.2	-40.8	2.15 V	198	49.3	-1.9
10	#28460.00	37.3 AV	68.2	-30.9	2.15 V	198	39.2	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 3 : 5965 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	72.1 PK	88.2	-16.1	1.92 H	88	70.3	1.8
2	#5925.00	66.7 AV	68.2	-1.5	1.92 H	88	64.9	1.8
3	*5965.00	115.5 PK			1.92 H	88	113.7	1.8
4	*5965.00	105.0 AV			1.92 H	88	103.2	1.8
5	11930.00	53.8 PK	74.0	-20.2	2.23 H	113	42.3	11.5
6	11930.00	43.9 AV	54.0	-10.1	2.23 H	113	32.4	11.5
7	17895.00	55.0 PK	74.0	-19.0	1.63 H	81	32.9	22.1
8	17895.00	44.7 AV	54.0	-9.3	1.63 H	81	22.6	22.1
9	23860.00	46.3 PK	74.0	-27.7	2.10 H	171	49.6	-3.3
10	23860.00	36.3 AV	54.0	-17.7	2.10 H	171	39.6	-3.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	74.7 PK	88.2	-13.5	2.29 V	91	72.9	1.8
2	#5925.00	65.4 AV	68.2	-2.8	2.29 V	91	63.6	1.8
3	*5965.00	115.8 PK			2.29 V	91	114.0	1.8
4	*5965.00	106.0 AV			2.29 V	91	104.2	1.8
5	11930.00	56.3 PK	74.0	-17.7	1.18 V	232	44.8	11.5
6	11930.00	44.8 AV	54.0	-9.2	1.18 V	232	33.3	11.5
7	17895.00	59.3 PK	74.0	-14.7	2.39 V	288	37.2	22.1
8	17895.00	47.5 AV	54.0	-6.5	2.39 V	288	25.4	22.1
9	23860.00	47.5 PK	74.0	-26.5	2.25 V	226	50.8	-3.3
10	23860.00	38.0 AV	54.0	-16.0	2.25 V	226	41.3	-3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 43 : 6165 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6165.00	116.2 PK			1.91 H	77	113.8	2.4
2	*6165.00	105.4 AV			1.91 H	77	103.0	2.4
3	12330.00	53.6 PK	74.0	-20.4	2.18 H	110	42.9	10.7
4	12330.00	43.7 AV	54.0	-10.3	2.18 H	110	33.0	10.7
5	18495.00	55.4 PK	74.0	-18.6	1.67 H	80	62.0	-6.6
6	18495.00	45.1 AV	54.0	-8.9	1.67 H	80	51.7	-6.6
7	#24660.00	46.4 PK	88.2	-41.8	2.11 H	185	48.5	-2.1
8	#24660.00	36.6 AV	68.2	-31.6	2.11 H	185	38.7	-2.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6165.00	116.0 PK			2.25 V	93	113.6	2.4
2	*6165.00	106.3 AV			2.25 V	93	103.9	2.4
3	12330.00	56.4 PK	74.0	-17.6	1.14 V	237	45.7	10.7
4	12330.00	44.8 AV	54.0	-9.2	1.14 V	237	34.1	10.7
5	18495.00	59.7 PK	74.0	-14.3	2.41 V	287	66.3	-6.6
6	18495.00	47.7 AV	54.0	-6.3	2.41 V	287	54.3	-6.6
7	#24660.00	47.7 PK	88.2	-40.5	2.26 V	217	49.8	-2.1
8	#24660.00	38.1 AV	68.2	-30.1	2.26 V	217	40.2	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 91 : 6405 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	115.2 PK			1.87 H	99	112.2	3.0
2	*6405.00	104.9 AV			1.87 H	99	101.9	3.0
3	#12810.00	54.0 PK	88.2	-34.2	2.19 H	109	43.2	10.8
4	#12810.00	44.1 AV	68.2	-24.1	2.19 H	109	33.3	10.8
5	19215.00	55.5 PK	74.0	-18.5	1.60 H	74	62.0	-6.5
6	19215.00	45.1 AV	54.0	-8.9	1.60 H	74	51.6	-6.5
7	#25620.00	45.7 PK	88.2	-42.5	2.09 H	161	47.0	-1.3
8	#25620.00	35.8 AV	68.2	-32.4	2.09 H	161	37.1	-1.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	115.3 PK			2.27 V	87	112.3	3.0
2	*6405.00	105.7 AV			2.27 V	87	102.7	3.0
3	#12810.00	56.0 PK	88.2	-32.2	1.21 V	223	45.2	10.8
4	#12810.00	44.4 AV	68.2	-23.8	1.21 V	223	33.6	10.8
5	19215.00	59.0 PK	74.0	-15.0	2.41 V	300	65.5	-6.5
6	19215.00	47.3 AV	54.0	-6.7	2.41 V	300	53.8	-6.5
7	#25620.00	47.3 PK	88.2	-40.9	2.28 V	230	48.6	-1.3
8	#25620.00	37.9 AV	68.2	-30.3	2.28 V	230	39.2	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 99 : 6445 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	115.6 PK			1.92 H	91	112.3	3.3
2	*6445.00	105.4 AV			1.92 H	91	102.1	3.3
3	#12890.00	54.1 PK	88.2	-34.1	2.26 H	126	43.4	10.7
4	#12890.00	44.4 AV	68.2	-23.8	2.26 H	126	33.7	10.7
5	19335.00	55.3 PK	74.0	-18.7	1.57 H	79	61.8	-6.5
6	19335.00	44.9 AV	54.0	-9.1	1.57 H	79	51.4	-6.5
7	#25780.00	46.5 PK	88.2	-41.7	2.05 H	186	47.7	-1.2
8	#25780.00	36.2 AV	68.2	-32.0	2.05 H	186	37.4	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	115.2 PK			2.29 V	94	111.9	3.3
2	*6445.00	105.6 AV			2.29 V	94	102.3	3.3
3	#12890.00	55.8 PK	88.2	-32.4	1.13 V	226	45.1	10.7
4	#12890.00	44.5 AV	68.2	-23.7	1.13 V	226	33.8	10.7
5	19335.00	59.5 PK	74.0	-14.5	2.35 V	272	66.0	-6.5
6	19335.00	47.6 AV	54.0	-6.4	2.35 V	272	54.1	-6.5
7	#25780.00	47.7 PK	88.2	-40.5	2.25 V	232	48.9	-1.2
8	#25780.00	38.1 AV	68.2	-30.1	2.25 V	232	39.3	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 107 : 6485 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	115.3 PK			1.95 H	76	111.7	3.6
2	*6485.00	104.6 AV			1.95 H	76	101.0	3.6
3	#12970.00	53.6 PK	88.2	-34.6	2.18 H	97	42.8	10.8
4	#12970.00	43.5 AV	68.2	-24.7	2.18 H	97	32.7	10.8
5	19455.00	55.2 PK	74.0	-18.8	1.64 H	68	61.4	-6.2
6	19455.00	44.9 AV	54.0	-9.1	1.64 H	68	51.1	-6.2
7	#25940.00	46.4 PK	88.2	-41.8	2.12 H	186	47.5	-1.1
8	#25940.00	36.6 AV	68.2	-31.6	2.12 H	186	37.7	-1.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	115.4 PK			2.25 V	90	111.8	3.6
2	*6485.00	105.8 AV			2.25 V	90	102.2	3.6
3	#12970.00	55.8 PK	88.2	-32.4	1.15 V	221	45.0	10.8
4	#12970.00	44.4 AV	68.2	-23.8	1.15 V	221	33.6	10.8
5	19455.00	58.9 PK	74.0	-15.1	2.41 V	286	65.1	-6.2
6	19455.00	47.0 AV	54.0	-7.0	2.41 V	286	53.2	-6.2
7	#25940.00	47.5 PK	88.2	-40.7	2.22 V	221	48.6	-1.1
8	#25940.00	38.1 AV	68.2	-30.1	2.22 V	221	39.2	-1.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 115 : 6525 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	115.1 PK			1.91 H	93	111.4	3.7
2	*6525.00	104.8 AV			1.91 H	93	101.1	3.7
3	#13050.00	53.9 PK	88.2	-34.3	2.20 H	111	42.8	11.1
4	#13050.00	44.1 AV	68.2	-24.1	2.20 H	111	33.0	11.1
5	19575.00	54.7 PK	74.0	-19.3	1.66 H	83	61.0	-6.3
6	19575.00	44.7 AV	54.0	-9.3	1.66 H	83	51.0	-6.3
7	#26100.00	46.7 PK	88.2	-41.5	2.15 H	176	47.7	-1.0
8	#26100.00	36.6 AV	68.2	-31.6	2.15 H	176	37.6	-1.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	116.2 PK			2.30 V	91	112.5	3.7
2	*6525.00	106.3 AV			2.30 V	91	102.6	3.7
3	#13050.00	56.1 PK	88.2	-32.1	1.19 V	227	45.0	11.1
4	#13050.00	44.6 AV	68.2	-23.6	1.19 V	227	33.5	11.1
5	19575.00	59.3 PK	74.0	-14.7	2.38 V	288	65.6	-6.3
6	19575.00	47.2 AV	54.0	-6.8	2.38 V	288	53.5	-6.3
7	#26100.00	47.4 PK	88.2	-40.8	2.27 V	238	48.4	-1.0
8	#26100.00	38.2 AV	68.2	-30.0	2.27 V	238	39.2	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 123 : 6565 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	115.4 PK			1.92 H	102	111.4	4.0
2	*6565.00	104.7 AV			1.92 H	102	100.7	4.0
3	#13130.00	54.3 PK	88.2	-33.9	2.26 H	129	42.9	11.4
4	#13130.00	44.2 AV	68.2	-24.0	2.26 H	129	32.8	11.4
5	19695.00	54.7 PK	74.0	-19.3	1.67 H	66	60.9	-6.2
6	19695.00	44.3 AV	54.0	-9.7	1.67 H	66	50.5	-6.2
7	#26260.00	45.7 PK	88.2	-42.5	2.13 H	158	46.7	-1.0
8	#26260.00	35.9 AV	68.2	-32.3	2.13 H	158	36.9	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	115.7 PK			2.28 V	86	111.7	4.0
2	*6565.00	105.6 AV			2.28 V	86	101.6	4.0
3	#13130.00	56.7 PK	88.2	-31.5	1.18 V	246	45.3	11.4
4	#13130.00	45.3 AV	68.2	-22.9	1.18 V	246	33.9	11.4
5	19695.00	58.8 PK	74.0	-15.2	2.33 V	283	65.0	-6.2
6	19695.00	47.1 AV	54.0	-6.9	2.33 V	283	53.3	-6.2
7	#26260.00	47.5 PK	88.2	-40.7	2.31 V	225	48.5	-1.0
8	#26260.00	38.2 AV	68.2	-30.0	2.31 V	225	39.2	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 155 : 6725 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	115.8 PK			1.98 H	98	111.6	4.2
2	*6725.00	105.0 AV			1.98 H	98	100.8	4.2
3	#13450.00	53.5 PK	88.2	-34.7	2.29 H	98	40.9	12.6
4	#13450.00	43.6 AV	68.2	-24.6	2.29 H	98	31.0	12.6
5	20175.00	54.4 PK	74.0	-19.6	1.59 H	66	59.8	-5.4
6	20175.00	44.2 AV	54.0	-9.8	1.59 H	66	49.6	-5.4
7	#26900.00	46.8 PK	88.2	-41.4	2.10 H	178	47.8	-1.0
8	#26900.00	36.7 AV	68.2	-31.5	2.10 H	178	37.7	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	115.4 PK			2.33 V	76	111.2	4.2
2	*6725.00	105.9 AV			2.33 V	76	101.7	4.2
3	#13450.00	56.1 PK	88.2	-32.1	1.17 V	235	43.5	12.6
4	#13450.00	44.4 AV	68.2	-23.8	1.17 V	235	31.8	12.6
5	20175.00	59.0 PK	74.0	-15.0	2.36 V	273	64.4	-5.4
6	20175.00	47.2 AV	54.0	-6.8	2.36 V	273	52.6	-5.4
7	#26900.00	47.2 PK	88.2	-41.0	2.26 V	213	48.2	-1.0
8	#26900.00	37.6 AV	68.2	-30.6	2.26 V	213	38.6	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 179 : 6845 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	115.6 PK			1.88 H	75	111.1	4.5
2	*6845.00	105.1 AV			1.88 H	75	100.6	4.5
3	#13690.00	54.2 PK	88.2	-34.0	2.28 H	106	41.0	13.2
4	#13690.00	44.1 AV	68.2	-24.1	2.28 H	106	30.9	13.2
5	20535.00	55.3 PK	74.0	-18.7	1.68 H	73	60.5	-5.2
6	20535.00	44.9 AV	54.0	-9.1	1.68 H	73	50.1	-5.2
7	#27380.00	46.7 PK	88.2	-41.5	2.12 H	183	48.1	-1.4
8	#27380.00	36.4 AV	68.2	-31.8	2.12 H	183	37.8	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	115.6 PK			2.34 V	89	111.1	4.5
2	*6845.00	105.5 AV			2.34 V	89	101.0	4.5
3	#13690.00	56.8 PK	88.2	-31.4	1.20 V	238	43.6	13.2
4	#13690.00	45.1 AV	68.2	-23.1	1.20 V	238	31.9	13.2
5	20535.00	59.8 PK	74.0	-14.2	2.37 V	290	65.0	-5.2
6	20535.00	47.8 AV	54.0	-6.2	2.37 V	290	53.0	-5.2
7	#27380.00	47.7 PK	88.2	-40.5	2.28 V	215	49.1	-1.4
8	#27380.00	38.2 AV	68.2	-30.0	2.28 V	215	39.6	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 187 : 6885 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	115.5 PK			1.92 H	79	110.8	4.7
2	*6885.00	104.9 AV			1.92 H	79	100.2	4.7
3	#13770.00	53.2 PK	88.2	-35.0	2.23 H	103	39.9	13.3
4	#13770.00	43.4 AV	68.2	-24.8	2.23 H	103	30.1	13.3
5	20655.00	54.7 PK	74.0	-19.3	1.64 H	95	59.6	-4.9
6	20655.00	44.5 AV	54.0	-9.5	1.64 H	95	49.4	-4.9
7	#27540.00	46.1 PK	88.2	-42.1	2.07 H	181	47.6	-1.5
8	#27540.00	36.0 AV	68.2	-32.2	2.07 H	181	37.5	-1.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	115.5 PK			2.26 V	81	110.8	4.7
2	*6885.00	105.9 AV			2.26 V	81	101.2	4.7
3	#13770.00	55.8 PK	88.2	-32.4	1.18 V	231	42.5	13.3
4	#13770.00	44.4 AV	68.2	-23.8	1.18 V	231	31.1	13.3
5	20655.00	58.9 PK	74.0	-15.1	2.45 V	273	63.8	-4.9
6	20655.00	47.2 AV	54.0	-6.8	2.45 V	273	52.1	-4.9
7	#27540.00	47.3 PK	88.2	-40.9	2.27 V	223	48.8	-1.5
8	#27540.00	37.8 AV	68.2	-30.4	2.27 V	223	39.3	-1.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 211 : 7005 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	115.3 PK			1.95 H	100	109.6	5.7
2	*7005.00	104.9 AV			1.95 H	100	99.2	5.7
3	#14010.00	54.5 PK	88.2	-33.7	2.17 H	120	41.0	13.5
4	#14010.00	44.3 AV	68.2	-23.9	2.17 H	120	30.8	13.5
5	21015.00	54.7 PK	74.0	-19.3	1.64 H	89	59.2	-4.5
6	21015.00	44.6 AV	54.0	-9.4	1.64 H	89	49.1	-4.5
7	#28020.00	46.9 PK	88.2	-41.3	2.10 H	174	48.6	-1.7
8	#28020.00	36.6 AV	68.2	-31.6	2.10 H	174	38.3	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	115.9 PK			2.26 V	85	110.2	5.7
2	*7005.00	106.0 AV			2.26 V	85	100.3	5.7
3	#14010.00	56.2 PK	88.2	-32.0	1.18 V	231	42.7	13.5
4	#14010.00	44.7 AV	68.2	-23.5	1.18 V	231	31.2	13.5
5	21015.00	59.1 PK	74.0	-14.9	2.45 V	285	63.6	-4.5
6	21015.00	47.2 AV	54.0	-6.8	2.45 V	285	51.7	-4.5
7	#28020.00	47.3 PK	88.2	-40.9	2.21 V	212	49.0	-1.7
8	#28020.00	37.8 AV	68.2	-30.4	2.21 V	212	39.5	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 227 : 7085 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	113.2 PK			1.93 H	114	107.3	5.9
2	*7085.00	102.1 AV			1.93 H	114	96.2	5.9
3	#7125.00	67.7 PK	88.2	-20.5	1.93 H	114	61.4	6.3
4	#7125.00	60.7 AV	68.2	-7.5	1.93 H	114	54.4	6.3
5	#14170.00	53.7 PK	88.2	-34.5	2.25 H	106	39.4	14.3
6	#14170.00	43.5 AV	68.2	-24.7	2.25 H	106	29.2	14.3
7	21255.00	55.2 PK	74.0	-18.8	1.69 H	84	59.5	-4.3
8	21255.00	45.0 AV	54.0	-9.0	1.69 H	84	49.3	-4.3
9	#28340.00	46.7 PK	88.2	-41.5	2.13 H	167	48.3	-1.6
10	#28340.00	36.4 AV	68.2	-31.8	2.13 H	167	38.0	-1.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	115.5 PK			2.31 V	93	109.6	5.9
2	*7085.00	105.6 AV			2.31 V	93	99.7	5.9
3	#7125.00	72.1 PK	88.2	-16.1	2.31 V	93	65.8	6.3
4	#7125.00	63.0 AV	68.2	-5.2	2.31 V	93	56.7	6.3
5	#14170.00	56.2 PK	88.2	-32.0	1.23 V	246	41.9	14.3
6	#14170.00	44.9 AV	68.2	-23.3	1.23 V	246	30.6	14.3
7	21255.00	59.0 PK	74.0	-15.0	2.42 V	277	63.3	-4.3
8	21255.00	47.3 AV	54.0	-6.7	2.42 V	277	51.6	-4.3
9	#28340.00	47.0 PK	88.2	-41.2	2.25 V	210	48.6	-1.6
10	#28340.00	37.6 AV	68.2	-30.6	2.25 V	210	39.2	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 7 : 5985 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	69.1 PK	88.2	-19.1	1.95 H	111	67.3	1.8
2	#5925.00	59.4 AV	68.2	-8.8	1.95 H	111	57.6	1.8
3	*5985.00	109.3 PK			1.95 H	111	107.5	1.8
4	*5985.00	99.4 AV			1.95 H	111	97.6	1.8
5	11970.00	53.7 PK	74.0	-20.3	2.17 H	119	42.4	11.3
6	11970.00	42.8 AV	54.0	-11.2	2.17 H	119	31.5	11.3
7	17955.00	54.9 PK	74.0	-19.1	1.68 H	66	31.3	23.6
8	17955.00	43.8 AV	54.0	-10.2	1.68 H	66	20.2	23.6
9	23940.00	46.5 PK	74.0	-27.5	2.06 H	186	49.6	-3.1
10	23940.00	36.6 AV	54.0	-17.4	2.06 H	186	39.7	-3.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	69.4 PK	88.2	-18.8	2.39 V	100	67.6	1.8
2	#5925.00	60.6 AV	68.2	-7.6	2.39 V	100	58.8	1.8
3	*5985.00	110.4 PK			2.39 V	100	108.6	1.8
4	*5985.00	101.5 AV			2.39 V	100	99.7	1.8
5	11970.00	55.5 PK	74.0	-18.5	1.13 V	227	44.2	11.3
6	11970.00	43.0 AV	54.0	-11.0	1.13 V	227	31.7	11.3
7	17955.00	58.6 PK	74.0	-15.4	2.35 V	277	35.0	23.6
8	17955.00	46.9 AV	54.0	-7.1	2.35 V	277	23.3	23.6
9	23940.00	48.1 PK	74.0	-25.9	2.29 V	241	51.2	-3.1
10	23940.00	38.6 AV	54.0	-15.4	2.29 V	241	41.7	-3.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 39 : 6145 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6145.00	109.5 PK			1.95 H	107	107.2	2.3
2	*6145.00	99.7 AV			1.95 H	107	97.4	2.3
3	12290.00	54.0 PK	74.0	-20.0	2.14 H	124	43.1	10.9
4	12290.00	43.2 AV	54.0	-10.8	2.14 H	124	32.3	10.9
5	18435.00	54.8 PK	74.0	-19.2	1.67 H	65	61.4	-6.6
6	18435.00	43.5 AV	54.0	-10.5	1.67 H	65	50.1	-6.6
7	#24580.00	46.5 PK	88.2	-41.7	2.10 H	174	48.8	-2.3
8	#24580.00	36.5 AV	68.2	-31.7	2.10 H	174	38.8	-2.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6145.00	110.1 PK			2.44 V	95	107.8	2.3
2	*6145.00	101.2 AV			2.44 V	95	98.9	2.3
3	12290.00	56.2 PK	74.0	-17.8	1.08 V	216	45.3	10.9
4	12290.00	43.5 AV	54.0	-10.5	1.08 V	216	32.6	10.9
5	18435.00	58.5 PK	74.0	-15.5	2.32 V	287	65.1	-6.6
6	18435.00	46.7 AV	54.0	-7.3	2.32 V	287	53.3	-6.6
7	#24580.00	48.3 PK	88.2	-39.9	2.33 V	231	50.6	-2.3
8	#24580.00	38.5 AV	68.2	-29.7	2.33 V	231	40.8	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 87 : 6385 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	109.8 PK			1.98 H	110	106.8	3.0
2	*6385.00	99.7 AV			1.98 H	110	96.7	3.0
3	#12770.00	53.6 PK	88.2	-34.6	2.18 H	135	42.8	10.8
4	#12770.00	42.9 AV	68.2	-25.3	2.18 H	135	32.1	10.8
5	19155.00	54.6 PK	74.0	-19.4	1.71 H	54	61.1	-6.5
6	19155.00	43.8 AV	54.0	-10.2	1.71 H	54	50.3	-6.5
7	#25540.00	47.2 PK	88.2	-41.0	2.01 H	198	48.6	-1.4
8	#25540.00	37.1 AV	68.2	-31.1	2.01 H	198	38.5	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	109.7 PK			2.34 V	103	106.7	3.0
2	*6385.00	101.1 AV			2.34 V	103	98.1	3.0
3	#12770.00	55.3 PK	88.2	-32.9	1.13 V	239	44.5	10.8
4	#12770.00	43.0 AV	68.2	-25.2	1.13 V	239	32.2	10.8
5	19155.00	59.4 PK	74.0	-14.6	2.38 V	274	65.9	-6.5
6	19155.00	47.4 AV	54.0	-6.6	2.38 V	274	53.9	-6.5
7	#25540.00	48.6 PK	88.2	-39.6	2.35 V	251	50.0	-1.4
8	#25540.00	39.0 AV	68.2	-29.2	2.35 V	251	40.4	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.