

RF Mode	TX 802.11a 6G	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	93.4 PK			1.56 H	19	87.4	6.0
2	*6515.00	82.4 AV			1.56 H	19	76.4	6.0
3	#13030.00	45.2 PK	88.2	-43.0	2.65 H	185	31.9	13.3
4	#13030.00	35.9 AV	68.2	-32.3	2.65 H	185	22.6	13.3
5	19545.00	51.4 PK	74.0	-22.6	1.69 H	252	57.6	-6.2
6	19545.00	39.6 AV	54.0	-14.4	1.69 H	252	45.8	-6.2
7	#26060.00	54.3 PK	88.2	-33.9	1.63 H	281	55.7	-1.4
8	#26060.00	42.0 AV	68.2	-26.2	1.63 H	281	43.4	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	97.9 PK			1.12 V	267	91.9	6.0
2	*6515.00	89.7 AV			1.12 V	267	83.7	6.0
3	#13030.00	44.3 PK	88.2	-43.9	2.89 V	308	31.0	13.3
4	#13030.00	34.8 AV	68.2	-33.4	2.89 V	308	21.5	13.3
5	19545.00	53.1 PK	74.0	-20.9	2.11 V	176	59.3	-6.2
6	19545.00	41.3 AV	54.0	-12.7	2.11 V	176	47.5	-6.2
7	#26060.00	55.3 PK	88.2	-32.9	1.89 V	104	56.7	-1.4
8	#26060.00	44.0 AV	68.2	-24.2	1.89 V	104	45.4	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	93.0 PK			1.62 H	26	87.0	6.0
2	*6535.00	82.1 AV			1.62 H	26	76.1	6.0
3	#13070.00	46.4 PK	88.2	-41.8	2.71 H	175	33.0	13.4
4	#13070.00	36.7 AV	68.2	-31.5	2.71 H	175	23.3	13.4
5	19605.00	51.4 PK	74.0	-22.6	1.70 H	238	57.5	-6.1
6	19605.00	39.5 AV	54.0	-14.5	1.70 H	238	45.6	-6.1
7	#26140.00	54.2 PK	88.2	-34.0	1.64 H	292	55.5	-1.3
8	#26140.00	41.6 AV	68.2	-26.6	1.64 H	292	42.9	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	98.8 PK			1.06 V	269	92.8	6.0
2	*6535.00	90.4 AV			1.06 V	269	84.4	6.0
3	#13070.00	44.2 PK	88.2	-44.0	2.89 V	311	30.8	13.4
4	#13070.00	34.9 AV	68.2	-33.3	2.89 V	311	21.5	13.4
5	19605.00	51.7 PK	74.0	-22.3	2.14 V	182	57.8	-6.1
6	19605.00	40.4 AV	54.0	-13.6	2.14 V	182	46.5	-6.1
7	#26140.00	55.9 PK	88.2	-32.3	1.81 V	108	57.2	-1.3
8	#26140.00	44.0 AV	68.2	-24.2	1.81 V	108	45.3	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	93.2 PK			1.59 H	33	87.1	6.1
2	*6715.00	82.2 AV			1.59 H	33	76.1	6.1
3	#13430.00	46.4 PK	88.2	-41.8	2.74 H	190	31.5	14.9
4	#13430.00	36.7 AV	68.2	-31.5	2.74 H	190	21.8	14.9
5	20145.00	52.5 PK	74.0	-21.5	1.69 H	238	57.9	-5.4
6	20145.00	40.2 AV	54.0	-13.8	1.69 H	238	45.6	-5.4
7	#26860.00	54.5 PK	88.2	-33.7	1.64 H	273	55.6	-1.1
8	#26860.00	42.0 AV	68.2	-26.2	1.64 H	273	43.1	-1.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	97.9 PK			1.05 V	261	91.8	6.1
2	*6715.00	89.7 AV			1.05 V	261	83.6	6.1
3	#13430.00	44.3 PK	88.2	-43.9	2.83 V	305	29.4	14.9
4	#13430.00	34.9 AV	68.2	-33.3	2.83 V	305	20.0	14.9
5	20145.00	52.3 PK	74.0	-21.7	2.16 V	175	57.7	-5.4
6	20145.00	41.0 AV	54.0	-13.0	2.16 V	175	46.4	-5.4
7	#26860.00	55.3 PK	88.2	-32.9	1.86 V	112	56.4	-1.1
8	#26860.00	44.0 AV	68.2	-24.2	1.86 V	112	45.1	-1.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	93.0 PK			1.60 H	7	86.2	6.8
2	*6855.00	82.2 AV			1.60 H	7	75.4	6.8
3	#13710.00	45.9 PK	88.2	-42.3	2.68 H	203	30.2	15.7
4	#13710.00	36.4 AV	68.2	-31.8	2.68 H	203	20.7	15.7
5	20565.00	52.3 PK	74.0	-21.7	1.70 H	259	57.2	-4.9
6	20565.00	40.0 AV	54.0	-14.0	1.70 H	259	44.9	-4.9
7	#27420.00	54.1 PK	88.2	-34.1	1.66 H	286	55.7	-1.6
8	#27420.00	41.5 AV	68.2	-26.7	1.66 H	286	43.1	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	98.5 PK			1.06 V	251	91.7	6.8
2	*6855.00	90.6 AV			1.06 V	251	83.8	6.8
3	#13710.00	44.5 PK	88.2	-43.7	2.83 V	321	28.8	15.7
4	#13710.00	35.4 AV	68.2	-32.8	2.83 V	321	19.7	15.7
5	20565.00	52.5 PK	74.0	-21.5	2.15 V	171	57.4	-4.9
6	20565.00	41.0 AV	54.0	-13.0	2.15 V	171	45.9	-4.9
7	#27420.00	55.2 PK	88.2	-33.0	1.80 V	114	56.8	-1.6
8	#27420.00	43.7 AV	68.2	-24.5	1.80 V	114	45.3	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	92.9 PK			1.60 H	22	85.9	7.0
2	*6875.00	81.6 AV			1.60 H	22	74.6	7.0
3	#13750.00	45.7 PK	88.2	-42.5	2.70 H	193	29.9	15.8
4	#13750.00	36.2 AV	68.2	-32.0	2.70 H	193	20.4	15.8
5	20625.00	52.2 PK	74.0	-21.8	1.72 H	258	57.0	-4.8
6	20625.00	40.3 AV	54.0	-13.7	1.72 H	258	45.1	-4.8
7	#27500.00	54.0 PK	88.2	-34.2	1.64 H	280	55.2	-1.2
8	#27500.00	41.7 AV	68.2	-26.5	1.64 H	280	42.9	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	98.4 PK			1.04 V	241	91.4	7.0
2	*6875.00	90.0 AV			1.04 V	241	83.0	7.0
3	#13750.00	44.1 PK	88.2	-44.1	2.82 V	324	28.3	15.8
4	#13750.00	35.1 AV	68.2	-33.1	2.82 V	324	19.3	15.8
5	20625.00	52.3 PK	74.0	-21.7	2.16 V	181	57.1	-4.8
6	20625.00	40.8 AV	54.0	-13.2	2.16 V	181	45.6	-4.8
7	#27500.00	55.5 PK	88.2	-32.7	1.87 V	102	56.7	-1.2
8	#27500.00	44.0 AV	68.2	-24.2	1.87 V	102	45.2	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	93.2 PK			1.64 H	30	85.3	7.9
2	*7015.00	81.9 AV			1.64 H	30	74.0	7.9
3	#14030.00	46.1 PK	88.2	-42.1	2.70 H	196	30.2	15.9
4	#14030.00	36.7 AV	68.2	-31.5	2.70 H	196	20.8	15.9
5	21045.00	52.0 PK	74.0	-22.0	1.67 H	233	56.4	-4.4
6	21045.00	39.9 AV	54.0	-14.1	1.67 H	233	44.3	-4.4
7	#28060.00	54.1 PK	88.2	-34.1	1.68 H	290	55.5	-1.4
8	#28060.00	41.7 AV	68.2	-26.5	1.68 H	290	43.1	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	97.6 PK			1.08 V	253	89.7	7.9
2	*7015.00	89.7 AV			1.08 V	253	81.8	7.9
3	#14030.00	45.0 PK	88.2	-43.2	2.79 V	318	29.1	15.9
4	#14030.00	35.5 AV	68.2	-32.7	2.79 V	318	19.6	15.9
5	21045.00	52.5 PK	74.0	-21.5	2.16 V	174	56.9	-4.4
6	21045.00	40.9 AV	54.0	-13.1	2.16 V	174	45.3	-4.4
7	#28060.00	55.8 PK	88.2	-32.4	1.86 V	110	57.2	-1.4
8	#28060.00	44.2 AV	68.2	-24.0	1.86 V	110	45.6	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a 6G	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	92.9 PK			1.61 H	23	84.8	8.1
2	*7115.00	81.9 AV			1.61 H	23	73.8	8.1
3	#7125.00	70.6 PK	88.2	-17.6	1.61 H	23	62.4	8.2
4	#7125.00	46.6 AV	68.2	-21.6	1.61 H	23	38.4	8.2
5	#14230.00	46.4 PK	88.2	-41.8	2.67 H	194	29.3	17.1
6	#14230.00	36.7 AV	68.2	-31.5	2.67 H	194	19.6	17.1
7	21345.00	51.8 PK	74.0	-22.2	1.72 H	259	56.0	-4.2
8	21345.00	39.7 AV	54.0	-14.3	1.72 H	259	43.9	-4.2
9	#28460.00	54.8 PK	88.2	-33.4	1.69 H	276	56.2	-1.4
10	#28460.00	42.3 AV	68.2	-25.9	1.69 H	276	43.7	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	99.5 PK			3.05 V	57	91.4	8.1
2	*7115.00	91.6 AV			3.05 V	57	83.5	8.1
3	#7125.00	77.8 PK	88.2	-10.4	3.05 V	57	69.6	8.2
4	#7125.00	61.0 AV	68.2	-7.2	3.05 V	57	52.8	8.2
5	#14230.00	44.3 PK	88.2	-43.9	2.87 V	302	27.2	17.1
6	#14230.00	35.3 AV	68.2	-32.9	2.87 V	302	18.2	17.1
7	21345.00	52.6 PK	74.0	-21.4	2.14 V	169	56.8	-4.2
8	21345.00	41.2 AV	54.0	-12.8	2.14 V	169	45.4	-4.2
9	#28460.00	55.6 PK	88.2	-32.6	1.83 V	128	57.0	-1.4
10	#28460.00	44.0 AV	68.2	-24.2	1.83 V	128	45.4	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 1 : 5955 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.2 PK	88.2	-38.0	2.58 H	203	46.5	3.7
2	#5925.00	38.4 AV	68.2	-29.8	2.58 H	203	34.7	3.7
3	*5955.00	91.6 PK			2.58 H	203	87.7	3.9
4	*5955.00	81.1 AV			2.58 H	203	77.2	3.9
5	11910.00	46.5 PK	74.0	-27.5	2.64 H	196	33.1	13.4
6	11910.00	36.8 AV	54.0	-17.2	2.64 H	196	23.4	13.4
7	17865.00	52.2 PK	74.0	-21.8	1.69 H	244	30.5	21.7
8	17865.00	40.0 AV	54.0	-14.0	1.69 H	244	18.3	21.7
9	23820.00	53.8 PK	74.0	-20.2	1.67 H	266	56.3	-2.5
10	23820.00	41.6 AV	54.0	-12.4	1.67 H	266	44.1	-2.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.3 PK	88.2	-37.9	3.11 V	65	46.6	3.7
2	#5925.00	38.7 AV	68.2	-29.5	3.11 V	65	35.0	3.7
3	*5955.00	99.5 PK			3.11 V	65	95.6	3.9
4	*5955.00	90.3 AV			3.11 V	65	86.4	3.9
5	11910.00	44.0 PK	74.0	-30.0	2.87 V	303	30.6	13.4
6	11910.00	34.7 AV	54.0	-19.3	2.87 V	303	21.3	13.4
7	17865.00	52.6 PK	74.0	-21.4	2.15 V	184	30.9	21.7
8	17865.00	40.9 AV	54.0	-13.1	2.15 V	184	19.2	21.7
9	23820.00	55.6 PK	74.0	-18.4	1.87 V	117	58.1	-2.5
10	23820.00	43.9 AV	54.0	-10.1	1.87 V	117	46.4	-2.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 45 : 6175 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6175.00	91.7 PK			2.53 H	210	87.3	4.4
2	*6175.00	81.4 AV			2.53 H	210	77.0	4.4
3	12350.00	45.6 PK	74.0	-28.4	2.71 H	172	32.6	13.0
4	12350.00	36.3 AV	54.0	-17.7	2.71 H	172	23.3	13.0
5	18525.00	52.2 PK	74.0	-21.8	1.62 H	240	59.4	-7.2
6	18525.00	40.3 AV	54.0	-13.7	1.62 H	240	47.5	-7.2
7	#24700.00	53.7 PK	88.2	-34.5	1.64 H	269	55.3	-1.6
8	#24700.00	41.5 AV	68.2	-26.7	1.64 H	269	43.1	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6175.00	99.3 PK			3.17 V	81	94.9	4.4
2	*6175.00	90.4 AV			3.17 V	81	86.0	4.4
3	12350.00	44.8 PK	74.0	-29.2	2.86 V	310	31.8	13.0
4	12350.00	35.2 AV	54.0	-18.8	2.86 V	310	22.2	13.0
5	18525.00	52.0 PK	74.0	-22.0	2.10 V	186	59.2	-7.2
6	18525.00	40.6 AV	54.0	-13.4	2.10 V	186	47.8	-7.2
7	#24700.00	55.0 PK	88.2	-33.2	1.85 V	122	56.6	-1.6
8	#24700.00	43.7 AV	68.2	-24.5	1.85 V	122	45.3	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 93 : 6415 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	91.4 PK			2.55 H	207	86.1	5.3
2	*6415.00	80.6 AV			2.55 H	207	75.3	5.3
3	#12830.00	45.7 PK	88.2	-42.5	2.73 H	198	32.3	13.4
4	#12830.00	36.1 AV	68.2	-32.1	2.73 H	198	22.7	13.4
5	19245.00	51.7 PK	74.0	-22.3	1.66 H	241	58.4	-6.7
6	19245.00	39.9 AV	54.0	-14.1	1.66 H	241	46.6	-6.7
7	#25660.00	53.8 PK	88.2	-34.4	1.61 H	268	55.4	-1.6
8	#25660.00	41.6 AV	68.2	-26.6	1.61 H	268	43.2	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	99.5 PK			3.08 V	76	94.2	5.3
2	*6415.00	90.0 AV			3.08 V	76	84.7	5.3
3	#12830.00	44.8 PK	88.2	-43.4	2.83 V	326	31.4	13.4
4	#12830.00	35.5 AV	68.2	-32.7	2.83 V	326	22.1	13.4
5	19245.00	52.7 PK	74.0	-21.3	2.13 V	185	59.4	-6.7
6	19245.00	41.2 AV	54.0	-12.8	2.13 V	185	47.9	-6.7
7	#25660.00	55.2 PK	88.2	-33.0	1.87 V	101	56.8	-1.6
8	#25660.00	43.6 AV	68.2	-24.6	1.87 V	101	45.2	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 97 : 6435 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	92.2 PK			2.58 H	207	86.8	5.4
2	*6435.00	81.5 AV			2.58 H	207	76.1	5.4
3	#12870.00	46.0 PK	88.2	-42.2	2.73 H	184	32.6	13.4
4	#12870.00	36.5 AV	68.2	-31.7	2.73 H	184	23.1	13.4
5	19305.00	51.8 PK	74.0	-22.2	1.62 H	233	58.5	-6.7
6	19305.00	39.6 AV	54.0	-14.4	1.62 H	233	46.3	-6.7
7	#25740.00	54.6 PK	88.2	-33.6	1.66 H	268	56.0	-1.4
8	#25740.00	42.4 AV	68.2	-25.8	1.66 H	268	43.8	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6435.00	99.3 PK			3.15 V	68	93.9	5.4
2	*6435.00	89.8 AV			3.15 V	68	84.4	5.4
3	#12870.00	44.9 PK	88.2	-43.3	2.85 V	327	31.5	13.4
4	#12870.00	35.5 AV	68.2	-32.7	2.85 V	327	22.1	13.4
5	19305.00	51.9 PK	74.0	-22.1	2.05 V	186	58.6	-6.7
6	19305.00	40.6 AV	54.0	-13.4	2.05 V	186	47.3	-6.7
7	#25740.00	55.7 PK	88.2	-32.5	1.88 V	106	57.1	-1.4
8	#25740.00	44.3 AV	68.2	-23.9	1.88 V	106	45.7	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 105 : 6475 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	90.8 PK			2.59 H	210	85.1	5.7
2	*6475.00	80.6 AV			2.59 H	210	74.9	5.7
3	#12950.00	46.2 PK	88.2	-42.0	2.74 H	179	32.9	13.3
4	#12950.00	36.5 AV	68.2	-31.7	2.74 H	179	23.2	13.3
5	19425.00	52.3 PK	74.0	-21.7	1.61 H	237	59.1	-6.8
6	19425.00	40.3 AV	54.0	-13.7	1.61 H	237	47.1	-6.8
7	#25900.00	54.5 PK	88.2	-33.7	1.71 H	265	56.5	-2.0
8	#25900.00	42.1 AV	68.2	-26.1	1.71 H	265	44.1	-2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6475.00	99.9 PK			3.09 V	70	94.2	5.7
2	*6475.00	90.7 AV			3.09 V	70	85.0	5.7
3	#12950.00	44.5 PK	88.2	-43.7	2.80 V	303	31.2	13.3
4	#12950.00	35.2 AV	68.2	-33.0	2.80 V	303	21.9	13.3
5	19425.00	52.8 PK	74.0	-21.2	2.11 V	181	59.6	-6.8
6	19425.00	41.0 AV	54.0	-13.0	2.11 V	181	47.8	-6.8
7	#25900.00	56.0 PK	88.2	-32.2	1.87 V	117	58.0	-2.0
8	#25900.00	44.3 AV	68.2	-23.9	1.87 V	117	46.3	-2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	91.2 PK			2.57 H	202	85.2	6.0
2	*6515.00	80.9 AV			2.57 H	202	74.9	6.0
3	#13030.00	45.9 PK	88.2	-42.3	2.75 H	172	32.6	13.3
4	#13030.00	36.5 AV	68.2	-31.7	2.75 H	172	23.2	13.3
5	19545.00	51.5 PK	74.0	-22.5	1.71 H	253	57.7	-6.2
6	19545.00	39.7 AV	54.0	-14.3	1.71 H	253	45.9	-6.2
7	#26060.00	53.9 PK	88.2	-34.3	1.62 H	298	55.3	-1.4
8	#26060.00	41.8 AV	68.2	-26.4	1.62 H	298	43.2	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	99.4 PK			3.14 V	49	93.4	6.0
2	*6515.00	90.1 AV			3.14 V	49	84.1	6.0
3	#13030.00	44.7 PK	88.2	-43.5	2.79 V	317	31.4	13.3
4	#13030.00	35.4 AV	68.2	-32.8	2.79 V	317	22.1	13.3
5	19545.00	52.4 PK	74.0	-21.6	2.08 V	199	58.6	-6.2
6	19545.00	41.0 AV	54.0	-13.0	2.08 V	199	47.2	-6.2
7	#26060.00	55.4 PK	88.2	-32.8	1.89 V	122	56.8	-1.4
8	#26060.00	43.8 AV	68.2	-24.4	1.89 V	122	45.2	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	91.2 PK			2.52 H	213	85.2	6.0
2	*6535.00	80.7 AV			2.52 H	213	74.7	6.0
3	#13070.00	46.5 PK	88.2	-41.7	2.73 H	195	33.1	13.4
4	#13070.00	36.8 AV	68.2	-31.4	2.73 H	195	23.4	13.4
5	19605.00	51.3 PK	74.0	-22.7	1.70 H	238	57.4	-6.1
6	19605.00	39.6 AV	54.0	-14.4	1.70 H	238	45.7	-6.1
7	#26140.00	54.3 PK	88.2	-33.9	1.66 H	286	55.6	-1.3
8	#26140.00	41.8 AV	68.2	-26.4	1.66 H	286	43.1	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	99.6 PK			3.07 V	55	93.6	6.0
2	*6535.00	90.5 AV			3.07 V	55	84.5	6.0
3	#13070.00	44.5 PK	88.2	-43.7	2.78 V	315	31.1	13.4
4	#13070.00	35.4 AV	68.2	-32.8	2.78 V	315	22.0	13.4
5	19605.00	52.4 PK	74.0	-21.6	2.12 V	168	58.5	-6.1
6	19605.00	41.1 AV	54.0	-12.9	2.12 V	168	47.2	-6.1
7	#26140.00	55.6 PK	88.2	-32.6	1.88 V	122	56.9	-1.3
8	#26140.00	43.8 AV	68.2	-24.4	1.88 V	122	45.1	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	92.0 PK			2.56 H	218	85.9	6.1
2	*6715.00	81.5 AV			2.56 H	218	75.4	6.1
3	#13430.00	46.5 PK	88.2	-41.7	2.71 H	196	31.6	14.9
4	#13430.00	36.7 AV	68.2	-31.5	2.71 H	196	21.8	14.9
5	20145.00	51.3 PK	74.0	-22.7	1.64 H	255	56.7	-5.4
6	20145.00	39.4 AV	54.0	-14.6	1.64 H	255	44.8	-5.4
7	#26860.00	54.4 PK	88.2	-33.8	1.71 H	274	55.5	-1.1
8	#26860.00	41.8 AV	68.2	-26.4	1.71 H	274	42.9	-1.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	99.8 PK			3.15 V	64	93.7	6.1
2	*6715.00	90.6 AV			3.15 V	64	84.5	6.1
3	#13430.00	43.9 PK	88.2	-44.3	2.79 V	333	29.0	14.9
4	#13430.00	34.8 AV	68.2	-33.4	2.79 V	333	19.9	14.9
5	20145.00	52.7 PK	74.0	-21.3	2.16 V	173	58.1	-5.4
6	20145.00	40.9 AV	54.0	-13.1	2.16 V	173	46.3	-5.4
7	#26860.00	55.4 PK	88.2	-32.8	1.83 V	125	56.5	-1.1
8	#26860.00	43.7 AV	68.2	-24.5	1.83 V	125	44.8	-1.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	91.7 PK			2.58 H	193	84.9	6.8
2	*6855.00	81.5 AV			2.58 H	193	74.7	6.8
3	#13710.00	45.8 PK	88.2	-42.4	2.71 H	185	30.1	15.7
4	#13710.00	36.5 AV	68.2	-31.7	2.71 H	185	20.8	15.7
5	20565.00	51.7 PK	74.0	-22.3	1.64 H	244	56.6	-4.9
6	20565.00	39.4 AV	54.0	-14.6	1.64 H	244	44.3	-4.9
7	#27420.00	54.5 PK	88.2	-33.7	1.72 H	288	56.1	-1.6
8	#27420.00	42.1 AV	68.2	-26.1	1.72 H	288	43.7	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	100.1 PK			3.15 V	66	93.3	6.8
2	*6855.00	90.8 AV			3.15 V	66	84.0	6.8
3	#13710.00	44.4 PK	88.2	-43.8	2.83 V	326	28.7	15.7
4	#13710.00	35.3 AV	68.2	-32.9	2.83 V	326	19.6	15.7
5	20565.00	52.4 PK	74.0	-21.6	2.14 V	195	57.3	-4.9
6	20565.00	40.8 AV	54.0	-13.2	2.14 V	195	45.7	-4.9
7	#27420.00	55.8 PK	88.2	-32.4	1.88 V	109	57.4	-1.6
8	#27420.00	44.2 AV	68.2	-24.0	1.88 V	109	45.8	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	91.8 PK			2.52 H	203	84.8	7.0
2	*6875.00	81.1 AV			2.52 H	203	74.1	7.0
3	#13750.00	46.0 PK	88.2	-42.2	2.70 H	178	30.2	15.8
4	#13750.00	36.5 AV	68.2	-31.7	2.70 H	178	20.7	15.8
5	20625.00	52.0 PK	74.0	-22.0	1.72 H	257	56.8	-4.8
6	20625.00	40.1 AV	54.0	-13.9	1.72 H	257	44.9	-4.8
7	#27500.00	54.1 PK	88.2	-34.1	1.63 H	289	55.3	-1.2
8	#27500.00	41.9 AV	68.2	-26.3	1.63 H	289	43.1	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	99.3 PK			3.11 V	69	92.3	7.0
2	*6875.00	90.2 AV			3.11 V	69	83.2	7.0
3	#13750.00	44.5 PK	88.2	-43.7	2.82 V	302	28.7	15.8
4	#13750.00	35.2 AV	68.2	-33.0	2.82 V	302	19.4	15.8
5	20625.00	52.9 PK	74.0	-21.1	2.11 V	193	57.7	-4.8
6	20625.00	41.2 AV	54.0	-12.8	2.11 V	193	46.0	-4.8
7	#27500.00	56.1 PK	88.2	-32.1	1.90 V	124	57.3	-1.2
8	#27500.00	44.5 AV	68.2	-23.7	1.90 V	124	45.7	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	91.4 PK			2.56 H	189	83.5	7.9
2	*7015.00	81.2 AV			2.56 H	189	73.3	7.9
3	#14030.00	46.7 PK	88.2	-41.5	2.73 H	202	30.8	15.9
4	#14030.00	36.9 AV	68.2	-31.3	2.73 H	202	21.0	15.9
5	21045.00	51.7 PK	74.0	-22.3	1.63 H	242	56.1	-4.4
6	21045.00	39.9 AV	54.0	-14.1	1.63 H	242	44.3	-4.4
7	#28060.00	54.5 PK	88.2	-33.7	1.70 H	290	55.9	-1.4
8	#28060.00	42.0 AV	68.2	-26.2	1.70 H	290	43.4	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	99.4 PK			3.10 V	50	91.5	7.9
2	*7015.00	90.1 AV			3.10 V	50	82.2	7.9
3	#14030.00	44.0 PK	88.2	-44.2	2.82 V	313	28.1	15.9
4	#14030.00	34.9 AV	68.2	-33.3	2.82 V	313	19.0	15.9
5	21045.00	52.4 PK	74.0	-21.6	2.11 V	176	56.8	-4.4
6	21045.00	40.7 AV	54.0	-13.3	2.11 V	176	45.1	-4.4
7	#28060.00	55.9 PK	88.2	-32.3	1.91 V	127	57.3	-1.4
8	#28060.00	44.1 AV	68.2	-24.1	1.91 V	127	45.5	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	91.6 PK			2.38 H	194	83.5	8.1
2	*7115.00	81.5 AV			2.38 H	194	73.4	8.1
3	#7125.00	69.0 PK	88.2	-19.2	2.38 H	194	60.8	8.2
4	#7125.00	58.8 AV	68.2	-9.4	2.38 H	194	50.6	8.2
5	#14230.00	45.8 PK	88.2	-42.4	2.75 H	189	28.7	17.1
6	#14230.00	36.3 AV	68.2	-31.9	2.75 H	189	19.2	17.1
7	21345.00	52.0 PK	74.0	-22.0	1.65 H	246	56.2	-4.2
8	21345.00	40.0 AV	54.0	-14.0	1.65 H	246	44.2	-4.2
9	#28460.00	54.0 PK	88.2	-34.2	1.63 H	284	55.4	-1.4
10	#28460.00	41.9 AV	68.2	-26.3	1.63 H	284	43.3	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	99.6 PK			3.44 V	58	91.5	8.1
2	*7115.00	90.2 AV			3.44 V	58	82.1	8.1
3	#7125.00	73.3 PK	88.2	-14.9	3.44 V	58	65.1	8.2
4	#7125.00	66.9 AV	68.2	-1.3	3.44 V	58	58.7	8.2
5	#14230.00	44.3 PK	88.2	-43.9	2.87 V	330	27.2	17.1
6	#14230.00	35.1 AV	68.2	-33.1	2.87 V	330	18.0	17.1
7	21345.00	52.6 PK	74.0	-21.4	2.08 V	196	56.8	-4.2
8	21345.00	40.8 AV	54.0	-13.2	2.08 V	196	45.0	-4.2
9	#28460.00	55.3 PK	88.2	-32.9	1.91 V	105	56.7	-1.4
10	#28460.00	43.8 AV	68.2	-24.4	1.91 V	105	45.2	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 3 : 5965 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.3 PK	88.2	-37.9	2.37 H	202	46.6	3.7
2	#5925.00	38.6 AV	68.2	-29.6	2.37 H	202	34.9	3.7
3	*5965.00	91.1 PK			2.37 H	202	87.2	3.9
4	*5965.00	79.3 AV			2.37 H	202	75.4	3.9
5	11930.00	46.1 PK	74.0	-27.9	2.68 H	197	32.8	13.3
6	11930.00	36.5 AV	54.0	-17.5	2.68 H	197	23.2	13.3
7	17895.00	51.6 PK	74.0	-22.4	1.67 H	244	29.0	22.6
8	17895.00	39.7 AV	54.0	-14.3	1.67 H	244	17.1	22.6
9	23860.00	54.0 PK	74.0	-20.0	1.65 H	280	56.3	-2.3
10	23860.00	42.0 AV	54.0	-12.0	1.65 H	280	44.3	-2.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	49.6 PK	88.2	-38.6	3.47 V	64	45.9	3.7
2	#5925.00	38.6 AV	68.2	-29.6	3.47 V	64	34.9	3.7
3	*5965.00	97.1 PK			3.47 V	64	93.2	3.9
4	*5965.00	87.9 AV			3.47 V	64	84.0	3.9
5	11930.00	44.4 PK	74.0	-29.6	2.79 V	331	31.1	13.3
6	11930.00	35.3 AV	54.0	-18.7	2.79 V	331	22.0	13.3
7	17895.00	52.2 PK	74.0	-21.8	2.07 V	186	29.6	22.6
8	17895.00	40.6 AV	54.0	-13.4	2.07 V	186	18.0	22.6
9	23860.00	55.4 PK	74.0	-18.6	1.86 V	123	57.7	-2.3
10	23860.00	43.8 AV	54.0	-10.2	1.86 V	123	46.1	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 43 : 6165 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6165.00	91.2 PK			2.41 H	188	86.8	4.4
2	*6165.00	79.4 AV			2.41 H	188	75.0	4.4
3	12330.00	45.7 PK	74.0	-28.3	2.69 H	189	32.6	13.1
4	12330.00	36.1 AV	54.0	-17.9	2.69 H	189	23.0	13.1
5	18495.00	52.3 PK	74.0	-21.7	1.63 H	235	59.6	-7.3
6	18495.00	40.2 AV	54.0	-13.8	1.63 H	235	47.5	-7.3
7	#24660.00	54.1 PK	88.2	-34.1	1.64 H	275	55.9	-1.8
8	#24660.00	42.0 AV	68.2	-26.2	1.64 H	275	43.8	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6165.00	97.4 PK			3.53 V	80	93.0	4.4
2	*6165.00	88.0 AV			3.53 V	80	83.6	4.4
3	12330.00	44.5 PK	74.0	-29.5	2.87 V	333	31.4	13.1
4	12330.00	34.9 AV	54.0	-19.1	2.87 V	333	21.8	13.1
5	18495.00	52.4 PK	74.0	-21.6	2.16 V	199	59.7	-7.3
6	18495.00	41.1 AV	54.0	-12.9	2.16 V	199	48.4	-7.3
7	#24660.00	56.0 PK	88.2	-32.2	1.83 V	125	57.8	-1.8
8	#24660.00	44.5 AV	68.2	-23.7	1.83 V	125	46.3	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 91 : 6405 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	91.1 PK			2.38 H	213	85.8	5.3
2	*6405.00	79.6 AV			2.38 H	213	74.3	5.3
3	#12810.00	45.6 PK	88.2	-42.6	2.66 H	180	32.1	13.5
4	#12810.00	36.0 AV	68.2	-32.2	2.66 H	180	22.5	13.5
5	19215.00	52.3 PK	74.0	-21.7	1.69 H	258	59.0	-6.7
6	19215.00	40.3 AV	54.0	-13.7	1.69 H	258	47.0	-6.7
7	#25620.00	53.9 PK	88.2	-34.3	1.73 H	288	55.6	-1.7
8	#25620.00	41.6 AV	68.2	-26.6	1.73 H	288	43.3	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	97.3 PK			3.48 V	59	92.0	5.3
2	*6405.00	88.1 AV			3.48 V	59	82.8	5.3
3	#12810.00	44.6 PK	88.2	-43.6	2.81 V	331	31.1	13.5
4	#12810.00	35.3 AV	68.2	-32.9	2.81 V	331	21.8	13.5
5	19215.00	52.2 PK	74.0	-21.8	2.10 V	195	58.9	-6.7
6	19215.00	40.8 AV	54.0	-13.2	2.10 V	195	47.5	-6.7
7	#25620.00	55.9 PK	88.2	-32.3	1.85 V	114	57.6	-1.7
8	#25620.00	44.1 AV	68.2	-24.1	1.85 V	114	45.8	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 99 : 6445 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	91.2 PK			2.36 H	207	85.7	5.5
2	*6445.00	79.1 AV			2.36 H	207	73.6	5.5
3	#12890.00	46.1 PK	88.2	-42.1	2.69 H	202	32.8	13.3
4	#12890.00	36.8 AV	68.2	-31.4	2.69 H	202	23.5	13.3
5	19335.00	51.9 PK	74.0	-22.1	1.68 H	261	58.7	-6.8
6	19335.00	40.2 AV	54.0	-13.8	1.68 H	261	47.0	-6.8
7	#25780.00	54.1 PK	88.2	-34.1	1.66 H	262	55.5	-1.4
8	#25780.00	41.6 AV	68.2	-26.6	1.66 H	262	43.0	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	96.7 PK			3.45 V	59	91.2	5.5
2	*6445.00	87.6 AV			3.45 V	59	82.1	5.5
3	#12890.00	43.9 PK	88.2	-44.3	2.81 V	306	30.6	13.3
4	#12890.00	34.8 AV	68.2	-33.4	2.81 V	306	21.5	13.3
5	19335.00	53.1 PK	74.0	-20.9	2.16 V	178	59.9	-6.8
6	19335.00	41.4 AV	54.0	-12.6	2.16 V	178	48.2	-6.8
7	#25780.00	55.7 PK	88.2	-32.5	1.89 V	113	57.1	-1.4
8	#25780.00	44.4 AV	68.2	-23.8	1.89 V	113	45.8	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 107 : 6485 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	91.4 PK			2.41 H	200	85.6	5.8
2	*6485.00	79.7 AV			2.41 H	200	73.9	5.8
3	#12970.00	46.2 PK	88.2	-42.0	2.75 H	178	32.9	13.3
4	#12970.00	36.6 AV	68.2	-31.6	2.75 H	178	23.3	13.3
5	19455.00	51.2 PK	74.0	-22.8	1.67 H	251	57.8	-6.6
6	19455.00	39.5 AV	54.0	-14.5	1.67 H	251	46.1	-6.6
7	#25940.00	54.0 PK	88.2	-34.2	1.61 H	290	55.8	-1.8
8	#25940.00	41.9 AV	68.2	-26.3	1.61 H	290	43.7	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	96.9 PK			3.51 V	62	91.1	5.8
2	*6485.00	87.9 AV			3.51 V	62	82.1	5.8
3	#12970.00	44.5 PK	88.2	-43.7	2.84 V	309	31.2	13.3
4	#12970.00	35.0 AV	68.2	-33.2	2.84 V	309	21.7	13.3
5	19455.00	52.0 PK	74.0	-22.0	2.13 V	176	58.6	-6.6
6	19455.00	40.6 AV	54.0	-13.4	2.13 V	176	47.2	-6.6
7	#25940.00	55.3 PK	88.2	-32.9	1.81 V	125	57.1	-1.8
8	#25940.00	43.9 AV	68.2	-24.3	1.81 V	125	45.7	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 115 : 6525 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	90.7 PK			2.40 H	191	84.7	6.0
2	*6525.00	78.8 AV			2.40 H	191	72.8	6.0
3	#13050.00	45.6 PK	88.2	-42.6	2.72 H	183	32.3	13.3
4	#13050.00	36.3 AV	68.2	-31.9	2.72 H	183	23.0	13.3
5	19575.00	51.9 PK	74.0	-22.1	1.66 H	236	58.1	-6.2
6	19575.00	40.1 AV	54.0	-13.9	1.66 H	236	46.3	-6.2
7	#26100.00	54.4 PK	88.2	-33.8	1.64 H	282	55.8	-1.4
8	#26100.00	41.9 AV	68.2	-26.3	1.64 H	282	43.3	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	97.6 PK			3.50 V	75	91.6	6.0
2	*6525.00	88.2 AV			3.50 V	75	82.2	6.0
3	#13050.00	44.4 PK	88.2	-43.8	2.86 V	302	31.1	13.3
4	#13050.00	35.3 AV	68.2	-32.9	2.86 V	302	22.0	13.3
5	19575.00	52.6 PK	74.0	-21.4	2.11 V	180	58.8	-6.2
6	19575.00	41.3 AV	54.0	-12.7	2.11 V	180	47.5	-6.2
7	#26100.00	56.2 PK	88.2	-32.0	1.87 V	101	57.6	-1.4
8	#26100.00	44.4 AV	68.2	-23.8	1.87 V	101	45.8	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 123 : 6565 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	91.3 PK			2.33 H	195	85.2	6.1
2	*6565.00	79.5 AV			2.33 H	195	73.4	6.1
3	#13130.00	46.2 PK	88.2	-42.0	2.67 H	184	32.7	13.5
4	#13130.00	36.5 AV	68.2	-31.7	2.67 H	184	23.0	13.5
5	19695.00	52.6 PK	74.0	-21.4	1.69 H	261	58.6	-6.0
6	19695.00	40.4 AV	54.0	-13.6	1.69 H	261	46.4	-6.0
7	#26260.00	53.9 PK	88.2	-34.3	1.62 H	264	55.3	-1.4
8	#26260.00	41.6 AV	68.2	-26.6	1.62 H	264	43.0	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	96.3 PK			3.46 V	65	90.2	6.1
2	*6565.00	87.4 AV			3.46 V	65	81.3	6.1
3	#13130.00	44.5 PK	88.2	-43.7	2.81 V	322	31.0	13.5
4	#13130.00	35.3 AV	68.2	-32.9	2.81 V	322	21.8	13.5
5	19695.00	52.4 PK	74.0	-21.6	2.11 V	180	58.4	-6.0
6	19695.00	40.9 AV	54.0	-13.1	2.11 V	180	46.9	-6.0
7	#26260.00	54.9 PK	88.2	-33.3	1.80 V	120	56.3	-1.4
8	#26260.00	43.6 AV	68.2	-24.6	1.80 V	120	45.0	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 155 : 6725 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	91.7 PK			2.38 H	199	85.5	6.2
2	*6725.00	79.8 AV			2.38 H	199	73.6	6.2
3	#13450.00	46.2 PK	88.2	-42.0	2.69 H	173	31.4	14.8
4	#13450.00	36.6 AV	68.2	-31.6	2.69 H	173	21.8	14.8
5	20175.00	51.7 PK	74.0	-22.3	1.64 H	245	57.1	-5.4
6	20175.00	39.6 AV	54.0	-14.4	1.64 H	245	45.0	-5.4
7	#26900.00	53.7 PK	88.2	-34.5	1.70 H	280	55.0	-1.3
8	#26900.00	41.5 AV	68.2	-26.7	1.70 H	280	42.8	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	97.1 PK			3.51 V	68	90.9	6.2
2	*6725.00	87.8 AV			3.51 V	68	81.6	6.2
3	#13450.00	44.5 PK	88.2	-43.7	2.87 V	302	29.7	14.8
4	#13450.00	35.4 AV	68.2	-32.8	2.87 V	302	20.6	14.8
5	20175.00	52.8 PK	74.0	-21.2	2.15 V	172	58.2	-5.4
6	20175.00	41.2 AV	54.0	-12.8	2.15 V	172	46.6	-5.4
7	#26900.00	55.9 PK	88.2	-32.3	1.91 V	108	57.2	-1.3
8	#26900.00	44.1 AV	68.2	-24.1	1.91 V	108	45.4	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 179 : 6845 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	91.3 PK			2.37 H	210	84.6	6.7
2	*6845.00	79.6 AV			2.37 H	210	72.9	6.7
3	#13690.00	45.2 PK	88.2	-43.0	2.74 H	184	29.7	15.5
4	#13690.00	36.0 AV	68.2	-32.2	2.74 H	184	20.5	15.5
5	20535.00	52.1 PK	74.0	-21.9	1.65 H	262	57.0	-4.9
6	20535.00	40.0 AV	54.0	-14.0	1.65 H	262	44.9	-4.9
7	#27380.00	54.7 PK	88.2	-33.5	1.71 H	277	56.4	-1.7
8	#27380.00	42.3 AV	68.2	-25.9	1.71 H	277	44.0	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	96.8 PK			3.42 V	62	90.1	6.7
2	*6845.00	87.8 AV			3.42 V	62	81.1	6.7
3	#13690.00	44.4 PK	88.2	-43.8	2.85 V	329	28.9	15.5
4	#13690.00	35.2 AV	68.2	-33.0	2.85 V	329	19.7	15.5
5	20535.00	52.2 PK	74.0	-21.8	2.07 V	196	57.1	-4.9
6	20535.00	40.9 AV	54.0	-13.1	2.07 V	196	45.8	-4.9
7	#27380.00	56.3 PK	88.2	-31.9	1.86 V	110	58.0	-1.7
8	#27380.00	44.4 AV	68.2	-23.8	1.86 V	110	46.1	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 187 : 6885 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	91.7 PK			2.39 H	191	84.6	7.1
2	*6885.00	79.7 AV			2.39 H	191	72.6	7.1
3	#13770.00	45.5 PK	88.2	-42.7	2.68 H	193	29.7	15.8
4	#13770.00	36.0 AV	68.2	-32.2	2.68 H	193	20.2	15.8
5	20655.00	51.7 PK	74.0	-22.3	1.64 H	252	56.6	-4.9
6	20655.00	39.8 AV	54.0	-14.2	1.64 H	252	44.7	-4.9
7	#27540.00	54.0 PK	88.2	-34.2	1.71 H	284	55.3	-1.3
8	#27540.00	42.0 AV	68.2	-26.2	1.71 H	284	43.3	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	96.7 PK			3.45 V	69	89.6	7.1
2	*6885.00	87.5 AV			3.45 V	69	80.4	7.1
3	#13770.00	44.1 PK	88.2	-44.1	2.81 V	330	28.3	15.8
4	#13770.00	34.9 AV	68.2	-33.3	2.81 V	330	19.1	15.8
5	20655.00	52.1 PK	74.0	-21.9	2.09 V	186	57.0	-4.9
6	20655.00	40.4 AV	54.0	-13.6	2.09 V	186	45.3	-4.9
7	#27540.00	55.5 PK	88.2	-32.7	1.81 V	113	56.8	-1.3
8	#27540.00	44.0 AV	68.2	-24.2	1.81 V	113	45.3	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 211 : 7005 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	91.3 PK			2.42 H	193	83.4	7.9
2	*7005.00	79.3 AV			2.42 H	193	71.4	7.9
3	#14010.00	46.0 PK	88.2	-42.2	2.64 H	201	30.3	15.7
4	#14010.00	36.4 AV	68.2	-31.8	2.64 H	201	20.7	15.7
5	21015.00	51.4 PK	74.0	-22.6	1.61 H	244	55.8	-4.4
6	21015.00	39.5 AV	54.0	-14.5	1.61 H	244	43.9	-4.4
7	#28020.00	53.5 PK	88.2	-34.7	1.69 H	290	54.8	-1.3
8	#28020.00	41.4 AV	68.2	-26.8	1.69 H	290	42.7	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	97.5 PK			3.42 V	77	89.6	7.9
2	*7005.00	88.1 AV			3.42 V	77	80.2	7.9
3	#14010.00	44.4 PK	88.2	-43.8	2.83 V	317	28.7	15.7
4	#14010.00	35.3 AV	68.2	-32.9	2.83 V	317	19.6	15.7
5	21015.00	52.1 PK	74.0	-21.9	2.09 V	176	56.5	-4.4
6	21015.00	40.9 AV	54.0	-13.1	2.09 V	176	45.3	-4.4
7	#28020.00	55.4 PK	88.2	-32.8	1.92 V	105	56.7	-1.3
8	#28020.00	43.5 AV	68.2	-24.7	1.92 V	105	44.8	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 227 : 7085 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	91.5 PK			1.30 H	44	83.4	8.1
2	*7085.00	81.0 AV			1.30 H	44	72.9	8.1
3	#7125.00	54.9 PK	88.2	-33.3	1.30 H	44	46.7	8.2
4	#7125.00	42.3 AV	68.2	-25.9	1.30 H	44	34.1	8.2
5	#14170.00	45.3 PK	88.2	-42.9	2.68 H	201	28.5	16.8
6	#14170.00	36.0 AV	68.2	-32.2	2.68 H	201	19.2	16.8
7	21255.00	52.3 PK	74.0	-21.7	1.60 H	234	56.5	-4.2
8	21255.00	40.0 AV	54.0	-14.0	1.60 H	234	44.2	-4.2
9	#28340.00	54.4 PK	88.2	-33.8	1.70 H	282	55.7	-1.3
10	#28340.00	42.1 AV	68.2	-26.1	1.70 H	282	43.4	-1.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	99.1 PK			3.21 V	58	91.0	8.1
2	*7085.00	90.0 AV			3.21 V	58	81.9	8.1
3	#7125.00	54.7 PK	88.2	-33.5	3.21 V	58	46.5	8.2
4	#7125.00	43.0 AV	68.2	-25.2	3.21 V	58	34.8	8.2
5	#14170.00	44.0 PK	88.2	-44.2	2.86 V	318	27.2	16.8
6	#14170.00	34.8 AV	68.2	-33.4	2.86 V	318	18.0	16.8
7	21255.00	52.8 PK	74.0	-21.2	2.09 V	183	57.0	-4.2
8	21255.00	41.4 AV	54.0	-12.6	2.09 V	183	45.6	-4.2
9	#28340.00	55.2 PK	88.2	-33.0	1.85 V	130	56.5	-1.3
10	#28340.00	43.7 AV	68.2	-24.5	1.85 V	130	45.0	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 7 : 5985 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5923.66	50.4 PK	88.2	-37.8	1.31 H	355	46.7	3.7
2	#5923.66	38.0 AV	68.2	-30.2	1.31 H	355	34.3	3.7
3	*5985.00	90.2 PK			1.31 H	355	86.3	3.9
4	*5985.00	78.1 AV			1.31 H	355	74.2	3.9
5	11970.00	45.3 PK	74.0	-28.7	2.72 H	176	31.9	13.4
6	11970.00	36.1 AV	54.0	-17.9	2.72 H	176	22.7	13.4
7	17955.00	52.4 PK	74.0	-21.6	1.63 H	244	28.1	24.3
8	17955.00	40.2 AV	54.0	-13.8	1.63 H	244	15.9	24.3
9	23940.00	54.2 PK	74.0	-19.8	1.69 H	293	56.5	-2.3
10	23940.00	41.9 AV	54.0	-12.1	1.69 H	293	44.2	-2.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5923.66	51.1 PK	88.2	-37.1	3.10 V	65	47.4	3.7
2	#5923.66	42.0 AV	68.2	-26.2	3.10 V	65	38.3	3.7
3	*5985.00	99.1 PK			3.10 V	65	95.2	3.9
4	*5985.00	88.0 AV			3.10 V	65	84.1	3.9
5	11970.00	44.4 PK	74.0	-29.6	2.78 V	314	31.0	13.4
6	11970.00	35.3 AV	54.0	-18.7	2.78 V	314	21.9	13.4
7	17955.00	52.1 PK	74.0	-21.9	2.09 V	175	27.8	24.3
8	17955.00	40.4 AV	54.0	-13.6	2.09 V	175	16.1	24.3
9	23940.00	56.0 PK	74.0	-18.0	1.86 V	126	58.3	-2.3
10	23940.00	44.2 AV	54.0	-9.8	1.86 V	126	46.5	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 39 : 6145 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6145.00	90.5 PK			1.36 H	360	86.2	4.3
2	*6145.00	78.3 AV			1.36 H	360	74.0	4.3
3	12290.00	45.8 PK	74.0	-28.2	2.74 H	183	32.5	13.3
4	12290.00	36.0 AV	54.0	-18.0	2.74 H	183	22.7	13.3
5	18435.00	51.8 PK	74.0	-22.2	1.61 H	249	59.0	-7.2
6	18435.00	39.8 AV	54.0	-14.2	1.61 H	249	47.0	-7.2
7	#24580.00	53.7 PK	88.2	-34.5	1.61 H	268	55.6	-1.9
8	#24580.00	41.4 AV	68.2	-26.8	1.61 H	268	43.3	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6145.00	98.9 PK			3.11 V	67	94.6	4.3
2	*6145.00	87.9 AV			3.11 V	67	83.6	4.3
3	12290.00	44.7 PK	74.0	-29.3	2.77 V	329	31.4	13.3
4	12290.00	35.3 AV	54.0	-18.7	2.77 V	329	22.0	13.3
5	18435.00	52.8 PK	74.0	-21.2	2.09 V	199	60.0	-7.2
6	18435.00	41.4 AV	54.0	-12.6	2.09 V	199	48.6	-7.2
7	#24580.00	55.5 PK	88.2	-32.7	1.89 V	126	57.4	-1.9
8	#24580.00	43.7 AV	68.2	-24.5	1.89 V	126	45.6	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 87 : 6385 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	90.1 PK			1.28 H	345	84.9	5.2
2	*6385.00	77.8 AV			1.28 H	345	72.6	5.2
3	#12770.00	45.3 PK	88.2	-42.9	2.71 H	175	32.0	13.3
4	#12770.00	36.0 AV	68.2	-32.2	2.71 H	175	22.7	13.3
5	19155.00	51.6 PK	74.0	-22.4	1.65 H	252	58.3	-6.7
6	19155.00	39.6 AV	54.0	-14.4	1.65 H	252	46.3	-6.7
7	#25540.00	54.2 PK	88.2	-34.0	1.63 H	285	55.9	-1.7
8	#25540.00	41.9 AV	68.2	-26.3	1.63 H	285	43.6	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	99.3 PK			3.14 V	51	94.1	5.2
2	*6385.00	88.2 AV			3.14 V	51	83.0	5.2
3	#12770.00	44.5 PK	88.2	-43.7	2.84 V	328	31.2	13.3
4	#12770.00	34.9 AV	68.2	-33.3	2.84 V	328	21.6	13.3
5	19155.00	52.3 PK	74.0	-21.7	2.11 V	185	59.0	-6.7
6	19155.00	40.9 AV	54.0	-13.1	2.11 V	185	47.6	-6.7
7	#25540.00	55.5 PK	88.2	-32.7	1.86 V	130	57.2	-1.7
8	#25540.00	43.9 AV	68.2	-24.3	1.86 V	130	45.6	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 103 : 6465 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	89.8 PK			1.28 H	339	84.2	5.6
2	*6465.00	77.9 AV			1.28 H	339	72.3	5.6
3	#12930.00	45.7 PK	88.2	-42.5	2.71 H	192	32.4	13.3
4	#12930.00	36.3 AV	68.2	-31.9	2.71 H	192	23.0	13.3
5	19395.00	51.9 PK	74.0	-22.1	1.62 H	248	58.7	-6.8
6	19395.00	40.0 AV	54.0	-14.0	1.62 H	248	46.8	-6.8
7	#25860.00	53.7 PK	88.2	-34.5	1.64 H	273	55.4	-1.7
8	#25860.00	41.5 AV	68.2	-26.7	1.64 H	273	43.2	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	99.2 PK			3.04 V	57	93.6	5.6
2	*6465.00	88.1 AV			3.04 V	57	82.5	5.6
3	#12930.00	44.7 PK	88.2	-43.5	2.89 V	321	31.4	13.3
4	#12930.00	35.5 AV	68.2	-32.7	2.89 V	321	22.2	13.3
5	19395.00	52.0 PK	74.0	-22.0	2.08 V	177	58.8	-6.8
6	19395.00	40.6 AV	54.0	-13.4	2.08 V	177	47.4	-6.8
7	#25860.00	54.9 PK	88.2	-33.3	1.87 V	119	56.6	-1.7
8	#25860.00	43.5 AV	68.2	-24.7	1.87 V	119	45.2	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.