



**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Magnetic Wireless Power Bank_A14

Model No.: A14

Trademark: N/A

FCC ID: 2A4B3-A14

Report No.: E01A22080065F00601

Issue Date: September 20, 2022

Prepared for

Huizhou Tongyinhai Precision Electronics Co., Ltd.

**27 Xingwang Street, Gaobao Road, Lilin Town, Huicheng District,
Huizhou City, Guangdong Province**

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

**1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake
Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr.,
China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Electronic Technology Co., Ltd.**

VERIFICATION OF COMPLIANCE

Applicant:	Huizhou Tongyinhai Precision Electronics Co., Ltd. 27 Xingwang Street, Gaobao Road, Lilin Town, Huicheng District, Huizhou City, Guangdong Province
Manufacturer:	Huizhou Tongyinhai Precision Electronics Co., Ltd. 27 Xingwang Street, Gaobao Road, Lilin Town, Huicheng District, Huizhou City, Guangdong Province
Factory:	Huizhou Tongyinhai Precision Electronics Co., Ltd. 27 Xingwang Street, Gaobao Road, Lilin Town, Huicheng District, Huizhou City, Guangdong Province
Product Description:	Magnetic Wireless Power Bank_A14
Trade Mark:	N/A
Model Number:	A14

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.209(2022).

Date of Test : August 09, 2022 to August 19, 2022

Prepared by : _____



Reviewer & Authorized Signer : _____

Tiger Xu/ Supervisor

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A22080065F00601

Table of Contents

1	GENERAL INFORMATION	4
1.1	PRODUCT DESCRIPTION	4
1.2	RELATED SUBMITTAL(S) / GRANT(S).....	5
1.3	TEST METHODOLOGY	5
1.4	SPECIAL ACCESSORIES	5
1.5	EQUIPMENT MODIFICATIONS	5
1.6	TEST FACILITY.....	5
2	SYSTEM TEST CONFIGURATION.....	6
2.1	EUT CONFIGURATION	6
2.2	EUT EXERCISE	6
2.3	TEST PROCEDURE	6
2.4	CONFIGURATION OF TESTED SYSTEM.....	7
3	SUMMARY OF TEST RESULTS.....	7
4	TEST SYSTEM UNCERTAINTY.....	8
5	CONDUCTED EMISSIONS TEST.....	9
5.1	MEASUREMENT PROCEDURE	9
5.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
5.3	MEASUREMENT EQUIPMENT USED.....	9
5.4	CONDUCTED EMISSION LIMIT	9
5.5	MEASUREMENT RESULT	10
5.6	CONDUCTED MEASUREMENT PHOTO.....	13
6	RADIATED EMISSION TEST.....	14
6.1	MEASUREMENT PROCEDURE	14
6.2	TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3	MEASUREMENT EQUIPMENT USED.....	15
6.4	RADIATED EMISSION LIMIT	15
6.5	MEASUREMENT RESULT	17
6.6	RADIATED MEASUREMENT PHOTOS.....	21
7	20DB BANDWIDTH.....	22
7.1	20DB BANDWIDTH LIMIT	22
7.2	TEST INSTRUMENTS.....	22
7.3	TEST PROCEDURE	22
7.4	TEST SETUP.....	22
7.5	TEST RESULT.....	22
8	ANTENNA APPLICATION	24
8.1	ANTENNA REQUIREMENT	24
8.2	RESULT	24

1 General Information

1.1 Product Description

Characteristics	Description
Product Name	Magnetic Wireless Power Bank_A14
Model number	A14
Operation Mode	Wireless Charging
Input Rating	DC 5V, 3A, DC 9V, 2A
Power Supply	DC 5V, DC 9V from adapter Type-C OUT: DC 5V2A, 9V2.22A, 12V1.67A from battery
Operating Frequency	110KHz -148KHz
Wireless Charging Power	5W, 7.5W, 10W, 15W
Modulation Technique	ASK
Antenna Type	Induction coil
Sample receipt date	August 09, 2022

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: 2A4B3-A14 filing to comply with the FCC Part 15, Subpart C Rules.

1.3 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description
Name of Firm : Dong Guan Anci Electronic Technology Co., Ltd.
Site Location : 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, evelopment Zone, Dongguan City, Guangdong Pr., China.

2 System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the fixed in a particular direction according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trade Mark	Model No.	FCC ID	Note
1.	Magnetic Wireless Power Bank_A14	N/A	A14	2A4B3-A14	<i>EUT</i>
2.	iphone	Apple	A2176	N/A	<i>Support Equipment</i>

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.209	Radiated Emission	Compliant
§2.1049	20dB Bandwidth	Compliant
§15.203	Antenna Requirement	Compliant

4 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$


Remark: The coverage Factor ($k=2$), and measurement Uncertainty for a level of Confidence of 95%

5 Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2023-05-12
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2023-05-12
RF Cable	N/A	N/A	2#	2023-05-12
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2023-05-12
1# Shielded Room	chengyu	8m*4m*3.3m	N/A	2024-11-12
Test Software	Farad	EZ-EMC (Ver.ANCI-3A1)	N/A	N/A

5.4 Conducted Emission Limit

Conducted Emission

Frequency(MHz)

Quasi-peak

Average

0.15-0.5

66-56

56-46

0.5-5.0

56

46

5.0-30.0

60

50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.


5.5 Measurement Result

Operation Mode:	TX	Test Date :	2022/08/11
Frequency Range:	0.15MHz~30MHz	Temperature :	26°C
Test Result:	PASS	Humidity :	54 %
Test By:	Catus		

Pass


We pretested modes (Wireless Charging(15W), Wireless Charging(10W),Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst test data see follow the table.

Test mode: Wireless Charging 15W



Site:	843	Phase:	L1	Temperature(C):	26(C)
Limit:	FCC Part 18 C Conduction(QP)			Humidity(%):	54%
EUT:	Magnetic Wireless Power	Test Time:	2022-08-11 23:24:12		
	Bank_A14	Power Rating:	AC 120V/60Hz		
M/N.:	A14	Test Engineer:	Catus		
Mode:	Wireless Charging 15W				
Note:					


No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1660	39.52	10.29	49.81	65.16	-15.35	QP	
2	0.1660	26.73	10.29	37.02	55.16	-18.14	AVG	
3	0.1860	36.57	10.30	46.87	64.21	-17.34	QP	
4	0.1860	21.74	10.30	32.04	54.21	-22.17	AVG	
5	0.2220	32.55	10.30	42.85	62.74	-19.89	QP	
6	0.2220	19.49	10.30	29.79	52.74	-22.95	AVG	
7	0.4460	28.04	9.85	37.89	56.95	-19.06	QP	
8	0.4460	21.04	9.85	30.89	46.95	-16.06	AVG	
9	1.6500	25.12	10.41	35.53	56.00	-20.47	QP	
10	1.6500	19.87	10.41	30.28	46.00	-15.72	AVG	
11	2.0980	21.28	10.42	31.70	56.00	-24.30	QP	
12	2.0980	20.49	10.42	30.91	46.00	-15.09	AVG	



Site:	843	Phase:	N	Temperature(C):	26(C)
Limit:	FCC Part 18 C Conduction(QP)	Test Time:	2022-08-11 23:20:30		
EUT:	Magnetic Wireless Power Bank_A14	Power Rating:	AC 120V/60Hz		
M/N.:	A14	Test Engineer:	Catus		
Mode:	Wireless Charging 15W	Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1580	41.56	10.30	51.86	65.57	-13.71	QP	
2	0.1580	32.55	10.30	42.85	55.57	-12.72	AVG	
3	0.1740	38.03	10.30	48.33	64.77	-16.44	QP	
4	0.1740	29.99	10.30	40.29	54.77	-14.48	AVG	
5	0.2220	35.39	10.31	45.70	62.74	-17.04	QP	
6	0.2220	29.63	10.31	39.94	52.74	-12.80	AVG	
7	0.4220	29.71	9.88	39.59	57.41	-17.82	QP	
8 *	0.4220	25.30	9.88	35.18	47.41	-12.23	AVG	
9	0.7220	27.69	9.66	37.35	56.00	-18.65	QP	
10	0.7220	23.01	9.66	32.67	46.00	-13.33	AVG	
11	1.1180	27.59	9.30	36.89	56.00	-19.11	QP	
12	1.1180	23.04	9.30	32.34	46.00	-13.66	AVG	

5.6 Conducted Measurement Photo




6 Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



6.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022/11/12
2.	Pre-Amplifier	HP	8447D	2727A06172	2023-05-12
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2023-05-12
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022/11/12
5.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92 J-2m	N/A	2022/11/12
6.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92 J-0.3m	N/A	2022/11/12
7.	RF Cable	N/A	N/A	6#	2023-05-12
8.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2023-05-12
9.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500


15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result


We pretested modes (Wireless Charging(15W), Wireless Charging(10W),Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst mode (Wireless Charging(15W))test data see follow the table.



Site:	LAB	Antenna: Horizontal	Temperature(C): 24.3(C)
Limit:	FCC Part 15C 3m Radiation(QP)	Test Time:	Humidity(%): 53.2%
EUT:	Magnetic Wireless Power Bank_A14	Power Rating:	AC 120V/60Hz
M/N.:	A14	Test Engineer:	sunshine
Mode:	Wireless Charging 15W		
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	0.1111	71.92	6.29	78.21	106.61	-28.40	QP	100	236	
2	0.2262	63.35	5.70	69.05	100.47	-31.42	QP	100	254	
3	0.3259	56.95	5.80	62.75	97.32	-34.57	QP	100	120	
4	0.6622	44.15	6.45	50.60	71.19	-20.59	QP	100	103	
5	0.9939	42.16	6.05	48.21	67.67	-19.46	QP	100	271	
6	15.0548	40.90	6.95	47.85	69.50	-21.65	QP	100	152	

*:Maximum data x:Over limit !:over margin




Site:	LAB	Antenna::	Vertical	Temperature(C):	24.3(C)
Limit:	FCC Part 15C 3m Radiation(QP)	Test Time:		Humidity(%):	53.2%
EUT:	Magnetic Wireless Power Bank_A14	Power Rating:		Test Engineer:	sunshine
M/N.:	A14				
Mode:	Wireless Charging 15W				
Note:					

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	0.1135	68.07	6.28	74.35	106.43	-32.08	QP	100	236	
2	0.2217	62.89	5.73	68.62	100.65	-32.03	QP	100	254	
3	0.3326	58.54	5.81	64.35	97.14	-32.79	QP	100	120	
4	0.5410	44.88	6.34	51.22	72.94	-21.72	QP	100	103	
5	3.6406	38.28	6.38	44.66	69.50	-24.84	QP	100	271	
6*	14.7522	41.17	6.93	48.10	69.50	-21.40	QP	100	152	

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

We pretested modes (Wireless Charging(15W),Wireless Charging(10W),Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst test data see follow the table.


Test mode: Wireless Charging 15W



Site:	LAB	Antenna::	Vertical	Temperature(C):	26(C)
Limit:	FCC Part 15 Class B 3m Radiation(QP)	Test Time:	2022/08/11 22:03:52	Humidity(%):	54%
EUT:	Magnetic Wireless Power Bank_A14	Power Rating:	AC 120V/60Hz		
M/N.:	A14	Test Engineer:	AKi		
Mode:	Wireless Charging 15W				
Note:					

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	40.9881	23.60	-4.47	19.13	40.00	-20.87	QP	100	45	
2 *	47.9940	24.06	-4.23	19.83	40.00	-20.17	QP	100	45	
3	55.0274	23.71	-4.48	19.23	40.00	-20.77	QP	100	27	
4	109.0286	24.16	-4.53	19.63	43.50	-23.87	QP	100	27	
5	167.8243	23.42	-8.89	14.53	43.50	-28.97	QP	100	96	
6	201.3930	23.43	-5.02	18.41	43.50	-25.09	QP	100	96	

*:Maximum data x:Over limit !:over margin



Site:	LAB	Antenna::	Horizontal	Temperature(C):	23.4(C)
Limit:	FCC Part 15 Class B 3m Radiation(QP)			Humidity(%):	56.7%
EUT:	Magnetic Wireless Power Bank_A14	Test Time:		Power Rating:	AC 120V/60Hz
M/N.:	A14	Test Engineer:			sunshine
Mode:	Wireless Charging 15W				
Note:					

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1 *	43.2017	24.03	-4.40	19.63	40.00	-20.37	QP	100	45	
2	53.1313	23.52	-4.37	19.15	40.00	-20.85	QP	100	45	
3	106.7587	23.93	-4.62	19.31	43.50	-24.19	QP	100	27	
4	207.1226	23.32	-4.94	18.38	43.50	-25.12	QP	100	27	
5	269.4284	22.99	-3.13	19.86	46.00	-26.14	QP	100	96	
6	291.0360	23.06	-2.27	20.79	46.00	-25.21	QP	100	96	

6.6 Radiated Measurement Photos



7 20db Bandwidth

7.1 20dB Bandwidth Limit

None: for reporting purposed only.


7.2 Test Instruments

Refer a test equipment and calibration data table in this test report.

7.3 Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1KHz RBW and 3KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


7.4 Test Setup



7.5 Test Result

Frequency (KHz)	20dB Bandwidth (KHz)	Results
110	2.721	PASS

20 dB Bandwidth Test plot



Date: 12.AUG.2022 14:35:48

8 Antenna Application



8.1 Antenna requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


8.2 Result



The EUT's antenna, permanent attached antenna, used an Induction coil and integrated on PCB, The antenna's gain meets the requirement.



APPENDIX (Photos of EUT)











***** End of Page *****

