

Product Specifications sheet



Specification No.	20220920001
Effective date	2022/9/20

Customer Name:	Huizhou Tongyin Hai precision Electronic CO., ltd
Product Model	Magnetic charging bank wireless charging coil
DZ Part No.	TX-DZ43.50065-5.3-T10-K6.5-L60开双槽
Customer item No	42.13.44.27460

【 New issue, version revision】

【 This specification includes contents and 7 pages in total 】 【 RoHS Compliant 】

organize	Check	Approval
钟建立	/	马湘平

Dongguan Top Wiser Electronic Technology Co., Ltd

Factory address: 7th floor, east of building , xinbosheng Industrial Park,
No. 5, Xinyuan South Road, Tangxia Town, Dongguan City

Tel: 13147097490

【Within 30 days after the customer receives this acknowledgement, please return it with your signature and seal. If it is overdue, it will be deemed that the production will be carried out according to the standards of this acknowledgement】.

【customer approval】

Date:

Recognition status: full recognition conditional recognition refusal

Approval	Review	Recheck	Check

remark:

Product Specifications sheet

Customer Name:	Huizhou Tongyin Hai precision Electronic CO., Ltd	Customer item No	42.13.44.27460
DZ Part No.	TX-DZ43.50065-5.3-T10-K6.5-L60开双槽	Specification No.	20220920001
Issue/Revision History			
Version	Effective date	Change content / reason	Approval
01	2022/9/20	New specification release	马湘平
organize		check	approval
钟建立		/	马湘平

Product Specifications sheet

Customer Name: wuzhou Tongyin Hai precision Electronic CO., Ltd		Customer item No		42.13.44.27460		
DZ Part No		TX-DZ43.50065-5.3-T10-K6.5-L60开双槽		Specification No.		20220920001
				Version		01
◆ Overall dimensions				(unit: mm)		
				A	5.3 ±0.5	
				B	20.0 ±1.0	
				C	39.0 ±1.5	
				D	43.8 ±1.0	
				E	43.0 ±1.0	
				F	60.0 ±2.0	
				G	3.0 ±2.0	
				H	0.65 ±0.3	
				I	1.90 ±0.2	
◆ Electrical characteristics::						
parameter	specification		Test conditions	Test instrument		
L0	6.5 ±10%	μH	100KHz/1V	■TH1816B		
Q	>20	min	100KHz/1V	■TH1816B		
DCR	<95	mΩ	@ 25°C	■CH-502BC		
◆ Temperature class:						
Operating temperature	-40°C ~ 125°C					
peak Gain:	0dbi					
◆ list of materials:						
Item	Product Name	Material specificatio	Supplier	Remark		
1	Magnetic sheet	43.5*5.3*0.65T 开双槽		PC40 mengzinc		
2	Copper wire	0.08*24*2P		Propane copper covered wire		
3	High temperature	8MM		Rosh tape		
4	glue	D=43round slot 3M glue		Rosh tape		
5	tin	107H		ROSH tin		
6	glue	黄胶yellow glue		ROSH glue		
organize			check		approval	
钟建立			/		马湘平	