

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Report No.: RFBENL-WTW-P22010777

FCC ID: 2A4C6-GMP02

Model No.: WPEA-251ACNI(BT)

Received Date: 2022/1/24

Test Date: 2022/2/11 ~ 2022/3/11

Issued Date: 2022/4/7

Applicant: KONICA MINOLTA, INC.

Address: 2970, Ishikawa-machi, Hachioji-shi, Tokyo, Japan


Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / 723255 / TW2022

Designation Number:

Approved by:  , **Date:** 2022/4/7
May Chen / Manager

This test report consists of 73 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Claire Kuan / Specialist



Table of Contents

Release Control Record	4
1 Certificate	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	8
3.3 Channel List	9
3.4 Test Mode Applicability and Tested Channel Detail	10
3.5 Duty Cycle of Test Signal	11
3.6 Test Program Used and Operation Descriptions	12
3.7 Connection Diagram of EUT and Peripheral Devices	12
3.8 Configuration of Peripheral Devices and Cable Connections	13
4 Test Instruments	14
4.1 RF Output Power	14
4.2 Power Spectral Density	14
4.3 6 dB Bandwidth	14
4.4 Conducted Out of Band Emissions	14
4.5 AC Power Conducted Emissions	15
4.6 Unwanted Emissions below 1 GHz	16
4.7 Unwanted Emissions above 1 GHz	17
5 Limits of Test Items	18
5.1 RF Output Power	18
5.2 Power Spectral Density	18
5.3 6 dB Bandwidth	18
5.4 Conducted Out of Band Emissions	18
5.5 AC Power Conducted Emissions	18
5.6 Unwanted Emissions below 1 GHz	19
5.7 Unwanted Emissions above 1 GHz	19
6 Test Arrangements	20
6.1 RF Output Power	20
6.1.1 Test Setup	20
6.1.2 Test Procedure	20
6.2 Power Spectral Density	20
6.2.1 Test Setup	20
6.2.2 Test Procedure	20
6.3 6 dB Bandwidth	21
6.3.1 Test Setup	21
6.3.2 Test Procedure	21
6.4 Conducted Out of Band Emissions	21
6.4.1 Test Setup	21
6.4.2 Test Procedure	21
6.5 AC Power Conducted Emissions	22
6.5.1 Test Setup	22
6.5.2 Test Procedure	22
6.6 Unwanted Emissions below 1 GHz	23
6.6.1 Test Setup	23
6.6.2 Test Procedure	24
6.7 Unwanted Emissions above 1 GHz	25
6.7.1 Test Setup	25
6.7.2 Test Procedure	25
7 Test Results of Test Item	26



7.1	RF Output Power	26
7.2	Power Spectral Density	28
7.3	6 dB Bandwidth	30
7.4	Conducted Out of Band Emissions	32
7.5	AC Power Conducted Emissions	40
7.6	Unwanted Emissions below 1 GHz	42
7.7	Unwanted Emissions above 1 GHz.....	44
8	Pictures of Test Arrangements	72
9	Information of the Testing Laboratories	73



Release Control Record

Issue No.	Description	Date Issued
RFBENL-WTW-P22010777	Original release.	2022/4/7

1 Certificate

Product: 802.11ac/b/g/n Wi-Fi+BT Module

Brand: Sparklan

Test Model: WPEA-251ACNI(BT)

Sample Status: Engineering sample

Applicant: KONICA MINOLTA, INC.

Test Date: 2022/2/11 ~ 2022/3/11

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement ANSI C63.10-2013

procedure: KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -15.44 dB at 0.45863 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -3.2 dB at 166.29 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.1 dB at 2483.50, 4924.00 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.5 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.1 dB
	30 MHz ~ 1 GHz	5.5 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	5.1 dB
	18 GHz ~ 40 GHz	5.3 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	802.11ac/b/g/n Wi-Fi+BT Module
Brand	Sparklan
Test Model	WPEA-251ACNI(BT)
Status of EUT	Engineering sample
Power Supply Rating	DC 3.3V from host equipment
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11n mode
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 300 Mbps
Operating Frequency	2412 ~ 2462 MHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7
Output Power	693.119 mW (28.41 dBm)

Note:

1. There are WLAN (2.4GHz & 5GHz) and Bluetooth technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (5GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
WIFI 0 BT	0	RTI	C0255-ANG0027	2.8	2.4~2.4835	PCB	ipex(MHF)
				6.6	5.15~5.85		
WIFI 1	1	RTI	C0255-ANG0029	2.8	2.4~2.4835	PCB	ipex(MHF)
				6.6	5.15~5.85		

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2. The EUT incorporates a MIMO function:

2.4 GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	2TX	2RX
802.11g	2TX	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX

3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. The antenna with EUT can be used in the following ways: XYZ 3-Axis. Pre-scan in these ways and find the worst case as a representative test condition.
Worst Case:	1. X/ Y/ Z Worst Condition:Y Axis 2. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
AC Power Conducted Emissions	802.11n (HT20)	CDD	6	BPSK	MCS0
Unwanted Emissions below 1 GHz	802.11n (HT20)	CDD	6	BPSK	MCS0
Unwanted Emissions above 1 GHz	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0
	802.11n (HT40)	CDD	1, 6, 11	BPSK	MCS0
RF Output Power / 6 dB Bandwidth / Power Spectral Density / Conducted Out of Band Emissions	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0
	802.11n (HT40)	CDD	1, 6, 11	BPSK	MCS0

3.5 Duty Cycle of Test Signal

Duty cycle of test signal is $\geq 98\%$, duty factor is not required.
 Duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11b: Duty cycle = 12.203 ms / 12.309 ms = 99.1 %

802.11g: Duty cycle = 10.729 ms / 10.857 ms = 98.8 %

802.11n (HT20): Duty cycle = 18.606 ms / 18.712 ms = 99.4 %

802.11n (HT40): Duty cycle = 4.799 ms / 4.888 ms = 98.2 %




3.6 Test Program Used and Operation Descriptions


Controlling software (QRCT_CONN_v30161) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices

For Radiated Emission test



For AC Power Conducted Emission test



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Laptop	Lenovo	3000 N200	N/A	N/A	Provided by Lab
B	Test Tool	Sparklan Communications Inc	N/A	N/A	N/A	Supplied by applicant
C	Adapter	Lenovo	92P1105	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1.7	No	1	Provided by Lab
2	AC Cable	1	0.6	No	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2021/4/13	2022/4/12
Power Meter Anritsu	ML2495A	1529002	2021/6/21	2022/6/20
Pulse Power Sensor Anritsu	MA2411B	1339443	2021/5/31	2022/5/30
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	100964	2021/5/31	2022/5/30

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2022/3/8

4.2 Power Spectral Density

Refer to section 4.1 to get information of the instruments.

4.3 6 dB Bandwidth

Refer to section 4.1 to get information of the instruments.

4.4 Conducted Out of Band Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2021/4/13	2022/4/12
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	100964	2021/5/31	2022/5/30

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2022/3/8

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohms Terminator	50	3	2021/10/27	2022/10/26
Fixed attenuator STI	STI02-2200-10	005	2021/8/27	2022/8/26
LISN R&S	ESH3-Z5	848773/004	2021/10/29	2022/10/28
LISN R & S	ESH3-Z5	835239/001	2021/3/26	2022/3/25
RF Coaxial Cable JYEBO	5D-FB	COCCAB-001	2021/9/25	2022/9/24
Software BVADT	BVADT_Cond_V7.3.7.4	N/A	N/A	N/A
TEST RECEIVER R&S	ESCS 30	847124/029	2021/10/13	2022/10/12

Notes:

1. The test was performed in Conduction 1
2. Tested Date: 2022/2/28

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Test Receiver Agilent	N9038A	MY51210202	2021/11/19	2022/11/18
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Pre_Amplifier EMCI	EMC001340	980142	2021/5/24	2022/5/23
Loop Antenna TESEQ	HLA 6121	45745	2021/7/21	2022/7/20
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2022/1/6	2023/1/5
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-002	2022/1/6	2023/1/5
Pre_Amplifier EMCI	EMC330N	980701	2021/3/10	2022/3/9
Trilog Broadband Antenna Schwarzbeck	VULB 9168	9168-406	2021/10/27	2022/10/26
RF Coaxial Cable COMMATE/PEWC	8D	966-4-1	2021/3/17	2022/3/16
RF Coaxial Cable COMMATE/PEWC	8D	966-4-2	2021/3/17	2022/3/16
RF Coaxial Cable COMMATE/PEWC	8D	966-4-3	2021/3/17	2022/3/16
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-03	2022/1/10	2023/1/9

Notes:

1. The test was performed in 966 Chamber No. 4.
2. Tested Date: 2022/2/28

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-783	2021/11/14	2022/11/13
	BBHA 9170	BBHA9170519	2021/11/14	2022/11/13
Pre_Amplifier EMCI	EMC 12630 SE	980638	2021/4/7	2022/4/6
	EMC184045SE	980387	2022/1/10	2023/1/9
RF Cable-Frequency Range : 1-26.5GHz EMCI	EMC104-SM-SM-1200	160922	2021/12/24	2022/12/23
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2022/1/10	2023/1/9
RF Coaxial Cable EMCI	EMC104-SM-SM-2000	180502	2021/4/26	2022/4/25
	EMC104-SM-SM-6000	210704	2021/11/9	2022/11/8
RF Coaxial Cable EMEC	EM102-KMKM-450	21090301	2021/9/11	2022/9/10
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A
Test Receiver Agilent	N9038A	MY51210202	2021/11/19	2022/11/18

Notes:

1. The test was performed in 966 Chamber No. 4.
2. Tested Date: 2022/2/11 ~ 2022/3/11

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:


A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW $\geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.


Note:

The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.


Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup

For Radiated emission above 1 GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3.3 Vdc	Environmental Conditions:	25 °C, 60 % RH	Tested By:	Ryann Wu
--------------	---------	---------------------------	----------------	------------	----------

For Peak Power

802.11b

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	23.24	23.00	410.389	26.13	30	Pass
6	2437	21.35	20.90	259.485	24.14	30	Pass
11	2462	20.11	19.47	191.077	22.81	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 2.8 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	24.11	24.03	510.562	27.08	30	Pass
6	2437	24.86	25.15	633.537	28.02	30	Pass
11	2462	21.54	20.52	255.281	24.07	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 2.8 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	23.57	23.21	436.921	26.40	30	Pass
6	2437	25.13	25.65	693.119	28.41	30	Pass
11	2462	20.94	20.03	224.858	23.52	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 2.8 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
3	2422	22.73	22.23	354.609	25.50	30	Pass
6	2437	23.54	23.70	460.366	26.63	30	Pass
9	2452	20.81	20.03	221.197	23.45	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 2.8 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	21.34	20.92	259.739	24.15
6	2437	19.11	18.60	153.914	21.87
11	2462	17.74	17.11	110.834	20.45

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	19.17	18.30	150.212	21.77
6	2437	20.87	20.53	235.16	23.71
11	2462	15.31	14.34	61.127	17.86

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
1	2412	17.92	16.51	106.715	20.28
6	2437	22.00	21.94	314.804	24.98
11	2462	14.61	13.58	51.71	17.14

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Average Power (mW)	Total Average Power (dBm)
		Chain 0	Chain 1		
3	2422	16.81	16.15	89.183	19.50
6	2437	18.15	17.33	119.388	20.77
9	2452	14.46	13.56	50.624	17.04

7.2 Power Spectral Density

Input Power:	3.3 Vdc	Environmental Conditions:	25 °C, 60 % RH	Tested By:	Ryann Wu
--------------	---------	---------------------------	----------------	------------	----------

802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-0.88	-1.93	1.64	8.00	Pass
6	2437	-2.82	-3.98	-0.35	8.00	Pass
11	2462	-3.93	-5.81	-1.76	8.00	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain = gain of antenna element + 10 log (2 of TX antenna elements)
3. The directional gain is 5.81 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-6.15	-6.73	-3.42	8.00	Pass
6	2437	-4.23	-3.81	-1.00	8.00	Pass
11	2462	-9.48	-10.27	-6.85	8.00	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain = gain of antenna element + 10 log (2 of TX antenna elements)
3. The directional gain is 5.81 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-6.55	-8.00	-4.20	8.00	Pass
6	2437	-2.31	-3.89	-0.02	8.00	Pass
11	2462	-10.31	-11.39	-7.81	8.00	Pass

Notes:


1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain = gain of antenna element + 10 log (2 of TX antenna elements)
3. The directional gain is 5.81 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
3	2422	-11.85	-12.73	-9.26	8.00	Pass
6	2437	-10.56	-11.66	-8.06	8.00	Pass
9	2452	-13.50	-15.01	-11.18	8.00	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain = gain of antenna element + 10 log (2 of TX antenna elements)
3. The directional gain is 5.81 dBi < 6 dBi, so the power density limit shall not be reduced.



7.3 6 dB Bandwidth

Input Power:	3.3 Vdc	Environmental Conditions:	25 °C, 60 % RH	Tested By:	Ryann Wu
--------------	---------	---------------------------	----------------	------------	----------

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	9.09	8.6	0.5	Pass
6	2437	8.09	8.08	0.5	Pass
11	2462	8.09	8.1	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	15.2	15.77	0.5	Pass
6	2437	15.68	15.3	0.5	Pass
11	2462	15.12	15.18	0.5	Pass


802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	15.24	15.13	0.5	Pass
6	2437	16.53	15.46	0.5	Pass
11	2462	15.14	15.21	0.5	Pass


802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
3	2422	33.85	35.13	0.5	Pass
6	2437	32.8	34.19	0.5	Pass
9	2452	32.68	35.14	0.5	Pass


Spectrum Plot of Minimum Value




802.11b \ Chain1 : CH 6



802.11g \ Chain0 : CH 11



802.11n (HT20) \ Chain1 : CH 1



802.11n (HT40) \ Chain0 : CH 9











7.4 Conducted Out of Band Emissions

Input Power:	3.3 Vdc	Environmental Conditions:	25 °C, 60 % RH	Tested By:	Ryann Wu
--------------	---------	---------------------------	----------------	------------	----------









802.11b









802.11g







Chain 1 : CH 1




Chain 1 : CH 1




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 11



Chain 1 : CH 11




Chain 1 : CH 1 Band edge




Chain 1 : CH 11 Band edge




802.11n (HT20)




Chain 0 : CH 1




Chain 0 : CH 1




Chain 0 : CH 6




Chain 0 : CH 6




Chain 0 : CH 11




Chain 0 : CH 11




Chain 0 : CH 1 Band edge




Chain 0 : CH 11 Band edge




Chain 1 : CH 1




Chain 1 : CH 1




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 11



Chain 1 : CH 11




Chain 1 : CH 1 Band edge




Chain 1 : CH 11 Band edge




802.11n (HT40)




Chain 0 : CH 3




Chain 0 : CH 3




Chain 0 : CH 6




Chain 0 : CH 6




Chain 0 : CH 9




Chain 0 : CH 9




Chain 0 : CH 3 Band edge




Chain 0 : CH 9 Band edge




Chain 1 : CH 3




Chain 1 : CH 3




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 9



Chain 1 : CH 9



Chain 1 : CH 3 Band edge



Chain 1 : CH 9 Band edge


7.5 AC Power Conducted Emissions

RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Ryan Du		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15777	10.05	34.52	16.21	44.57	26.26	65.58	55.58	-21.01	-29.32
2	0.18121	10.05	38.18	27.19	48.23	37.24	64.43	54.43	-16.20	-17.19
3	0.22414	10.05	30.99	19.45	41.04	29.50	62.66	52.66	-21.62	-23.16
4	0.44676	10.07	25.43	16.18	35.50	26.25	56.94	46.94	-21.44	-20.69
5	1.45326	10.13	16.53	11.25	26.66	21.38	56.00	46.00	-29.34	-24.62
6	13.95718	10.86	15.88	8.51	26.74	19.37	60.00	50.00	-33.26	-30.63

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Ryan Du		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15003	10.02	38.96	19.81	48.98	29.83	66.00	56.00	-17.02	-26.17
2	0.17348	10.02	31.41	15.17	41.43	25.19	64.79	54.79	-23.36	-29.60
3	0.20862	10.03	26.11	8.56	36.14	18.59	63.26	53.26	-27.12	-34.67
4	0.22425	10.03	30.88	17.91	40.91	27.94	62.66	52.66	-21.75	-24.72
5	0.27114	10.03	26.15	16.77	36.18	26.80	61.08	51.08	-24.90	-24.28
6	0.45863	10.04	25.81	21.24	35.85	31.28	56.72	46.72	-20.87	-15.44

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.6 Unwanted Emissions below 1 GHz


RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	9 kHz ~ 1 GHz	Detector Function & Bandwidth	(QP) RB = 120kHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.16	32.8 QP	40.0	-7.2	1.00 H	237	46.5	-13.7
2	99.77	32.9 QP	43.5	-10.6	3.00 H	221	49.7	-16.8
3	166.07	40.2 QP	43.5	-3.3	1.50 H	208	52.5	-12.3
4	199.15	40.1 QP	43.5	-3.4	1.50 H	248	55.2	-15.1
5	497.90	38.4 QP	46.0	-7.6	1.50 H	215	43.6	-5.2
6	797.66	36.1 QP	46.0	-9.9	1.00 H	232	34.9	1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	9 kHz ~ 1 GHz	Detector Function & Bandwidth	(QP) RB = 120kHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.24	32.4 QP	40.0	-7.6	1.00 V	307	46.3	-13.9
2	166.29	40.3 QP	43.5	-3.2	1.00 V	293	52.6	-12.3
3	199.17	36.4 QP	43.5	-7.1	2.00 V	169	51.5	-15.1
4	432.02	38.5 QP	46.0	-7.5	1.50 V	287	45.2	-6.7
5	528.00	39.9 QP	46.0	-6.1	1.50 V	275	44.4	-4.5
6	797.83	32.6 QP	46.0	-13.4	1.50 V	264	31.4	1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




7.7 Unwanted Emissions above 1 GHz

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	1.98 H	13	64.3	-4.5
2	2390.00	49.8 AV	54.0	-4.2	1.98 H	13	54.3	-4.5
3	*2412.00	112.2 PK			1.98 H	13	116.7	-4.5
4	*2412.00	109.5 AV			1.98 H	13	114.0	-4.5
5	4824.00	50.7 PK	74.0	-23.3	1.24 H	91	50.7	0.0
6	4824.00	49.2 AV	54.0	-4.8	1.24 H	91	49.2	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.




RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.35	55.6 PK	74.0	-18.4	2.14 V	250	60.1	-4.5
2	2386.35	43.8 AV	54.0	-10.2	2.14 V	250	48.3	-4.5
3	*2412.00	100.6 PK			2.14 V	250	105.1	-4.5
4	*2412.00	98.5 AV			2.14 V	250	103.0	-4.5
5	4824.00	54.0 PK	74.0	-20.0	1.21 V	56	54.0	0.0
6	4824.00	53.2 AV	54.0	-0.8	1.21 V	56	53.2	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.8 PK	74.0	-18.2	1.93 H	14	60.3	-4.5
2	2390.00	45.7 AV	54.0	-8.3	1.93 H	14	50.2	-4.5
3	*2437.00	111.7 PK			1.93 H	14	116.2	-4.5
4	*2437.00	109.0 AV			1.93 H	14	113.5	-4.5
5	2483.50	56.0 PK	74.0	-18.0	1.93 H	14	60.5	-4.5
6	2483.50	46.3 AV	54.0	-7.7	1.93 H	14	50.8	-4.5
7	4874.00	53.5 PK	74.0	-20.5	1.46 H	276	53.7	-0.2
8	4874.00	52.9 AV	54.0	-1.1	1.46 H	276	53.1	-0.2
9	7311.00	42.7 PK	74.0	-31.3	1.63 H	241	36.5	6.2
10	7311.00	31.9 AV	54.0	-22.1	1.63 H	241	25.7	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.




RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.2 PK	74.0	-19.8	1.75 V	197	58.7	-4.5
2	2390.00	43.2 AV	54.0	-10.8	1.75 V	197	47.7	-4.5
3	*2437.00	99.8 PK			1.75 V	197	104.3	-4.5
4	*2437.00	97.5 AV			1.75 V	197	102.0	-4.5
5	2483.50	54.4 PK	74.0	-19.6	1.75 V	197	58.9	-4.5
6	2483.50	43.5 AV	54.0	-10.5	1.75 V	197	48.0	-4.5
7	4874.00	53.8 PK	74.0	-20.2	2.23 V	60	54.0	-0.2
8	4874.00	53.2 AV	54.0	-0.8	2.23 V	60	53.4	-0.2
9	7311.00	42.4 PK	74.0	-31.6	1.50 V	360	36.2	6.2
10	7311.00	29.8 AV	54.0	-24.2	1.50 V	360	23.6	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.6 PK			1.87 H	11	117.1	-4.5
2	*2462.00	110.5 AV			1.87 H	11	115.0	-4.5
3	2483.50	61.2 PK	74.0	-12.8	1.87 H	11	65.7	-4.5
4	2483.50	52.5 AV	54.0	-1.5	1.87 H	11	57.0	-4.5
5	4924.00	55.0 PK	74.0	-19.0	1.66 H	200	55.0	0.0
6	4924.00	53.9 AV	54.0	-0.1	1.66 H	200	53.9	0.0
7	7386.00	43.2 PK	74.0	-30.8	1.20 H	220	36.7	6.5
8	7386.00	32.3 AV	54.0	-21.7	1.20 H	220	25.8	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.1 PK			1.76 V	207	104.6	-4.5
2	*2462.00	97.9 AV			1.76 V	207	102.4	-4.5
3	2483.50	56.5 PK	74.0	-17.5	1.76 V	207	61.0	-4.5
4	2483.50	45.1 AV	54.0	-8.9	1.76 V	207	49.6	-4.5
5	4924.00	54.5 PK	74.0	-19.5	1.90 V	46	54.5	0.0
6	4924.00	53.5 AV	54.0	-0.5	1.90 V	46	53.5	0.0
7	7386.00	44.4 PK	74.0	-29.6	1.87 V	56	37.9	6.5
8	7386.00	32.1 AV	54.0	-21.9	1.87 V	56	25.6	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.96 H	15	68.0	-4.5
2	2390.00	53.1 AV	54.0	-0.9	1.96 H	15	57.6	-4.5
3	*2412.00	110.9 PK			1.96 H	15	115.4	-4.5
4	*2412.00	102.8 AV			1.96 H	15	107.3	-4.5
5	4824.00	64.3 PK	74.0	-9.7	1.94 H	56	64.3	0.0
6	4824.00	51.3 AV	54.0	-2.7	1.94 H	56	51.3	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	2.59 V	244	61.5	-4.5
2	2390.00	44.1 AV	54.0	-9.9	2.59 V	244	48.6	-4.5
3	*2412.00	105.8 PK			2.59 V	244	110.3	-4.5
4	*2412.00	95.5 AV			2.59 V	244	100.0	-4.5
5	4824.00	64.1 PK	74.0	-9.9	1.95 V	44	64.1	0.0
6	4824.00	51.0 AV	54.0	-3.0	1.95 V	44	51.0	0.0

Remarks:

1. Emission Level(dBUV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.3 PK	74.0	-17.7	1.96 H	21	60.8	-4.5
2	2390.00	47.9 AV	54.0	-6.1	1.96 H	21	52.4	-4.5
3	*2437.00	111.2 PK			1.96 H	21	115.7	-4.5
4	*2437.00	103.1 AV			1.96 H	21	107.6	-4.5
5	2483.50	57.2 PK	74.0	-16.8	1.96 H	21	61.7	-4.5
6	2483.50	48.7 AV	54.0	-5.3	1.96 H	21	53.2	-4.5
7	4874.00	66.5 PK	74.0	-7.5	1.89 H	61	66.7	-0.2
8	4874.00	53.4 AV	54.0	-0.6	1.89 H	61	53.6	-0.2
9	7311.00	42.7 PK	74.0	-31.3	1.60 H	77	36.5	6.2
10	7311.00	30.6 AV	54.0	-23.4	1.60 H	77	24.4	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.5 PK	74.0	-19.5	1.76 V	216	59.0	-4.5
2	2390.00	43.6 AV	54.0	-10.4	1.76 V	216	48.1	-4.5
3	*2437.00	105.6 PK			1.76 V	216	110.1	-4.5
4	*2437.00	96.1 AV			1.76 V	216	100.6	-4.5
5	2483.50	54.6 PK	74.0	-19.4	1.76 V	216	59.1	-4.5
6	2483.50	43.8 AV	54.0	-10.2	1.76 V	216	48.3	-4.5
7	4874.00	61.1 PK	74.0	-12.9	2.07 V	36	61.3	-0.2
8	4874.00	48.2 AV	54.0	-5.8	2.07 V	36	48.4	-0.2
9	7311.00	46.9 PK	74.0	-27.1	1.00 V	182	40.7	6.2
10	7311.00	33.3 AV	54.0	-20.7	1.00 V	182	27.1	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.4 PK			2.37 H	2	114.9	-4.5
2	*2462.00	102.1 AV			2.37 H	2	106.6	-4.5
3	2483.50	67.5 PK	74.0	-6.5	2.37 H	2	72.0	-4.5
4	2483.50	53.6 AV	54.0	-0.4	2.37 H	2	58.1	-4.5
5	4924.00	61.7 PK	74.0	-12.3	1.87 H	49	61.7	0.0
6	4924.00	48.8 AV	54.0	-5.2	1.87 H	49	48.8	0.0
7	7386.00	43.1 PK	74.0	-30.9	1.57 H	76	36.6	6.5
8	7386.00	30.7 AV	54.0	-23.3	1.57 H	76	24.2	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.




RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	104.8 PK			2.53 V	251	109.3	-4.5
2	*2462.00	95.3 AV			2.53 V	251	99.8	-4.5
3	2483.50	58.8 PK	74.0	-15.2	2.53 V	251	63.3	-4.5
4	2483.50	47.4 AV	54.0	-6.6	2.53 V	251	51.9	-4.5
5	4924.00	56.8 PK	74.0	-17.2	2.02 V	37	56.8	0.0
6	4924.00	44.4 AV	54.0	-9.6	2.02 V	37	44.4	0.0
7	7386.00	46.3 PK	74.0	-27.7	1.00 V	181	39.8	6.5
8	7386.00	32.9 AV	54.0	-21.1	1.00 V	181	26.4	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.7 PK	74.0	-10.3	1.96 H	14	68.2	-4.5
2	2390.00	53.4 AV	54.0	-0.6	1.96 H	14	57.9	-4.5
3	*2412.00	110.5 PK			1.96 H	14	115.0	-4.5
4	*2412.00	101.9 AV			1.96 H	14	106.4	-4.5
5	4824.00	61.1 PK	74.0	-12.9	1.87 H	42	61.1	0.0
6	4824.00	48.4 AV	54.0	-5.6	1.87 H	42	48.4	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.3 PK	74.0	-15.7	2.20 V	212	62.8	-4.5
2	2390.00	47.4 AV	54.0	-6.6	2.20 V	212	51.9	-4.5
3	*2412.00	105.7 PK			2.20 V	212	110.2	-4.5
4	*2412.00	96.2 AV			2.20 V	212	100.7	-4.5
5	4824.00	56.4 PK	74.0	-17.6	2.08 V	24	56.4	0.0
6	4824.00	44.1 AV	54.0	-9.9	2.08 V	24	44.1	0.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.2 PK	74.0	-10.8	2.01 H	24	67.7	-4.5
2	2390.00	52.7 AV	54.0	-1.3	2.01 H	24	57.2	-4.5
3	*2437.00	114.7 PK			2.01 H	24	119.2	-4.5
4	*2437.00	105.8 AV			2.01 H	24	110.3	-4.5
5	2483.50	65.2 PK	74.0	-8.8	2.01 H	24	69.7	-4.5
6	2483.50	53.3 AV	54.0	-0.7	2.01 H	24	57.8	-4.5
7	4874.00	66.5 PK	74.0	-7.5	1.47 H	200	66.7	-0.2
8	4874.00	53.3 AV	54.0	-0.7	1.47 H	200	53.5	-0.2
9	7311.00	42.6 PK	74.0	-31.4	1.26 H	170	36.4	6.2
10	7311.00	30.9 AV	54.0	-23.1	1.26 H	170	24.7	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.4 PK	74.0	-15.6	1.82 V	218	62.9	-4.5
2	2390.00	48.7 AV	54.0	-5.3	1.82 V	218	53.2	-4.5
3	*2437.00	109.3 PK			1.82 V	218	113.8	-4.5
4	*2437.00	99.5 AV			1.82 V	218	104.0	-4.5
5	2483.50	58.9 PK	74.0	-15.1	1.82 V	218	63.4	-4.5
6	2483.50	49.2 AV	54.0	-4.8	1.82 V	218	53.7	-4.5
7	4874.00	63.7 PK	74.0	-10.3	1.48 V	152	63.9	-0.2
8	4874.00	50.5 AV	54.0	-3.5	1.48 V	152	50.7	-0.2
9	7311.00	43.5 PK	74.0	-30.5	1.34 V	180	37.3	6.2
10	7311.00	31.7 AV	54.0	-22.3	1.34 V	180	25.5	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.3 PK			2.12 H	11	113.8	-4.5
2	*2462.00	100.9 AV			2.12 H	11	105.4	-4.5
3	2483.50	65.7 PK	74.0	-8.3	2.12 H	11	70.2	-4.5
4	2483.50	53.2 AV	54.0	-0.8	2.12 H	11	57.7	-4.5
5	4924.00	61.1 PK	74.0	-12.9	1.82 H	46	61.1	0.0
6	4924.00	48.3 AV	54.0	-5.7	1.82 H	46	48.3	0.0
7	7386.00	42.7 PK	74.0	-31.3	1.60 H	78	36.2	6.5
8	7386.00	30.5 AV	54.0	-23.5	1.60 H	78	24.0	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.6 PK			2.41 V	175	108.1	-4.5
2	*2462.00	94.1 AV			2.41 V	175	98.6	-4.5
3	2483.50	57.6 PK	74.0	-16.4	2.41 V	175	62.1	-4.5
4	2483.50	46.3 AV	54.0	-7.7	2.41 V	175	50.8	-4.5
5	4924.00	56.7 PK	74.0	-17.3	2.00 V	27	56.7	0.0
6	4924.00	44.1 AV	54.0	-9.9	2.00 V	27	44.1	0.0
7	7386.00	46.0 PK	74.0	-28.0	1.00 V	193	39.5	6.5
8	7386.00	32.9 AV	54.0	-21.1	1.00 V	193	26.4	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 3 : 2422 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.4 PK	74.0	-9.6	1.98 H	14	68.9	-4.5
2	2390.00	53.2 AV	54.0	-0.8	1.98 H	14	57.7	-4.5
3	*2422.00	103.6 PK			1.98 H	14	108.1	-4.5
4	*2422.00	95.2 AV			1.98 H	14	99.7	-4.5
5	4844.00	60.9 PK	74.0	-13.1	1.30 H	188	61.1	-0.2
6	4844.00	47.3 AV	54.0	-6.7	1.30 H	188	47.5	-0.2
7	7266.00	42.3 PK	74.0	-31.7	1.67 H	186	36.2	6.1
8	7266.00	32.9 AV	54.0	-21.1	1.67 H	186	26.8	6.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 3 : 2422 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.2 PK	74.0	-14.8	2.17 V	202	63.7	-4.5
2	2390.00	48.2 AV	54.0	-5.8	2.17 V	202	52.7	-4.5
3	*2422.00	100.9 PK			2.17 V	202	105.4	-4.5
4	*2422.00	91.3 AV			2.17 V	202	95.8	-4.5
5	4844.00	58.7 PK	74.0	-15.3	1.53 V	168	58.9	-0.2
6	4844.00	45.5 AV	54.0	-8.5	1.53 V	168	45.7	-0.2
7	7266.00	44.9 PK	74.0	-29.1	1.32 V	184	38.8	6.1
8	7266.00	32.0 AV	54.0	-22.0	1.32 V	184	25.9	6.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.2 PK	74.0	-12.8	2.14 H	13	65.7	-4.5
2	2390.00	48.0 AV	54.0	-6.0	2.14 H	13	52.5	-4.5
3	*2437.00	108.5 PK			2.14 H	13	113.0	-4.5
4	*2437.00	99.9 AV			2.14 H	13	104.4	-4.5
5	2483.50	64.7 PK	74.0	-9.3	2.14 H	13	69.2	-4.5
6	2483.50	53.5 AV	54.0	-0.5	2.14 H	13	58.0	-4.5
7	4874.00	60.4 PK	74.0	-13.6	1.31 H	199	60.6	-0.2
8	4874.00	46.8 AV	54.0	-7.2	1.31 H	199	47.0	-0.2
9	7311.00	42.3 PK	74.0	-31.7	1.66 H	173	36.1	6.2
10	7311.00	33.1 AV	54.0	-20.9	1.66 H	173	26.9	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.1 PK	74.0	-17.9	3.66 V	328	60.6	-4.5
2	2390.00	44.1 AV	54.0	-9.9	3.66 V	328	48.6	-4.5
3	*2437.00	98.3 PK			3.66 V	328	102.8	-4.5
4	*2437.00	89.1 AV			3.66 V	328	93.6	-4.5
5	2483.50	56.9 PK	74.0	-17.1	3.66 V	328	61.4	-4.5
6	2483.50	45.3 AV	54.0	-8.7	3.66 V	328	49.8	-4.5
7	4874.00	58.2 PK	74.0	-15.8	1.50 V	152	58.4	-0.2
8	4874.00	45.0 AV	54.0	-9.0	1.50 V	152	45.2	-0.2
9	7311.00	44.9 PK	74.0	-29.1	1.28 V	193	38.7	6.2
10	7311.00	32.1 AV	54.0	-21.9	1.28 V	193	25.9	6.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 9 : 2452 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	105.2 PK			2.17 H	11	109.7	-4.5
2	*2452.00	96.8 AV			2.17 H	11	101.3	-4.5
3	2483.50	65.2 PK	74.0	-8.8	2.17 H	11	69.7	-4.5
4	2483.50	53.9 AV	54.0	-0.1	2.17 H	11	58.4	-4.5
5	4904.00	60.0 PK	74.0	-14.0	1.25 H	202	60.1	-0.1
6	4904.00	46.4 AV	54.0	-7.6	1.25 H	202	46.5	-0.1
7	7356.00	42.7 PK	74.0	-31.3	1.69 H	160	36.4	6.3
8	7356.00	33.3 AV	54.0	-20.7	1.69 H	160	27.0	6.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




RF Mode	TX 802.11n (HT40)	Channel	CH 9 : 2452 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	20 °C, 70 % RH
Tested By	Ryan Du		


Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	98.4 PK			2.13 V	191	102.9	-4.5
2	*2452.00	89.1 AV			2.13 V	191	93.6	-4.5
3	2483.50	59.9 PK	74.0	-14.1	2.13 V	191	64.4	-4.5
4	2483.50	49.0 AV	54.0	-5.0	2.13 V	191	53.5	-4.5
5	4904.00	58.3 PK	74.0	-15.7	1.44 V	147	58.4	-0.1
6	4904.00	45.2 AV	54.0	-8.8	1.44 V	147	45.3	-0.1
7	7356.00	44.9 PK	74.0	-29.1	1.23 V	203	38.6	6.3
8	7356.00	32.1 AV	54.0	-21.9	1.23 V	203	25.8	6.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.




Plot of Band Edge




802.11n (HT20) Channel 2


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11n (HT20) Channel 11


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)



Vertical (Average)



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---