

RF Exposure Report

Project Number: 4887489**Proposal Number:** SUW-202201002180**Report Number:** 4887489EMC04**Revision Level:** 0**Client:** Pison Technology, Inc**Equipment Under Test:** Hand Motion Control Band**Model Name:** Vulcan**Model Number:** VT01**Module Model:** N/A**FCC ID:** 2A4CW-VT01**Applicable Standards:** 47 CFR §§ 2.1093 (Portable)

FCC KDB 447498 D01 General RF Exposure Guidance v06

Report issued on: 29 September 2022**Result:** Exempt from SAR evaluation

FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01

Report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:

A handwritten signature in black ink that reads 'Brandon E. Osborn'.

Brandon Osborn, EMC/RF Project Engineer

Reviewed by:

A handwritten signature in blue ink that reads 'Stephen Whalen'.

Stephen Whalen, SAR/EMC Manager

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	CLIENT INFORMATION	3
1.2	TEST LABORATORY	3
1.3	GENERAL INFORMATION OF EUT	3
1.4	SEPARATION DISTANCE	3
2	SAR EXCLUSION CALCULATIONS	4
3	REVISION HISTORY	5

1 General Information

1.1 Client Information

Name: Pison Technology, Inc
Address: 179 South Street 4th Floor
City, State, Zip, Country: Boston, MA 02111, USA

1.2 Test Laboratory

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01

1.3 General Information of EUT

Type of Product: Hand Motion Control Band
Model Name: Vulcan
Model Number: VT01
Serial Number: 50A1675F
Module Model: N/A

Frequency Ranges: 2402 – 2480 MHz (Bluetooth/BLE)
Antenna Gain: Internal Wire, 2402-2480MHz, 2.0dBi*
Max Conducted Output Power: Bluetooth LE: 4.0dBm

Sample Received Date: 04 March 2022, 27 July 2022 (C011)
Dates of testing: 07-10 March 2022, 22-26 September 2022 (4dBm retest)

**Data was not measured by SGS laboratory and therefore not responsible for accuracy. Data obtained via customer, specification sheet, previous regulatory filing or other.*

1.4 Separation Distance

The closest exposure distance occurs when a user places his or her hand on top of the band directly above the antenna.

2 SAR Exclusion Calculations

The highest output power in conjunction with the Upper and Lower frequency boundaries have been used to demonstrate compliance for both Bluetooth LE transmission mode.

Power levels were referenced from measurements captured in report number 4887489EMC01.

The EUT is considered an extremity application.

External Bluetooth LE (Low Channel)

447498 D01 General RF Exposure Guidance v06

SAR test exclusion calculations

Section 4.3: General SAR test exclusion guidance / Section 4.3.1: Standalone SAR test exclusion considerations

	Input	Select Units	
Max Power:	1.8	dBm	
Duty Cycle:	100.0%		<= Source based time average duty cycle
Min separation distance:	5	mm	
Frequency, f:	2402	MHz	

Value reference Number	Values used for Calculation		Reference number definition
v1	2.000	mW	[max. power of channel, including tune-up tolerance, mW] 'Rounded to nearest mW'
v2	5	mm	[min. test separation distance, mm] 'Rounded to nearest mm'
v3	1.550		[f(GHz)]

a) For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
 $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,

Exclusion Calculation(1g):	0.6199	number	$\leq [v2 / v3] \text{ must be less than } 3$
Exclusion Calculation(10g):	0.6199	number	$\leq [v2 / v3] \text{ must be less than } 7.5$

Conclusions (Body):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Body applications		
Conclusions (Extremity):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Extremity applications		

External Bluetooth LE (High Channel)

447498 D01 General RF Exposure Guidance v06

SAR test exclusion calculations

Section 4.3: General SAR test exclusion guidance / Section 4.3.1: Standalone SAR test exclusion considerations

	Input	Select Units	
Max Power:	1.8	dBm	
Duty Cycle:	100.0%		<= Source based time average duty cycle
Min separation distance:	5	mm	
Frequency, f:	2480	MHz	

Value reference Number	Values used for Calculation		Reference number definition
v1	2.000	mW	[max. power of channel, including tune-up tolerance, mW] 'Rounded to nearest mW'
v2	5	mm	[min. test separation distance, mm] 'Rounded to nearest mm'
v3	1.575		[f(GHz)]

a) For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
 $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,

Exclusion Calculation(1g):	0.6299	number	$\leq [v2 / v3] \text{ must be less than } 3$
Exclusion Calculation(10g):	0.6299	number	$\leq [v2 / v3] \text{ must be less than } 7.5$

Conclusions (Body):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Body applications		
Conclusions (Extremity):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Extremity applications		

3 Revision History

Revision Level	Description of changes	Revision Date
0	Initial Release	29 September 2022