



# FCC RF Test Report

**APPLICANT** : Amazon.com Services LLC  
**EQUIPMENT** : Wireless Tablet  
**MODEL NAME** : R2SP8T  
**FCC ID** : 2A4DH-2576  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure  
**TEST DATE(S)** : Jan. 06, 2022 ~ Feb. 17, 2022

We, Sporton International Inc. (Kunshan) would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan) the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*Alex Wang*

Approved by: Alex Wang / Manager



**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY ..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Product Feature of Equipment Under Test..... 5

    1.3 Product Specification of Equipment Under Test..... 5

    1.4 Modification of EUT ..... 7

    1.5 Testing Location ..... 8

    1.6 Test Software..... 8

    1.7 Applicable Standards..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Carrier Frequency and Channel ..... 9

    2.2 Test Mode ..... 11

    2.3 Connection Diagram of Test System..... 13

    2.4 Support Unit used in test configuration and system ..... 14

    2.5 EUT Operation Test Setup ..... 14

    2.6 Measurement Results Explanation Example..... 14

**3 TEST RESULT ..... 15**

    3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement ..... 15

    3.2 Maximum Conducted Output Power Measurement ..... 17

    3.3 Power Spectral Density Measurement ..... 19

    3.4 Unwanted Emissions Measurement..... 22

    3.5 AC Conducted Emission Measurement..... 27

    3.6 Antenna Requirements..... 29

**4 LIST OF MEASURING EQUIPMENT ..... 30**

**5 UNCERTAINTY OF EVALUATION ..... 31**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS**

**APPENDIX E. DUTY CYCLE PLOTS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1 ~ U-NII-2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.22 dB at 5150.000 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 15.06 dB at 0.150 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	N/A	N/A	Pass	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Amazon.com Services LLC  
410 Terry Avenue N, Seattle, WA 98109-5210, United States

## 1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Tablet
Model Name	R2SP8T
FCC ID	2A4DH-2576

## 1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz



<p><b>Maximum Output Power to Antenna</b></p>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 13.88 dBm / 0.0244 W  802.11n HT20 : 13.75 dBm / 0.0237 W  802.11n HT40 : 13.77 dBm / 0.0238 W  802.11ac VHT20: 13.76 dBm / 0.0238 W  802.11ac VHT40: 13.79 dBm / 0.0239 W  802.11ac VHT80: 10.36 dBm / 0.0109 W  <b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 13.90 dBm / 0.0245 W  802.11n HT20 : 13.73 dBm / 0.0236 W  802.11n HT40 : 13.79 dBm / 0.0239 W  802.11ac VHT20: 13.74 dBm / 0.0237 W  802.11ac VHT40: 13.80 dBm / 0.0240 W  802.11ac VHT80: 9.41 dBm / 0.0087 W  <b>&lt;5500 MHz ~ 5720 MHz &gt;</b>  802.11a : 14.02 dBm / 0.0252 W  802.11n HT20 : 13.78 dBm / 0.0239 W  802.11n HT40 : 13.90 dBm / 0.0245 W  802.11ac VHT20: 13.79 dBm / 0.0239 W  802.11ac VHT40: 13.92 dBm / 0.0247 W  802.11ac VHT80: 13.68 dBm / 0.0233 W  <b>&lt;5745 MHz ~ 5825 MHz&gt;</b>  802.11a : 14.01 dBm / 0.0252 W  802.11n HT20 : 13.83 dBm / 0.0242 W  802.11n HT40 : 13.89 dBm / 0.0245 W  802.11ac VHT20: 13.88 dBm / 0.0244 W  802.11ac VHT40: 13.93 dBm / 0.0247 W  802.11ac VHT80: 13.72 dBm / 0.0236 W</p>
<p><b>99% Occupied Bandwidth</b></p>	<p><b>&lt; Ant 1&gt;:</b>  <b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 17.183 MHz  802.11ac VHT20 : 18.022 MHz  802.11ac VHT40 : 36.364 MHz  802.11ac VHT80 : 75.445 MHz  <b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 17.183 MHz  802.11ac VHT20 : 18.062 MHz  802.11ac VHT40 : 36.444 MHz  802.11ac VHT80 : 75.604 MHz  <b>&lt;5500 MHz ~ 5720 MHz&gt;</b>  802.11a : 17.183 MHz  802.11ac VHT20 : 18.062 MHz  802.11ac VHT40 : 36.364 MHz  802.11ac VHT80 : 75.445 MHz  <b>&lt;5745 MHz ~ 5825 MHz&gt;</b>  802.11a : 17.183 MHz  802.11ac VHT20 : 18.022 MHz  802.11ac VHT40 : 36.444 MHz  802.11ac VHT80 : 75.285 MHz  <b>&lt; Ant 2&gt;:</b>  <b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 17.143 MHz  802.11ac VHT20 : 18.062 MHz  802.11ac VHT40 : 36.444 MHz</p>



	802.11ac VHT80 : 75.604 MHz <b>&lt;5260 MHz ~ 5320 MHz&gt;</b> 802.11a : 17.143 MHz 802.11ac VHT20 : 18.062 MHz 802.11ac VHT40 : 36.444 MHz 802.11ac VHT80 : 75.285 MHz <b>&lt;5500 MHz ~ 5720 MHz&gt;</b> 802.11a : 17.183 MHz 802.11ac VHT20 : 18.062 MHz 802.11ac VHT40 : 36.444 MHz 802.11ac VHT80 : 75.764 MHz <b>&lt;5745 MHz ~ 5825 MHz&gt;</b> 802.11a : 17.183 MHz 802.11ac VHT20 : 18.062 MHz 802.11ac VHT40 : 36.364 MHz 802.11ac VHT80 : 75.285 MHz
<b>Antenna Type / Gain</b>	<b>&lt;5180 MHz ~ 5240 MHz&gt;</b> <Ant. 1> : IFA Antenna with gain 0.60dBi <Ant. 2> : Monopole Antenna with gain 0.80dBi <b>&lt;5260 MHz ~ 5320 MHz&gt;</b> <Ant. 1> : IFA Antenna with gain 1.00dBi <Ant. 2> : Monopole Antenna with gain 0.90dBi <b>&lt;5500 MHz ~ 5720 MHz&gt;</b> <Ant. 1> : IFA Antenna with gain 0.90dBi <Ant. 2> : Monopole Antenna with gain 0.90dBi <b>&lt;5745 MHz ~ 5825 MHz&gt;</b> <Ant. 1> : IFA Antenna with gain 1.00dBi <Ant. 2> : Monopole Antenna with gain 0.90dBi
<b>Type of Modulation</b>	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac/ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

**Note:**

1. For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their higher conducted power.
2. The device only support SISO mode for WLAN 5GHz.

### 1.4 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.5 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

### 1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	Rohde&Schwarz	EMC32	10.60.0.0

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 <sup>#</sup>	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 <sup>#</sup>	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 <sup>#</sup>	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 <sup>#</sup>	5775	165	5825



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 <sup>#</sup>	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 <sup>#</sup>	5690	144	5720
	142*	5710		

Note:

1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "<sup>#</sup>" were 802.11ac VHT80.



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

Simultaneous transmission
BLE CH39(2480MHz)+ 802.11ac VHT80 CH42(5210MHz)

Remark: For Radiated Test Cases, The tests were performed with Adapter, Earphone and USB Cable 1

<b>AC Conducted Emission</b>	Mode 1 : Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter1)
--------------------------------------	---

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11a	802.11a	802.11a	802.11a
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11ac VHT20	802.11ac VHT20	802.11ac VHT20	802.11ac VHT20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11ac VHT40	802.11ac VHT40	802.11ac VHT40	802.11ac VHT40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	122	-
Straddle		-	-	138	-

## 2.3 Connection Diagram of Test System

For Conducted Emission:



For Radiated Emission:





### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
4.	Earphone	Lenovo	P121	N/A	N/A	Unshielded,1.2m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

### 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

### 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$Offset = RF\ cable\ loss + attenuator\ factor.$$

Following shows an offset computation example with cable loss 6.75 dB and 10dB attenuator.

$$Offset(dB) = RF\ cable\ loss(dB) + attenuator\ factor(dB).$$

$$= 6.75 + 10 = 16.75\ (dB)$$



### 3 Test Result

#### 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

##### 3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW)
	<ol style="list-style-type: none"> <li>Set RBW = approximately 1% of the emission bandwidth.</li> <li>Set the VBW &gt; RBW.</li> <li>Detector = Peak.</li> <li>Trace mode = max hold</li> <li>Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.</li> <li>For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) <math>\geq 3 * RBW</math>.</li> <li>Measure and record the results in the test report.</li> </ol>
<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	<ol style="list-style-type: none"> <li>Set RBW = 100kHz.</li> <li>Set the VBW <math>\geq 3 * RBW</math>.</li> <li>Detector = Peak.</li> <li>Trace mode = max hold</li> <li>Measure the maximum width of the emission that is 6 dB down from the peak of the emission.</li> <li>Measure and record the results in the test report.</li> </ol>

### 3.1.4 Test Setup



### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where x is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section F) Maximum power spectral density.

#### **For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz**

##### **# Method SA-2 #**

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW  $\geq$  3 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add  $10 \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

#### **For devices operating in the band 5.725 - 5.85 GHz**


##### **# Method SA-2 #**

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW  $\geq$  1 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add  $10 \log(500\text{kHz}/\text{RBW})$  to the test result.
- Add  $10 \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



### 3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of  $-27\text{dBm/MHz}$ .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of  $-27\text{ dBm/MHz}$ . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of  $-27\text{ dBm/MHz}$  in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of  $-27\text{ dBm/MHz}$ .

- (2) For transmitters operating in the 5.725-5.85 GHz band:  
15.407(b)(4)(i) All emissions shall be limited to a level of  $-27\text{ dBm/MHz}$  at 75 MHz or more above or below the band edge increasing linearly to  $10\text{ dBm/MHz}$  at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of  $15.6\text{ dBm/MHz}$  at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of  $27\text{ dBm/MHz}$  at the band edge.



(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) -104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E<sub>Meas</sub> is the field strength of the emission at the measurement distance, in dBµV/m

d<sub>Meas</sub> is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### 3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.
  - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
    - RBW = 120 kHz
    - VBW = 300 kHz
    - Detector = Peak
    - Trace mode = max hold
  - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW  $\geq$  3 MHz
    - Detector = Peak
    - Sweep time = auto
    - Trace mode = max hold
  - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
    - RBW = 1 MHz
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be




measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### 3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C&D.

### 3.4.7 Duty Cycle

Please refer to Appendix E.

### 3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C&D.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.5.4 Test Setup



### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.6 Antenna Requirements**

### **3.6.1 Standard Applicable**

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.6.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.6.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 14, 2021	Feb. 11, 2022~ Feb. 17, 2022	Oct. 13, 2022	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2022	Feb. 11, 2022~ Feb. 17, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2022	Feb. 11, 2022~ Feb. 17, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 12, 2021	Feb. 11, 2022~ Feb. 17, 2022	Jul. 11, 2022	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 16, 2021	Jan. 06, 2022	Oct. 15, 2022	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz	Apr. 12, 2021	Jan. 06, 2022	Apr. 11, 2022	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Jan. 06, 2022	Oct. 29, 2022	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	May 27, 2021	Jan. 06, 2022	May 26, 2022	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 25, 2021	Jan. 06, 2022	Apr. 24, 2022	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2022	Jan. 06, 2022	Jan. 04, 2023	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Apr. 12, 2021	Jan. 06, 2022	Apr. 11, 2022	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2022	Jan. 06, 2022	Jan. 04, 2023	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	1Ghz-18Ghz	Jul. 30, 2021	Jan. 06, 2022	Jul. 29, 2022	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 13, 2021	Jan. 06, 2022	Apr. 12, 2022	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 06, 2022	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 06, 2022	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 06, 2022	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 21, 2021	Feb. 14, 2022	Apr. 20, 2022	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 14, 2021	Feb. 14, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Oct. 14, 2021	Feb. 14, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 14, 2021	Feb. 14, 2022	Oct. 13, 2022	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------



## **Appendix A. Conducted Test Results**



## A1. Conducted Test Results

Test Engineer:	Jiang Jun	Temperature:	21~25	°C
Test Date:	2022.2.11~2022.2.17	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**Average Power Table**

FCC U-NII-1 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	36	5180	13.22	13.81		24.00	24.00	0.60	0.80	Pass
11a	6Mbps	1	44	5220	13.32	13.72		24.00	24.00	0.60	0.80	Pass
11a	6Mbps	1	48	5240	13.39	13.88		24.00	24.00	0.60	0.80	Pass
HT20	MCS0	1	36	5180	13.39	13.70		24.00	24.00	0.60	0.80	Pass
HT20	MCS0	1	44	5220	13.22	13.75		24.00	24.00	0.60	0.80	Pass
HT20	MCS0	1	48	5240	13.29	13.67		24.00	24.00	0.60	0.80	Pass
HT40	MCS0	1	38	5190	11.00	12.63		24.00	24.00	0.60	0.80	Pass
HT40	MCS0	1	46	5230	13.34	13.77		24.00	24.00	0.60	0.80	Pass
VHT20	MCS0	1	36	5180	13.40	13.71		24.00	24.00	0.60	0.80	Pass
VHT20	MCS0	1	44	5220	13.23	13.76		24.00	24.00	0.60	0.80	Pass
VHT20	MCS0	1	48	5240	13.33	13.69		24.00	24.00	0.60	0.80	Pass
VHT40	MCS0	1	38	5190	11.04	12.65		24.00	24.00	0.60	0.80	Pass
VHT40	MCS0	1	46	5230	13.36	13.79		24.00	24.00	0.60	0.80	Pass
VHT80	MCS0	1	42	5210	7.93	10.36		24.00	24.00	0.60	0.80	Pass

**TEST RESULTS DATA**  
**Average Power Table**

FCC U-NII-2A single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	52	5260	13.41	13.90		23.94	23.97	1.00	0.90	26.99	Pass
11a	6Mbps	1	60	5300	13.49	13.82		23.96	23.98	1.00	0.90	26.99	Pass
11a	6Mbps	1	64	5320	13.48	13.81		23.96	23.93	1.00	0.90	26.99	Pass
HT20	MCS0	1	52	5260	13.26	13.72		23.98	23.98	1.00	0.90	26.99	Pass
HT20	MCS0	1	60	5300	13.26	13.73		23.98	23.98	1.00	0.90	26.99	Pass
HT20	MCS0	1	64	5320	13.22	13.60		23.98	23.98	1.00	0.90	26.99	Pass
HT40	MCS0	1	54	5270	13.50	13.79		23.98	23.98	1.00	0.90	26.99	Pass
HT40	MCS0	1	62	5310	11.10	11.98		23.98	23.98	1.00	0.90	26.99	Pass
VHT20	MCS0	1	52	5260	13.27	13.73		23.98	23.98	1.00	0.90	26.99	Pass
VHT20	MCS0	1	60	5300	13.35	13.74		23.98	23.98	1.00	0.90	26.99	Pass
VHT20	MCS0	1	64	5320	13.23	13.65		23.98	23.98	1.00	0.90	26.99	Pass
VHT40	MCS0	1	54	5270	13.53	13.80		23.98	23.98	1.00	0.90	26.99	Pass
VHT40	MCS0	1	62	5310	11.13	12.00		23.98	23.98	1.00	0.90	26.99	Pass
VHT80	MCS0	1	58	5290	8.36	9.41		23.98	23.98	1.00	0.90	26.99	Pass

**TEST RESULTS DATA**  
**Average Power Table**

FCC U-NII-2C single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	100	5500	13.16	13.66		23.96	23.94	0.90	0.90	26.99	Pass
11a	6Mbps	1	116	5580	13.29	13.82		23.94	23.93	0.90	0.90	26.99	Pass
11a	6Mbps	1	140	5700	13.75	14.02		23.94	23.94	0.90	0.90	26.99	Pass
HT20	MCS0	1	100	5500	13.03	13.57		23.98	23.98	0.90	0.90	26.99	Pass
HT20	MCS0	1	116	5580	13.14	13.69		23.98	23.98	0.90	0.90	26.99	Pass
HT20	MCS0	1	140	5700	12.45	12.82		23.98	23.98	0.90	0.90	26.99	Pass
HT40	MCS0	1	102	5510	11.64	11.37		23.98	23.98	0.90	0.90	26.99	Pass
HT40	MCS0	1	110	5550	13.16	13.58		23.98	23.98	0.90	0.90	26.99	Pass
HT40	MCS0	1	134	5670	12.57	13.73		23.98	23.98	0.90	0.90	26.99	Pass
VHT20	MCS0	1	100	5500	13.05	13.59		23.98	23.98	0.90	0.90	26.99	Pass
VHT20	MCS0	1	116	5580	13.15	13.70		23.98	23.98	0.90	0.90	26.99	Pass
VHT20	MCS0	1	140	5700	12.47	12.87		23.98	23.98	0.90	0.90	26.99	Pass
VHT40	MCS0	1	102	5510	11.65	11.39		23.98	23.98	0.90	0.90	26.99	Pass
VHT40	MCS0	1	110	5550	13.19	13.59		23.98	23.98	0.90	0.90	26.99	Pass
VHT40	MCS0	1	134	5670	12.63	13.79		23.98	23.98	0.90	0.90	26.99	Pass
VHT80	MCS0	1	106	5530	9.59	12.26		23.98	23.98	0.90	0.90	26.99	Pass
VHT80	MCS0	1	122	5610	13.22	13.50		23.98	23.98	0.90	0.90	26.99	Pass

FCC U-NII-2C straddle channel single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	144	5720	13.71	13.94		23.96	23.93	0.90	0.90	26.99	Pass
HT20	MCS0	1	144	5720	13.47	13.78		23.98	23.98	0.90	0.90	26.99	Pass
HT40	MCS0	1	142	5710	13.57	13.90		23.98	23.98	0.90	0.90	26.99	Pass
VHT20	MCS0	1	144	5720	13.49	13.79		23.98	23.98	0.90	0.90	26.99	Pass
VHT40	MCS0	1	142	5710	13.59	13.92		23.98	23.98	0.90	0.90	26.99	Pass
VHT80	MCS0	1	138	5690	13.37	13.68		23.98	23.98	0.90	0.90	26.99	Pass

## A1. Conducted Test Results

Test Engineer:	Jiang Jun	Temperature:	21~25	°C
Test Date:	2022.2.11~2022.2.17	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**Average Power Table**

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	13.79	13.90		30.00	30.00	1.00	0.90	Pass
11a	6Mbps	1	157	5785	13.74	14.01		30.00	30.00	1.00	0.90	Pass
11a	6Mbps	1	165	5825	13.72	13.92		30.00	30.00	1.00	0.90	Pass
HT20	MCS0	1	149	5745	13.49	13.81		30.00	30.00	1.00	0.90	Pass
HT20	MCS0	1	157	5785	13.52	13.83		30.00	30.00	1.00	0.90	Pass
HT20	MCS0	1	165	5825	13.53	13.80		30.00	30.00	1.00	0.90	Pass
HT40	MCS0	1	151	5755	13.58	13.86		30.00	30.00	1.00	0.90	Pass
HT40	MCS0	1	159	5795	13.55	13.89		30.00	30.00	1.00	0.90	Pass
VHT20	MCS0	1	149	5745	13.52	13.86		30.00	30.00	1.00	0.90	Pass
VHT20	MCS0	1	157	5785	13.55	13.85		30.00	30.00	1.00	0.90	Pass
VHT20	MCS0	1	165	5825	13.57	13.88		30.00	30.00	1.00	0.90	Pass
VHT40	MCS0	1	151	5755	13.60	13.91		30.00	30.00	1.00	0.90	Pass
VHT40	MCS0	1	159	5795	13.56	13.93		30.00	30.00	1.00	0.90	Pass
VHT80	MCS0	1	155	5775	13.40	13.72		30.00	30.00	1.00	0.90	Pass



<b>Ambient Condition:</b> <u>25</u> °C, <u>45</u> %RH,
<b>Test Date:</b> <u>2022.2.11~2022.2.17</u> <b>Test Engineer:</b> <u>Jiang Jun</u>

### Emission Bandwidth

#### Test Result

TestMode	Antenna	Frequency [MHz]	26db EBW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11A	Ant1	5180	19.60	5170.20	5189.80	---	---
	Ant2	5180	19.72	5170.24	5189.96	---	---
	Ant1	5220	19.80	5210.12	5229.92	---	---
	Ant2	5220	19.72	5210.12	5229.84	---	---
	Ant1	5240	19.68	5230.08	5249.76	---	---
	Ant2	5240	19.64	5230.20	5249.84	---	---
	Ant1	5260	19.68	5250.20	5269.88	---	---
	Ant2	5260	19.80	5250.04	5269.84	---	---
	Ant1	5300	19.76	5290.16	5309.92	---	---
	Ant2	5300	19.88	5290.04	5309.92	---	---
	Ant1	5320	19.76	5310.08	5329.84	---	---
	Ant2	5320	19.64	5310.20	5329.84	---	---
	Ant1	5500	19.76	5490.16	5509.92	---	---
	Ant2	5500	19.68	5490.12	5509.80	---	---
	Ant1	5580	19.68	5570.16	5589.84	---	---
	Ant2	5580	19.64	5570.20	5589.84	---	---
	Ant1	5700	19.68	5690.16	5709.84	---	---
	Ant2	5700	19.68	5690.24	5709.92	---	---
	Ant1	5720	19.76	5710.20	5729.96	---	---
	Ant2	5720	19.64	5710.16	5729.80	---	---
	Ant1	5720_UNII-2C	14.8	5710.20	5725	---	---
	Ant2	5720_UNII-2C	14.84	5710.16	5725	---	---
	Ant1	5720_UNII-3	4.96	5725	5729.96	---	---
	Ant2	5720_UNII-3	4.8	5725	5729.80	---	---
	Ant1	5745	19.72	5735.24	5754.96	---	---
	Ant2	5745	19.72	5735.12	5754.84	---	---
	Ant1	5785	19.92	5775.04	5794.96	---	---
	Ant2	5785	19.84	5775.12	5794.96	---	---
	Ant1	5825	19.68	5815.08	5834.76	---	---
	Ant2	5825	19.68	5815.16	5834.84	---	---



TestMode	Antenna	Frequency [MHz]	26db EBW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11AC20SISO	Ant1	5180	20.12	5170.00	5190.12	---	---
	Ant2	5180	20.00	5170.00	5190.00	---	---
	Ant1	5220	20.04	5209.88	5229.92	---	---
	Ant2	5220	20.00	5209.96	5229.96	---	---
	Ant1	5240	20.12	5230.04	5250.16	---	---
	Ant2	5240	19.96	5230.08	5250.04	---	---
	Ant1	5260	20.04	5250.00	5270.04	---	---
	Ant2	5260	19.96	5250.08	5270.04	---	---
	Ant1	5300	20.04	5290.04	5310.08	---	---
	Ant2	5300	20.16	5289.96	5310.12	---	---
	Ant1	5320	19.84	5310.08	5329.92	---	---
	Ant2	5320	20.04	5310.00	5330.04	---	---
	Ant1	5500	19.96	5490.08	5510.04	---	---
	Ant2	5500	20.00	5489.96	5509.96	---	---
	Ant1	5580	19.96	5570.00	5589.96	---	---
	Ant2	5580	20.16	5569.92	5590.08	---	---
	Ant1	5700	19.96	5690.12	5710.08	---	---
	Ant2	5700	20.16	5689.92	5710.08	---	---
	Ant1	5720	20.08	5709.96	5730.04	---	---
	Ant2	5720	20.20	5709.88	5730.08	---	---
	Ant1	5720_UNII-2C	15.04	5709.96	5725	---	---
	Ant2	5720_UNII-2C	15.12	5709.88	5725	---	---
	Ant1	5720_UNII-3	5.04	5725	5730.04	---	---
	Ant2	5720_UNII-3	5.08	5725	5730.08	---	---
	Ant1	5745	20.00	5735.00	5755.00	---	---
	Ant2	5745	20.04	5735.04	5755.08	---	---
	Ant1	5785	20.00	5775.00	5795.00	---	---
	Ant2	5785	19.88	5775.00	5794.88	---	---
	Ant1	5825	20.16	5814.92	5835.08	---	---
	Ant2	5825	20.20	5814.88	5835.08	---	---





TestMode	Antenna	Frequency [MHz]	26db EBW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11AC40SISO	Ant1	5190	40.96	5169.60	5210.56	---	---
	Ant2	5190	40.88	5169.68	5210.56	---	---
	Ant1	5230	40.80	5209.68	5250.48	---	---
	Ant2	5230	41.28	5209.44	5250.72	---	---
	Ant1	5270	40.80	5249.60	5290.40	---	---
	Ant2	5270	41.20	5249.36	5290.56	---	---
	Ant1	5310	40.88	5289.60	5330.48	---	---
	Ant2	5310	41.60	5289.20	5330.80	---	---
	Ant1	5510	40.96	5489.52	5530.48	---	---
	Ant2	5510	40.80	5489.76	5530.56	---	---
	Ant1	5550	40.80	5529.60	5570.40	---	---
	Ant2	5550	40.72	5529.68	5570.40	---	---
	Ant1	5670	40.96	5649.60	5690.56	---	---
	Ant2	5670	40.72	5649.68	5690.40	---	---
	Ant1	5710	41.04	5689.52	5730.56	---	---
	Ant2	5710	41.04	5689.52	5730.56	---	---
	Ant1	5710_UNII-2C	35.48	5689.52	5725	---	---
	Ant2	5710_UNII-2C	35.48	5689.52	5725	---	---
	Ant1	5710_UNII-3	5.56	5725	5730.56	---	---
	Ant2	5710_UNII-3	5.56	5725	5730.56	---	---
	Ant1	5755	40.88	5734.60	5775.48	---	---
	Ant2	5755	40.80	5734.52	5775.32	---	---
	Ant1	5795	41.04	5774.36	5815.40	---	---
	Ant2	5795	40.80	5774.52	5815.32	---	---
11AC80SISO	Ant1	5210	81.12	5169.52	5250.64	---	---
	Ant2	5210	80.96	5169.68	5250.64	---	---
	Ant1	5290	81.60	5249.20	5330.80	---	---
	Ant2	5290	81.28	5249.36	5330.64	---	---
	Ant1	5530	81.44	5489.36	5570.80	---	---
	Ant2	5530	81.12	5489.52	5570.64	---	---
	Ant1	5610	81.12	5569.68	5650.80	---	---
	Ant2	5610	81.12	5569.52	5650.64	---	---
	Ant1	5690	81.28	5649.52	5730.80	---	---
	Ant2	5690	81.12	5649.52	5730.64	---	---
	Ant1	5690_UNII-2C	75.48	5649.52	5725	---	---
	Ant2	5690_UNII-2C	75.48	5649.52	5725	---	---
	Ant1	5690_UNII-3	5.8	5725	5730.80	---	---
	Ant2	5690_UNII-3	5.64	5725	5730.64	---	---
	Ant1	5775	81.12	5734.52	5815.64	---	---
	Ant2	5775	81.12	5734.52	5815.64	---	---



Test Graphs

