





# TEST REPORT

FCC ID.....	2A4DZ-X228394	
Test Report No.....	TCT220222E007	
Date of issue.....	Mar. 29, 2022	
Testing laboratory .....	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name.....	MITA EXPEDITIONS LLC	
Address.....	3821 Bedford Avenue, Brooklyn, New York, 11229, United States	
Manufacturer's name ...	MITA EXPEDITIONS LLC	
Address.....	3821 Bedford Avenue, Brooklyn, New York, 11229, United States	
Standard(s) .....	FCC CFR Title 47 Part 1.1310 KDB 680106 D01 RF Exposure Wireless Charging App v03r01	
Product Name.....	Super Charging Station	
Trade Mark .....	TECHSMARTER	
Model/Type reference.....	X2	
Rating(s) .....	Adapter Information: Model: X-12PD Input: AC 100-240V, 50/60Hz, 1.5A USB-C1 Output: DC 5V, 3A/DC 9V, 3A/DC 12V, 3A/DC 15V, 3A/DC 20V, 5A (100W MAX) Total Output: 100W(max)	
Date of receipt of test item .....	Feb. 22, 2022	
Date (s) of performance of test.....	Feb. 22, 2022 ~ Mar. 29, 2022	
Tested by (+signature) ...	Aaron MO	
Check by (+signature)....	Beryl ZHAO	
Approved by (+signature):	Tomsin	



**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

<b>1. General Product Information .....</b>	<b>3</b>
1.1. EUT description .....	3
1.2. Model(s) list.....	3
<b>2. Facilities and Accreditations .....</b>	<b>4</b>
2.1. Facilities .....	4
2.2. Location .....	4
<b>3. Test Results and Measurement Data .....</b>	<b>5</b>
3.1. Requirements.....	5
3.2. Test Setup .....	6
3.3. Test Procedure .....	6
3.4. Test Equipment List .....	6
3.5. Test Result .....	6
3.6. Test Set-up Photo.....	12

## 1. General Product Information

### 1.1. EUT description

Product Name.....:	Super Charging Station
Model/Type reference.....:	X2
Sample Number.....:	TCT220222E006-0101
Operation Frequency .....	127.77kHz, 135.72kHz, 326.54kHz
Modulation Type.....:	Load modulation
Antenna Type.....:	Inductive loop coil Antenna
Rating(s) .....	Adapter Information: Model: X-12PD Input: AC 100-240V, 50/60Hz, 1.5A USB-C1 Output: DC 5V, 3A/DC 9V, 3A/DC 12V, 3A/DC 15V, 3A/ DC 20V, 5A (100W MAX) Total Output: 100W(max)

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

None.

## 2. Facilities and Accreditations

### 2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098  
SHENZHEN TONGCE TESTING LAB  
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1  
SHENZHEN TONGCE TESTING LAB  
CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

### 2.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

### 3. Test Results and Measurement Data

#### 3.1. Requirements

According to the item 5.b of KDB 680106 D01v03:

Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.


- (1) Power transfer frequency is less than 1 MHz.
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz  
 \*=Plane-wave equivalent power density  
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

### 3.2. Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 15cm measured from the center of the probe(s) to the edge of the device.

### 3.3. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at 15 cm surrounding the device and 20 cm above the top surface of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v03. Remark;  
The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

### 3.4. Test Equipment List

Equipment	Manufacturer	Model No.	Calibration Due
Magnetic field meter	NARDA	ELT-400	Feb. 24, 2023
Mobile Phone	SM-G9350	R28HA2ER3GT	/

### 3.5. Test Result

**E-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (V/m)**

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (V/m)	Limits Test (V/m)
127.77	Full load	1.37	1.16	1.77	1.35	1.48	307	614
127.77	Half load	1.05	1.75	1.41	1.21	1.53	307	614
127.77	No load	1.31	1.71	1.16	1.65	1.37	307	614
135.72	Full load	1.30	1.12	1.82	1.44	1.52	307	614
135.72	Half load	1.14	1.67	1.39	1.27	1.73	307	614
135.72	No load	1.26	1.59	1.24	1.58	1.45	307	614
326.54	Full load	1.38	1.25	1.62	1.45	1.32	307	614
326.54	Half load	1.24	1.81	1.38	1.52	1.65	307	614
326.54	No load	1.35	1.83	1.19	1.66	1.47	307	614

**H-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (A/m)**

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (A/m)	Limits Test ((A/m)
127.77	Full load	0.218	0.190	0.205	0.222	0.194	0.815	1.63
127.77	Half load	0.191	0.184	0.200	0.199	0.181	0.815	1.63
127.77	No load	0.195	0.181	0.186	0.182	0.178	0.815	1.63
135.72	Full load	0.212	0.192	0.207	0.221	0.195	0.815	1.63
135.72	Half load	0.195	0.186	0.201	0.190	0.186	0.815	1.63
135.72	No load	0.190	0.184	0.182	0.187	0.177	0.815	1.63
326.54	Full load	0.205	0.191	0.209	0.223	0.195	0.815	1.63
326.54	Half load	0.187	0.182	0.201	0.195	0.181	0.815	1.63
326.54	No load	0.196	0.189	0.182	0.181	0.177	0.815	1.63

Note:1.  $uT=1.25*(A/m)$ ,  $1mT=1000000Ut$



**E-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (V/m)**

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (V/m)	Limits Test (V/m)
127.77 135.72 326.54	Full load	1.63	1.57	1.82	1.62	1.76	307	614
	Half load	1.45	1.92	1.53	1.72	1.86	307	614
	No load	1.69	1.99	1.41	1.80	1.71	307	614



**H-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (A/m)**

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (A/m)	Limits Test ((A/m)
127.77 135.72 326.54	Full load	0.275	0.202	0.219	0.231	0.207	0.815	1.63
	Half load	0.198	0.163	0.220	0.212	0.198	0.815	1.63
	No load	0.197	0.197	0.207	0.197	0.188	0.815	1.63

Note:1.  $uT=1.25*(A/m)$ ,  $1mT=1000000Ut$

According to KDB 680106 D01 v03 section 5, b, satisfy the following conditions.

Requirement of KDB 680106 D01	Yes/No	Description
Power transfer frequency is less than 1MHz	Yes	The device operate in the frequency range 127.77kHz, 135.72kHz, 326.54kHz
Output power from each primary coil is less than or equal to 15 watts	Yes	The maximum output power of the primary coil is 15W. The maximum output power of mobile phone is 15W, that of Bluetooth headset is 5W and that of watch is 5W.
The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes	The transfer system includes single coil that is able to detect receiver device.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only(portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

### 3.6. Test Set-up Photo


Front




Back




Left



Right



TOP



**\*\*\*\*\*END OF REPORT\*\*\*\*\***