



RF Exposure Evaluation Declaration

Report No.: S20230809559508-G1

Issue Date: 01-02-2024

Applicant: IGEN TECH CO.,Ltd.
Address: Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China
FCC ID: 2A4FR-MW-4E
Product: WiFi Module
Model No.: MW-4E
Trade Mark: /
FCC Rule Part(s): CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.
Item Receipt date: Aug. 24, 2023
Test Date: Sep. 13~ Sep. 17, 2023

Compiled By Guangze Ding
(Guangze Ding)
Senior Test Engineer
Approved By Line Chen
(Line Chen)
Engineer Manager



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Revision History

Report No.	Version	Description	Issue Date
S20230809559508	Rev. 01	/	10-07-2023
S20230809559508-G1	Rev. 02	1. This report shall be replaced by report S20230809559508, which shall be invalid immediately upon the issuance of this report. 2. The initial issuance date of report S20230809559508 was Oct 07, 2023, and the first amendment to the report was made on Dec 29, 2023, change the address to Block F4, No. 200, Linghu Avenue, Wuxi, Jiangsu, P. R. China on page 1.	01-02-2024

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	WiFi Module
Model Name:	MW-4E
Trade Mark:	/
Input Voltage Range:	DC 5V
Wi-Fi Specification:	802.11b/g/n20
Bluetooth Version:	5.0

1.2. Product Specification Subjective to this Report

Frequency Range:	WIFI:802.11b/g/n20: 2412 ~ 2462MHz BLE:2402~2480MHz
Channel Number:	802.11b/g/n20: 11 BLE:40
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM BLE:GFSK
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n/: MCS0~MCS7 BLE:1Mbps
Antenna Type:	Rod antenna
Antenna Gain:	3.16 dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	WiFi Module
Test Item	RF Exposure Evaluation

Mode	Frequency (MHz)	Maximum Conducted OutputPower (dBm)	Antenna Gain (dBi)	PG		MPE (mW/cm ²)	MPE Limits (mW/cm ²)
				(dBm)	(mW)		
WIFI	2412~2462	16.46	3.16	19.62	91.6	0.06	1.00
BLE	2402~2480	9.86	3.16	13.02	20.0	0.01	1.00

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

Remark: 2. Use the maximum gain of all bands when evaluating

Remark: 3. BT and 5G wifi can't transmit simultaneously.

CONCLUSION:

The Max Power Density at R (20 cm) = $0.06\text{mW/cm}^2 < 1\text{mW/cm}^2$.

So the EUT complies with the requirement.

_____ The End _____