

TEST REPORT

Product Name : mutalk 2 dedicated communication dongle
Model Number : SVP-D2U1B
FCC ID : 2A4GC-SVPD2U1

Prepared for : Shiftall Inc.
Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo,
Tokyo, Japan(settled in Shenzhen Qianhai Business
Secretary Co., Ltd.)

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F.,Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2403080023E00202R
Date(s) of Tests : March 08, 2024 to April 02, 2024
Date of issue : April 02, 2024

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	6



1. TEST RESULT CERTIFICATION

Applicant : Shiftall Inc.
 Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo, Tokyo, Japan
 Manufacturer : Shiftall Inc.
 Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo, Tokyo, Japan
 Factory : Sunitec Electronic Technology Limited
 Address : 1F-4F Building WeiXiangTai Industrial Zone, NO.725, DaSan village, XingFu Community, FuCheng street, LongHua District, ShenZhen, GuangDong province, China
 EUT : mutalk 2 dedicated communication dongle
 Model Name : SVP-D2U1B
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : March 08, 2024 to April 02, 2024

Warren Deng

Prepared by : Warren Deng /Editor

Tim Dong

Reviewer : Tim Dong /Supervisor


Sam Lv

Approve & Authorized Signer : Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2403080023E00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	mutalk 2 dedicated communication dongle
Model Number:	SVP-D2U1B
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for GFSK modulation
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz for 1Mbps; 2404-2478MHz for 2Mbps;
Number of Channels:	40 channels for BLE
Transmit Power Max:	-5.01 dBm(0.000316 W) for BLE
Antenna Gain:	0.77 dBi
Power supply:	DC 5V from USB
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain:0.77 dBi

Mode	Transmit Frequency(MHz)	Mode	Measured Power (dBm)	E.I.R.P(dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
1M	2402	GFSK	-5.67	-4.90	-5±1	-4	0.1234004	3
	2441	GFSK	-6.31	-5.54	-6±1	-5	0.0988130	3
	2480	GFSK	-5.02	-4.25	-5±1	-4	0.1253880	3
2M	2404	GFSK	-5.78	-5.01	-6±1	-5	0.0980204	3
	2441	GFSK	-6.31	-5.54	-6±1	-5	0.0988130	3
	2478	GFSK	-5.01	-4.24	-5±1	-4	0.1253880	3

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***