

TEST REPORT

Product Name : HaritoraX Wireless
Model Number : SVP-MC3S
FCC ID : 2A4GC-SVPMC3S

Prepared for : Shiftall Inc.
Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo,
Tokyo, Japan

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2308010104E00403R
Date(s) of Tests : June 28, 2023 to August 08, 2023
Date of issue : August 08, 2023

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Shiftall Inc.
 Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo, Tokyo, Japan
 Manufacturer : Shiftall Inc.
 Address : 4F TokyoDaiwa Bldg., 2-6-10 Nihonbashibakurocho, Chuo, Tokyo, Japan
 Factory : P. IMES Corporation
 Address : Block 16 Phase IV, Cavite Economic Zone, Rosario, Cavite PHILIPPINES
 EUT : HaritoraX Wireless
 Model Name : SVP-MC3S
 Trademark : HaritoraX Wireless


Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 15.249, § 2.1093	PASS


The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules § 15.247(i), § 15.249, § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : June 28, 2023 to August 08, 2023

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approved & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2308010104E00403R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	HaritoraX Wireless
Model Number:	SVP-MC3S
Sample:	1#
Device Type:	Bluetooth V5.0
Data Rate:	BLE 1Mbps&2Mbps SRD 1Mbps&2Mbps
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	40 Channels for BLE 11 channels and 40 frequencies for SRD
Transmit Power Max:	BLE: -7.93 dBm(0.000161 W) SRD: 79.08 dBuV@3m
Antenna Type:	Chip Antenna
Antenna Gain:	-2.52 dBi
Power supply:	DC 5V from Speaker, DC 3.7V from battery
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

RF EXPOSURE EVALUATION

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

According to ANSI C63.10-2013

9.5 Equations to calculate EIRP

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$\text{EIRP} = E + 20 \log(d) - 104.7 \quad (22)$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E is the field strength of the emission at the measurement distance, in dB μ V/m

d is the measurement distance, in m

4. Measurement Result

Antenna gain: -2.52 dBi

The manufacturer states that BLE and 2.4G cannot work at the same time.

The measurement results are as follows:

BLE

Mode	Channel Frequency (MHz)	Measured Power (dBm)	E. I.R.P (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
GFSK_1M	2402	-8.27	-10.79	-9±1	-8	0.0491266	3
	2440	-8.08	-10.60	-9±1	-8	0.0495238	3
	2480	-7.93	-10.45	-8±1	-7	0.0628428	3
GFSK_2M	2402	-8.35	-10.87	-9±1	-8	0.0491266	3
	2440	-8.12	-10.64	-9±1	-8	0.0495238	3
	2480	-8	-10.52	-8±1	-7	0.0628428	3

2.4G

Mode	Channel Freq. (MHz)	Max Field Strength (dBuV/m)	peak output power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
GFSK	2402	75.65	-22.0276	-23±1	-22	0.00195576	3
GFSK	2440	79.08	-18.5976	-19±1	-18	0.00495136	3
GFSK	2480	78.74	-18.9376	-19±1	-18	0.00499178	3

According to KDB 447498, no stand-alone required for Chip antenna, and no simultaneous SAR measurement is required.

*** End of Report ***