FCC ID: 2A4M6-007N

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in KDB 447498 D01 V06 and 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
(A) Limits f	or Occupational/Controlled	Exposures	× 0	
614	1.63	*(100)	G 6	
1842/f	4.89/f	*(900/f ²)	6	
61.4	0.163	91.0	6	
Or Col		f/300	6	
O) cer	, C° x	5	6	
(B) Limits for C	General Population/Uncontro	olled Exposure	-01	
614	1.63	*(100)	30	
824/f	2.19/f	*(180/f ²)	30	
27.5	0.073	0.2	30	
	Or Col	f/1500	30	
7	x Or con	1.0	30	
	strength (V/m) (A) Limits f 614 1842/f 61.4 (B) Limits for C 614 824/f	strength (V/m) (A) Limits for Occupational/Controlled 614 1.63 1842/f 4.89/f 61.4 0.163 (B) Limits for General Population/Uncontrolled 614 1.63 824/f 2.19/f	Strength (V/m) Magnetic field strength (A/m) Power density (mW/cm²)	

f = frequency in MHz

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

EIRP=E_{Meas}+20log(d_{Meas})-104.7

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dB_µ V/m

d_{Meas} is the measurement distance, in m

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

X OV. COX N. Cet a Eval D. Cert

Test Result of RF Exwifi 2.4G mode:	posure Evaluation	on Orio					
Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm ²)	Result		
802.11b	17.671	58.4925	0.02008	1.0	PASS		
802.11g	15.974	39.5731	0.01359	ر 1.0 <u>ا</u>	PASS		
802.11n HT20	14.912	30.9885	0.01064	1.0	PASS		