


# FCC MPE Report

## RF EXPOSURE REPORT

Applicant	Shenzhen Hismith Technology Co., Ltd
Address	605, 6th Floor, NO.8, Hetanguang-xinhe Street, Maantang Community, Bantian Street, Longgang District, Shenzhen, Guangdong, CN
Manufacturer or Supplier	Shenzhen Hismith Technology Co., Ltd
Address	605, 6th Floor, NO.8, Hetanguang-xinhe Street, Maantang Community, Bantian Street, Longgang District, Shenzhen, Guangdong, CN
Product	Auxfun sex machine/Auxfun
Trade Mark	HISMITH
Model	STOY0430-APP
Additional Model & Model Difference	N/A
Date of tests	09. 01~09. 09, 2024
<input checked="" type="checkbox"/> FCC Part 2 (Section 2.1093) <input checked="" type="checkbox"/> KDB 447498 D01 <input checked="" type="checkbox"/> IEEE C95.1	
<b>CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement</b>	

Tested by

:



(Suny Zhuo)

Reviewed by


:



(Blue Hu)

Approved & Authorized Signer

:



(Binglee)

# FCC MPE Report

---

## Table of Contents

1. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS .....	3
2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT .....	5
3. MOBILE DEVICE EVALUATION METHOD AND LIMIT .....	6
4. MEASUREMENT RESULT .....	7
5. CONCLUSION: .....	7

# FCC MPE Report

---

## 1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures.

When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions.

- a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

- b) For 100 MHz to 6 GHz and test separation distances  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

- 1)  $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for } 50 \text{ mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz

# FCC MPE Report

---

- 2)  $\{[\text{Power allowed at } \textit{numeric threshold} \text{ for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500 \text{ MHz}$  and  $\leq 6 \text{ GHz}$
- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):
  - 1) For test separation distances  $> 50 \text{ mm}$  and  $< 200 \text{ mm}$ , the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
  - 2) For test separation distances  $\leq 50 \text{ mm}$ , the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$
  - 3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

# FCC MPE Report

---

## 2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

Following FCC KDB 447498 D01 "General SAR test exclusion guidance" The corresponding SAR ExclusionThreshold condition, listed below:

1)The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances <50mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})^2} \right] \left( \frac{f(\text{GHz})}{3.0} \right)^2$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2)At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

- a)  $\left[ \frac{\text{Threshold at 50 mm in step 1) + (test separation distance - 50mm)}}{(f(\text{MHz})/150)^2} \right]$  mW, at 100MHz to 1500 MHz;
- b)  $\left[ \frac{\text{Threshold at 50 mm in step 1) + (test separation distance - 50 mm)}}{10} \right]$  mW at > 1500 MHz and < 6GHz;

3)At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a)The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $(1 + \log(100/f(\text{MHz})))$  for test separation distances > 50 mm and < 200 mm.

b)The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances 50 mm.

c)SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

# FCC MPE Report

## 3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR S2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons

### LIMITS FOR GENERAL POPULATION UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 – 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 -- 300	27.5	0.073	0.2	30
300 – 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

\*Note:

1. f= Frequency in MHz \* Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR SS2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

# FCC MPE Report

---

## 4. MEASUREMENT RESULT

Test Mode	Channel Frequency (MHz)	FieldStrength (dBu V/m)	Max Output power(mW)	Calculati on Value (Note 1)	Threshold Value
GFSK					
Lowest	2440	103.19	6.25	1.76	3.0

Note 1: Calculation Value =[(max. power of channel, mW)/(min. test separation distance, mm)] [ $\sqrt{f}$ (GHz)].

Fox example:  $6.25/5*\sqrt{2.440}=1.76\leq 3.0$

Note 2:Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m)-95.23

Note 3:Max Power (mW) =  $10^{(\text{Max power (dBm)}/10)}$

**According to KDB447498 D01 V06, threshold at which no SAR required is  $\leq 3.0$  for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.**

## 5. Conclusion:

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.