Shenzhen Accurate Technology Co., Ltd.

Report No.: SZNS1220224-05893E-RF

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	$*(180/f^2)$	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

Limits for General Population/Uncontrolled Exposure

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

- P = power input to the antenna (in appropriate units, e.g., mW). G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

Shenzhen Accurate Technology Co., Ltd.

For worst case:

	Frequency (MHz)	Ant	Maximum Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
			(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	$(\mathrm{mW/cm}^2)$
	2402-2480	1	0	1	1	1.26	20	0.0003	1
	2402-2480	2	0	1	1	1.26	20	0.0003	1

Note: 1. The tune up conducted power was declared by the applicant.2. The Bluetooth antenna 1 is transmitted by module 1, Bluetooth antenna 2 is transmitted by module 2, and they can transmit at the same time.

Simultaneous transmitting consideration (worst case):

The ratio= Power Density $_{Ant1/limit}$ + Power Density $_{Ant2/limit}$ =0.0003/1+0.0003/1=0.0006<1.0, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.