



FCC Part 15C Test Report

FCC ID: 2A4WP-GMS1

IC:28295-GMS1

Applicant: Shenzhen Speediance Living Technology co.,Ltd

Address: 8A-F, Konka R&D Building, No. 28, South 12th Road, Science and Technology Park, Nanshan District, Shenzhen, guangdong province, China.

Manufacturer: Shenzhen Speediance Living Technology co.,Ltd

Address: 8A-F, Konka R&D Building, No. 28, South 12th Road, Science and Technology Park, Nanshan District, Shenzhen, guangdong province, China.

EUT: Interactive Multi-Media Digital Fitness Equipment

Trade Mark: SPEEDIANCE

Model Number: GMA1100A4, GMA1100B4, GMA1100A5, GMA1100B5(Remark:The model for sale in the United States are GMA1100A4, GMA1100B4; The model for sale in Canada are GMA1100A5, GMA1100B5)

Date of Receipt: Feb. 24, 2022

Test Date: Feb. 25, 2022 - Aug. 10, 2022

Date of Report: Aug. 12, 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.247
RSS-247 Issue 2: February 2017,
RSS-Gen Issue 5 April 2019
ANSI C63.4:2014

Test Result: Pass

Report Number: DL-20220328004E-0

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	4
1.2 MEASUREMENT UNCERTAINTY	4
2. GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION Limits	10
3.1.2 TEST PROCEDURE	10
3.1.3 DEVIATION FROM TEST STANDARD	10
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	15
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	15
3.2.5 EUT OPERATING CONDITIONS	16
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	17
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	18
3.2.8 TEST RESULTS (1GHZ~25GHZ)	20
3.3 RADIATED BAND EMISSION MEASUREMENT	21
3.3.1 TEST REQUIREMENT:	21
3.3.2 TEST PROCEDURE	21
3.3.3 DEVIATION FROM TEST STANDARD	21
3.3.4 TEST SETUP	22
3.3.5 EUT OPERATING CONDITIONS	22
4. PEAK OUTPUT POWER	24
4.1 APPLIED PROCEDURES / LIMIT	24
4.2 TEST PROCEDURE	24
4.3 DEVIATION FROM STANDARD	24



Table of Contents	Page
4.4 TEST SETUP	24
4.5 EUT OPERATION CONDITIONS	24
4.6 TEST RESULTS	25
5. POWER SPECTRAL DENSITY TEST	26
5.1 APPLIED PROCEDURES / LIMIT	26
5.2 TEST PROCEDURE	26
5.3 DEVIATION FROM STANDARD	26
5.4 TEST SETUP	26
5.5 EUT OPERATION CONDITIONS	26
5.6 TEST RESULTS	27
6. 6DB BANDWIDTH TEST	30
6.1 APPLIED PROCEDURES / LIMIT	30
6.2 TEST PROCEDURE	30
6.3 DEVIATION FROM STANDARD	30
6.4 TEST SETUP	30
6.5 EUT OPERATION CONDITIONS	30
6.6 TEST RESULTS	31
7. OUT OF BAND EMISSIONS TEST	36
7.1 TEST LIMIT	36
7.1.1 TEST PROCEDURE	36
7.1.2 TEST SETUP	36
7.1.3 TEST RESULT	36
8. SPURIOUS RF CONDUCTED EMISSION	39
8.1 TEST LIMIT	39
8.1.1 TEST PROCEDURE	39
8.1.2 TEST SETUP	39
8.1.3 TEST RESULT	39
9. ANTENNA REQUIREMENT	43
9.1 STANDARD REQUIREMENT	43
9.1.1 EUT ANTENNA	43
10. TEST SEUUP PHOTO	44
11. EUT PHOTO	44



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C RSS-247 Issue 2: February 2017 RSS-Gen Issue 5 April 2019			
Standard Section	Test Item	Judgment	Remark
15.207 RSS-Gen 8.8	Conducted Emission	PASS	
15.209(a) RSS-Gen §6.13	Radiated Spurious Emission	PASS	
FCC part 15.247(d) RSS-247 5.5	Band Edge Emission	PASS	
15.247(b)(1) RSS-247 5.4(d)	Peak Output Power	PASS	
15.247(a)(2) RSS-247 5.2(a)	6dB Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e) RSS-247 5.2(b)	Power Spectral Density	PASS	
FCC part 15.247(d) RSS-Gen 8.9	Spurious RF Conducted Emission	PASS	
FCC part 15.203/15.247 (c) RSS-Gen 6.8	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

ISED Registration number: 27485

IC Registered No.:CN0118

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	± 2.56 dB
2	RF power,conducted	± 0.42 dB
3	Spurious emissions,conducted	± 2.76 dB
4	All emissions,radiated(<1G)	± 3.65 dB
5	All emissions,radiated(>1G)	± 4.89 dB
6	Temperature	± 0.5 °C
7	Humidity	± 2 %



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Interactive Multi-Media Digital Fitness Equipment
Model No.:	GMA1100A4
Sample ID:	DL-20220311004E-1#
HVIN:	GMA1100A5, GMA1100B5
Serial No.:	GMA1100B4, GMA1100A5, GMA1100B5(Remark:The model for sale in the United States are GMA1100A4, GMA1100B4; The model for sale in Canada are GMA1100A5, GMA1100B5)
Model Difference	All PCB board, circuit, structure and internal of these model(s) are the same, Only model number is different for these model.
Operation Frequency:	2412~2462 MHz for 802.11b/g/nHT20 2422~2452 MHz for 802.11nHT40
Channel numbers:	11 Channels for 802.11b/g/n(HT20) 7 channels for 802.11nHT40
Channel separation:	5MHz
Modulation technology:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n(20): DSSS (CCK, DQPSK,DBPSK)+OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Rate of Transmitter	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 150Mbps
Antenna Type:	Internal Antenna
Antenna gain:	2.46dBi
Power supply:	AC100-240V ~ 50-60Hz
Power:	1600W



Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.

2. Channel List(802.11b/g/nHT20)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
01	2.412	08	2.447
02	2.417	09	2.452
03	2.422	10	2.457
04	2.427	11	2.462
05	2.432		
06	2.437		
07	2.442		

Channel List(802.11nHT40)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
03	2.422	08	2.447
04	2.427	09	2.452
05	2.432		
06	2.437		
07	2.442		



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11nHT20 CH1/ CH6/ CH11
Mode 4	802.11nHT40 CH3/ CH6/ CH09
Mode 5	Link Mode


For Conducted & Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11nHT20 CH1/ CH6/ CH11
Mode 4	802.11nHT40 CH3/ CH6/ CH09
Mode 5	Link Mode

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Interactive Multi-Media Digital Fitness Equipment	GMA1100A4	N/A	EUT
AE	Notebook	B40-80	MP07F6JD	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: rtwpriv			
Mode	802.11b	802.11g	802.11n HT20	802.11n HT40
Data Rate	1Mbps	1Mbps	MSC0	MSC0
Power Setting of Softwave	60	60	60	66

**2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS**

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 06, 2021	Nov. 05, 2022
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 06, 2021	Nov. 05, 2022
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 06, 2021	Nov. 05, 2022
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 06, 2021	Nov. 05, 2022
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 06, 2021	Nov. 05, 2022
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 06, 2021	Nov. 05, 2022
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 06, 2021	Nov. 05, 2022
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 06, 2021	Nov. 05, 2022
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 06, 2021	Nov. 05, 2022
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 06, 2021	Nov. 05, 2022
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 06, 2021	Nov. 05, 2022
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 06, 2021	Nov. 05, 2022
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 06, 2021	Nov. 05, 2022
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 06, 2021	Nov. 05, 2022
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 06, 2021	Nov. 05, 2022
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 06, 2021	Nov. 05, 2022

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 25, 2019	Nov. 24, 2022
2	EMI Receiver	R&S	ESR	101421	Nov. 06, 2021	Nov. 05, 2022
3	LISN	R&S	ENV216	102417	Nov. 06, 2021	Nov. 05, 2022
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 06, 2021	Nov. 05, 2022

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	IC
0.50 -5.0	56.00	46.00	IC
5.0 -30.0	60.00	50.00	IC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

Remark:

1. All modes were tested at AC 120V and 240V, only the worst result of AC 120V was reported.
2. Remark: We tested at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode at the antenna single and recored the worst data 802.11b mode in report.



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Transmitting 802.11b mode




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.48	17.86	9.69	0.05	27.60	46.36	-18.76	Average
2	0.48	24.69	9.69	0.05	34.43	56.36	-21.93	QP
3	0.57	18.25	9.67	0.05	27.97	46.00	-18.03	Average
4	0.57	25.62	9.67	0.05	35.34	56.00	-20.66	QP
5	0.70	17.78	9.64	0.05	27.47	46.00	-18.53	Average
6	0.70	25.31	9.64	0.05	35.00	56.00	-21.00	QP
7	0.78	18.57	9.63	0.05	28.25	46.00	-17.75	Average
8	0.78	25.23	9.63	0.05	34.91	56.00	-21.09	QP
9	0.83	17.19	9.63	0.05	26.87	46.00	-19.13	Average
10	0.83	25.16	9.63	0.05	34.84	56.00	-21.16	QP
11	1.30	17.61	9.60	0.06	27.27	46.00	-18.73	Average
12	1.30	23.35	9.60	0.06	33.01	56.00	-22.99	QP



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Transmitting 802.11b mode



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.45	18.29	9.62	0.05	27.96	46.93	-18.97	Average
2	0.45	25.05	9.62	0.05	34.72	56.93	-22.21	QP
3	0.53	17.85	9.63	0.05	27.53	46.00	-18.47	Average
4	0.53	25.39	9.63	0.05	35.07	56.00	-20.93	QP
5	0.59	17.98	9.63	0.05	27.66	46.00	-18.34	Average
6	0.59	25.62	9.63	0.05	35.30	56.00	-20.70	QP
7	0.68	17.72	9.63	0.05	27.40	46.00	-18.60	Average
8	0.68	24.69	9.63	0.05	34.37	56.00	-21.63	QP
9	0.78	18.45	9.63	0.05	28.13	46.00	-17.87	Average
10	0.78	25.32	9.63	0.05	35.00	56.00	-21.00	QP
11	0.94	16.73	9.63	0.06	26.42	46.00	-19.58	Average
12	0.94	24.36	9.63	0.06	34.05	56.00	-21.95	QP



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~230	180	3
230~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 5	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


Remark:

1. All modes of 802.11b/g/n20/n40 were test at Low, Middle, and High channel, only the worst result of 802.11b Low Channel was reported for below 1GHz test.
2. Remark: We tested at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode at the antenna single and recored the worst data 802.11b mode in report.



3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Transmitting 802.11b mode		



	ReadAntenna	Cable	Limit	Over				
Freq	Level	Factor	Loss	Level	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB		
1	78.41	24.93	8.00	0.86	33.79	40.00	-6.21	QP
2	79.80	24.06	8.00	0.87	32.93	40.00	-7.07	QP
3	82.94	23.00	8.55	0.86	32.41	40.00	-7.59	QP
4	84.70	20.83	8.55	0.86	30.24	40.00	-9.76	QP
5	397.63	16.54	16.27	1.29	34.10	46.00	-11.90	QP
6	452.72	18.21	17.60	1.50	37.31	46.00	-8.69	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	Transmitting 802.11b mode		



	ReadAntenna	Cable	Limit	Over			
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	35.00	16.25	15.85	0.42	32.52	40.00	-7.48 QP
2	58.82	24.62	7.48	0.51	32.61	40.00	-7.39 QP
3	69.60	24.27	7.49	0.81	32.57	40.00	-7.43 QP
4	86.81	24.07	8.75	0.86	33.68	40.00	-6.32 QP
5	121.98	28.16	8.46	0.84	37.46	43.50	-6.04 QP
6	394.85	20.45	16.28	1.28	38.01	46.00	-7.99 QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;

**3.2.8 TEST RESULTS (1GHZ~25GHZ)**

802.11b(Record the wors test data in report.)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	4824.00	66.41	50.65	6.88	31.29	53.93	74.00	-20.07	PK
V	4824.00	56.83	50.65	6.88	31.29	44.35	54.00	-9.65	AV
V	7236.00	64.59	49.98	7.16	36.63	58.4	74.00	-15.6	PK
V	7236.00	53.16	49.98	7.16	36.63	46.97	54.00	-7.03	AV
V	16087.00	50.43	51.53	11.34	41.52	51.76	74.00	-22.24	PK
H	4824.00	66.97	50.65	6.88	31.29	54.49	74.00	-19.51	PK
H	4824.00	56.91	50.65	6.88	31.29	44.43	54.00	-9.57	AV
H	7236.00	64.32	49.98	7.16	36.63	58.13	74.00	-15.87	PK
H	7236.00	52.98	49.98	7.16	36.63	46.79	54.00	-7.21	AV
H	16087.00	49.33	51.53	11.34	41.52	50.66	74.00	-23.34	PK
operation frequency:2437									
V	4874.00	65.49	50.67	6.89	31.38	53.09	74.00	-20.91	PK
V	4874.00	55.37	50.67	6.89	31.38	42.97	54.00	-11.03	AV
V	7311.00	63.41	50.02	7.24	36.63	57.26	74.00	-16.74	PK
V	7311.00	53.72	50.02	7.24	36.63	47.57	54.00	-6.43	AV
V	16087.00	49.36	51.53	11.34	41.52	50.69	74.00	-23.31	PK
H	4874.00	65.34	50.67	6.89	31.38	52.94	74.00	-21.06	PK
H	4874.00	55.27	50.67	6.89	31.38	42.87	54.00	-11.13	AV
H	7311.00	63.51	50.02	7.24	36.63	57.36	74.00	-16.64	PK
H	7311.00	53.29	50.02	7.24	36.63	47.14	54.00	-6.86	AV
H	16087.00	47.21	51.53	11.34	41.52	48.54	74.00	-25.46	PK
operation frequency:2462									
V	4924.00	66.53	50.79	6.83	31.36	53.93	74.00	-20.07	PK
V	4924.00	56.32	50.79	6.83	31.36	43.72	54.00	-10.28	AV
V	7386.00	64.05	50.11	7.25	36.58	57.77	74.00	-16.23	PK
V	7386.00	53.88	50.11	7.25	36.58	47.6	54.00	-6.4	AV
V	16087.00	50.16	51.53	11.34	41.52	51.49	74.00	-22.51	PK
H	4924.00	66.53	50.79	6.83	31.36	53.93	74.00	-20.07	PK
H	4924.00	55.74	50.79	6.83	31.36	43.14	54.00	-10.86	AV
H	7386.00	64.59	50.11	7.25	36.58	58.31	74.00	-15.69	PK
H	7386.00	54.32	50.11	7.25	36.58	48.04	54.00	-5.96	AV
H	16087.00	48.16	51.53	11.34	41.52	49.49	74.00	-24.51	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**3.3 RADIATED BAND EMISSION MEASUREMENT****3.3.1 TEST REQUIREMENT:**

FCC Part15 C Section 15.209 and 15.205, RSS-Gen Issue 5 Section RSS-247 §6.2.1

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to RSS-Gen Issue 5.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

We tested at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode at the antenna single and recored the worst data mode in report.

**3.3.6 TEST RESULT**

802.11b (Record the worst test data in report.)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	2390.00	75.32	52.12	2.73	27.38	53.31	74.00	-20.69	PK
V	2390.00	64.17	52.12	2.73	27.38	42.16	54.00	-11.84	AV
V	2400.00	75.29	52.16	2.78	27.41	53.32	74.00	-20.68	PK
V	2400.00	63.19	52.16	2.78	27.41	41.22	54.00	-12.78	AV
H	2390.00	75.49	52.12	2.73	27.38	53.48	74.00	-20.52	PK
H	2390.00	64.31	52.12	2.73	27.38	42.3	54.00	-11.7	AV
H	2400.00	75.21	52.16	2.78	27.41	53.24	74.00	-20.76	PK
H	2400.00	63.14	52.16	2.78	27.41	41.17	54.00	-12.83	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	2483.50	74.83	52.23	2.86	27.44	52.9	74.00	-21.1	PK
V	2483.50	64.12	52.23	2.86	27.44	42.19	54.00	-11.81	AV
V	2500.00	75.03	52.26	2.88	27.49	53.14	74.00	-20.86	PK
V	2500.00	64.82	52.26	2.88	27.49	42.93	54.00	-11.07	AV
H	2483.50	74.63	52.23	2.86	27.44	52.7	74.00	-21.3	PK
H	2483.50	65.81	52.23	2.86	27.44	43.88	54.00	-10.12	AV
H	2500.00	74.11	52.26	2.88	27.49	52.22	74.00	-21.78	PK
H	2500.00	65.93	52.26	2.88	27.49	44.04	54.00	-9.96	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4. PEAK OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

FCC PART15 (15.247), SUBPART C, RSS-247 ISSUE 2: FEBRUARY 2017				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(i) RSS-247 §6.2.1	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

4.2 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW \geq RBW
Sweep = auto
Detector function = peak
Trace = max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz

Mode	Test Channel	Peak Output Power (dBm)	LIMIT (dBm)	Result
802.11b	Low	13.129	30.00	PASS
	Moddle	12.852	30.00	PASS
	High	11.961	30.00	PASS
802.11g	Low	10.769	30.00	PASS
	Moddle	9.665	30.00	PASS
	High	9.503	30.00	PASS
802.11n HT20	Low	10.348	30.00	PASS
	Moddle	9.776	30.00	PASS
	High	9.270	30.00	PASS
802.11n HT40	Low	7.451	30.00	PASS
	Moddle	7.091	30.00	PASS
	High	6.058	30.00	PASS



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC PART15 C SECTION 15.247 (E), RSS-247 ISSUE 2: FEBRUARY 2017				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (e) RSS-247 §6.2.1	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW ≥ 3kHz
VB	VBW ≥ 3RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.6 TEST RESULTS**


Mode	Test Channel	Reading Level (dBm)	Limit (dBm)	Result
802.11b	Low	-6.117	8	PASS
	Moddle	-6.210	8	PASS
	High	-5.543	8	PASS
802.11g	Low	-9.119	8	PASS
	Moddle	-8.955	8	PASS
	High	-8.851	8	PASS
802.11n20	Low	-9.451	8	PASS
	Moddle	-9.623	8	PASS
	High	-9.270	8	PASS
802.11n40	Low	-9.270	8	PASS
	Moddle	-11.223	8	PASS
	High	-10.885	8	PASS




802.11b




802.11g



2412MHz




2412MHz



2437MHz



2437MHz




2462MHz

2462MHz




802.11n HT20



802.11n HT40




2412MHz




2422MHz



2437MHz



2437MHz



2462MHz

2452MHz



6. 6DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC PART15 (15.247) , SUBPART C, RSS-247 ISSUE 2: FEBRUARY 2017				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2) RSS-247 §5.2(1) &RSS-Gen§6.6	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS

	Test Channel	6dB Bandwidth (MHz)	99% Occupied bandwidth(MHz)	Limit (MHz)	Result
802.11b	Low	10.71	15.580	0.5	Pass
	Middle	9.87	15.511	0.5	Pass
	High	11.01	15.416	0.5	Pass
802.11g	Low	16.47	16.611	0.5	Pass
	Middle	16.40	16.515	0.5	Pass
	High	16.40	16.501	0.5	Pass
802.11n HT20	Low	17.62	17.720	0.5	Pass
	Middle	17.65	17.735	0.5	Pass
	High	17.60	17.706	0.5	Pass
802.11n HT40	Low	36.33	36.223	0.5	Pass
	Middle	36.36	36.239	0.5	Pass
	High	36.22	36.213	0.5	Pass



6dB Bandwidth

802.11b




802.11g



2412MHz




2412MHz



2437MHz



2437MHz




2462MHz

2462MHz




6dB Bandwidth


802.11n HT20




802.11n HT40




2412MHz




2422MHz



2437MHz



2437MHz



2462MHz

2452MHz