RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Smart watch
Model Name	I39H
Series Model	I36, I66, I70, I72, I76, I79, I50, I96, I99
FCC ID	2A54SI39H

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·[√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.
Where f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR/EDR:
P_t= -0.204dBm=0.95mW
The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.
The result for RF exposure evaluation SAR=(0.95mW / 5mm).[√2.441GHz)]=0.30<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE:
P_t= -1.360dBm=0.73mW
The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.
The result for RF exposure evaluation SAR=(0.73mW / 5mm).[√2.402GHz)]=0.23<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE 1M:
P_t= 6.221dBm=4.19mW
The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.
The result for RF exposure evaluation SAR=(4.19mW / 5mm).[√2.402GHz)]=1.30<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE 2M:
P_t=6.219dBm=4.19mW
The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.
The result for RF exposure evaluation SAR=(4.19mW / 5mm).[√2.402GHz)]=1.30<3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.