



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

RF Exposure Evaluation

FCC ID: 2A54U-DTNOI7

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v07, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

Passed

Not Applicable

BT

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
DH5	2402	-4.33	-5±1	-4	0.40	0.1234	3.00	Pass
	2441	-4.85	-5±1	-4	0.40	0.1244		
	2480	-5.93	-6±1	-5	0.32	0.0996		
2DH5	2402	-3.79	-4±1	-3	0.50	0.1554		
	2441	-4.43	-5±1	-4	0.40	0.1244		
	2480	-5.29	-6±1	-5	0.32	0.0996		
3DH5	2402	-3.34	-4±1	-3	0.50	0.1554		
	2441	-4.04	-5±1	-4	0.40	0.1244		
	2480	-5.12	-6±1	-5	0.32	0.0996		



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	1.63	1±1	2	1.58	0.4913	3.00	Pass
	2440	1.28	1±1	2	1.58	0.4951		
	2480	0.84	1±1	2	1.58	0.4992		
GFSK_2M	2402	1.66	1±1	2	1.58	0.4913		
	2440	1.31	1±1	2	1.58	0.4951		
	2480	0.9	1±1	2	1.58	0.4992		

Note:

- The BT&BLE maximum antenna gain is -0.7dBi.
- The exposure safety distance is less than 5mm.
- This device does support simultaneous Transmitter, $0.1554+0.4992=0.6554<3$.

--THE END--