



FCC Part 15E Test Report

FCC ID: 2A54Y-X5A

Applicant: Shenzhen TFIRETEK Technology Co., Ltd.

Address: Floor 2, Building A, Queshan Guanghao Industrial Park, Taoyuan Community, Dalang Street, Longhua District, Shenzhen

Manufacturer: Shenzhen TFIRETEK Technology Co., Ltd.

Address: Floor 2, Building A, Queshan Guanghao Industrial Park, Taoyuan Community, Dalang Street, Longhua District, Shenzhen

EUT: Projector

Trade Mark: N/A

Model Number: X5A
X5H-A, X5S-A, X5A-Pro, X5A-Max, X5SA-Pro, X5SA-Max, X5B, X5H-B, X5S-B, X5B-Pro, X5B-Max, X5SB-Pro, X5SB-Max, X5C, X5H-C, X5S-C, X5C-Pro, X5C-Max, X5SC-Pro, X5SC-Max

Date of Receipt: Sep. 21, 2023

Test Date: Sep. 21, 2023 – Nov. 14, 2023

Date of Report: Nov. 14, 2023

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 E 15.407
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20231018032-5E

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

Page

1 . SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3 . EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	10
3.1.2 TEST PROCEDURE	10
3.1.3 DEVIATION FROM TEST STANDARD	10
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	15
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	15
3.2.5 EUT OPERATING CONDITIONS	16
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	17
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	18
3.2.8 TEST RESULTS (1GHZ~40GHZ)	20
3.3 RADIATED BAND EMISSION MEASUREMENT	23
3.3.1 TEST REQUIREMENT:	23
3.3.2 TEST PROCEDURE	23
3.3.3 DEVIATION FROM TEST STANDARD	23
3.3.4 TEST SETUP	23
3.3.5 EUT OPERATING CONDITIONS	23
4 . AVERAGE OUTPUT POWER	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD	25
4.1.3 TEST SETUP	25
4.1.4 EUT OPERATION CONDITIONS	25
4.1.5 TEST RESULTS	26
5 . POWER SPECTRAL DENSITY TEST	29
5.1 APPLIED PROCEDURES / LIMIT	29
5.1.1 TEST PROCEDURE	29
5.1.2 DEVIATION FROM STANDARD	29
5.1.3 TEST SETUP	29
5.1.4 EUT OPERATION CONDITIONS	29
5.1.5 TEST RESULTS	30



Table of Contents	Page
6 . 6DB BANDWIDTH TEST	33
6.1 APPLIED PROCEDURES / LIMIT	33
6.1.1 TEST PROCEDURE	33
6.1.2 DEVIATION FROM STANDARD	33
6.1.3 TEST SETUP	33
6.1.4 EUT OPERATION CONDITIONS	33
6.1.5 TEST RESULTS	34
7 . DUTY CYCLE TEST SIGNAL	37
7.1 APPLIED PROCEDURES / LIMIT	37
7.1.1 TEST PROCEDURE	37
7.1.2 DEVIATION FROM STANDARD	37
7.1.3 TEST SETUP	37
7.1.4 EUT OPERATION CONDITIONS	37
7.1.5 TEST RESULTS	38
8 . FREQUENCY STABILITY	39
8.1 APPLIED PROCEDURES / LIMIT	39
8.1.1 TEST PROCEDURE	39
8.1.2 DEVIATION FROM STANDARD	39
8.1.3 TEST SETUP	39
8.1.4 EUT OPERATION CONDITIONS	39
8.1.5 TEST RESULTS	40
9 . TRANSMISSION IN THE ABSENCE OF DATA	41
9.1 STANDARD REQUIREMENT	41
9.2 TEST RESULT	41
10 . ANTENNA REQUIREMENT	41
10.1 STANDARD REQUIREMENT	41
10.2 EUT ANTENNA	41
11 . TEST SEUUP PHOTO	42
12 . EUT PHOTO	44



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.407(b), 15.209	Radiated Spurious Emission	PASS	
15.407 (b)	Band Edge Emission	PASS	
15.407 (a)	Average Output Power	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(e)	6dB bandwidth	PASS	
15.407(g)	Frequency Stability	PASS	
15.407(c)	Transmission in case of Absence of Information	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118



1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	6dB Bandwidth	$\pm 0.2\text{MHz}$
9	PSD	$\pm 0.69\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Projector
Trademark:	N/A
Model No.:	X5A X5H-A, X5S-A, X5A-Pro, X5A-Max, X5SA-Pro, X5SA-Max, X5B, X5H-B, X5S-B, X5B-Pro, X5B-Max, X5SB-Pro, X5SB-Max, X5C, X5H-C, X5S-C, X5C-Pro, X5C-Max, X5SC-Pro, X5SC-Max
Model Difference	All samples are the same except the model name and outlook color, so we prepare " X5A" for test only.
Operation Frequency:	5745-5825MHz(802.11a/n (HT20)) 5755-5795MHz(802.11n (HT40))
Channel numbers:	See channel list
Channel separation:	20MHz/40MHz
Modulation technology:	64QAM, 16QAM, QPSK, BPSK for OFDM
Rate of Transmitter	802.11a: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps 802.11n: Up to 500Mbps
Antenna Type:	FPC antenna
Antenna gain:	2.2 dBi
Power supply:	100-240V~ 50/60Hz

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



2. Channel List

Channel List for 802.11a/n(HT20)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

Channel List for 802.11n(HT40)			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted Emission		
Pretest Mode	Channel	Band 4
Mode 1	802.11a/n HT20	CH149, CH157, CH165
Mode 2	802.11n HT40	CH151, CH159
Mode 3	Link Mode	

For Radiated Emission		
Pretest Mode	Channel	Band 4
Mode 1	802.11a/n HT20	CH149, CH157, CH165
Mode 2	802.11n HT40	CH151, CH159
Mode 3	Link Mode	

Note: 1. The measurements are performed at the highest, middle, lowest available channels.
2. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.



2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.3 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Projector	X5A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting			
Test software Version	Test program: FrequencyTool_v0.3.1		
Mode	802.11a	802.11n HT20	802.11n HT40
Data Rate	6Mbps	MSC0	MSC0
Power Setting of Software	60	60	66

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
2	EMI Receiver	R&S	ESR	101421	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
3	LISN	R&S	ENV216	102417	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 05, 2022/ Nov. 04, 2023	Nov. 04, 2023/ Nov. 03, 2024

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.244400	33.77	9.39	43.16	51.95	-8.79	AVG	P	
2	0.247900	44.75	9.39	54.14	61.83	-7.69	QP	P	
3	0.636000	36.09	9.41	45.50	56.00	-10.50	QP	P	
4	0.636000	22.90	9.41	32.31	46.00	-13.69	AVG	P	
5 *	0.982500	41.10	9.33	50.43	56.00	-5.57	QP	P	
6	0.982500	24.50	9.33	33.83	46.00	-12.17	AVG	P	
7	1.455000	25.54	9.61	35.15	46.00	-10.85	AVG	P	
8	1.459500	40.28	9.62	49.90	56.00	-6.10	QP	P	
9	3.605900	38.69	9.80	48.49	56.00	-7.51	QP	P	
10	3.660000	24.13	9.80	33.93	46.00	-12.07	AVG	P	
11	13.064700	15.08	10.19	25.27	50.00	-24.73	AVG	P	
12	13.317000	29.64	10.20	39.84	60.00	-20.16	QP	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.181400	43.44	9.46	52.90	64.42	-11.52	QP	P	
2	0.181400	32.57	9.46	42.03	54.42	-12.39	AVG	P	
3 *	0.370400	41.48	9.23	50.71	58.49	-7.78	QP	P	
4	0.375000	27.84	9.24	37.08	48.39	-11.31	AVG	P	
5	0.888000	34.81	9.36	44.17	56.00	-11.83	QP	P	
6	0.888000	17.45	9.36	26.81	46.00	-19.19	AVG	P	
7	1.283900	35.94	9.59	45.53	56.00	-10.47	QP	P	
8	1.283900	18.88	9.59	28.47	46.00	-17.53	AVG	P	
9	2.516900	33.85	9.96	43.81	56.00	-12.19	QP	P	
10	2.516900	17.80	9.96	27.76	46.00	-18.24	AVG	P	
11	5.937000	36.40	10.10	46.50	60.00	-13.50	QP	P	
12	6.004500	21.24	10.10	31.34	50.00	-18.66	AVG	P	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120/60HZ
Test Mode :	Mode 3	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.2.7 TEST RESULTS (Between 30MHz – 1GHz)

Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120/60HZ		
Test Mode :	Mode 3		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Margin dB	Detector
1		30.0000	35.39	-15.00	20.39	40.00	-19.61	QP
2		46.3402	36.84	-11.91	24.93	40.00	-15.07	QP
3		127.6645	45.27	-15.69	29.58	43.50	-13.92	QP
4		179.3863	43.05	-14.59	28.46	43.50	-15.04	QP
5		401.8383	40.14	-8.27	31.87	46.00	-14.13	QP
6	*	830.4000	33.99	-1.26	32.73	46.00	-13.27	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
test voltage :	AC 120/60HZ		
Test Mode :	Mode 3		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Margin dB	Detector
1	*	35.6238	46.12	-13.76	32.36	40.00	-7.64	QP
2		60.0690	41.71	-12.58	29.13	40.00	-10.87	QP
3		85.2980	47.87	-16.39	31.48	40.00	-8.52	QP
4		135.5061	44.87	-15.93	28.94	43.50	-14.56	QP
5		222.1697	41.44	-12.13	29.31	46.00	-16.69	QP
6		378.5842	40.29	-8.68	31.61	46.00	-14.39	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8 TEST RESULTS (1ghz~40ghZ)**

802.11a band 4

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBUV)	(dB)	(dB)	(dB/m)	(dBUV/m)	(dBUV/m)	(dB)	
operation frequency:5745									
V	11490	54.41	49.05	15.3	37.39	58.05	74	-15.95	PK
V	11490	41.11	49.05	15.3	37.39	44.75	54	-9.25	AV
V	17235	55.43	49.16	15.27	40.45	61.99	68.2	-6.21	PK
V	17235	41.07	49.16	15.27	40.45	47.63	54	-6.37	AV
H	11490	52.45	49.05	15.3	37.39	56.09	74	-17.91	PK
H	11490	42.27	49.05	15.3	37.39	45.91	54	-8.09	AV
H	17235	51.46	49.16	15.27	40.45	58.02	68.2	-10.18	PK
H	17235	40.35	49.16	15.27	40.45	46.91	54	-7.09	AV
operation frequency:5785									
V	11570	51.74	49.09	15.34	37.42	55.41	74	-18.59	PK
V	11570	41.23	49.09	15.34	37.42	44.9	54	-9.1	AV
V	17355	50.50	49.18	15.29	40.47	57.08	68.2	-11.12	PK
V	17355	40.34	49.18	15.29	40.47	46.92	54	-7.08	AV
H	11570	50.72	49.09	15.34	37.42	54.39	74	-19.61	PK
H	11570	42.13	49.09	15.34	37.42	45.8	54	-8.2	AV
H	17355	48.90	49.18	15.29	40.47	55.48	68.2	-12.72	PK
H	17355	40.27	49.18	15.29	40.47	46.85	54	-7.15	AV
operation frequency:5825									
V	11650	52.14	49.11	15.37	37.46	55.86	74	-18.14	PK
V	11650	41.43	49.11	15.37	37.46	45.15	54	-8.85	AV
V	17475	49.37	49.21	15.34	40.51	56.01	68.2	-12.19	PK
V	17475	40.57	49.21	15.34	40.51	47.21	54	-6.79	AV
H	11650	57.56	49.11	15.37	31.31	55.13	74	-18.87	PK
H	11650	48.15	49.11	15.37	31.31	45.72	54	-8.28	AV
H	17475	49.43	49.21	15.34	40.51	56.07	68.2	-12.13	PK
H	17475	40.27	49.21	15.34	40.51	46.91	54	-7.09	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBUV)	(dB)	(dB)	(dB/m)	(dBUV/m)	(dBUV/m)	(dB)	
operation frequency:5745									
V	11490	49.32	49.05	15.3	37.39	52.96	74	-21.04	PK
V	11490	42.22	49.05	15.3	37.39	45.86	54	-8.14	AV
V	17235	48.67	49.16	15.27	40.45	55.23	68.2	-12.97	PK
V	17235	40.33	49.16	15.27	40.45	46.89	54	-7.11	AV
H	11490	49.41	49.05	15.3	37.39	53.05	74	-20.95	PK
H	11490	41.25	49.05	15.3	37.39	44.89	54	-9.11	AV
H	17235	48.33	49.16	15.27	40.45	54.89	68.2	-13.31	PK
H	17235	40.66	49.16	15.27	40.45	47.22	54	-6.78	AV
operation frequency:5785									
V	11570	52.42	49.09	15.34	37.42	56.09	74	-17.91	PK
V	11570	42.36	49.09	15.34	37.42	46.03	54	-7.97	AV
V	17355	49.28	49.18	15.29	40.47	55.86	68.2	-12.34	PK
V	17355	40.65	49.18	15.29	40.47	47.23	54	-6.77	AV
H	11570	49.43	49.09	15.34	37.42	53.1	74	-20.9	PK
H	11570	43.37	49.09	15.34	37.42	47.04	54	-6.96	AV
H	17355	49.44	49.18	15.29	40.47	56.02	68.2	-12.18	PK
H	17355	40.81	49.18	15.29	40.47	47.39	54	-6.61	AV
operation frequency:5825									
V	11650	51.35	49.11	15.37	37.46	55.07	74	-18.93	PK
V	11650	41.55	49.11	15.37	37.46	45.27	54	-8.73	AV
V	17475	48.31	49.21	15.34	40.51	54.95	68.2	-13.25	PK
V	17475	40.7	49.21	15.34	40.51	47.34	54	-6.66	AV
H	11650	57.38	49.11	15.37	31.31	54.95	74	-19.05	PK
H	11650	44.44	49.11	15.37	31.31	42.01	54	-11.99	AV
H	17475	49.33	49.21	15.34	40.51	55.97	68.2	-12.23	PK
H	17475	40.76	49.21	15.34	40.51	47.4	54	-6.6	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBUV)	(dB)	(dB)	(dB/m)	(dBUV/m)	(dBUV/m)	(dB)	
operation frequency:5755									
V	11510	49.19	49.07	15.33	37.41	52.86	74	-21.14	PK
V	11510	41.57	49.07	15.33	37.41	45.24	54	-8.76	AV
V	17265	49.68	49.17	15.28	40.46	56.25	68.2	-11.95	PK
V	17265	40.32	49.17	15.28	40.46	46.89	54	-7.11	AV
H	11510	48.40	49.07	15.33	37.41	52.07	74	-21.93	PK
H	11510	41.21	49.07	15.33	37.41	44.88	54	-9.12	AV
H	17265	49.99	49.17	15.28	40.46	56.56	68.2	-11.64	PK
H	17265	40.30	49.17	15.28	40.46	46.87	54	-7.13	AV
operation frequency:5795									
V	11590	49.22	49.11	15.37	37.46	52.94	74	-21.06	PK
V	11590	41.28	49.11	15.37	37.46	45	54	-9	AV
V	17385	48.5	49.21	15.34	40.51	55.14	68.2	-13.06	PK
V	17385	40.41	49.21	15.34	40.51	47.05	54	-6.95	AV
H	11590	57.61	49.11	15.37	31.31	55.18	74	-18.82	PK
H	11590	44.76	49.11	15.37	31.31	42.33	54	-11.67	AV
H	17385	48.22	49.21	15.34	40.51	54.86	68.2	-13.34	PK
H	17385	40.30	49.21	15.34	40.51	46.94	54	-7.06	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 CONDUCTED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.407

(4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	5150MHz	5725MHz
Stop Frequency	5250MHz	5850MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average	

3.3.2 TEST PROCEDURE

Test method: FCC KDB 789033 G)& Parts 15.407(b)(4) & 15.209(a)

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



3.3.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT


The antenna gain is compensated in the test data.



802.11a




5745MHz




5825MHz

802.11n HT20




5745MHz



5825MHz

802.11n HT40



5755MHz



5795MHz



4. AVERAGE OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
VBW ≥ RBW
Sweep = auto
Detector function = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
Trace = max hold

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**4.1.5 TEST RESULTS**


Temperature:	25 °C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	AC 120/60HZ

Mode	Test Channel	Average Output Power (dBm)	Duty factor (dB)	Total Output Power(dB)	LIMIT (dBm)
802.11a	Low	9.605	0.69	10.295	30
	Middle	9.470	0.69	10.160	30
	High	9.502	0.69	10.192	30
802.11n HT20	Low	10.293	0.11	10.403	30
	Middle	10.145	0.11	10.255	30
	High	9.671	0.11	9.781	30
802.11n HT40	Low	9.493	0.21	9.703	30
	High	9.819	0.21	10.029	30






802.11n HT40



5755MHz



5795MHz



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW \geq 1MHz for band 1 RBW \geq 510KHz for band 4
VB	VBW \geq 3RBW
Detector	RMS (i.e., power averaging).
Trace	Max Hold
Sweep Time	Auto


5.1.1 TEST PROCEDURE

- Place the EUT on the table and set it in transmitting mode.
- The testing follows FCC KDB 789033 D02.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.
- For U-NII1, U-NII-2A, U-NII-2C Band:
Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
For U-NII-3 Band:
Set RBW=510 kHz, VBW=3*RBW, where span is enough to capture the entire bandwidth, Sweep time = Auto (601 pts), detector = sample, traces 100 sweeps of video averaging. (SA-2 with the omission of procedure x, the integration with 26dB EBW bandwidth)
- Use the cursor on spectrum to peak search the highest level of trace
- Record the max. reading and add 10 log(1/duty cycle).
we test all antennas, the antenna 1 was worst mode and the data recording in the report.
- Duty factor Reference is made to the test results in Section 7.1.5.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


**5.1.5 TEST RESULTS**

	Mode	Test Channel	Reading Level (dBm)	Duty factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
Band4	802.11a	Low	-2.673	0.69	-1.983	30.00	PASS
		Middle	-2.87	0.69	-2.18	30.00	PASS
		High	-2.921	0.69	-2.231	30.00	PASS
	802.11n20	Low	-1.992	0.11	-1.882	30.00	PASS
		Middle	-2.709	0.11	-2.599	30.00	PASS
		High	-3.187	0.11	-3.077	30.00	PASS
	802.11n40	Low	-6.035	0.21	-5.825	30.00	PASS
		High	-6.034	0.21	-5.824	30.00	PASS






802.11n HT40



5755MHz



5795MHz



6. 6DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

There is no limit bandwidth for U-NII-1, U-NII-2-A and U-NII-2-C.
The minimum of 6dB Bandwidth measurement is 0.5 MHz for U-NII-3


6.1.1 TEST PROCEDURE

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	30MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**6.1.5 TEST RESULTS**


		Test Channel	6dB Bandwidth (MHz)	6dB Bandwidth Limit (MHz)	Result
Band 4	802.11a	Low	16.053	>0.5	Pass
		Middle	15.456	>0.5	Pass
		High	16.287	>0.5	Pass
	802.11n HT20	Low	15.416	>0.5	Pass
		Middle	15.051	>0.5	Pass
		High	13.650	>0.5	Pass
	802.11n HT40	Low	35.106	>0.5	Pass
		High	35.085	>0.5	Pass




802.11a




802.11n HT20




5745MHz




5745MHz



5785MHz



5785MHz




5825MHz


5825MHz



802.11n HT40



5755MHz



5795MHz



7. DUTY CYCLE TEST SIGNAL

7.1 APPLIED PROCEDURES / LIMIT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.


7.1.1 TEST PROCEDURE

1. Set RBW = 1 MHz.
2. Set the video bandwidth (VBW) \geq RBW.
3. Detector = Peak.
4. Sweep = auto couple.
5. Allow the trace to stabilize.
6. Span=0

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.1.5 TEST RESULTS

Operation Mode		Duty Cycle(%)	Duty Fator (dB) 10 * log (1/ Duty cycle)
Band 4	802.11a	85.38	0.69
	802.11n(HT20)	97.61	0.11
	802.11n(HT40)	95.34	0.21





8. FREQUENCY STABILITY

8.1 APPLIED PROCEDURES / LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


8.1.1 TEST PROCEDURE

1. The EUT was placed inside temperature chamber and powered and powered by nominal DC voltage.
2. Set EUT as normal operation.
3. Turn the EUT on and couple its output to spectrum.
4. Turn the EUT off and set the chamber to the highest temperature specified.
5. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT and measure the operating frequency.
6. Repeat step with the temperature chamber set to the lowest temperature.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



8.1.5 TEST RESULTS

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)		Δ Frequency (MHz)	
			802.11a	802.11n HT20	802.11a	802.11n HT20
AC 132V	-20°C	5745	5745.0328	5745.0323	-0.0328	-0.0316
		5785	5785.0348	5785.0325	-0.0348	-0.0318
		5825	5825.0307	5825.0318	-0.0307	-0.0311
AC 108V		5745	5745.0216	5745.0524	-0.0216	-0.0513
		5785	5785.0350	5785.0316	-0.0350	-0.0309
		5825	5825.0426	5825.0435	-0.0426	-0.0426
AC 120V	25°C	5745	5745.0348	5745.0342	-0.0348	-0.0335
		5785	5785.0405	5785.0426	-0.0405	-0.0417
		5825	5825.0217	5825.0214	-0.0217	-0.0209
AC 132V	50°C	5745	5745.0649	5745.0664	-0.0649	-0.0650
		5785	5785.0436	5785.0441	-0.0436	-0.0432
		5825	5825.0652	5825.0616	-0.0652	-0.0603
AC 108V		5745	5745.0467	5745.0438	-0.0467	-0.0429
		5785	5785.0229	5785.0244	-0.0229	-0.0239
		5825	5825.0750	5825.0713	-0.0750	-0.0698

Test Voltage	Test Temp.	Measured Frequency (MHz)	Spectrum Frequency (MHz)	Δ frequency (MHz)
			802.11n HT40	802.11n HT40
AC 132V	-20°C	5755	5755.0502	-0.0502
		5795	5795.0622	-0.0622
AC 108V		5755	5755.0209	-0.0209
		5795	5795.0434	-0.0434
AC 120V	25°C	5755	5755.0230	-0.0230
		5795	5795.0500	-0.0500
AC 132V	50°C	5755	5755.0417	-0.0417
		5795	5795.0340	-0.0340
AC 108V		5755	5755.0305	-0.0305
		5795	5795.0414	-0.0414



9. TRANSMISSION IN THE ABSENCE OF DATA

9.1 STANDARD REQUIREMENT

According to §15.407(c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

9.2 TEST RESULT

No non-compliance noted:
Refer to the theory of operation.

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



10.2 EUT ANTENNA

The EUT antenna is FPC Antenna, It comply with the standard requirement.



11. TEST SEUUP PHOTO

Radiated Measurement Photos








Conducted Measurement Photos










12. EUT PHOTO


















***** END OF REPORT *****