

RF Test Data for Bluetooth LE (Conducted Measurements)

General Description of EUT	
Product Name:	GT3 MAX
Test Model:	GT3 MAX
Sample ID:	202208-0162-4-2#
Environmental Conditions	
Temperature:	25°C
Relative Humidity:	55%
Test Voltage:	DC 3.7V
Test Engineer:	Huang jian ping
Note: For a more detailed features description, please refer to the report TBR-C-202208-0162-6	

Contents


1. Duty Cycle	3
2. Maximum Conducted Output Power	7
3. -6dB Bandwidth	11
4. Occupied Channel Bandwidth	15
5. Maximum Power Spectral Density Level	19
6. Band Edge	23
7. Conducted RF Spurious Emission	28
8. Restrict Band	35

1. Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1Mbps	2402	Ant1	100	0	0
NVNT	BLE 1Mbps	2440	Ant1	100	0	0
NVNT	BLE 1Mbps	2480	Ant1	100	0	0
NVNT	BLE 2Mbps	2402	Ant1	100	0	0
NVNT	BLE 2Mbps	2440	Ant1	100	0	0
NVNT	BLE 2Mbps	2480	Ant1	100	0	0

Test Graphs


Duty Cycle NVNT BLE 1Mbps 2402MHz Ant1




Duty Cycle NVNT BLE 1Mbps 2440MHz Ant1




Duty Cycle NVNT BLE 1Mbps 2480MHz Ant1




Duty Cycle NVNT BLE 2Mbps 2402MHz Ant1



Duty Cycle NVNT BLE 2Mbps 2440MHz Ant1







Duty Cycle NVNT BLE 2Mbps 2480MHz Ant1





2. Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	7.173	30	Pass
NVNT	BLE 1Mbps	2440	Ant1	7.206	30	Pass
NVNT	BLE 1Mbps	2480	Ant1	7.139	30	Pass
NVNT	BLE 2Mbps	2402	Ant1	7.19	30	Pass
NVNT	BLE 2Mbps	2440	Ant1	7.22	30	Pass
NVNT	BLE 2Mbps	2480	Ant1	7.142	30	Pass








3. -6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	0.68	0.5	Pass
NVNT	BLE 1Mbps	2440	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.68	0.5	Pass
NVNT	BLE 2Mbps	2402	Ant1	1.3	0.5	Pass
NVNT	BLE 2Mbps	2440	Ant1	1.35	0.5	Pass
NVNT	BLE 2Mbps	2480	Ant1	1.38	0.5	Pass


Test Graphs


-6dB Bandwidth NVNT BLE 1Mbps 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2440MHz Ant1








4. Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1Mbps	2402	Ant1	1.046
NVNT	BLE 1Mbps	2440	Ant1	1.041
NVNT	BLE 1Mbps	2480	Ant1	1.041
NVNT	BLE 2Mbps	2402	Ant1	2.076
NVNT	BLE 2Mbps	2440	Ant1	2.094
NVNT	BLE 2Mbps	2480	Ant1	2.09



Test Graphs



OBW NVNT BLE 1Mbps 2402MHz Ant1



OBW NVNT BLE 1Mbps 2440MHz Ant1








5. Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-5.69	8	Pass
NVNT	BLE 1Mbps	2440	Ant1	-5.043	8	Pass
NVNT	BLE 1Mbps	2480	Ant1	-4.275	8	Pass
NVNT	BLE 2Mbps	2402	Ant1	-8.384	8	Pass
NVNT	BLE 2Mbps	2440	Ant1	-7.225	8	Pass
NVNT	BLE 2Mbps	2480	Ant1	-8.003	8	Pass



Test Graphs



PSD NVNT BLE 1Mbps 2402MHz Ant1



PSD NVNT BLE 1Mbps 2440MHz Ant1








6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-61.81	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-62.79	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-60.64	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-60.04	-20	Pass



Test Graphs



Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Ref





Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Emission










7. Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-48.61	-20	Pass
NVNT	BLE 1Mbps	2440	Ant1	-49.09	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-49.29	-20	Pass
NVNT	BLE 2Mbps	2402	Ant1	-47.01	-20	Pass
NVNT	BLE 2Mbps	2440	Ant1	-46.18	-20	Pass
NVNT	BLE 2Mbps	2480	Ant1	-48.21	-20	Pass

Test Graphs


Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1Mbps 2480MHz Ant1 Emission





Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 2Mbps 2402MHz Ant1 Emission






Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2Mbps 2480MHz Ant1 Emission




8. Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2310	-49.49	2	47.77	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2310	-59.02	2	38.24	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2386.8	-46.06	2	51.2	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2389.872	-58.66	2	38.6	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-49.51	2	47.75	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-58.67	2	38.59	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-47.37	2	49.89	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-56.99	2	40.27	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.752	-43.79	2	53.47	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.512	-56.99	2	40.27	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-48.28	2	48.98	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-58.67	2	38.59	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-49.23	2	48.03	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2310	-59.04	2	38.22	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2328.624	-45.62	2	51.64	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2389.68	-58.66	2	38.6	Average	54	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-47.36	2	49.9	Peak	74	Pass
NVNT	BLE 2Mbps	2402	Ant1	2390	-58.67	2	38.59	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-43.2	2	54.06	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.5	-51.35	2	45.91	Average	54	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.512	-43.2	2	54.06	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2483.512	-51.35	2	45.91	Average	54	Pass


NVNT	BLE 2Mbps	2480	Ant1	2500	-50.46	2	46.8	Peak	74	Pass
NVNT	BLE 2Mbps	2480	Ant1	2500	-58.63	2	38.63	Average	54	Pass

Test Graphs


Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Peak




Restrict Band NVNT BLE 1Mbps 2402MHz Ant1 Average




Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Peak




Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Average




Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Peak




Restrict Band NVNT BLE 2Mbps 2402MHz Ant1 Average



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 2Mbps 2480MHz Ant1 Average



-----END OF THE REPORT-----