

TEST REPORT

Applicant Name : HONGKONG ZHINYU TECHNOLOGY CO., LIMITED
Address : FLAT/RM A 12/F ZJ 300, 300 LOCKHART ROAD, WAN CHAI,
HONG KONG, China
Report Number : RA230601-30842E-RF-00
FCC ID: 2A598-T129L

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Sleep Sound Machine
Model No.: T129L
Multiple Model(s) No.: T130L, T131L, T132L, T133L
Trade Mark: BGOVERSS
Date Received: 2023/06/01
Report Date: 2023/06/25

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:

Roger Ling

Roger Ling
EMC Engineer

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290

Fax: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- RF EXPOSURE.....	12
APPLICABLE STANDARD	12
RESULT	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP.....	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
FACTOR & OVER LIMIT CALCULATION.....	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
FACTOR & OVER LIMIT/MARGIN CALCULATION	19
TEST DATA	19
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
APPENDIX	32
APPENDIX A: DTS BANDWIDTH	32
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	37
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	42
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	43
APPENDIX E: BAND EDGE MEASUREMENTS.....	48
APPENDIX F: DUTY CYCLE	51

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230601-30842E-RF-00	Original Report	2023-06-25

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Sleep Sound Machine
Tested Model	T129L
Multiple Model(s)	T130L, T131L, T132L, T133L (model difference see product declaration letter of similarity)
Frequency Range	2.4G Wi-Fi: 2412-2472MHz
Maximum Conducted Average Output Power	Wi-Fi: 802.11b: 15.78dBm, 802.11g: 14.95dBm, 802.11n-HT20: 14.78dBm, 802.11n-HT40: 13.80dBm
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	1.3dBi (provided by the applicant)
Voltage Range	DC 5V from Adapter
Sample serial number	26FK-3 for Conducted Emission and Radiated Emissions below 1 GHz 26FK-1 for Radiated Emissions above 1 GHz 26FK-2for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: AS0601A-0501000USU Input: AC 100-240V, 50/60Hz, 0.2A MAX Output: DC 5V, 1000mA

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions	9k-30MHz	2.74dB,k=2
	150kHz-30MHz	2.92dB,k=2
Emissions, Radiated	9kHz - 30MHz	2.06dB
	30MHz - 1GHz	5.08dB
	1GHz- 18GHz	4.96dB
	18GHz-26.5GHz	5.16dB
	26.5GHz-40GHz	4.64dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For Wi-Fi mode, total 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

802.11 b&802.11g&802.11n-HT20 mode was tested with Channel 1, 7 and 13.
802.11n-HT40 mode was tested with Channel 3, 7 and 11.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“Wifi Test Tool v1.6.0 release.exe”* software was used to test and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	24	24	24
802.11g	6Mbps	55	55	55
802.11n-HT20	MCS0	55	55	55
802.11n-HT40	MCS0	55	55	55

The software and power level was provided by applicant.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Bull	Receptacle	902#	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Detachable DC Cable	1.2	Adapter	EUT
Un-shielded Un-detachable Cable	1.5	Receptacle	LISN/AC Mains

Block Diagram of Test Setup


For conducted emission



For Radiated Emissions below 1 GHz:



For Radiated Emissions above 1 GHz:



Note: the support table edge was flush with the center of turntable

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) (3) & §2.1091	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Conducted Emission Test Software: e3 191218 (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/1 8G-10SS	5	2022/11/25	2023/11/24
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
Agilent	Power Sensor	U2021XA	MY5425003	2023/02/25	2024/02/24
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- RF Exposure

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Frequency (MHz)	Antenna Gain		Tune up conducted power (dBm)	ERP		Evaluation Distance (m)	ERP Limit (W)
	(dBi)	(dBd)		(dBm)	(W)		
2412-2472	1.3	-0.85	16.0	15.15	0.033	0.2	0.768

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 1.3dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{level} - \text{Limit} \\ \text{Level} &= \text{reading level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	46 %
ATM Pressure:	101 kPa

The testing was performed by Jerry Wu on 2023-06-19.

EUT operation mode: Transmitting


Wi-Fi: (Worst case is 802.11b mode, Low Channel)

AC 120V/60 Hz, Line



Site : Shielding Room
Condition: Line
Job No. : RA230601-30842E-RF
Mode : 2.4G WIFI Transmitting
Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.168	10.34	25.63	35.97	55.04	-19.07	Average
2	0.168	10.34	38.09	48.43	65.04	-16.61	QP
3	0.219	10.31	22.21	32.52	52.87	-20.35	Average
4	0.219	10.31	33.26	43.57	62.87	-19.30	QP
5	0.447	10.54	27.00	37.54	46.92	-9.38	Average
6	0.447	10.54	30.81	41.35	56.92	-15.57	QP
7	0.523	10.58	13.72	24.30	46.00	-21.70	Average
8	0.523	10.58	24.23	34.81	56.00	-21.19	QP
9	2.246	10.42	11.87	22.29	46.00	-23.71	Average
10	2.246	10.42	17.68	28.10	56.00	-27.90	QP
11	5.376	10.56	6.98	17.54	50.00	-32.46	Average
12	5.376	10.56	13.80	24.36	60.00	-35.64	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA230601-30842E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.166	10.28	25.19	35.47	55.14	-19.67	Average
2	0.166	10.28	37.38	47.66	65.14	-17.48	QP
3	0.214	10.30	21.33	31.63	53.06	-21.43	Average
4	0.214	10.30	33.03	43.33	63.06	-19.73	QP
5	0.447	10.45	24.74	35.19	46.92	-11.73	Average
6	0.447	10.45	31.24	41.69	56.92	-15.23	QP
7	0.511	10.47	14.07	24.54	46.00	-21.46	Average
8	0.511	10.47	22.50	32.97	56.00	-23.03	QP
9	4.160	10.53	10.62	21.15	46.00	-24.85	Average
10	4.160	10.53	17.72	28.25	56.00	-27.75	QP
11	5.305	10.51	10.74	21.25	50.00	-28.75	Average
12	5.305	10.51	18.57	29.08	60.00	-30.92	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247, RSS-247, RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Corrected Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22.3~26.5 °C
Relative Humidity:	52~54 %
ATM Pressure:	101 kPa

The testing was performed by Jason Liu on 2023-06-19 for below 1GHz and Jimi Zheng on 2023-06-12 for above 1GHz.


EUT operation mode: Transmitting

(Pre-scan in the X, Y and Z axes of orientation, the worst case orientation was photo and recorded)

30MHz-1GHz: (Worst case is 802.11b mode, low Channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA230601-30842E-RF
Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	94.470	-12.60	40.41	27.81	43.50	-15.69	Peak
2	148.376	-15.36	40.42	25.06	43.50	-18.44	Peak
3	204.955	-11.83	50.81	38.98	43.50	-4.52	QP
4	395.894	-6.79	34.99	28.20	46.00	-17.80	Peak
5	765.386	-0.39	31.48	31.09	46.00	-14.91	Peak
6	947.930	1.98	33.90	35.88	46.00	-10.12	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230601-30842E-RF
Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	42.768	-9.97	29.82	19.85	40.00	-20.15	Peak
2	67.261	-13.48	35.98	22.50	40.00	-17.50	Peak
3	92.584	-13.12	34.66	21.54	43.50	-21.96	Peak
4	132.801	-14.98	37.53	22.55	43.50	-20.95	Peak
5	205.225	-11.83	52.08	40.25	43.50	-3.25	QP
6	396.415	-6.78	33.47	26.69	46.00	-19.31	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11b									
Low Channel 2412MHz									
2388.68	68.23	PK	162	1.3	H	-10.62	57.61	74	-16.39
2388.68	52.52	AV	162	1.3	H	-10.62	41.90	54	-12.10
2387.75	68.11	PK	335	1.8	V	-10.62	57.49	74	-16.51
2387.75	52.40	AV	335	1.8	V	-10.62	41.78	54	-12.22
2390	65.91	PK	197	2.4	H	-10.62	55.29	74	-18.71
2390	51.98	AV	197	2.4	H	-10.62	41.36	54	-12.64
2390	65.79	PK	127	2.1	V	-10.62	55.17	74	-18.83
2390	51.87	AV	127	2.1	V	-10.62	41.25	54	-12.75
4824	64.04	PK	102	2	H	-5.55	58.49	74	-15.51
4824	56.42	AV	102	2	H	-5.55	50.87	54	-3.13
4824	63.53	PK	181	1.1	V	-5.55	57.98	74	-16.02
4824	55.68	AV	181	1.1	V	-5.55	50.13	54	-3.87
Middle Channel 2442MHz									
4884	62.71	PK	300	2.4	H	-5.20	57.51	74	-16.49
4884	55.24	AV	300	2.4	H	-5.20	50.04	54	-3.96
4884	62.15	PK	221	1.5	V	-5.20	56.95	74	-17.05
4884	54.28	AV	221	1.5	V	-5.20	49.08	54	-4.92
High Channel 2472MHz									
2483.5	66.99	PK	291	1.4	H	-10.46	56.53	74	-17.47
2483.5	55.78	AV	291	1.4	H	-10.46	45.32	54	-8.68
2483.5	66.86	PK	250	2	V	-10.46	56.4	74	-17.60
2483.5	55.64	AV	250	2	V	-10.46	45.18	54	-8.82
2486.81	71.07	PK	154	2	H	-10.43	60.64	74	-13.36
2486.81	60.54	AV	154	2	H	-10.43	50.11	54	-3.89
2485.96	70.90	PK	2	2	V	-10.44	60.46	74	-13.54
2485.96	60.21	AV	2	2	V	-10.44	49.77	54	-4.23
4944	61.03	PK	98	2.2	H	-5.01	56.02	74	-17.98
4944	51.46	AV	98	2.2	H	-5.01	46.45	54	-7.55
4944	60.60	PK	12	1.4	V	-5.01	55.59	74	-18.41
4944	50.54	AV	12	1.4	V	-5.01	45.53	54	-8.47

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11g									
Low Channel 2412MHz									
2389.83	70.44	PK	245	2.2	H	-10.62	59.82	74	-14.18
2389.83	54.52	AV	245	2.2	H	-10.62	43.90	54	-10.10
2389.28	70.11	PK	152	1.9	V	-10.62	59.49	74	-14.51
2389.28	54.29	AV	152	1.9	V	-10.62	43.67	54	-10.33
2390	68.63	PK	121	2.1	H	-10.62	58.01	74	-15.99
2390	53.95	AV	121	2.1	H	-10.62	43.33	54	-10.67
2390	68.30	PK	230	1.3	V	-10.62	57.68	74	-16.32
2390	53.78	AV	230	1.3	V	-10.62	43.16	54	-10.84
4824	62.50	PK	156	1.7	H	-5.55	56.95	74	-17.05
4824	47.38	AV	156	1.7	H	-5.55	41.83	54	-12.17
4824	62.23	PK	352	1.2	V	-5.55	56.68	74	-17.32
4824	47.15	AV	352	1.2	V	-5.55	41.60	54	-12.40
Middle Channel 2442MHz									
4884	61.41	PK	357	1.8	H	-5.20	56.21	74	-17.79
4884	46.10	AV	357	1.8	H	-5.20	40.9	54	-13.10
4884	61.17	PK	85	2.2	V	-5.20	55.97	74	-18.03
4884	45.85	AV	85	2.2	V	-5.20	40.65	54	-13.35
High Channel 2472MHz									
2483.5	77.02	PK	355	2.1	H	-10.46	66.56	74	-7.44
2483.5	60.70	AV	355	2.1	H	-10.46	50.24	54	-3.76
2483.5	76.59	PK	159	1.7	V	-10.46	66.13	74	-7.87
2483.5	59.47	AV	159	1.7	V	-10.46	49.01	54	-4.99
2484.84	81.04	PK	157	2.5	H	-10.45	70.59	74	-3.41
2484.84	61.25	AV	157	2.5	H	-10.45	50.8	54	-3.20
2484.39	80.63	PK	236	2	V	-10.45	70.18	74	-3.82
2484.39	61.07	AV	236	2	V	-10.45	50.62	54	-3.38
4944	60.11	PK	8	1	H	-5.01	55.10	74	-18.90
4944	44.82	AV	8	1	H	-5.01	39.81	54	-14.19
4944	59.90	PK	308	1.5	V	-5.01	54.89	74	-19.11
4944	44.56	AV	308	1.5	V	-5.01	39.55	54	-14.45

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n20									
Low Channel 2412MHz									
2385.89	71.90	PK	155	1.9	H	-10.63	61.27	74	-12.73
2385.89	54.68	AV	155	1.9	H	-10.63	44.05	54	-9.95
2387.78	71.60	PK	107	2.5	V	-10.62	60.98	74	-13.02
2387.78	54.53	AV	107	2.5	V	-10.62	43.91	54	-10.09
2390	68.84	PK	158	1.7	H	-10.62	58.22	74	-15.78
2390	54.11	AV	158	1.7	H	-10.62	43.49	54	-10.51
2390	68.62	PK	297	1.7	V	-10.62	58.00	74	-16.00
2390	53.98	AV	297	1.7	V	-10.62	43.36	54	-10.64
4824	62.77	PK	19	1.7	H	-5.55	57.22	74	-16.78
4824	47.32	AV	19	1.7	H	-5.55	41.77	54	-12.23
4824	62.51	PK	287	1.7	V	-5.55	56.96	74	-17.04
4824	47.04	AV	287	1.7	V	-5.55	41.49	54	-12.51
Middle Channel 2442MHz									
4884	62.11	PK	100	1.8	H	-5.20	56.91	74	-17.09
4884	46.42	AV	100	1.8	H	-5.20	41.22	54	-12.78
4884	61.88	PK	33	2.2	V	-5.20	56.68	74	-17.32
4884	46.20	AV	33	2.2	V	-5.20	41	54	-13.00
High Channel 2472MHz									
2483.5	78.16	PK	84	1.7	H	-10.46	67.7	74	-6.30
2483.5	60.45	AV	84	1.7	H	-10.46	49.99	54	-4.01
2483.5	77.88	PK	34	1.1	V	-10.46	67.42	74	-6.58
2483.5	60.17	AV	34	1.1	V	-10.46	49.71	54	-4.29
2484.46	80.28	PK	297	1.1	H	-10.45	69.83	74	-4.17
2484.46	61.09	AV	297	1.1	H	-10.45	50.64	54	-3.36
2483.97	79.94	PK	332	2	V	-10.46	69.48	74	-4.52
2483.97	60.83	AV	332	2	V	-10.46	50.37	54	-3.63
4944	60.40	PK	255	2.5	H	-5.01	55.39	74	-18.61
4944	44.83	AV	255	2.5	H	-5.01	39.82	54	-14.18
4944	60.15	PK	227	1.4	V	-5.01	55.14	74	-18.86
4944	44.59	AV	227	1.4	V	-5.01	39.58	54	-14.42

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n40									
Low Channel 2422MHz									
2389.83	78.48	PK	347	2.5	H	-10.62	67.86	74	-6.14
2389.83	55.63	AV	347	2.5	H	-10.62	45.01	54	-8.99
2389.32	78.11	PK	320	1.7	V	-10.62	67.49	74	-6.51
2389.32	55.34	AV	320	1.7	V	-10.62	44.72	54	-9.28
2390	77.02	PK	306	1.3	H	-10.62	66.40	74	-7.60
2390	55.09	AV	306	1.3	H	-10.62	44.47	54	-9.53
2390	76.80	PK	290	1.7	V	-10.62	66.18	74	-7.82
2390	54.87	AV	290	1.7	V	-10.62	44.25	54	-9.75
4844	61.60	PK	347	1.8	H	-5.52	56.08	74	-17.92
4844	45.44	AV	347	1.8	H	-5.52	39.92	54	-14.08
4844	61.32	PK	244	1.1	V	-5.52	55.80	74	-18.20
4844	45.21	AV	244	1.1	V	-5.52	39.69	54	-14.31
Middle Channel 2442MHz									
4884	61.10	PK	243	1.1	H	-5.20	55.9	74	-18.10
4884	44.89	AV	243	1.1	H	-5.20	39.69	54	-14.31
4884	60.85	PK	281	2.2	V	-5.20	55.65	74	-18.35
4884	44.67	AV	281	2.2	V	-5.20	39.47	54	-14.53
High Channel 2462MHz									
2483.5	78.36	PK	323	1.3	H	-10.46	67.9	74	-6.10
2483.5	59.19	AV	323	1.3	H	-10.46	48.73	54	-5.27
2483.5	78.12	PK	139	1.7	V	-10.46	67.66	74	-6.34
2483.5	58.94	AV	139	1.7	V	-10.46	48.48	54	-5.52
2484.87	80.49	PK	56	1.6	H	-10.45	70.04	74	-3.96
2484.87	59.74	AV	56	1.6	H	-10.45	49.29	54	-4.71
2484.28	80.23	PK	30	2.5	V	-10.46	69.77	74	-4.23
2484.28	59.49	AV	30	2.5	V	-10.46	49.03	54	-4.97
4924	60.56	PK	58	1.6	H	-5.03	55.53	74	-18.47
4924	44.48	AV	58	1.6	H	-5.03	39.45	54	-14.55
4924	60.34	PK	236	1.5	V	-5.03	55.31	74	-18.69
4924	44.27	AV	236	1.5	V	-5.03	39.24	54	-14.76

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading


Margin = Corrected Amplitude - Limit

The other spurious emission which is 20dB below to the limit was not recorded.


1-18 GHz:

Pre-scan Plots:

802.11 b Low Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 b Low Channel
Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25~26 °C
Relative Humidity:	52~55 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-06-13.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.2.3.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25~26 °C
Relative Humidity:	52~55 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-06-13.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	25~26 °C
Relative Humidity:	52~55 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-06-13.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix.

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.3

Method AVGPS-1 uses trace averaging with EUT transmitting at full power throughout each sweep.

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Employ trace averaging (rms) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Test Data

Environmental Conditions

Temperature:	25~26 °C
Relative Humidity:	52~55 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-06-15.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Result: Compliant. Please refer to the Appendix.


APPENDIX

Appendix A: DTS Bandwidth


Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.04	0.5	PASS
		2442	12.08	0.5	PASS
		2472	13.04	0.5	PASS
11G	Ant1	2412	15.36	0.5	PASS
		2442	15.16	0.5	PASS
		2472	15.32	0.5	PASS
11N20SISO	Ant1	2412	15.08	0.5	PASS
		2442	15.08	0.5	PASS
		2472	15.04	0.5	PASS
11N40SISO	Ant1	2422	35.12	0.5	PASS
		2442	35.12	0.5	PASS
		2462	35.12	0.5	PASS

Test Graphs




11G_Ant1_2412




Date: 13.JUN.2023 09:18:48

11G_Ant1_2442




Date: 13.JUN.2023 09:23:05

11G_Ant1_2472




Date: 13.JUN.2023 09:23:59

11N20SISO_Ant1_2412




Date: 13.JUN.2023 09:25:47

11N20SISO_Ant1_2442




Date: 13.JUN.2023 09:34:53

11N20SISO_Ant1_2472




Date: 13.JUN.2023 09:35:53

11N40SISO_Ant1_2422




Date: 13.JUN.2023 09:37:42

11N40SISO_Ant1_2442



Date: 13.JUN.2023 09:40:21

11N40SISO_Ant1_2462




Date: 13.JUN.2023 09:41:18

Appendix B: Occupied Channel Bandwidth**Test Result**


Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	15.305	---	---
		2442	15.305	---	---
		2472	15.305	---	---
11G	Ant1	2412	17.582	---	---
		2442	17.582	---	---
		2472	17.582	---	---
11N20SISO	Ant1	2412	18.462	---	---
		2442	18.462	---	---
		2472	18.462	---	---
11N40SISO	Ant1	2422	36.204	---	---
		2442	36.204	---	---
		2462	36.204	---	---

Test Graphs


11B_Ant1_2412




11B_Ant1_2442



11B_Ant1_2472




11G_Ant1_2412




Date: 13.JUN.2023 09:18:58

11G_Ant1_2442




Date: 13.JUN.2023 09:23:16

11G_Ant1_2472




Date: 13.JUN.2023 09:24:10

11N20SISO_Ant1_2412




Date: 13.JUN.2023 09:25:58

11N20SISO_Ant1_2442




Date: 13.JUN.2023 09:35:04

11N20SISO_Ant1_2472




Date: 13.JUN.2023 09:36:04

11N40SISO_Ant1_2422




Date: 13.JUN.2023 09:37:52

11N40SISO_Ant1_2442



Date: 13.JUN.2023 09:40:32

11N40SISO_Ant1_2462



Date: 13.JUN.2023 09:41:29


Appendix C: Maximum conducted output power**Test Result Average**

Test Mode	Antenna	Frequency[MHz]	Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	15.78	≤30.00	PASS
		2442	15.72	≤30.00	PASS
		2472	14.26	≤30.00	PASS
11G	Ant1	2412	14.95	≤30.00	PASS
		2442	14.75	≤30.00	PASS
		2472	13.23	≤30.00	PASS
11N20SISO	Ant1	2412	14.78	≤30.00	PASS
		2442	14.56	≤30.00	PASS
		2472	13.05	≤30.00	PASS
11N40SISO	Ant1	2422	13.80	≤30.00	PASS
		2442	13.35	≤30.00	PASS
		2462	12.80	≤30.00	PASS


Appendix D: Maximum power spectral density**Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/10kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-12.23	≤8.00	PASS
		2442	-12.21	≤8.00	PASS
		2472	-13.56	≤8.00	PASS
11G	Ant1	2412	-12.76	≤8.00	PASS
		2442	-12.45	≤8.00	PASS
		2472	-14.39	≤8.00	PASS
11N20SISO	Ant1	2412	-13.06	≤8.00	PASS
		2442	-12.97	≤8.00	PASS
		2472	-14.37	≤8.00	PASS
11N40SISO	Ant1	2422	-15.44	≤8.00	PASS
		2442	-15.24	≤8.00	PASS
		2462	-16.44	≤8.00	PASS

Test Graphs




11G_Ant1_2412




Date: 15 JUN 2023 15:19:43

11G_Ant1_2442




Date: 15 JUN 2023 15:20:11

11G_Ant1_2472




Date: 15 JUN 2023 15:20:48

11N20SISO_Ant1_2412




Date: 15 JUN 2023 15:21:34

11N20SISO_Ant1_2442




Date: 15 JUN 2023 15:21:58

11N20SISO_Ant1_2472




Date: 15 JUN 2023 15:22:36




Appendix E: Band edge measurements

Test Graphs




11G Ant1 Low 2412




Date: 13 JUN 2023 09:19:40

11G Ant1 High 2472




Date: 13 JUN 2023 09:24:52

11N20SISO Ant1 Low 2412




Date: 13 JUN 2023 09:26:39




Appendix F: Duty Cycle**Test Result**

Test Mode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	100.00	100.00	100.00
11G	Ant1	2442	1.39	1.41	98.58
11N20SISO	Ant1	2442	1.30	1.32	98.48
11N40SISO	Ant1	2442	100.00	100.00	100.00

Test Graphs





***** END OF REPORT *****